


### Technical Specifications

#### HP EliteDisplay E273d 27-inch Docking Monitor




#### Front

1. Function Buttons

2. Power Button

### Technical Specifications

#### HP EliteDisplay E273d 27-inch Docking Monitor



1. DC Power IN Connector
2. DC Power OUT Connector
3. Security Cable Slot
4. HDMI Port
5. DisplayPort™ 1.2 OUT Port
6. VGA Port
7. Audio-in Jack

#### Back

8. USB Type-C™ Port
9. USB Type-B™ Port
10. Network Jack
11. USB Type-A Port
12. USB Type-A Port
13. USB Type-A Ports (2)
14. Headset Port

### Technical Specifications

**Models:** 5WN63A8/5WN63U9/5WN63AA/5WN63A7/5WN63AS/5WN63AT

<b>Panel Specifications</b>	<p><b>Display Size (Diagonal)</b> 27.0 in</p> <p><b>Display Panel Type</b> IPS w/LED backlight</p> <p><b>Micro-Edge Bezel</b> Yes, 3-sided</p> <p><b>Native Resolution*</b> 1920 x 1080 @60 Hz</p> <p><b>Native Resolution Note</b> The video card of the connected PC must be capable of supporting 1920 x 1080 at 60 Hz and include 1 HDMI or 1 VGA or 1 DP output or USB Type-C™ DP Alt Mode to drive the monitor at the Preferred Mode.</p> <p><b>Panel Bit Depth</b> 8 Bit (6 Bit + A-FRC)</p> <p><b>Aspect Ratio</b> 16:9</p> <p><b>Brightness Typical</b> 250 cd/m<sup>2</sup></p> <p><b>Static Contrast Ratio - Typical</b> 1000:1</p> <p><b>Static Contrast Ratio - Minimum</b> 700:1</p> <p><b>Dynamic Contrast Ratio (DCR)</b> 5,000,000:1</p> <p><b>Pixel Pitch</b> 0.3114 x 0.3114 mm</p> <p><b>Pixels Per Inch (PPI)</b> 81.59</p> <p><b>Backlight Lamp Life (to half brightness - in hours)</b> 30k minimum</p> <p><b>Anti-Glare Panel</b> Yes</p> <p><b>Response Time - Typical</b> 5ms (GTG)</p> <p><b>Horizontal Viewing Angle (typical CR&gt;10)</b> 178°</p> <p><b>Vertical Viewing Angle (typical CR&gt;10)</b> 178°</p> <p><b>Panel Active Area (w x h)</b> 597.88(H) x 336.3(V)</p> <p><b>Preset Graphic Modes/Supported Resolutions</b> 640×480 @59.940Hz 720×400 @70.087Hz 800×600 @60.317Hz 1024×768 @60.004Hz 1280×720 @60Hz 1280×800 @59.810Hz 1280×1024 @60.020Hz 1440×900 @59.887Hz 1600×900 @60Hz 1680×1050 @59.954Hz 1920×1080 @60Hz</p> <p><b>Maximum Resolution</b> 1920×1080 @ 60HZ</p> <p><b>Recommended Resolution</b> 1920×1080 @ 60HZ</p> <p><b>Vertical Scan Range</b> 50 - 60 Hz</p> <p><b>Horizontal Scan Range</b> 30 - 80 kHz</p> <p><b>Default Color Temperature</b> Neutral (6500 K)</p> <p><b>Maximum Pixel Clock Speed</b> 170 MHz</p> <p><i>*VGA or DisplayPort™ 1.2 or HDMI 1.4 required to drive panel at its native resolution</i></p>
-----------------------------	--

NOTE: Performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

### Technical Specifications

<b>Color Gamut Coverage</b>	<b>NTSC sRGB</b>	72% >94% sRGB
<b>Color Management</b>	<b>Color Space / Subsampling Support Default Color Temperature Low Blue Light Modes RGB Channel Adjust</b>	RGB 4:4:4, YCbCr 4:4:4, YCbCr 4:2:2 Neutral (6500 K) Yes Yes, Gain
<b>Monitor Specifications</b>	<b>Exterior Color of Monitor Bezel and Stand Plug &amp; Play Tilt Swivel Pivot Height Adjustment Range VESA Mounting  Security Lock Ready Detachable Base Warranty</b>	Asteroid in bezel and bucket frame and black in stand  Yes -5 TO +23 DEGREES Yes, 45° Pivot (CW & counter CW). Detent at 0 degrees Yes, 150 mm Yes, 100 mm with integrated mount or with included bracket Yes Yes, ships detached 3-3-0 NA/TW/EMEA/ANZ/JPN/VIET/THAI 3-3-3 INDIA/PRC
<b>Multimedia</b>	<b>Webcam Microphone</b>	Yes, 720p Yes, 2
<b>On Screen Display (OSD)</b>	<b>On Screen Display User Controls  User Programmable Modes Monitor Control Buttons or Switches  User-Assignable Function Buttons Languages</b>	Brightness, Contrast, Color Control, Input Control, Image Control, Power control, Menu Control, Management, USB Host Selection, Information, EXIT Yes, 10 Menu, Minus ("-")/Information, Plus ("+")/Viewing Modes, Back/Next Active Input, Power Yes, 3 (8 options) 10 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese and S-Chinese)
<b>Connector Types</b>	<b>DisplayPort™ HDMI USB Type-C™ VGA HDCP support Audio Output Audio Input Ethernet</b>	1 DisplayPort 1.2 out 1 HDMI 1.4 1 USB3.1 Type C upstream ports 1 VGA Yes, (USB-C Video and HDMI, Displaylink) 1, Analog 1, Analog Yes
<b>USB Port Specifications</b>	<b>USB Version  USB Hub Downstream Ports Upstream Ports Fast Charging USB Ports Power Output Maximum</b>	3.1  Yes 4 Ports 2 Ports (Type-C & Type-B) 1 Port (Upper in side BD) Fast Charging: 7.5W; Standard 4.5W
<b>USB-Type C™ Port Specifications</b>	<b>USB-Type C™ Version  Upstream USB-Type C™ Ports Video Support</b>	USB 3.1 Gen1 / 5 G bps  1 Port USB-C Alt mode – DisplayPort™ 1.2

### Technical Specifications

	<b>Power Output</b>	5V/9V/10V/12V/15V/20V
	<b>Power Output Maximum</b>	65 W Max
<b>Special Features</b>	<b>Remote Manageability</b>	No
	<b>User Presets</b>	Yes
	<b>Power Output over DC OUT</b>	90 w (From Monitor)
<b>Power &amp; Operating Specs</b>	<b>Power Supply</b>	External
	<b>Power Source</b>	100 – 240 VAC 50/60 Hz
	<b>Power Consumption - Maximum</b>	170 W (Without DC power out, with power delivery)
	<b>Energy Saving/Standby Mode</b>	0.5W
	<b>Power Consumption - Typical</b>	40 W
	<b>Power cable length</b>	1830mm: 398062-001,150304-008,130627-008,121565-001,285052-001,100613-008,286496-001,109197-008,653326-001,438723-001,393312-001 2500mm: 187487-001,100661-001,401328-001 1800mm: 100614-009 2000mm: 403440-001
<b>EU Energy Efficiency Class (EC1062)</b>	<b>Visible Screen Size</b>	27"/68,5 cm
<b>Operating Conditions</b>	<b>Operating Temperature - Celsius</b>	5° - 35°C
	<b>Operating Temperature - Fahrenheit</b>	41° - 95°F
	<b>Non-operating Temperature - Celsius</b>	-20° - 60°C
	<b>Non-operating Temperature - Fahrenheit</b>	-4° - 140°F
	<b>Operating Humidity</b>	20% - 80% (non-condensing)
	<b>Non-operating Humidity</b>	5% - 95%
	<b>Operating Altitude</b>	0 - 5,000 m (16,400 ft.)
	<b>Non-operating Altitude</b>	0 - 12.192 m (40,000 ft.)
<b>Environmental Features and Certifications</b>	<b>Mercury-free LED display backlighting</b>	Yes, Mercury-free LED backlights
	<b>Arsenic-Free Display Glass</b>	Yes
	<b>Low Halogen**</b>	GSE HP-00011-01B, table 2 defines low-halogen (BFR, CFR, PVC)
	<b>Agency Approvals and Certifications</b>	WW application CE,CB,KC/KCC/NOM/ICE/ISO 9241-307/ EAC/TUV-GS/cTUVus/PSB/CCC/CEL/ISC/VCCI/FCC/BSMI/Vietnam MEPS/Australian-New Zealand MEPS/WEEE/BIS
	<b>Microsoft WHQL Certification</b>	Win 10, Win 8.1, Win 7
	<b>SmartWay Transport Partnership - NA only</b>	Yes (NA SKU)

\*\*External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.

Note: DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries.

<b>Contains Recycled Plastics</b>	<b>Contains Recycled Plastics in Back Cover</b>	85% (5% Ocean Bound Plastic)
	<b>Contains Recycled Plastics in Base/Stand</b>	85% (5% Ocean Bound Plastic)

### Technical Specifications

	<b>Contains Recycled Plastics in Other Parts</b>	85% (Deco, Middle Frame)	
	<b>Recyclable Packaging (Box, packing materials)</b>	0% recyclable Plastics content by total weight of packing materials	
	<b>Recyclable Plastics</b>	All	
	<b>Recyclable Packaging (Box, packing materials)</b>	All	
<b>Unit Product/Package Specifications</b>	<b>Product Dimensions</b> (Unpacked with stand) (W x D x H)	<b>Metric</b> 61.094 x 21.4 x 50.85 cm	<b>Imperial</b> 24.05 x 8.43 x 20.02 in
	<b>Product Dimensions</b> (Packed) (W x D x H)	73.2 x 28.2 x 44.6 cm	28.82 x 11.1 x 17.56 in
	<b>Display Head Dimensions</b> (Unpacked without stand) (W x D x H)	61.094 x 4.632 x 36.3 cm	24.05 x 1.824 x 14.29 in
	<b>Base Area Footprint</b> (w x d mm)	260.0 x 214 mm	10.236 x 8.425 in
	<b>Bezel Measurements</b>	Top 1.36 mm	Top 0.0535 in
		Side 1.36 mm	Side 0.0535 in
		Bottom 19.2 mm	Bottom 0.756 in
<b>Product Weight</b> (Unpacked with stand)	7.52 kg	16.58 lb	
<b>Pallet Information</b>	<b>Pallet Dimensions</b> (L x W x H)	1140L x 740W x 125H mm	44.88L x 29.13W x 4.92H inch
	<b>Pallet Layers</b>	20/40" Wooden- 4 layers	
	<b>Pallet Product per Layer</b>	4 sets	
	<b>Total Products per Pallet</b>	16 sets	
	<b>Container Load, 20-Foot</b>	224 units	
	<b>Container Load, 40-Foot</b>	512 units	
	<b>Container Load, 40-Foot HighQ</b>	640 units	
<b>Software Included</b>	Install DisplayLink USB Driver Software Install Monitor INF/ICM Software Install HP Display Assistant Install Cyberlink YouCam Open Auto-Adjustment Utility (for VGA input only)		
<b>Recommended Accessories*</b>	<b>Description</b>	<b>Part Number</b>	
	HP B300 PC Mounting Bracket	2DW53AA	
	HP Quick Release Bracket 2	6KD15AA	
	HP S101 Speaker Bar	5UU40AA	
	HP Hot Desk Stand	W2Z73AA	
	HP Executive 15.6 Backpack	6KD07AA	
	HP Sure Key Cable Lock	6UW42AA	
	<i>*Sold separately and availability may vary by country</i>		
<b>What's in the box?</b>	AC power cord (1.83 m) 6.0 ft USB C-C cable (1.8 m) 5.9 ft USB A-B Cable (1.8 m) 5.9 ft DC-DC Cable (1.8 m) 5.9 ft DC Jack Dongle HDMI Cable External power supplier (230 W) QSP		

### Technical Specifications

Product notice

**NOTE: Included cables may vary by country.**

#### **User Guide and Warranty Languages**

##### **User Guide Languages**

English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish

##### **Warranty Languages**

English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish.

### *Technical Specifications*

Copyright © 2019 HP Development Company, L.P.

The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Microsoft and Windows are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. ENERGY STAR is a registered trademark owned by the U.S. Environmental Protection Agency.



### Summary

Change Log	
<b>V1 to V2</b>	