

# HP Super Heavyweight Plus Matte Paper



**HP Super Heavyweight Plus Matte Paper is a best-in-class graphics display media that delivers superior image quality. It maximises productivity with application versatility, instant dry time and great laminate compatibility**

- HP Super Heavyweight Plus Matte Paper is designed to resist rippling at high ink densities without sacrificing image quality or productivity for professional-looking prints.
- HP Super Heavyweight Plus Matte Paper delivers superior print quality including vibrant, full-colour graphics and outstanding photorealistic images for the most important applications.

- HP Super Heavyweight Plus Matte Paper is an extra-heavy, bright white media with a smooth matte surface and added stiffness which gives a highly professional look and feel.

Companies which produce posters and presentations, POS and retail displays. Geographic Information Systems (GIS), Architecture (AEC) and Engineering (CAD). Tradeshow and event displays.

# HP Super Heavyweight Plus Matte Paper

## Compatibility

HP Designjet printers	HP Ink Supplies	Front panel setting
HP Designjet 5500/5000 Printer series	HP 81 Dye & 83 UV Ink Supplies	Super HW Plus Paper
HP Designjet 4000 Printer series	HP 90 Ink Supplies	Canvas
HP Designjet 3000CP/2000CP Printer series	HP CP Dye & UV Ink Supplies	Heavy Coated Paper
HP Designjet 1000 Printer series	HP 80 Dye Ink Supplies	Heavy Coated Paper

For the latest ICC/Media profiles, please visit [www.hp.com/go/designjet/supplies/support](http://www.hp.com/go/designjet/supplies/support) (click on the ICC profiles and select your printer). For non-Post Script printers see your external RIP Vendor.

Weight	210 g/m <sup>2</sup> per ISO 536 Test Method
Thickness	10.2 mil/260 microns per ISO 534 Test Method
Brightness	91% per TAPPI T-452 Test Method
CIE whiteness	130 per CIE Ganz 82 Test Method
Lamination	Excellent compatibility with thermal, heat assist and pressure sensitive film laminates. Visit HP's website for more information on lamination partners at: <a href="http://www.hp.com/go/designjet/supplies">www.hp.com/go/designjet/supplies</a>
Finish	Matte
Operating temperature	15 to 35° C
Operating humidity	20 to 80% RH
Waterfastness	Not waterfast when printed with dye inks. Excellent waterfastness when printed with UV inks
Lightfastness (Indoor Commercial Window) Dye Ink	Indoor use away from heavy sunlight
Lightfastness (Indoor Commercial Window) UV Ink	Greater than 1 year
Dry time	Quick dry (@ 23°C, 50% RH)
Shelf time	1 year, unopened in original packaging
Storage temperature	0 to 40° C
Storage humidity	5 to 95% RH
Country of origin	Switzerland

Ordering information	Product Numbers	Roll sizes	UPC codes
	Q6626A	610 mm x 30.5 m	8 82780-05066 2
	Q6627A	914 mm x 30.5 m	8 82780-05067 9
	Q6628A	1067 mm x 30.5 m	8 82780-05068 6
	Q6630A	1524 mm x 30.5 m	8 82780-05070 9

**Warranty Large Format Media** HP large format printing material is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. If for any reason the user is unsatisfied with HP large format printing materials they should contact their HP reseller.

© Copyright 2005 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For information on similar products, please visit HP Designjet Supplies at [www.hp.com/go/designjet/supplies](http://www.hp.com/go/designjet/supplies)

4AA0-2040EEE. October 2005

