

HP LaserJet P4510 Printer series



HP's fastest single-function black-and-white LaserJet Printer series offers high performance, fast speeds up to 60 ppm, reliable security and the flexibility to expand its capabilities with a choice of paper handling and device management options.



HP LaserJet P4515n
Printer



HP LaserJet P4515x
Printer

An excellent choice for larger workgroups of 15+ users per printer in managed SMB and Enterprise environments who need a very reliable, high-performing, secure and easily manageable LaserJet printer.

Achieve more with HP's fastest single-function black-and-white LaserJet workgroup printer.

Experience legendary reliability and consistent print quality at extremely fast speeds of up to 60 ppm, made possible by new HP toner technology.

No time is lost waiting for the printer to warm up as Instant-on Technology ensures the first page prints out as fast as 8.5 seconds from Ready mode.

Built-in Gigabit networking lets you share the printer across large workgroups.

Use a single driver—the HP Universal Print Driver communicates directly with each HP device on your network¹.

Enjoy robust security and effortless ease of use and management.

Experience industry-leading security capabilities such as advanced IPSec encryption, as well as support for standard security protocols. Prevent unauthorised network access with management features like 802.1X authentication and password protection, and guard sensitive information with support for private printing.

Just press the Folder button to view your stored jobs, enter a PIN, and print your documents.

Simplify fleet management tasks and reduce IT costs with HP Web Jetadmin²

Meet growing business needs with this flexible and expandable printer's performance capabilities.

Upgrade your printer as business needs change: this printer accommodates a variety of media types and sizes and lets you expand with an optional two-sided printing accessory³, additional 500-sheet⁴ or 1,500 sheet input tray, an envelope feeder, 5-bin mailbox, stacker, or stapler/stacker accessory. You can also select either regular or high-capacity print cartridges⁵ to meet your specific business needs. Improve performance and increase storage capacity with an optional EIO hard disk.

¹ Download the free HP Universal Print Driver Series for Windows at www.hp.com/go/upd

² For more information visit www.hp.com/go/webjetadmin

³ Standard on HP LaserJet P4515x. Cut paper consumption in half with optional automatic two-sided printing

⁴ 2nd 500-sheet paper tray standard on HP LaserJet P4515x. Purchase additional trays separately

⁵ HP LaserJet CC364A Black Print Cartridge (10000 pages); HP LaserJet CC364X Black Print Cartridge (24000 pages).

Product walkaround

HP LaserJet P4515X Printer shown with optional 500-sheet 5 bin Mailbox, optional 500-sheet input trays 3 and 4, optional 1,500-sheet high capacity input tray, optional printer stand

1. Control panel simultaneously displays up to four lines of text and animated graphics and features a built in 10 key pad
2. Optional 500-sheet 5-bin mailbox with sorting capability
3. 500-sheet top output bin
4. Adjustable 100-sheet multipurpose input tray 1 for special media
5. 500 sheet input tray 2
6. 500-sheet input tray 3
7. Optional 500-sheet input tray 4
8. Optional 1,500-sheet high capacity input tray
9. HP Jetdirect Gigabit Ethernet embedded print server with IPSec
10. A powerful 540 MHz processor and 128 MB of standard printing memory, expandable up to 640 MB
11. EIO expansion slot supports an optional parallel card, hard disk, or Jetdirect print server
12. One external and two internal Host USB 2.0 like ports for third party connections
13. Security lock slot
14. Hi-Speed USB 2.0 port for direct connection to printer
15. 100-sheet rear output bin
16. Duplexer for automatic two sided printing
17. Optional printer stand enables printer mobility



Series at a glance



HP LaserJet P4515n Printer

- Print speed of up to 60 ppm
- 128 MB RAM (max 640 MB)
- 540 MHz processor
- HP Jetdirect Gigabit Ethernet embedded print server with IPSec
- Standard input capacity of 600-sheets with 1x100 sheet tray and 1x500-sheet input tray
- Expandable to 3600 pages with optional 3x500-sheet input trays and a 1500-sheet high-capacity input tray
- Recommended monthly print volume 5000 to 20000 pages
- Duty cycle up to 275000 pages



HP LaserJet P4515x Printer

- As P4515n with automatic duplexer for two-sided printing and additional 500-sheet Feeder/Tray

Recommended accessories



CB518A
HP LaserJet 500-sheet Feeder/Tray
The HP 500-sheet input tray and feeder increases flexibility by providing one additional paper tray, increasing output capacity and decreasing user intervention.



CB523A
HP LaserJet 1500-sheet High-capacity Input Tray
Ideal for handling large high volume print jobs, the HP 1500-sheet high capacity input tray helps to increase productivity and minimise user interventions.



CB519A
HP LaserJet Automatic Duplexer for Two-sided Printing Accessory
The automatic duplexer for two-sided printing enables you to cut paper consumption by up to 50% and save money.



CB520A
HP LaserJet 500-sheet 5-bin Mailbox
Find your printed output quickly and easily with the HP LaserJet 500-sheet 5-Bin Mailbox. Assign each mailbox bin to an individual, workgroup or department for easy job retrieval. It can also be used as a sorter/collator, stacker or job separator.



CB524A
HP LaserJet 75-sheet Envelope Feeder
The HP LaserJet 75-sheet Envelope Feeder enables simple and efficient business mailing and eliminates the need for manual loading as you can print up to 75 envelopes at a time.



CB522A
HP LaserJet 500-sheet Stapler/Stacker
This stapler/stacker offers an additional 500-sheets output capacity and an automatic stapling capability (up to 15 pages), enabling simple, convenient and efficient finishing of documents with automatic offset.

HP Global Solutions Catalogue

HP Global Solutions partners deliver and integrate a wide range of business printing solutions: Products can be mixed, matched and customized. Solutions include: E-forms and stationery, Barcodes and cheque printing (OCR and MICR), Printing from SAP R/3 and ERP packages, Secure printing, Host printing, Cost-controlled printing and copying, Print job accounting and special industry solutions. Go to www.hp.com/eur/gsc for more information.

Ordering information



HP LaserJet P4515n Printer (CB514A)

Printer, right-angled power cord, control panel overlay, software and documentation on CD-ROM, print cartridge, Getting Started Guide, support flyer



HP LaserJet P4515x Printer (CB516A)

Additional 500-sheet paper tray and automatic duplexer for two sided printing

Accessories, Supplies and Support

Accessories

| | |
|---------------|---|
| CB518A | HP LaserJet 500-sheet Feeder/Tray |
| CB523A | HP LaserJet 1500-sheet High-capacity Input Tray |
| CB519A | HP LaserJet Automatic Duplexer for Two-sided Printing Accessory |
| CB520A | HP LaserJet 500-sheet 5-bin Mailbox |
| CB524A | HP LaserJet 75-sheet Envelope Feeder |
| CB522A | HP LaserJet 500-sheet Stapler/Stacker |
| Q3216A | HP 1000-staple Cartridge |
| CB521A | HP LaserJet 500-sheet Stacker |
| CB525A | HP LaserJet P4010/P4510 Series Printer Stand |
| CB527A | HP LaserJet 400-sheet Custom Media Tray |
| J8019A | HP Secure High Performance EIO Hard Disk |
| J7972G | HP 1284B Parallel Card |
| CC413A | HP 64 MB 144-pin x32 DDR2 DIMM |
| CC414A | HP 128 MB 144-pin x32 DDR2 DIMM |
| CE483A | HP 512 MB 144-pin x32 DDR2 DIMM |
| CB389A | HP 220-volt User Maintenance Kit |
| CB388A | HP 110-volt User Maintenance Kit |

Supplies

| | |
|----------------|--|
| CC364A | HP LaserJet CC364A Black Print Cartridge Average cartridge yields 10000 standard pages. Declared yield value in accordance with ISO/IEC 19752* |
| CC364X | HP LaserJet CC364X Black Print Cartridge Average cartridge yields 24000 standard pages. Declared yield value in accordance with ISO/IEC 19752* |
| CC364XD | HP LaserJet CC364X Dual Pack Black Print Cartridges Average cartridge yields 24000 standard pages per cartridge for a total of 48000 standard pages. Declared yield value in accordance with ISO/IEC 19752* |

Connectivity

| | |
|---------------|--|
| J7916G | HP Jetdirect 635n IPv6/IPsec Print Server |
| J7934G | HP Jetdirect 620n Fast Ethernet Print Server |
| J8007G | HP Jetdirect 690n IPv6/IPSec 802.11g Wireless Print Server |
| J8021A | HP Jetdirect ew2500 802.11b/g Wireless Print Server |

Service & support

| | |
|-----------------|---|
| UJ516A/E | HP Care Pack, Next Business Day On-site, 3 years |
| UJ522E | HP Care Pack, Same Business Day On-site within 4 hours 13x5, 3 years |
| UJ517E | HP Care Pack, Next Business Day On-site, 4 years |
| UJ518E | HP Care Pack, Next Business Day On-site, 5 years |
| UJ525PE | HP Care Pack, Post Warranty Next Business Day On-site, 1 year |
| UJ527PE | HP Care Pack, Post Warranty Same Business Day On-site within 4 hours 13x5, 1 year |
| UK661E | HP Care Pack, Next Business Day On-site, 3 years (3 kits limit) |
| UC742E | HP Care Pack Installation and Network configuration for 1 network printer |

For a complete list of supplies, accessories and services, please refer to <http://www.hp.com>



Technical specifications

| | | | |
|--|---|--|----------------------------|
| Print technology | Monochrome Laser | | |
| Print speed | A4black: Up to 60 ppm First page out Black: As fast as 8.5 sec (from ready mode) Exact speed varies depending on the system configuration, software program, and document complexity | | |
| Processor | 540 MHz, Motorola ColdFire® V5x | | |
| Memory | 128 MB, Expandable to 640 MB through one 144-pin 32-bit DDR2 DIMM slot | | |
| Print resolution | Up to 1200 x 1200 dpi | | |
| Print quality | HP REt, HP FastRes 1200, HP ProRes 1200, HP 600 dpi, Hp 300 dpi | | |
| Printer languages | HP PCL 6, HP PCL 5e, HP Postscript level 3 emulation, direct PDF (v 1.4) printing (Printer memory 128 MB required, 192 MB recommended) | | |
| Economical printing | Return to PowerSave mode after print job due to instant-on fuser technology (saves electricity), N-up printing and two-sided printing (saves paper), Draftmode (saves toner) | | |
| Typefaces/fonts | 80 HP font set (plus Greek, Hebrew, Cyrillic, Arabic) | | |
| Recommended Monthly Page Volume | 5000 to 20000 | | |
| Duty cycle (monthly, A4) | Up to 275000 pages | | |
| Print margins | top: 6 mm, left: 5 mm, right: 5 mm, bottom: 6 mm | | |
| Media handling | Input | Capacity | Weight |
| | Tray 1 | sheets: 100, envelopes: 10 | 60 to 200 g/m ² |
| | Tray 2 | sheets: 500 | 60 to 120 g/m ² |
| | Tray 3 (optional) | sheets: 500 | 60 to 120 g/m ² |
| | Output: | Envelopes: Up to 10. Transparencies: Up to 600 | |
| | Duplex printing: | P4515n: Automatic (optional); P4515x: Automatic (standard) | |
| Media types | Paper (bond, colour, letterhead, plain, preprinted, prepunched, recycled, rough), envelopes, labels, cardstock, transparencies | | |
| Interface and connectivity | Embedded Jetdirect (Gigabit Ethernet) print server, 1 Hi-Speed USB 2.0, 1 EIO slot, 1 external and 2 internal Host USB 2.0-like ports for 3rd party connection, optional: HP Jetdirect internal print servers; HP Jetdirect external print servers; HP wireless print servers; HP Secure High Performance EIO Hard Disk J8019A (CPE OZ firmware of 10.1 or higher required). For more information on available HP networking solutions visit http://www.hp.com/go/jetdirect | | |
| Operating systems compatibility | Microsoft® Windows® 2000, XP Home, XP Professional, Server 2003; Certified for Windows Vista®; Mac OS X v10.2, v10.3 or higher Optional: Mac OS X v10.5, OS/2, UNIX, linux, HP OpenVMS, Most recent printer drivers and software for all supported operating systems available at http://www.hp.com/support/hpljp4510series ; if no access to the Internet, see support flyer that came in printer box | | |
| Network operating systems compatibility | Via an HP Jetdirect print server: Microsoft® Windows® 2000, Server 2003, XP, 2003 64-bit, XP 64-bit; Windows Vista®, Windows Vista® 64-bit (For Microsoft® IPv6 compatible with Microsoft® Windows® 2003, XP, and Windows Vista®); Novell® 5.1 and later; Mac OS X v10.2, v10.3, v10.4 and later; RED HAT Linux 7.x and later; SUSE Linux 8.x and later; HP-UX 10.20, 11.x, 11.1; Solaris® 2.5 and later (SPARC® systems only); IBM® AIX 3.2.5 and later; MPE-iX; Citrix® MetaFrame Server; Microsoft® Windows® Terminal Services, optional: Microsoft® Windows® 2000, XP Home, XP Professional, Server 2003; Apple Mac OS X v10.2, v10.3, v10.4, v10.5 | | |
| Minimum system requirements | Microsoft® Windows® 2000: 133 MHz processor, 64 MB RAM, CD-ROM drive; Microsoft® Windows® XP Home and Professional: 233 MHz processor, 64 MB RAM, CD-ROM drive; Microsoft® Windows® Server 2003: 550 MHz processor, 128 MB RAM (standard edition), 220 MB of free hard disk space for Microsoft® Windows®, 1 GHz processor, 512 MB RAM (Windows Vista® Ready, check user guide for minimum hard drive space); CD-ROM drive or Internet connection, IEEE 1284-compliant bidirectional parallel port, USB (compatible with USB 1.1 or 2.0 specifications), Mac OS X v10.2 or higher; PowerPC G3, G4, G5, or Intel® Core processor; 160 MB free hard disk space; CD-ROM drive, USB port or IEEE 1284-B compliant parallel port | | |
| Software | Print drivers and installation software on CD-ROM: HP PCL 5e, HP PCL 6, Postscript, Postscript Printer Description files, HP LaserJet Utility (Mac), Macintosh software | | |
| Control panel | 2.29 x 5.33 cm 4-Line LCD display, 3 light-emitting diode (LED) indicator lights (Ready, Data, Attention), buttons (10 numeric keys, Information, Return, Stop/Cancel, OK, Toggle up/down) | | |
| Printer management | HP Web Jetadmin, HP LaserJet Utility, HP Embedded Web Server, HP Easy Printer Care | | |
| Power | Requirements: Input voltage 100 to 127 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz); 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz). Consumption: 910 watts maximum (active/printing), 20 watts maximum (ready), 15 watts maximum (sleep), 0 watts maximum (off). Typical electricity consumption (TEC) 5.049 kWh/Week | | |
| Dimensions (w x d x h) | Out of package: P4515n: 419 x 450 x 393 mm; P4515x: 419 x 508 x 546 mm Packaged: P4515n: 570 x 535 x 500 mm; P4515x: 790 x 600 x 540 mm | | |
| Weight | Out of package: P4515n: 25.82 kg; P4515x: 35.12 kg Packaged: P4515n: 27 kg; P4515x: 36 kg | | |
| Operating environment | Operating temperature: 15 to 32.5° C. Recommended operating temperature: 10 to 32° C. Operating humidity: 10 to 80% RH. Recommended operating humidity: 10 to 80% RH. Storage temperature: 0 to 35° C. Storage humidity: 10 to 95% RH. Noise level per ISO 9296: Sound power: LwAd 7.4 B(A) (active/printing), 4.8 B(A) (ready). Sound pressure: LpAm60 dB(A) (active/printing), 31 dB(A) (ready) | | |
| Product certifications | Safety certifications: IEC 60950-1 (International), EN 60950-1+A11 (EU), IEC 60825-1+A1+A2, UL/cUL Listed (US/Canada), GS license (Europe), EN 60825-1+A1+A2 (Class 1 Laser/LED Device) GB4943-2001, Low Voltage Directive 2006/95/EC with CE Marking (Europe); other safety approvals as required by individual countries | | |
| Warranty | One year on-site warranty. Optional HP Care Pack services available. Warranty and support options vary by product, country and local legal requirements. | | |

<http://www.hp.com/uk>



© Copyright 2008 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP Products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Published in EMEA 10/10 4AA1-8019EEE

