



HP Air Release Adhesive Gloss Cast Vinyl creates high-impact, long-term applications on curved and flat surfaces. This competitively priced media is built to last and provides reliable printing, durability and clean removal.

Ideal for Print Service Providers who produce signage applications, in particular vehicle and fleet graphics applications.

Get real value with this competitively priced adhesive gloss cast vinyl. You get reliable HP performance from printing to installation to removal. And you get long-lasting outdoor durability.

Enjoy the ease of working with this opaque permanent adhesive vinyl. A special adhesive technology makes it easy to release air during installation and prevents bubbles. With little glue residue, it removes cleanly, even after 5 years.

Gain peace of mind for the life of the application with a new HP Performance Warranty¹ for this media that covers image performance, durability and clean removal with little glue residue.

¹Some warranty limitations apply, see the HP Performance Warranty for HP Air Release Adhesive Gloss Cast Vinyl.

HP Air Release Adhesive Gloss Cast Vinyl

Compatibility

For compatibility information, please refer to the latest Large Format Supplies Compatibility chart on www.hp.com/go/designjet/supplies

For the latest ICC/media profiles, please visit www.hp.com/go/designjet/supplies (click on ICC profiles and select your printer). For non-post script printers see your external RIP vendor.

Product specifications

| | | | |
|--|---|-------------------|------------------|
| Weight | 260 g/m ² (with liner), 100 g/m ² (without liner) per ISO 536 Test Method | | |
| Thickness | 9.5 mil/240 microns (with liner), 2 mil/50 microns (without liner) per ISO 534 Test Method | | |
| Opacity | 100% (with liner) per TAPPI T-425 Test Method; 99% (without liner) per TAPPI T-426 Test Method | | |
| Brightness | 76% (with liner) per TAPPI T-452 Test Method | | |
| Whiteness | 82% (with liner) per CIE Ganz 82 Test Method | | |
| Lamination | Yes (cold) | | |
| Finish | Gloss | | |
| Adhesive backing | Permanent Acrylic | | |
| Operating temperature | 15 to 30° C | | |
| Operating humidity | 30 to 70% RH | | |
| Lightfastness (Outdoor) Low-solvent Ink | 3 years un laminated, 5 years laminated. For details: http://www.hp.com/go/supplies/printpermanence . | | |
| Flame Retardant | No | | |
| Waterfastness | Yes | | |
| Dry time | Immediate with Latex inks, 10 minutes with Low-solvent inks | | |
| Shelf time | 1 year, unopened in original packaging | | |
| Storage temperature | 20 to 24° C | | |
| Storage humidity | 45 to 55% RH | | |
| Country of origin | Product of Italy | | |
| Ordering information | Product Numbers | Roll sizes | UPC codes |
| | CG934A | 1 524 mm x 45.7 m | 884962102138 |
| | CG935A | 1 372 mm x 45.7 m | 884962102145 |
| | CG936A | 1 372 mm x 91.4 m | 884962102152 |
| Warranty | HP warrants to you, the end user customer, that HP Air Release Adhesive Gloss Cast Vinyl will be free from defects in materials and workmanship after the date of purchase for a period of five years in most display environments. (Product exposed to substantial amounts of extreme direct sunlight will be subject to a four year warranty period.) For complete warranty information, visit: http://www.hp.com/go/HPMediaWarranties | | |

© 2009 Hewlett-Packard Development Company, L.P.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For more information about HP Large Format Printing Material, visit
<http://www.hp.com/go/designjet/supplies>

Published in EMEA 4AA2-9437 EEE

