



HP LaserJet Pro M1530 Multifunction Printer series

Ideal for business users with small and medium offices who need to print two-sided documents, and scan, copy and fax from a cost-effective, networked MFP that can also receive print jobs from mobile devices[1].



Do more with a fast, networked MFP and two-sided printing.

- Stay productive: print at up to 25 ppm A4 and get a first page out in as fast as 8.5 seconds with Instant-on Technology[2].
- Share printing resources on a network with built-in 10/100 Ethernet connectivity.
- Use the 35-page automatic document feeder to print two-sided pages, or to copy and fax multiple-page documents.
- Save paper and time: fax documents directly to and from a PC and desktop applications, and control access to the faxing features with assigned PINs.

Print from anywhere[1] and use intuitive features.

- HP ePrint[1] enables you to print when and where you like, using a mobile phone, notebook PC or other mobile device.
- Simplify printing tasks with an intuitive and easy to navigate control panel and LCD. Use ID Copy to create a one-sided copy of a two-sided ID.
- Easily find and purchase cartridge replacements with HP SureSupply[3] and install them without hassle.
- Use embedded HP tools for easy MFP configuration, operation and maintenance.



Create a variety of high-quality business documents in multiple sizes.

- Print professional documents with bold text and sharp images, using Original HP LaserJet print cartridges for consistently excellent quality every time you print.
- Achieve improved print quality with HP FastRes 1200: bring your documents to life with fine details, solid fills and smooth transitions.
- Add variety to your documents: the 10-sheet priority tray and 250-sheet paper tray enable you to use a variety of media sizes and types.

ECO HIGHLIGHTS

- Reduce energy by up to 50% with Instant-on Technology[1].
- Save up to four times the energy with Instant-on Copy[2].
- Reduce clutter and waste - scan, store and share documents digitally.

ENERGY STAR® Qualified

[1] Energy savings based on HP testing using the ENERGY STAR® program's Typical Electricity Consumption (TEC) method on HP LaserJet products with Instant-on Technology vs. top competitive models as of March 2009.

[2] When compared with fluorescent tubes, Instant-on Copy with LED technology drops energy use by 4 times in idle mode and 1.4 times in copy mode.

Please recycle your computing hardware and printing supplies. HP asset management and recycling services make responsible disposal easy.

www.hp.com/ecosolutions



[1] May require an Internet connection to the printer. Feature works with any Internet and e-mail-capable device and requires a firmware upgrade. For details, www.hp.com/go/ePrintCenter.

[2] Measured using ISO/IEC 24734, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

[3] Programme features and availability may vary by country. For more information, visit www.hp.com/learn/suresupply.





HP LaserJet Pro M1530 Multifunction Printer series

TECHNICAL SPECIFICATIONS

Functions	Print, copy, scan, fax
Standard Printer Languages	HP PCL 6, HP PCL 5, HP postscript level 3 emulation
Print Resolution	Black (best): Up to 600 x 600 dpi (1200 effective dpi with HP FastRes 1200); Black (normal): Up to 600 x 600 dpi (1200 effective dpi with HP FastRes 1200)
Print Technology Resolution	HP REt, HP FastRes 1200
Print Technology	Laser
Print Speed	Black (A4): Up to 25 ppm; First Page Out Black: As fast as 8.5 sec
Number Of Print Cartridges	1 (black)
Printer Smart Software Features	Duplex printing; HP Universal Print Driver and HP Web Jetadmin supported
Duty Cycle	Monthly, A4: Up to 8000 pages
Recommended Monthly Page Volume	500 to 2000
Print margins	top: 4 mm, left: 4 mm, right: 4 mm, bottom: 4 mm
Twain Version	Version 1.9
Color Scanning	Yes
Scan Type	Flatbed, ADF
Scan Resolution	Enhanced: Up to 19200 dpi; Hardware: Up to 1200 x 1200 dpi; Optical: Up to 1200 dpi
Scan Speed	Up to 15 ppm; Black (normal): Up to 15 ppm; ADF: Up to 15 ppm
Gray Scale Levels/Bit Depth	256; 24-bit
Scan File Format	JPEG, TIF, BMP, GIF, PDF, PNG
Scan Input Modes	Front control panel scan, Copy or Fax buttons, scanning via HP LaserJet Scan (Windows®), HP Director (Macintosh) or TWAIN-compliant or WIA-compliant software.
Scan Size Maximum	Flatbed: 216 x 297 mm
Copy Resolution	Black (text and graphics): Up to 600 x 600 dpi; Colour (text and graphics): Up to 600 x 600 dpi (1200 effective dpi with HP FastRes 1200)
Copy Speed	Black (A4): Up to 25 cpm
Maximum Number Of Copies	Up to 99 copies
Copier Resize	25 to 400%
Fax Resolution	Black and White, Best Mode: Up to 300 x 300 dpi (halftone enabled); Black and White, Standard Mode: 203 x 98 dpi
Fax Speed	3 sec per page
Fax Features	Fax Memory (A4): Up to 400 pages; Auto Fax Reduction Supported: Yes; Auto-Redialing: Yes; Fax Delayed Sending: Yes; Distinctive Ring Detection Supported: Yes; Fax Forwarding Supported: Yes; Fax Phone TAM Interface Supported: Yes; Fax Polling Supported: Yes (poll to receive only); Fax Telephone Mode Supported: Yes; Junk Barrier Supported: Yes; Maximum Speed Dialing Numbers: Up to 120 numbers (119 group dials); PC Interface Supported: Yes; Remote Retrieval Capability Supported: No; Telephone Handset Supported: No
Modem	33.6 kbps
Standard Connectivity	1 Hi-Speed USB 2.0 port; 1 10/100 Ethernet network port
Network Capabilities	Network Ready: Standard (built-in Ethernet)
Control Panel	2-line LCD text display; Buttons (Alphanumeric, Navigational); Copy buttons (Start copy, Reduce/Enlarge, Lighter/Darker, Copy menu, Number of copies); Fax buttons (Start fax, Phone book, Fax menu, Redial, Speed Dial); LED indicator lights (Setup, Left, Ok, Right, Back, Cancel)
Display	2-line LCD (text) display
Maximum/Standard Memory	128 MB
Processor Type/Speed	Freescale Coldfire® V5X processor; 500 MHz
Duplex Print Options	Automatic (standard)
Media Type And Capacity, tray 1	ADF: sheets: 35; Tray 1: sheets: 250
Media Types Supported	Paper (heavy, letterhead, light, plain, preprinted, prepunched, recycled, rough), envelopes, transparencies, labels, postcards
Media Weight	Tray 1: 60 to 163 g/m ²
Custom Media Sizes	Priority Tray: 76 x 127 to 216 x 356 mm; 250-sheet Tray 2: 76 x 187 to 216 x 356 mm
Auto Document Feeder Capacity	Standard, 35 sheets
Print Handling	250-sheet input tray, 1-sheet priority tray, 35-sheet Automatic Document Feeder (ADF), 100-sheet output bin Input Capacity: Up to 250 sheets, Up to 10 envelopes Output Capacity: Up to 100 sheets, Up to 10 envelopes, Up to 10 sheets transparencies
Power	Power Supply Type: Built-in power supply Power Requirements: Input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz), 2.9 A Power Consumption: 445 watts active, 0.2 watts off, (Auto-Off) powersave, 4.7 watts standby Typical Electricity Consumption (TEC) Number: 1.386 kWh/Week
Software Included	Windows®: HP Installer/Uninstaller, HP PCL 6 print driver, HP WIA Scan Driver, HP TWAIN Scan Driver, HP Scan, HP Fax Setup Wizard, HP Send Fax, HP Fax Print Driver, Readiris Software; Mac: HP Installer/Uninstaller, HP PS driver, HP Scan, HP Setup Assistant, HP Fax Print Driver, HP Ink Widget, HP Utility, Readiris Software

Compatible Operating Systems	Full software installs supported on: Windows® 7 32-bit and 64-bit, Windows® Vista 32-bit and 64-bit, Microsoft® Windows® XP 32-bit (SP2 or higher); Driver only installs supported on: Microsoft® Windows® Server 2003 32-bit (SP3 or higher), Server 2008 32-bit and 64-bit; Mac OS X v10.5.8, v10.6; Linpus Linux (9.4, 9.5), RED HAT Enterprise Linux 5.0 (supported with a pre-built package); SUSE Linux (10.3, 11.0, 11, 11.1, 11.2), Fedora™ (9, 9.0, 10, 10.0, 11.0, 11, 12, 12.0), Ubuntu® (8.04, 8.04.1, 8.04.2, 8.10, 9.04, 9.10, 10.04), Debian (5.0, 5.0.1, 5.0.2, 5.0.3) (supported by the automatic installer); HPUX 11 and Solaris® 8/9
Minimum System Requirements	PC: Windows® 7, Windows Vista®: 1 GHz 32-bit (x86) or 64-bit (x64) processor, 1 GB RAM (32-bit) or 2 GB RAM (64-bit), 200 MB free hard disk space, CD/DVD-ROM or Internet, USB or Network port; Microsoft® Windows® XP (32-bit) Service Pack 2: Pentium® 233 MHz processor, 512 KB RAM (32-bit) or 2 GB RAM (64-bit), 200 MB free hard disk space, CD/DVD-ROM or Internet, USB or Network port; MAC: Mac OS X v10.5.8, v10.6; PowerPC G4, G5, or Intel® Core Processor; 256 MB RAM; 300 MB free hard disk space; CD/DVD-ROM or Internet; USB or Network port
Acoustics	Acoustic Power Emissions: 6.5 B(A)
Operating Environment	Operating Temperature Range: 15 to 32.5° C Recommended Operating Temperature: 17.5 to 25° C Storage Temperature Range: -20 to 40° C Non-Operating Humidity Range: 10 to 90% RH Operating Humidity Range: 10 to 80% RH Recommended Humidity Operating Range: 30 to 70% RH
Product Certifications	CISPR 22: 2005 +A1/EN 55022: 2006 +A1 Class B, EN 61000-3-2: 2006, EN 61000-3-3: 1995+A1 +A2, EN 55024: 1998+A1+A2, FCC Title 47 CFR, GB9254-1998, EMC Directive 2004/108/EC with CE Marking (Europe), other EMC approvals as required by individual countries; Safety certifications: IEC 60950-1 (International); EN 60950-1+A11 (EU); IEC 60825-1+A1+A2; GS License (Europe); EN 60825-1+A1+A2 (Class 1 Laser/LED Device); Low Voltage Directive 2006/95/EC with CE Marking (Europe); other safety approvals as required by individual countries; ENERGY STAR: Yes; Telecom: ES 203 021, R&TTE Directive 1999/5/EC (Annex II) with CE Marking (Europe); FCC Part 68; other Telecom approvals as required by individual countries
Product Dimensions	w x d x h: 441 x 343 x 373 mm
Product Weight	11.7 kg
What's In The Box	CE538A: HP LaserJet M1536dnf MFP; HP LaserJet Introductory Black Print Cartridge; control panel overlay; ADF input support; CDs containing device software and electronic User's Guide; Getting Started Guide; Support flyer; power cord(s); Telecom Fax cable
Warranty	One-year limited warranty. Warranty and support options vary by product, country and local legal requirements.
Country Of Origin	Product of China
Accessories	Q6264A HP Hi-Speed USB Cable (6 ft./1.8 m)
Supplies	CE278A HP LaserJet CE278A Black Print Cartridge Average cartridge yields 2100 standard pages. Declared yield value in accordance with ISO/IEC 19752. CHP110 HP Office Paper-500 sht/A4/210 x 297 mm CHP210 HP Printing Paper-500 sht/A4/210 x 297 mm CHP310 HP LaserJet Paper-500 sht/A4/210 x 297 mm
Service And Support Options	UH761E HP Care Pack, Exchange Service (standard turn around time), 3 years UH757E HP Care Pack, Next Business Day Exchange Service, 3 years UH764E HP Care Pack, Return to Depot Exchange Service, 3 years (UH761E: Austria, Belgium, Denmark, Finland, France, Germany, Ireland, Italy, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland, UK. UH757E: Austria, Belgium, Denmark, Finland, France, Germany, Ireland, Italy, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland, UK, Czech Republic, Greece, Hungary, Poland, Slovakia. UH764E: Baltics, Bulgaria, Czech Republic, Dom Tom, EEM, Greece, Hungary, Israel, Malta, MEMA, Moldova, Poland, Romania, South Africa, Russia, Slovakia, Slovenia, Turkey)

Count on dependable support to create the best image possible. We can help you enhance your printing and imaging environment, protect your IT investment, and grow your business—with expert support that's affordable, personal, and tailored to your needs through HP Care Pack Services.

For more information, visit our website at <http://www.hp.com>

HP LaserJet Pro M1530 Multifunction Printer series

© Copyright 2010 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. All brand and product names are trademarks or registered trademarks of their respective companies. The information contained in this document is subject to change without notice.

Published in EMEA September 2010 4AA3-1031EEE