



HP Designjet T1500 ePrinter series

Newly designed, two-roll, web-connected ePrinter for demanding teams



Innovative user experience

- Eliminate the output clutter—get flat, collated prints thanks to the integrated output stacking tray
- Gain control—monitor media rolls, view printer status on the touchscreen, and track jobs during printing
- Load two paper rolls effortlessly—even when seated—with front loading and automatic paper-roll alignment
- Print up to A0/E with a compact, 36-inch printer designed with a flat surface for quick checking of your printouts

Top performance in multi-user environments

- Help cut downtime—print multiple jobs on different media types and sizes with two rolls and smart switching
- Manage job queues, track print costs, print borderless¹ images, get what you see with true print previews
- Get dark blacks, true neutral grays, and vivid colours with six Original HP inks and the HP printhead
- Print complex files fast—one A1/D-size in 21 seconds with a 320-GB hard drive and parallel processing power

Print from virtually anywhere²

- Use your Apple® or Android™ smartphone or tablet to print from virtually anywhere²
- Access and print projects when you're out of the office, using HP Designjet ePrint & Share² or USB printing
- Automatically save copies of your projects to the cloud when you print using HP Designjet ePrint & Share²
- Print without drivers using a USB stick or directly email projects to your HP Designjet T1500 ePrinter²

For more information, please visit hp.com/go/DesignjetT1500

¹ Photo paper is required to print borderless images.

² Requires an HP Designjet ePrint & Share account, Internet connection to the printer, and connected Internet-capable device. When using the HP Designjet ePrint & Share mobile app, a compatible Apple® iOS or Android™ device and Internet connection are required. Data or connection charges may apply. Print times may vary. For more information, visit hp.com/go/eprintandshare.



1. With Aurasma installed, please go to the HP Designjet channel at <http://auras.ma/s/ke25m>
2. Without Aurasma installed, please download it:
 - a. Google Play - <http://auras.ma/s/android>
 - b. Apple Store - <http://auras.ma/s/ios>Once done, go to the HP Designjet channel at <http://auras.ma/s/ke25m>
3. Open the application and point to the image to view the HP Designjet video

Technical specifications

Print	Line drawings ³	21 sec/page on A1/D, 120 A1/D prints per hour on Draft mode	
	Print resolution	Up to 2400 x 1200 optimised dpi from 1200 x 1200 input dpi and Optimisation for Photo Paper selected	
	Margins (top x bottom x left x right)	Roll: 5 x 5 x 5 x 5 mm (0.2 x 0.2 x 0.2 x 0.2 in) (borderless on photo papers) Sheet: 5 x 22 x 5 x 5 mm (0.2 x 0.87 x 0.2 x 0.2 in)	
	Technology	HP Thermal Inkjet	
	Ink types	Dye-based (C, G, M, pK, Y); pigment-based (mK)	
	Ink drop	6 pl (C, M, Y, G, pK); 9 pl (mK)	
	Printheads	1 (C, G, M, mK, pK, Y)	
	Line accuracy	+/- 0.1% ⁴	
	Minimum line width	0.02 mm (0.0008 in) (HP-GL/2 addressable)	
	Guaranteed minimum line width	0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E)) ⁵	
	Media	Handling	Input: two automatic front-loading roll feeds, smart roll switching, sheet feed; Output: integrated output stacking tray (from A4/A to AO/E, with up to 50 A1/D-size capacity), media bin, automatic cutter
		Weight	60 to 328 g/m ²
		Size	Rolls: 279 to 914 mm (11 to 36 in) Sheets: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Standard sheets: A4, A3, A2, A1, AO (A, B, C, D, E)
Thickness		Up to 0.5 mm (19.7 mil)	
Memory	Basic ePrinter:	64 GB (virtual) ⁶	
	PostScript ePrinter:	64 GB (virtual) ⁶ , 320 GB hard disk	
Connectivity⁷	Interfaces (standard)	Gigabit Ethernet (1000 Base-T)	
	Print languages	Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URFL PostScript ePrinter: Adobe PostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URFL	
	Printing paths	Printer driver, HP Designjet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB flash drive, email printing	
	Drivers (included)	HP-GL/2, HP-RTL drivers for Windows® (AutoCAD® optimised); HP PCL 3 GUI driver for Mac OS X; PostScript Windows, Linux, and Mac drivers ⁸	
Dimensions (w x d x h)	Printer	1399 x 916 x 1110 mm (55.1 x 36.1 x 43.7 in)	
	Shipping	1502 x 759 x 775 mm (59.1 x 29.9 x 30.5 in)	
Weight	Printer	88 kg (194 lb)	
	Shipping	116.5 kg (256.3 lb)	
What's in the box	HP Designjet T1500 ePrinter, printhead, ink cartridges, stacking tray, printer stand and media bin, spindles, quick reference guide, setup poster, drivers and utilities DVD, power cord		
Environmental ranges	Operating temperature:	5 to 40°C (41 to 104°F)	
	Storage temperature:	-25 to 55°C (-13 to 131°F)	
	Operating humidity:	20 to 80% RH	
Acoustic	Sound pressure:	47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep)	
	Sound power:	6.5 B(A) (printing); 5.8 B(A) (ready); <1.9 B(A) (sleep)	
Power consumption	< 120 watts (printing), < 260 watts (maximum), < 4 watts (< 7 watts with embedded Digital Front End) (sleep), 0.1 watts (auto-off), 0 watts (off hardswitch)		
	Input voltage (auto ranging)	100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 4.2 A max (peak current)	
Certification	Safety	USA and Canada (CSA certified), EU (LVD and EN60950-1 compliant), Russia (GOST), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KATS)	
	Electromagnetic	Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC)	
	Environmental	ENERGY STAR, WEEE, EU RoHS, China RoHS, REACH, EuP, FEMP, EPEAT Bronze	
Warranty	One-year limited hardware warranty		

Ordering information

Product	CR356A	HP Designjet T1500 36-in ePrinter
	CR357A	HP Designjet T1500 36-in PostScript ePrinter
Accessories	CN538A	HP Designjet 3-in Core Adapter
	COE65A	HP Designjet T9x0/Tx500 36-in Spindle
	CQ654B/CQ654C	HP Designjet HD Scanner
	B3P06A	HP 727 Designjet Printhead
Original HP ink cartridges	B3P17A	HP 727 40-ml Photo Black Designjet Ink Cartridge
	B3P13A	HP 727 40-ml Cyan Designjet Ink Cartridge
	B3P14A	HP 727 40-ml Magenta Designjet Ink Cartridge
	B3P15A	HP 727 40-ml Yellow Designjet Ink Cartridge
	B3P18A	HP 727 40-ml Gray Designjet Ink Cartridge
	C1Q11A	HP 727 69-ml Matte Black Designjet Ink Cartridge
	B3P23A	HP 727 130-ml Photo Black Designjet Ink Cartridge
	B3P19A	HP 727 130-ml Cyan Designjet Ink Cartridge
	B3P20A	HP 727 130-ml Magenta Designjet Ink Cartridge
	B3P21A	HP 727 130-ml Yellow Designjet Ink Cartridge
	B3P24A	HP 727 130-ml Gray Designjet Ink Cartridge
	B3P22A	HP 727 130-ml Matte Black Designjet Ink Cartridge ⁹
	C1Q12A	HP 727 300-ml Matte Black Designjet Ink Cartridge
Original HP large format printing materials	C1861A	HP Bright White Inkjet Paper (FSC® certified) ¹⁰ 914 mm x 45.7 m (36 in x 150 ft)
	C6020B	HP Coated Paper (PEFC™ certified) ¹¹ 914 mm x 45.7 m (36 in x 150 ft)
	C6030C	HP Heavyweight Coated Paper (PEFC™ certified) ¹⁰ 914 mm x 30.5 m (36 in x 100 ft)
	Q1421A	HP Universal Satin Photo Paper ¹¹ 914 mm x 30.5 m (36 in x 100 ft)
	Service and support	U7Z08E
	U7Z11E	HP 3 year Next Business Day Onsite Support with Defective Media Retention
	U7Z88E	HP 3 year 4-hour response, 9x5 Onsite Support
	U7Z91E	HP 3 year 4-hour response, 13x5 Onsite Support
	U7Z94PE	HP 1 year Post Warranty, Next Business Day Onsite Support
	U7Z95PE	HP 1 year Post Warranty Next Business Day Onsite Support with Defective Media Retention
	U7Z99PE	HP 1 year Post Warranty, 4-hour response, 13x5 Onsite Support

HP Designjet Support Services offer solutions for business critical environments — installation, extended support and maintenance, as well as variety of value added services.

For more information, please visit hp.com/go/designjetsupport.

Use Original HP inks and printheads to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimised printing system to provide precise line accuracy as well as dark blacks. For more information, visit hp.com/go/OriginalHPInks.

For the entire HP Large Format Printing Materials portfolio, please see globalBMG.com/hp.

³ Mechanical printing time. Printed in Fast mode, using HP Bright White Inkjet Paper (Bond) and Original HP inks.

⁴ +/-0.1% of the specified vector length or +/-0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on AO/E printing material in Best or Normal mode with HP Matte Film and HP Original HP inks.

⁵ Measured on HP Matte Film.

⁶ Based on 1.5 GB RAM.

⁷ Includes an embedded Jetdirect print server.

⁸ Included with PostScript printers only.

⁹ Available only in Europe, Middle East, and Africa.

¹⁰ FSC® trademark license code FSC®-C017543, see fsc.org. PEFC™ trademark license code PEFC™/29-31-198, see pefc.org. Not all FSC®- or PEFC™-certified products are available in all regions.

¹¹ Can be recycled through commonly available recycling programs.



For more information, please visit hp.com/go/DesignjetT1500

© Copyright 2014 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Adobe and Adobe PostScript 3 are trademarks of Adobe Systems Incorporated. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Windows is a U.S. registered trademark of Microsoft Corporation. PANTONE is the property of Pantone, Inc. Mac and the Mac logo are trademarks of Apple Computer, Inc., registered in the U.S. and other countries.

4AA4-5694EEP, February 2013, Rev. 4

This is an HP Indigo digital print.

