

Data sheet



HP Graphical POS Pole Display

Point of Sale



June 2016

HP Graphical POS Pole Display

The HP Graphical POS Pole Display is a stylish and durable 2-line customer-facing display that delivers clear, easy-to-read text and graphics for displaying product prices and retailer logos and designs. The display also supports complex character sets and a range of languages.

Stylish and functional communicator

Adjustable swivel, tilt and height help you customize the perfect position wherever you need to place the display and create a clearer line of sight between the store associate and customers.

Modern flush-glass, bezel-less design is aesthetically compatible with all HP Retail Systems³ and most HP retail displays.

Familiar compatibility

Get up and running quickly with the industry-standard interface, command modes, and drivers that help ensure out-of-the-box compatibility with your current installed retail systems.

Smart design

To help prevent damages, the electronic components are contained in the display panel at the top of the pole.

The compact, weighted base fits into a range of tight spaces and stays in place on the counter. A two-hole screw pattern on the base of the display offers additional security for bolting the display to the counter or work space.¹

For more information about the HP Graphical POS Pole Display, please visit hp.com/go/POS.

1 Mounting hardware sold separately

3 The HP rp5800 retail system must be configured with a 12 volt PUSB port to provide power and data.

HP Graphical POS Pole Display

Specifications

Display Type	Vacuum Fluorescent Display, Blue Green
Brightness	350-700 cd/m ² (max)
Character number/font	20 x 2; 20 x 2 for 16 x 16 font, 10 x 1 for 32 x 32 font, 320 x 32 for graphics
Character type	95 Alphanumeric, 32 International Characters
Panel Dimensions LxWxH	226 x 40.25 x 72mm
Support (pole) Dimensions LxWxH	3 pole sections included: 130mm each
Rectangular Base Dimensions LxWxH	180mm x 140mm x 24mm
Interface/Connection	12V Powered USB
Command codes	ADM788, AEDEX, CD5520, DSP880, EMAX, Epson, LD540, Logic Control, UTC/P / UTC/S
Viewing Angle	90 degrees Max
Horizontal Rotation	180 degrees Max
Cable length	5.35 ft. (1.63m)
Weight	586.9g (VFD and cable) 50.8g (1 pole) 1.06kg (rectangular base)
Color	HP Black
Agency certifications	CE, FCC Class B, Canadian ICES-003 Class B, MIC, WEEE, C-Tick, WHQL
Drivers	Windows native, OPOS, JPOS
Operating Systems (compatible with)	Windows 10 (32-bit and 64-bit)* Windows 10 IoT (32-bit and 64-bit)* Windows 7 Professional (32-bit and 64-bit)** Windows Embedded POSReady 2009 Windows Embedded POSReady 7 (32-bit and 64-bit)
Warranty	Three (3) year limited warranty with advance exchange when purchased from HP. Additional HP Care Pack Services options are available to extend warranty coverage. HP Care Pack ² Services extend service contracts beyond the standard warranties. To choose the right level of your HP product, use the HP Care Pack Services Lookup Tool at hp.com/go/lookuptool . Additional HP Care Pack Services information by product is available at hp.com/hps/carepack .
Compatibility	The HP Graphical POS Pole Display is compatible with all HP Retail Systems. ³
Option kit includes:	HP Graphical POS Pole Display, Point of Sale System Software and the Options Warranty Manual

2 Service levels and response times for HP Care Pack Services may vary depending on your geographic location. Service starts from date of hardware purchase. Restrictions and limitations apply. See hp.com/go/cpc for details.

3 The HP rp5800 retail system must be configured with a 12 volt PUSB port to provide power and data.

Sign up for updates

hp.com/go/getupdated

© Copyright 2013 - 2016 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. All other trademarks are the property of their respective owners.

4AA4-6670ENW, June 2016

