HP ElitePad Rugged Case



Sophistication. Durability. We've got you covered.

Help protect your HP ElitePad wherever you work with a business rugged designed for use in busy, high-traffic environments.



- The case's cutouts keep all of the HP ElitePad's buttons, controls, and connectors easily accessible.
- Comfortably hold the HP ElitePad in one hand with the case's convenient back hand strap and write and input data on the screen with the other hand.
- Expand what you can do with a suite of accessories designed specifically for the HP ElitePad and turn a true business tablet into a total business solution.
- Get the peace of mind of a one-year limited warranty.
- Note: The HP ElitePad Rugged Case passes Mil Spec 810G Spec (Drop: Method 516.6 Proc IV; Wind/Rain: Method 506.5 Proc I)*

HP ElitePad Rugged Case





Compatibility	HP ElitePad
Dimensions	Out of Package: 275.85 x 192.71 x 22.95 mm Dimensions (case or master carton, metric): 330 x 425 x 405 mm Case or master carton quantity: 10 Minimum order quantity: 10 Count of layers in pallet: 8 Quantity per Pallet: 400 Packed: 370 x 200 x 60 mm
Weight	Out of Package: 600 g Packed
Warranty	One-year limited warranty. Technical support is available seven days a week, 24 hours a day, by phone, as well as online support forums. Certain restrictions and exclusions apply.
Additional information	P/N: H4R89AA UPC/EAN code: 887111609533
Country of Origin	China
What's in the box	HP ElitePad Rugged Case; Stand; Hand strap; Shoulderstrap; Documentation



The product could differ from the images shown. © 2013 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

^{*}Test results are not a guarantee of future performance under these test conditions.