

# HP Desktop Mini DVD ODD Expansion Module



## Expand your storage

Add a DVD DVD-Writer to your HP Desktop Mini PC with HP Desktop Mini DVD ODD Expansion Module.<sup>1</sup>

## Easy assembly

Slide and hook the Module to the PC with the included screws, connect with the included USB 3.0 cable, and use the integrated VESA mount to place the Module wherever you need it.

## Increase your storage and your flexibility

Quickly and easily back up your files to DVD, and access media and data from DVDs and CDs.

## Make it secure

Physically secure your HP Desktop Mini<sup>2</sup> to the Module with the security screw included in each Kit.

## Mix and match

Use this Module alongside another Module, or with the Security Sleeve, to create a custom solution for your HP Desktop Mini.<sup>2</sup>

## Award-winning support

Rest easy with a one-year limited warranty.

<sup>1</sup> Each sold separately. See product QuickSpecs for exact configurations.

<sup>2</sup> Each sold separately. See product QuickSpecs for exact configurations.

## HP Desktop Mini DVD ODD Expansion Module



<b>Model number</b>	K9Q83AA	
<b>Dimensions (w x l x d)</b>	0.9 x 7 x 6.9 in (22.8 x 177 x 174.6 mm)	
<b>Weight</b>	712g (25.12oz)	
<b>Color</b>	Jack Black	
<b>Host Interface</b>	USB 3.0 Type B female connector	
<b>Disc Capacity</b>	Up to 8.5 GB DVD double-layer or 4.7 GB standard single-layer	
<b>Write / Read speeds</b>	DVD+R	Up to 8X
	DVD+RW	Up to 8X
	DVD+R DL	Up to 6X
	DVD-R DL	Up to 6X
	DVD-R	Up to 8X
	DVD-RW	Up to 6X
	CD-R	Up to 24X
	CD-RW	Up to 24X
<b>Connectors Single output</b>	USB 3.0 Type B	
<b>Access times (typical reads, including setting)</b>	Random	DVD-ROM: 160 ms (typical), CD-ROM: 140 ms (typical)
	Full Stroke	DVD-ROM: 280 ms (typical), CD-ROM: 280 ms (typical)
<b>Power</b>	Source	USB 3.0 Type B female connector
	DC Power Requirement	5 VDC $\pm$ 5%-100 mV ripple p-p
	DC Current	5 VDC - 1000 mA typical, 1600 mA maximum
<b>Environmental (all conditions non-condensing)</b>	Temperature (operating)	41° to 122° F (5° to 50° C)
	Relative Humidity (operating)	10% to 80%
	Maximum Wet Bulb Temperature (operating)	86° F (30° C)
<b>VESA mount</b>	Yes, 100mm	
<b>Option kit contents</b>	3 4mm ladder screws, 3 8mm ladder screws, 1 29mm secured torx screw, 1 54mm secured torx screw, 1 29mm torx screw, 1 54mm torx screw, 1 50mm USB 3.0 Type B USB to Type A cable, 1 80mm USB 3.0 Type B USB to Type A cable, Installation guide, Warranty	
<b>Expansion Module Overview</b>	These modules can be mounted to the DM directly and to another module with screws in the kit that allow the module to slide into place. All modules can be used with the PC that is wrapped in the Security/Dual VESA Sleeve, and all can be mounted with standard VESA 100mm requirements. Both options can be secured in place with a tamper-resistant screw. They are powered by a single USB connection cable. The HP 260 and ProDesk 400 can support 2 expansion modules at a time using 2 USB Type A ports on the back of the unit	
<b>Compatibility</b>	HP 260 Desktop Mini, HP ProDesk 400 Desktop Mini, HP ProDesk 600 Desktop Mini, HP EliteDesk 705 Desktop Mini, HP EliteDesk 800 Desktop Mini	

**Sign up for updates**  
[hp.com/go/getupdated](http://hp.com/go/getupdated)



Share with colleagues



Rate this document

© Copyright 2016 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

