

Data sheet

HP Pro x2 612 Rugged Case



Maximum tablet protection, minimalist design.

Carry your HP Pro x2 612 into the daily fray without worry. The sturdy and stylish HP Pro x2 612 Rugged Case helps shield your tablet from bumps without adding extra bulk and is designed to pass MIL-STD 810G testing¹.

Handy cutouts.

Keep all of your tablet's buttons, controls, cameras, and connectors easily accessible. Block unused ports as needed, or keep them clean, with the included plugs.² Store your pen in the case's pen holder.

Ready to carry or recline.

Use the padded shoulder strap to keep your hands free. Flip the case open and adjust the easel kickstand up to 60 degrees for comfortable interaction with the tablet and keyboard on a desk or table.

Get comfortable.

Find your most comfortable setting for holding the case with the 360-degree rotatable elastic hand strap. Switch to the wipeable hand strap as your preference or workplace requires.

¹MIL-STD 810G testing is pending and is not intended to demonstrate fitness for U.S. Department of Defense contract requirements or for military use. MIL-STD 810G test results are not a guarantee of future performance under these test conditions. Damage under the MIL-STD 810G test conditions or any accidental damage requires an optional HP Accidental Damage Protection Care Pack.

²USB-C™ port cannot be blocked.

Specifications



HP Pro x2 612 Rugged Case


Model number	Z7T26AA								
Dimensions	12.8 x 9 x 0.75 in (325 x 229 x 19 mm)								
Weight	<table border="0"> <tr> <td>Rugged case</td> <td>0.93 lb (420g)</td> </tr> <tr> <td>Shoulder strap w/dog clip</td> <td>0.23 lb (103.3g)</td> </tr> <tr> <td>TPU hand strap</td> <td>0.09 lb (41g)</td> </tr> <tr> <td>Elastic hand strap</td> <td>0.01 lb (5g)</td> </tr> </table>	Rugged case	0.93 lb (420g)	Shoulder strap w/dog clip	0.23 lb (103.3g)	TPU hand strap	0.09 lb (41g)	Elastic hand strap	0.01 lb (5g)
Rugged case	0.93 lb (420g)								
Shoulder strap w/dog clip	0.23 lb (103.3g)								
TPU hand strap	0.09 lb (41g)								
Elastic hand strap	0.01 lb (5g)								
Shoulder Strap Dimensions	<table border="0"> <tr> <td>Length</td> <td>Shortest 41.73 in (106cm)</td> </tr> <tr> <td>(Adjustable)</td> <td>Longest 65.35 (166cm)</td> </tr> <tr> <td>Width</td> <td>2.76 in (70mm)</td> </tr> <tr> <td>Thickness</td> <td>0.24 in (6mm)</td> </tr> </table>	Length	Shortest 41.73 in (106cm)	(Adjustable)	Longest 65.35 (166cm)	Width	2.76 in (70mm)	Thickness	0.24 in (6mm)
Length	Shortest 41.73 in (106cm)								
(Adjustable)	Longest 65.35 (166cm)								
Width	2.76 in (70mm)								
Thickness	0.24 in (6mm)								
TPU hand strap	<table border="0"> <tr> <td>Length</td> <td>13.46 in (341.97mm)</td> </tr> <tr> <td>Width</td> <td>1.93 in (49mm)</td> </tr> <tr> <td>Thickness</td> <td>0.31 in (8mm)</td> </tr> </table>	Length	13.46 in (341.97mm)	Width	1.93 in (49mm)	Thickness	0.31 in (8mm)		
Length	13.46 in (341.97mm)								
Width	1.93 in (49mm)								
Thickness	0.31 in (8mm)								
Elastic hand strap	<table border="0"> <tr> <td>Length</td> <td>9.11 in (231.4mm)</td> </tr> <tr> <td>Width</td> <td>1.61 in (41mm)</td> </tr> <tr> <td>Thickness</td> <td>0.08 in (2mm)</td> </tr> </table>	Length	9.11 in (231.4mm)	Width	1.61 in (41mm)	Thickness	0.08 in (2mm)		
Length	9.11 in (231.4mm)								
Width	1.61 in (41mm)								
Thickness	0.08 in (2mm)								
Materials	PC, TPU								
Option kit contents	HP Pro x2 612 Rugged Case, shoulder strap, TPU hand strap, elastic hand strap, port plugs, documentation								
Compatibility	HP Pro x2 612 G2 Tablet HP Pro x2 612 G2 Tablet with Collaboration Keyboard								

Sign up for updates
hp.com/go/getupdated





 Share with colleagues


 Rate this document

© Copyright 2017 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum.

4AA6-8986ENW, March 2017, Rev 1.

