HP PageWide Pro 772dw Multifunction Printer Specifications Table

Functions / Multitasking Supported	Print, copy, scan, fax / Yes
Print Speed[5 6]	**Black (ISO)**: Up to 35 ppm; **Color (ISO)**: Up to 35 ppm; **First Page Out Black**: As fast as 8.25 sec; **First Page Out Color**: As fast as 8.25 sec; **Black (Draft)**: Up to 55 ppm; **Color (Draft)**: Up to 55 ppm
Print Resolution	**Black (best)**: Up to 1200 x 1200 optimized dpi from 600 x 600 input dpi (on Unspecified, Plain, HP Premium Presentation Matte, and HP Brochure Matte); **Color (best)**: Up to 2400 x 1200 optimized dpi from 600 x 600 input dpi (on HP Advanced Photo Papers)
Print Technology	HP PageWide Technology with pigmented inks
Printer Drivers Included	Windows PCL 6 Discrete; Mac PS; Windows HP UPD (PCL 6, PS); Linux; UNIX; SAP
Print Cartridges Number	4 (1 each black, cyan, magenta, yellow)
Borderless Printing	No
Standard Print languages	HP PCLXL (PCL6), PCL5, native PDF, HP Postscript Level 3 emulation, native Office, PJL, JPEG, PCLM
Printer Smart Software Features	HP Mobile Apps, Google Cloud Print v2, HP EasyColor, print preview, automatic two-sided printing, print multiple pages per sheet (2, 4, 6, 9, 16), collation, booklet printing, cover pages, tray selection, scaling, Portrait/Landscape orientation, High Quality Grayscale and Black Ink Only, General Office/Professional/Presentation/Maximum dpi print modes, front USB port, copy/scan/fax; Control Panel Shortcuts; HP UPD PIN printing; HP Color Access Control; Optional: HP and third party extensibility solutions.
Printer Management	HP Web Jetadmin; Embedded Web Server; HP UPD Printer Administrator Resource Kit; HP Utility (Mac), HP JetAdvantage Security Manager optional
Scan Type / Technology	Flatbed, ADF / Contact Image Sensor (CIS)
Scan Resolution	**Hardware**: Up to 600 x 600 dpi; **Optical**: Up to 600 dpi
Scan File Format	Scan File Type supported by Software: Bitmap (.bmp), JPEG (.jpg), PDF (.pdf), PNG (.png), Rich Text (.rtf), Searchable PDF (.pdf), Text (.txt), TIFF (.tif)
Scan Input Modes	Front panel applications: Copy, Scan to E-mail with LDAP e-mail address lookup, Scan to Network Folder, Scan to USB, Scan to Sharepoint, Scan to Computer with SW. Client applications: EWS, HP Scan App, Compatible with HP Capture and Route
Scan Size	**ADF**: 297 x 432 mm; 11.7 x 17 in Maximum; 101 x 152 mm, 4 x 6 in Minimum; **Flatbed**: 297 x 432 mm; 11.7 x 17 in
Scan Speed	Up to 50 ipm (mono and color), LEF*
Scanner Advanced Features	Image adjustments; Output quality setting; Selectable scan resolution 75 to 1200 dpi; Job notification; Scan and save to destinations: network folder, Computer, Sharepoint, USB flash drive, e-mail; OCR software is included with the printer, OCR is completed at the PC, see software section for more details.
Bit Depth / Grayscale levels	24-bit (color); 8-bit (gray) / 256
Digital Sending Standard Features	Scan-to E-mail with LDAP email address lookup; Scan-to Network Folder; Scan-to USB; Scan-to Sharepoint; Scan-to Computer with SW; Fax Archive-to Network Folder; Fax Archive to E-mail; Fax-to Computer; Enable/Disable Fax; Enabel/Disable color Fax, Color Access Control; Native Authorization &authenticatrion; Quick Sets
Copy Speed[3]	**Black (ISO)**: Up to 35 cpm; **Color (ISO)**: Up to 35 cpm; **Black (Draft)**: Up to 55 cpm; **Color (Draft)**: Up to 55 cpm
Copy Resolution	**Black (text and graphics)**: Up to 600 dpi; Up to 600 dpi; **Color (text and graphics)**: Up to 600 dpi
Maximum Number Of Copies	Up to 999 copies
Copier Resize	25 to 400%
Copier Settings	ID Copy; Resize; Quality; Lighter/Darker; Two-sided copying; Tray Selection; Collate; Binding Marging;; Copy Preview with Crop and rezise; Enhancements; Enable/Disable copy; Enable/Disable copy color; Auto Color Selection; Color Access Control; Native Authorization &authenticatrion; Set as New Defaults
Fax Speed	**Up to**: 33.6 kbps
Fax Resolution	**Black (best)**: 300 x 300 dpi; **Color (best)**: 200 x 200 dpi; **Black (standard)**: 203 x 98 dpi; **Color (standard)**: 200 x 200 dpi
Fax Smart Software Features	Digital Fax - Fax to Computer is available with Windows and Macintosh, visit http://www.hp.com/support to download the latest software.
Fax Features[4]	**Fax Memory**: Up to 500 pages (black and white); **Auto Fax Reduction Supported**: Yes; **Auto-Redialing**: Yes; **Fax Delayed Sending**: Yes; **Distinctive Ring Detection Supported**: Yes; **Fax Forwarding Supported**: Yes; **Fax Phone TAM Interface Supported**: Yes; **Fax Polling Supported**: No; **Fax Telephone Mode Supported**: Yes; **Junk Barrier Supported**: Yes, requires Caller ID; **Maximum Speed Dialing Numbers**: No Limit; **PC Interface Supported**: Yes, HP Software support provided; **Telephone Handset Supported**: Yes
Standard Connectivity	*2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Ethernet 10/100 Base-TX network; 2 RJ-11 modem port/phone line; 802.11 b/g/n - dual band Station; NFC; Bluetooth Smart; WiFi Direct
Network Capabilities	Yes, via built-in Ethernet, wireless 802.11b/g/n - dual band
Wireless Capability	Yes, built-in WiFi 802.11b/g/n - dual band
Mobile Printing Capability	Apple AirPrint™; Mopria™-certified; Android Plug-in; Wi-FI Direct Printing; HP ePrint; Google Cloud Print 2.0; Mobile Apps; Windows 8/10; Windows 10 mobile; Chromebook
Memory	**Standard**: 1.5 GB; **Maximum**: 1.5 GB
Processor Speed	1.5 GHz / **Hard disk:** None (printer uses eMMC solid state drive (SSD)). Standard eMMC memory= 16GB, upgradeable to 128GB
Duty Cycle[7]	**Monthly, A4**: Up to 75,000 pages
Recommended Monthly Page Volume[8]	2500 to 15,000
Media Types Supported	Plain paper, HP EcoFFICIENT, HP Premium Presentation Matte 120g, HP Brochure Matte 180g, HP Brochure Glossy, HP Advanced Photo Papers, Light 60-74g, Intermediate 85-95g, Mid-Weight 96-110g, Heavy 111-130g, Extra Heavy 131-175g, Cardstock 176-220g, Labels, Letterhead, Envelope, Heavy Envelope, Preprinted, Prepunched, Colored, Bond, Recycled, Rough
Media Weight Supported[10]	Tray 1: 60 to 120 g/m² (plain paper); 125 to 300 g/m² (photo); 75 to 90 g/m² (envelope); 120 to 180 g/m² (brochure); 163 to 200 g/m² (card); Tray 2: 60 to 120 g/m² (plain paper); 125 to 250 g/m² (photo); 75 to 90 g/m² (envelope); 120 to 180 g/m² (brochure); 163 to 200 g/m² (card); Tray 3: 60 to 120 g/m² (plain paper); 125 to 250 g/m² (photo); 120 to 180 g/m² (brochure); 163 to 200 g/m² (card)
MedianSizesnSupported	lftH,ltIlttHvltAFnltFnlt,z.tfvnttnbct""7tfvuttnbut""7tfmuttnm,t""ltTcti1kNdlt5R%J*ltUY–Q–=t flmttncut""ltUV–Q–=t,wBttHnltGcltNAFcltAFct2tAltF+Q€tF2AltFcMnltFct2tAltF5RVVR+tZtAltImzltlbvttfvnt ""t2tA7tlbBttfvut""t2tAltRRQ°V–®Rt2tAltFBt2tAltImz.tl,ctfmut""t2tAltTBti1kNdt2tAltF+Q€tFlt NVJVR"R™VltSRVVR+ltAFcltFcltBttJtq=°;*Rt1J²J™tS=~VQJ+&tA=VJVR&ltImz.tlbvttfvnt""7tlbBttfvut ""7tl,ctfmut""lt-RQ°V–®RltTBti1kNdltTmti1kNdltBttvltcttmltlutltBtQ"ltFBltq=°;*Rt1J²J™t S=~VQJ+&tA=VJVR&t2tAltFmlt1J²J™R~RtS=~VQJ+&ltG°~V=°2~~Æ&t"R&–Jlt-™9R*=²R~lt-™9R*=²RtTBlt -™9R*=²Rtelult1J²J™R~Rt-™9R*=²RtG€=°tenlt1J²J™R~Rt-™9R*=²Rt2t3*Jt¿R™lt-™9R*=²RtGBlt -™9R*=²Rtebllt-™9R*=²Rtq5lt-™9R*=²Rt6=™J+Q€lt-™9R*=²RtGmltGJ+&~ltBtt;tk™&RtQJ+&ltq=°;*Rt1J²J™t S=~VQJ+&tA=VJVR&ltcttmtk™&RtQJ+&ltq=°;*Rt1J²J™tS=~VQJ+&tA=VJVR&t2tAltFmtk™&RtQJ+&lt1J²J™R~Rt S=~VQJ+&ltG°~V="2~~Æ&t"R&–JltS€=V=t6R&–JltBttvtS€=V=t6R&–Jltcmt S€=V=t"R&–JltlutltBtQ"lt 1J²J™R~RtS=~VQJ+&t4J%JX–tS€=V=tGJ+&~
Media Sizes Custom	Tray 1 supports (99.06 to 304.8mm) x (148.08 to 457.2 mm), Tandem Trays support (210.05 to 297.18 mm) x (148.08 to 215.9 mm), Universal Trays support (210.05 to 297.18 mm) x (148.08 to 431.8 mm)
Paper Handling	2 x 550-sheet Tandem Input Tray; 100-sheet multi-purpose tray; 500-sheet face-down output bin; **Duplex Options**: Automatic (standard); **Auto Document Feeder Capacity**: 100 sheets; **Envelope Feeder**: No (but will feed envelopes through MP Tray); **Standard Paper Trays**: 3; **Input Capacities**: Up to 1100 sheets Tandem Tray; Up to 100 sheets - MP Tray standard; Up to 10 envelopes; None transparencies; Up to 1600 + 200 + 200+ 40 for A5 size and larger; Up to 40 for smaller than A5 size; Up to 1600 + 200 + 200 + 40 sheets labels; None - Tandem Tray; 100 - MP Tray legal; **Output Capacities**: Up to 500 sheets standard; Up to 50 envelopes; None transparencies; Up to 200 cards; Up to 200 sheets labels; Up to 500 sheets legal

MedianSizesnSupported	lftH,ltIlttHvltAFnltFnlt,z.tfvnttnbct""7tfvuttnbut""7tfmuttnm,t""ltTcti1kNdlt5R%J*ltUY–Q–=t flmttncut""ltUV–Q–=t,wBttHnltGcltNAFcltAFct2tAltF+Q€tF2AltFcMnltFct2tAltImzltlbvttfvnt ""t2tA7tlbBttfvut""t2tAltRRQ°V–®Rt2tAltFBt2tAltImz.tl,ctfmut""t2tAltTBti1kNdt2tAltF+Q€tFlt NVJVR"R™VltSRVVR+ltAFcltFcltBttJtq=°;*Rt1J²J™tS=~VQJ+&tA=VJVR&ltImz.tlbvttfvnt""7tlbBttfvut ""7tl,ctfmut""lt-RQ°V–®RltTBti1kNdltTmti1kNdltBttvltcttmltlutltBtQ"ltFBltq=°;*Rt1J²J™t S=~VQJ+&tA=VJVR&t2tAltFmlt1J²J™R~RtS=~VQJ+&ltG°~V="2~~Æ&t"R&–Jlt-™9R*=²R~lt-™9R*=²RtTBlt -™9R*=²Rtelult1J²J™R~Rt-™9R*=²RtG€="tenlt1J²J™R~Rt-™9R*=²Rt2t3*Jt¿R™lt-™9R*=²RtGBlt -™9R*=²Rtebllt-™9R*=²Rtq5lt-™9R*=²Rt6=™J+Q€lt-™9R*=²RtGmltGJ+&~ltBtt;tk™&RtQJ+&ltq=°;*Rt1J²J™t S=~VQJ+&tA=VJVR&ltcttmtk™&RtQJ+&ltq=°;*Rt1J²J™tS=~VQJ+&tA=VJVR&t2tAltFmtk™&RtQJ+&lt1J²J™R~Rt S=~VQJ+&ltG°~V="2~~Æ&t"R&–JltS€=V=t6R&–JltBttvtS€=V=t6R&–Jltcmt S€=V=t"R&–JltlutltBtQ"lt 1J²J™R~RtS=~VQJ+&t4J%JX–tS€=V=tGJ+&~
Media Sizes Custom	Tray 1 supports (99.06 to 304.8mm) x (148.08 to 457.2 mm), Tandem Trays support (210.05 to 297.18 mm) x (148.08 to 215.9 mm), Universal Trays support (210.05 to 297.18 mm) x (148.08 to 431.8 mm)
Paper Handling	2 x 550-sheet Tandem Input Tray; 100-sheet multi-purpose tray; 500-sheet face-down output bin; **Duplex Options**: Automatic (standard); **Auto Document Feeder Capacity**: 100 sheets; **Envelope Feeder**: No (but will feed envelopes through MP Tray); **Standard Paper Trays**: 3; **Input Capacities**: Up to 1100 sheets Tandem Tray; Up to 100 sheets - MP Tray standard; Up to 10 envelopes; None transparencies; Up to 1600 + 200 + 200+ 40 for A5 size and larger; Up to 40 for smaller than A5 size; Up to 1600 + 200 + 200 + 40 sheets labels; None - Tandem Tray; 100 - MP Tray legal; **Output Capacities**: Up to 500 sheets standard; Up to 50 envelopes; None transparencies; Up to 200 cards; Up to 200 sheets labels; Up to 500 sheets legal
What's in the box	**W1B31C** HP PageWide Pro 772dw Multifunction Printer; HP 992 Setup Black PageWide Cartridge (~6,000 pages); HP 992 Setup Cyan PageWide Cartridge; HP 992 Setup Magenta PageWide Cartridge; HP 992 Setup Yellow PageWide Cartridge (CMY composite ~3,000 pages); power cord; installation guide
Replacement Cartridges	HP 992A Black Original PageWide Cartridge (~10,000 pages); HP 992A Cyan Original PageWide Cartridge; HP 992A Magenta Original PageWide Cartridge; HP 992A Yellow Original PageWide Cartridge (CMY composite ~8,300 pages); HP 992X High Yield Black Original PageWide Cartridge (~20,000 pages); HP 992X High Yield Cyan Original PageWide Cartridge; HP 992X High Yield Magenta Original PageWide Cartridge; HP 992X High Yield Yellow Original PageWide Cartridge (CMY composite ~16,000 pages)
Product Dimensions	**W x D x H**: 598 x 531 x 572 mm; 23.5 x 20.9 x 22.5 in; **Maximum**: 1524 x 956 x 870 mm; 60 x 37.7 x 34.3
Product Weight[1]	59.50 kg; 131.17 lb
Warranty Features	One-year, on-site warranty, service and support; one-year technical phone support, chat, and e-mail
Energy Efficiency Compliance	ENERGY STAR® certified; EPEAT® Silver; Blue Angel, China CCC and CECP
Control Panel	4.3" CGD (color Graphic Display), IR touchscreen for P772dn&dw series; 8" CGD (color Graphics Display), Cap touchscreen for P772zt series
Display Description	4.3 in CGD (Color Graphic Display), IR touchscreen for P772dn&dw series; 8 in CGD (Color Graphics Display), Cap touchscreen for P772zt series
Software Included	Windows Installer for discrete PCL 6 driver with Printer Assistant tools and Scan/Fax software; Mac Installer for PS driver with HP Utility and Scan/Fax software; HP Participation Study; OCR software is included with the printer, OCR is completed at the PC, see software section for more details.
Compatible Operating Systems	Windows 10 (32- and 64-bit), Windows 8/8.1 (32- and 64-bit), Windows 7 (32- and 64-bit), Windows Vista (32-bit), Windows XP SP3 (32-bit), Mac OS X 10.12 Sierra, Mac OS X v10.11 El Capitan, OS X v10.10 Yosemite, Linux (see www.hp.com/go/linuxprinting), UNIX (see www.hp.com/go/unixmodelscripts)
Compatible Network Operating Systems	Windows 10 (32- and 64-bit), Windows 8/8.1 (32- and 64-bit), Windows 7 (32- and 64-bit), Windows XP SP3/Vista (limited Legacy 32-bit support), Mac OS X v10.12 Sierra, Mac OS X v10.11 El Capitan, OS X v10.10 Yosemite, Windows Server 2016 64-bit, Windows Server 2012 R2/Terminal Services 64-bit, Windows Server 2012 64-bit (Cluster support, Terminal Services), Windows Server 2008 R2 64-bit (SP1, Standard/Enterprise Edition, Cluster support), Windows Server 2008 64-bit (SP1, SP2, Enterprise Edition, Cluster Support), Windows Server 2008 Legacy 32-bit (SP1, SP2, Standard/Enterprise Edition, Cluster support, Terminal Services), Windows Server 2003 R2 Legacy 32-bit (Standard/Enterprise Edition SP2), Windows Server 2003 Legacy 32-bit (SP1, SP2, Cluster support, Terminal Services), Citrix (see also www.hp.com/go/citrix) XenDesktop 5.X and 7.X, Windows Server 2012/2012R2/2008R2 with Citrix XenApp 6.0/6.5/7.X, Windows Server 2008 Terminal Services with Citrix XenApp 5.0/XenApp 5.0 Feature Pack 2 and 3, Novell Client for Open Enterprise Server 2/Netware 6.5, Novell iPrint Client v5.X (www.novell.com/iprint), Linux (For more information, see www.hp.com/go/linuxprinting), SAP (For more information, see www.hp.com/go/sap/print), UNIX (For more information, see www.hp.com/go/unixmodelscripts), mobile printing (For more information, see www.hp.com/go/mobileprinting)
Minimum System Requirements	**PC**: Windows® 10, 8.1, 8, 7: 1 GHz 32-bit or 64-bit processor, 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer. Windows Vista®: 800 MHz processor (32-bit only), 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8. Windows® XP SP3 or higher (32-bit only): any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8; **MAC**: Apple® OS X v10.12 Sierra, OS X v10.11 El Capitan, OS X v10.10 Yosemite; minimum 1.2 GB available HD space; Internet required; USB port
Power[2]	**Power Supply Type**: Internal (Built-in) Universal Power Supply; **Power Requirements**: Input voltage: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz); **Power Consumption**: 68.7 watts (printing), 20.95 watts (ready), 2.01 watts (sleep), 0.17 watts (off)
Acoustics	**Acoustic Power Emissions**: 7.0 B(A); **Acoustic Pressure Emissions**: 55 dB(A) (mono/color printing), 50 dB(A) (ADF mono copying), 50 dB(A) (ADF color copying), 50 dB(A) (ADF color scanning), 50 dB(A) (ADF mono scanning), Inaudible (idle)
Operating Environment	**Operating Temperature Range**: 15 to 30°C; **Recommended Operating Temperature**: 15 to 30°C; **Storage Temperature Range**: -40 to 60ºC; **Non-Operating Humidity Range**: 5 to 90% RH; **Operating Humidity Range**: 20 to 80% RH; **Recommended Humidity Operating Range**: 20 to 80% RH
Security Management	SSL/TLS (HTTPS), LDAP authentication; optional HP and 3rd party authentication solutions (e.g. badge readers) IPP over TLS; WPA2-Enterprise wired; 802.1x wireless authentication (EAP-TLS, LEAP, and PEAP); Pre-Shared Key Authentication for Wireless (PSK); firewall, certificates configuration; Control panel lock; Password protect EWS; Unused protocol and service disablement; Syslog; Signed firmware; Administrator settings; native authentication and authorization access control, native color access control ; configurable authentication time out; UPD PIN printing; Mopy mode via UPD PIN printing; compatible with optional HP JetAdvantage Security Manager
Accessories	HP PageWide 550-sheet Paper Tray (A7W99A); HP PageWide 550-sheet Paper Tray and Stand (W1B50A); HP PageWide 3x550 sheet Paper Tray and Stand (W1B51A); HP Page Wide 4000-sheet HCI Paper Tray and Stand (W1B52A); HP HW Integration Pocket Control Panel 8"; HP HW Integration Pocket Control Panel 4.3"; HP 128GB Memory Module
HP Service and Support Options	Installation, three, four and five year care packs

Learn more at
hp.com