



# HP LaserJet Enterprise M609dn

This HP LaserJet Printer with JetIntelligence combines exceptional performance and energy efficiency with professional-quality documents right when you need them—all while protecting your network from attacks with the industry’s deepest security.



### The world’s most secure printing<sup>1</sup>

- With HP Sure Start, each printer regularly checks its operating code and repairs itself from attempted hacks.
- Help prevent potential attacks and take immediate action with instant notification of security issues.
- Centralize control of your printing environment with HP Web Jetadmin—and help build business efficiency.<sup>2</sup>
- Give workgroups what they need to succeed. Easily choose and deploy over 180 HP and third-party solutions.

### High-speed performance meets energy efficiency

- Speed through tasks and save paper. Print two-sided documents nearly as fast as one-sided.
- This printer wakes up fast and prints your first page faster—in as quickly as 7.8 seconds.<sup>4</sup>
- This printer uses exceptionally low amounts of energy thanks to its innovative design and toner technology.<sup>5</sup>
- Paper handling options include a wheeled stand and 550-sheet input feeder for paper sizes A6 to legal.

### More. Pages, Performance, and Protection.<sup>6</sup>

- Produce sharp text, bold blacks, and crisp graphics with precision black toner.
- Original HP Toner cartridges with JetIntelligence deliver more pages per cartridge than predecessors.<sup>6</sup>
- Help retain the Original HP quality you paid for with anti-fraud and cartridge authentication technology.
- Spend less time replacing toner, and more on business. Choose high-yield toner cartridges.<sup>7</sup>



<sup>1</sup> Based on HP review of 2016 published security features of competitive in-class printers. Only HP offers a combination of security features that can monitor to detect and automatically stop an attack then self-validate software integrity in a reboot. For a list of printers, visit <http://www.hp.com/go/PrintersThatProtect>. For more information: <http://www.hp.com/go/printersecurityclaims> <sup>2</sup> HP Web Jetadmin is available for download at no additional charge at <http://www.hp.com/go/webjetadmin> <sup>3</sup> Measured using ISO/IEC 24734, excludes first set of test documents. For more information, see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration, software application, driver, and document complexity. <sup>4</sup> Measured after 15 min in sleep. Exact speed varies depending on the system configuration, software application, driver, document complexity and time in sleep. <sup>5</sup> Based on HP testing using the ENERGY STAR® program’s Typical Electricity Consumption (TEC) method or as reported in energystar.gov versus the top three leading competitors as of 8/2015. Actual results may vary. For details see <http://www.hp.com/go/Ljclaims> <sup>6</sup> More pages versus predecessor cartridges claim based on page-yield comparison of HP 37X High Yield Black Original LaserJet Toner Cartridges with HP 87X High Yield Black Original LaserJet Toner Cartridges. For more information, see <http://www.hp.com/go/learnabouthsupplies> <sup>7</sup> HP 37X High Yield Black Original LaserJet Toner Cartridges not included; please purchase separately. <sup>8</sup> An FCC Class A emissions compliant device meets the less stringent (higher) levels of emissions allowed by the FCC for a product operation in a commercial environment. An FCC class A device cannot be marketed for use in a residential environment and an FCC class A device should not be purchased for use in a residential environment due to the increased risk of interference to radio communications.

# HP LaserJet Enterprise M609dn Specifications Table

<b>Functions / Multitasking Supported</b>	Print
<b>Print Speed</b>	<b>A4:</b> Up to 71 ppm. <b>Letter:</b> Up to 75 ppm black; <sup>7</sup> <b>First Page Out:</b> As fast as 5.4 sec black; <sup>9</sup>
<b>Print Resolution</b>	<b>Black (best):</b> Up to 1200 x 1200 dpi
<b>Print Technology</b>	Laser
<b>Print Resolution Technologies</b>	FastRes 1200; 1200 x 1200 dpi
<b>Print Cartridges Number</b>	1 (black)
<b>Standard Print languages</b>	HP PCL 6, HP PCL 5 (HP PCL 5 driver available from the Web only), HP Postscript level 3 emulation, native PDF printing (v. 1.7), Apple AirPrint™
<b>Printer Smart Software Features</b>	Print preview, duplex printing, print multiple pages per sheet (2, 4, 6, 9, 16), collation, watermarks, store print jobs, easy-access USB
<b>Printer Management</b>	HP JetAdvantage Security Manager; HP SNMP Proxy Agent; HP Web JetAdmin Software; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal Print Driver
<b>Standard Connectivity</b>	1 Hi-Speed USB 2.0 Device; 2 Hi-Speed USB 2.0 Host; 1 Gigabit Ethernet 10/100/1000T network
<b>Mobile Printing Capability</b>	HP ePrint; Apple AirPrint™; Mopria-certified <sup>5</sup>
<b>Memory</b>	<b>Standard:</b> 512 MB, <b>Maximum:</b> 1.5 GB, MAX memory, when 1 GB Accessory DIMM is installed
<b>Processor Speed</b>	1.2 GHz
<b>Duty Cycle</b>	<b>Monthly, A4:</b> Up to 300,000 pages
<b>Recommended Monthly Page Volume</b>	5000 to 30,000
<b>Media Types Supported</b>	Paper (plain, light, bond, recycled, heavy, extra heavy, cardstock, pre-printed, pre-punched, colored, rough, heavy rough), mono transparency, labels, letterhead, envelope, heavy envelope
<b>Media Weight Supported</b>	Feeder 1: 60 to 199 g/m <sup>2</sup> ; Feeder 2: 60 to 120 g/m <sup>2</sup>
<b>Media Sizes Supported</b>	feeder 1: A4, A5, A6, RA4, B5 (JIS), B6 (JIS), 10 x 15 cm, Oficio (216 x 340 mm), 16K, envelopes (C5, B5, C6, DL ISO), Postcard (JIS single and double); feeder 2: A4, A5, A5-R, B5 (JIS), 16K
<b>Media Sizes Custom</b>	feeder 1: 76 x 127 to 216 x 356 mm; feeder 2: 99 x 148 to 216 x 356 mm
<b>Paper Handling</b>	100-sheet multipurpose feeder; 550-sheet input feeder; 500 sheet output bin; <b>Duplex Options:</b> Automatic (standard); <b>Envelope Feeder:</b> Yes, 75 (optional); <b>Standard Paper Trays:</b> 2; <b>Input Capacities:</b> Up to 650 sheets standard; <b>Output Capacities:</b> Up to 500 sheets standard; Up to 75 envelopes; 200 transparencies
<b>What's in the box</b>	<b>K0QZ1A</b> HP LaserJet Printer; HP Black Original LaserJet Toner Cartridge (~11K yield); CD with software drivers and documentation; Documentation (Hardware Install Guide); Power cord <sup>2</sup>
<b>Replacement Cartridges</b>	HP 37A Black Original LaserJet Toner Cartridge (11,000 yield) CF237A; HP 37X High Yield Black Original LaserJet Toner Cartridge (25,000 yield) CF237X; HP 37Y Extra High Yield Black Original LaserJet Toner Cartridge (41,000 yield) CF237Y <sup>5</sup>
<b>Product Dimensions</b>	<b>W x D x H:</b> 431 x 466 x 380 mm; 17 x 18.3 x 15 in; <b>Maximum:</b> 431 x 1040 x 453 mm; 17 x 40.9 x 17.8 in
<b>Product Weight</b>	21.6 kg; 47.7 lbs
<b>Warranty Features</b>	One-year, next-business day, onsite warranty. Warranty and support options vary by product, country and local legal requirements. Go to <a href="http://hp.com/support">hp.com/support</a> to learn about HP award winning service and support options in your region. (wty code 4G)
<b>Control Panel</b>	Rotating 2.7-in QVGA LCD (color graphics) with 24 key pad.
<b>Display Description</b>	2.7-in (6.86 cm) QVGA LCD (color graphics) rotating (adjustable angle)
<b>Software Included</b>	HP Connected, HP Device Experience (DXP), HP PCL 6 (XPS) Printer Driver, HP Software Installer/Uninstaller, Mac OS Welcome Screen (Directs users to 123.hp.com or OS App Source for printer software), Online user manuals
<b>Fonts and Typefaces</b>	105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP Postscript level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono WorldType); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); Additional font solutions available via third-party flash memory cards; HP LaserJet Fonts and IPDS Emulation available at <a href="http://www.hp.com/go/laserjetfonts">http://www.hp.com/go/laserjetfonts</a>
<b>Compatible Operating Systems</b>	Android, Linux Boss (5.0), Linux Debian (7.0, 7.1, 7.2, 7.3, 7.4, 7.5, 7.6, 7.7, 7.8, 7.9, 8.0, 8.1, 8.2, 8.3, 8.4, 8.5, 8.6), Linux Fedora (22, 23, 24), Linux Mint (17, 17.1, 17.2, 17.3, 18), Linux Red Hat Enterprise (6.0, 7.0), Linux SUSE (13.2, 42.1), Linux Ubuntu (12.04, 14.04, 15.10, 16.04, 16.10), OS macOS 10.12 Sierra, OS X 10.10 Yosemite, OS X 10.11 El Capitan, UNIX, Windows 10 all 32- & 64-bit editions (excluding RT OS for Tablets), Windows 7 all 32- & 64-bit editions, Windows 8/8.1 all 32- & 64-bit editions (excluding RT OS for Tablets), Windows Vista all 32bit editions (Home Basic, Premium, Professional, etc.), Windows XP SP3 32-bit editions (XP Home, XP Pro, etc.)

<b>Compatible Operating Systems</b>	Android, Linux Boss (5.0), Linux Debian (7.0, 7.1, 7.2, 7.3, 7.4, 7.5, 7.6, 7.7, 7.8, 7.9, 8.0, 8.1, 8.2, 8.3, 8.4, 8.5, 8.6), Linux Fedora (22, 23, 24), Linux Mint (17, 17.1, 17.2, 17.3, 18), Linux Red Hat Enterprise (6.0, 7.0), Linux SUSE (13.2, 42.1), Linux Ubuntu (12.04, 14.04, 15.10, 16.04, 16.10), OS macOS 10.12 Sierra, OS X 10.10 Yosemite, OS X 10.11 El Capitan, UNIX, Windows 10 all 32- & 64-bit editions (excluding RT OS for Tablets), Windows 7 all 32- & 64-bit editions, Windows 8/8.1 all 32- & 64-bit editions (excluding RT OS for Tablets), Windows Vista all 32bit editions (Home Basic, Premium, Professional, etc.), Windows XP SP3 32-bit editions (XP Home, XP Pro, etc.)
<b>Compatible Network Operating Systems</b>	Citrix MetaFrame Presentation Server 3.0, Citrix MetaFrame XP Presentation Server (Feature Release 1, 2, and 3), Citrix on Windows Server 2003/2003R2, Citrix on Windows Server 2008/2008R2/2008 R2 SP1, Citrix on Windows Server 2012/2012R2, Citrix Presentation Server 4.0/4.5, Citrix XenApp 5.0 (Plus Feature Pack 2 & 3) for Windows Server 2008 Terminal Services 32- and 64-bit, Citrix XenApp 6.0/6.5 (For Windows Server 2008 R2 Terminal Services, 32- and 64-bit), Citrix XenApp 6.0/6.5/7.5 (For Windows Server 2008 R2 SP1 Terminal Services, 32- and 64-bit), Citrix XenApp 7.5 (For Windows Server 2012 and 2012 R2 Terminal Services, 64-bit), Citrix XenDesktop 5.6 (For Windows Server 2008 R2 Terminal Services, 32- and 64-bit), Citrix XenDesktop 5.6/7.0/7.5 (For Windows Server 2008 R2 SP1 Terminal Services, 32- and 64-bit), Citrix XenDesktop 7.0/7.5 (For Windows Server 2012 and 2012 R2 Terminal Services, 64-bit), Novell NetWare 6.5/SP8 Novell Clients <a href="http://www.novell.com/print">www.novell.com/print</a> , Novell Print Appliance v1.0, Novell Open Enterprise Server 11/SP1, Novell Open Enterprise Server 2 for Linux, Novell Servers <a href="http://www.novell.com/iprint">www.novell.com/iprint</a> , Windows Server 2003/2003 R2 32-/64-bit (SP1/SP2) Standard/Enterprise/Datacenter (+ Cluster & Terminal Services), Windows Server 2003/2003 R2 32-bit (SP1/SP2), Standard/Enterprise (+ Cluster & Terminal Services), Windows Server 2008 R2 64-bit (SP1) Standard/Enterprise (+ Cluster & Terminal Services), Windows Server 2008 R2 32-/64-bit (SP1) Standard/Enterprise (+ Cluster & Terminal Services), Windows Server 2008/2008 R2 32-/64-bit (SP1/SP2) Standard/Enterprise/Datacenter (+ Cluster & Terminal Services), Windows Server 2012/2012 R2 64-bit Standard/Foundation/Essentials/Datacenter (+ Cluster & Terminal Services)
<b>Minimum System Requirements</b>	<b>PC:</b> 2 GB available hard disk space; OS hardware requirements see <a href="http://microsoft.com">microsoft.com</a> ; <b>MAC:</b> 1.3 GB available hard drive space; Internet; OS hardware requirements see <a href="http://apple.com">apple.com</a> for more info
<b>Power</b>	<b>Power Supply Type:</b> Built in 115V or 220V Power Supply (Not dual voltage, power supply varies by part number with # Option code identifier); <b>Power Requirements:</b> 100W - 127V nominal @ +/-10% (min 90V, max 140V); 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz); 12 A; 220V - 240V nominal, @ +/-10% (min 198V, Max 264V); 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz); 6 A; <b>Power Consumption:</b> 780 watts (printing), 15.3 watts (ready), 3.1 watts (sleep), < 0.1 watts (Auto Off/Manual On), < 0.1 watts (Manual Off) <sup>3</sup>
<b>Acoustics</b>	<b>Acoustic Power Emissions:</b> 7.1 B(A); <b>Acoustic Pressure Emissions:</b> 56 dB(A)
<b>Operating Environment</b>	<b>Operating Temperature Range:</b> 15 to 32.5°C; <b>Recommended Operating Temperature:</b> 59 to 90.5°F; <b>Storage Temperature Range:</b> -20 to 40°C; <b>Non-Operating Humidity Range:</b> 10 to 80% RH; <b>Operating Humidity Range:</b> 30 to 70% RH; <b>Recommended Humidity Operating Range:</b> 10 to 90% RH
<b>Security Management</b>	Identity management: Kerberos authentication; LDAP authentication; 1000 user PIN codes; optional HP and 3rd party advanced authentication solutions (e.g., badge readers); Network: IPsec/firewall with Certificate, Pre-Shared Key, and Kerberos authentication; Supports WPA-10 IPsec configuration Plug-in; 802.1X authentication (EAP-PEAP, EAP-TLS); SNMPv3; HTTPS; Certificates; Access Control List; Data: Storage Encryption; Encrypted PDF & Email (uses FIPS 140 validated cryptographic libraries from Microsoft); Secure Erase; SSL/TLS (HTTSP); Encrypted Credentials; Device: Security lock slot; USB port disablement; hardware integration pocket for security solutions; Intrusion Detection with Red Balloon Security Technology - Constant in-device monitoring for attacks; SureStart Secure Boot - BIOS Integrity Checking with self-healing capability; Whitelisting - loads only known good code (DLLs, EXEs, ...); Security management: Compatible with HP JetAdvantage Security Manager; Device Security Syslog Messages processed and accessible in Arcsight and Splunk SIEMs
<b>Accessories</b>	HP LaserJet 550-Sheet Paper Feeder LOH17A, HP LaserJet 2100 sheet Paper feeder LOH18A, HP LaserJet Printer Stand LOH19A, HP LaserJet Stapler/Stacker/Mailbox LOH20A, HP Envelope Feeder LOH21A, HP Internal USB Ports B5L28A, HP Secure High Perf Hard Disk Drive B5L29A, HP Jetdirect 2900nw Print Server UB031A, HP Trusted Platform Module Accessory F5562A, 1 GB Memory DIMM Kit G6W84A, HP Extension Tray Cover LOH22A
<b>HP Service and Support Options</b>	U9M22E HP 5 year Next Business Day HW Support w/Defective Media Retention, U9M25E HP 5 year 4 hour 9x5 HW Support w/Defective Media Retention, U9M28E HP 5 year 4 hour 13x5 HW Support w/Defective Media Retention, U9NA1E HP 5 year Next Business Day Call To Repair HW Support w/DMR, U9NA4E HP 5 year Next Business Day Exchange Service, U9NB5PE HP 2 year Post Warranty Next Business Day Hardware Support w/DMR, U9NB7PE HP 2 year Post Warranty 4 hour 9x5 Hardware Support w/DMR, U9NB8PE HP 1 year Post Warranty 4 hour 13x5 Hardware Support w/DMR, U9NC0PE HP 2 yr Post Warranty Next Business Day Call To Repair HW Support w/DMR, U9NC1PE HP 1 year Post Warranty Next Business Day Exchange Service

Learn more at [hp.com](http://hp.com)

<sup>1</sup> EPEAT® registered where applicable. EPEAT registration varies by country. See <http://www.epeat.net> for registration status by country. <sup>2</sup> Cartridges included; yields 11,000 black pages based on ISO/IEC 19798 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see <http://www.hp.com/go/learnaboutsupplies> <sup>3</sup> Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. <sup>4</sup> Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. <sup>5</sup> May require a firmware upgrade to be compatible, download at <http://www.hp.com/go/support> <sup>6</sup> Measured using ISO/IEC 24734, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration, software application, driver, and document complexity. <sup>7</sup> Measured using ISO 24734 Feature Test, A5 Landscape Feed. Speed may vary based on content, PC, media orientation, and media type. <sup>8</sup> Measured using ISO/IEC 17629. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration, software application, driver, and document complexity. <sup>9</sup> eMMC is non-volatile storage; Firmware encryption (AES 128 or AES 256) of customer/job data; Secure Cryptographic Erase - Job Data; Secure Erase - Disk <sup>10</sup> Based on the BA TEC method with the following possible exceptions: 1 minute or less sleep delay setting, Wi-Fi disabled.

