

HP USB-C Universal Dock



Universal enterprise docking for your fixed or shared workspaces

Transform your HP notebook or tablet into a complete desktop experience with the HP USB-C Universal Dock, which delivers USB-C™ charging¹ and connections for your network, dual 4K displays, and accessories with one cable connection.

Expansion for all the ways you work

Connect to your accessories with one USB 3.0 charging port, three USB 2.0 ports, and one USB-C™ charging/data port. Drive Dual 4K displays or one 5K display² from two DisplayPort™ ports. Use RJ-45 for Gigabit Ethernet and network manageability.³

Enterprise-class network manageability

Support network manageability³ of your device and the dock with PXE boot support, Wake-on LAN, MAC Address Pass-Through, and LAN/WLAN switching.⁴

Universal compatibility

Use one dock for all of your devices with support for multi-generation HP notebooks and tablets. Connect to the dock through the included USB-C™ cable or the included USB-C™ to USB-A adapter.

Give your platform a power boost

Avoid downtime with up to 60W of power to charge and power your connected notebook or tablet through the powered USB-C™ port, or select notebooks through the optional HP 4.5mm and USB Dock Adapter.¹

Click or call support

Get the reassurance of a one-year limited warranty.

1. See product QuickSpecs for exact charging capacities. Only available with direct USB-C™ cable connection on the dock or through the HP 4.5mm and USB Dock Adapter, sold separately.

2. Sold separately.

3. Internet access required and sold separately.

4. LAN/WLAN switching is only supported on Windows 10 with select platforms.

5. Lock sold separately.

Specifications



HP USB-C Universal Dock

Part number	1MK33AA
Model Number	HSA-B005DS
Dimensions	7.87 x 2.76 x 1.1 in (200 x 70 x 28 mm)
Weight	0.77 lb (0.350 kg)
Normal Operation Voltage	19.5V
Average Operation Power	77W
Max Operation power	88W
Temperature (Operation)	32~104 °F (0~40 °C)
Temperature (Non-Operation)	-4~140 °F (-20~+60 °C)
Relative humidity (Operation)	5%~90% RH, non-condensing
Relative humidity (Non-Operation)	5%~95% RH, non-condensing
Altitude (Operation)	10000 ft (3048 m)
Altitude (Non-Operation)	30000 ft (9144 m)
Shock (Operation)	40G, 2ms, half-sine
Shock (Non-Operation)	240G, 2ms, half-sine
Random Vibration (Operation)	~0.21Grms, 5~500 Hz
Random Vibration (Non-Operation)	~2.09Grms, 5-500 Hz, Non-Operating
Option kit contents	HP USB-C™ Universal Dock, AC power cord, 90W A/C adapter, USB-A to USB-C™ adapter, and documentation

Sign up for updates
hp.com/go/getupdated



Share with colleagues



Rate this document

© Copyright 2017 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries.

4AA7-0147ENW, June 2017, Rev 1.

