Print, copy, scan, fax (optional)

# HP PageWide Managed Color MFP E77660dn



HP Managed MFPs and printers are optimised for managed environments. Offering increased monthly page volumes and fewer interventions, this portfolio of products can help reduce printing and copying costs. See your HP Authorized Reseller for details.





## Affordable colour printing for every office

- Depend on lasting value. Get the results you expect for a game-changing low cost per colour page.
- Print more pages and replace cartridges less often with optional high-yield cartridges.<sup>2</sup>
- Print even faster—and save even more per page—by setting this printer to General Office mode.<sup>3</sup>
- Help keep energy costs down with the most efficient printer in its class.<sup>4</sup>



# Minimal interruptions. Maximum uptime.

- Minimize interruptions with an HP PageWide Managed MFP designed for the least maintenance in its class.5
- Print speeds up to 50% faster than competitors—as fast as 80 ppm in colour and black-and-white.
- Tailor this MFP to the needs of your business with a wide range of paper-handling accessories.
- Scan files directly to Microsoft® Office 365 and SharePoint, plus email, USB, and network folders.



## The world's most secure printing<sup>1</sup>

- With HP Sure Start, each printer regularly checks its operating code and repairs itself from attempted hacks.
- Protect information on the MFP and in transit over the network, and store data on the encrypted hard disk.<sup>8</sup>
- Monitor activity to detect and stop attacks, then automatically reboot with run-time intrusion detection.
- Whitelisting checks firmware during startup to help ensure it's authentic, good code—digitally signed by HP.

Based on HP review of 2016 published security features of competitive in-class printers. Only HP offers a combination of security features that can monitor to detect and automatically stop an attack then self-validate software integrity in a reboot. For a list of printers, visit hp.com/go/PrintersThatProtect. For more information: hp.com/go/printersecurityclaims

High-yield cartridges are not included in printer purchase; purchase separately. Comparison is based on ISO 24711 cartridge yields for HP 982X series High-Yield Original PageWide Cartridges compared with

HP 982A series Original PageWide Cartridges. Learn more at hp.com/go/learnaboutsupplies Comparison based on printing in Professional Mode.

Energy claim based on TEC data reported on energystar.gov as of March 2017. Data normalized to determine energy efficiency of in-class A3 colour laser printers (\$1500-\$2999) and MFPs (\$3000-\$7499)

as of February 2017, excluding other HP PageWide products. Subject to device settings. Actual results may vary.

Fewer service parts claim based on BLI analysis of leading in-class A3 MFPs as of August 2016; calculations use publicly available and/or published manufacturer rated yields for long-life consumables and assume 600,000 pages printed (using a 60% black/40% colour ratio). Learn more at hp.com/go/pagewideclaims
Comparison of HP PageWide A3 devices with the majority of in-class colour ink/laser MFPs (\$3000-\$7499), and colour ink/laser single function printers (\$1500-\$2999) as of April 2017; market share as

reported by IDC as of Q4 2016, excluding other HP PageWide products. HP PageWide speeds based on General Office mode and exclude first page. Learn more at <u>hp.com/go/printerspeeds</u> Requires an Internet connection to the printer. Services may require registration. App availability varies by country, language, and agreements. For details, see hpconnected.com

Some features require additional purchase. A FutureSmart service pack update may be required to activate security features. Learn more at hp.com/go/printsecurity

## **Technical specifications**

Print	Print, copy, scan, fax (optional)
Duplex print options	Automatic (standard)
Technology	HP PageWide Technology
Speed <sup>1</sup>	Black: Up to 80 ppm (General office mode, A4); Up to 60 ppm (Professional mode, A4); Colour: Up to 80 ppm (General Office mode, A4); Up to 60 ppm (Professional mode): Up to 40 ppm
First page out <sup>2</sup>	Black (A4, ready): As fast as 7.1 seconds; Colour (A4, ready): As fast as 7.1 seconds
Resolution	Black (best): Up to 1200 x 1200 optimised dpi from 600 x 600 input dpi (on Unspecified, Plain, HP Premium Presentation Matte, and HP Brochure Matte); Colour (best): Up to 2400 x 1200 optimised dpi from 600 x 600 input dpi (on HP Advanced Photo Papers)
Languages	HP PCL 5c; HP postscript level 3 emulation; PDF 1.7
HP ePrint capability	Yes
Print cartridges	4 (1 each black, cyan, magenta, yellow)
Printer management	HP JetAdvantage Security Manager; HP SNMP Proxy Agent; HP Web JetAdmin Software; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal Print Driver
Printer smart software features	HP SureStart; Run-time Intrusion detection; Whitelisting; HP Trusted Platform Module; HP JetAdvantage Security Manager; HP Web Jetadmin; Open Extensibility Platform, FutureSmart Firmware, HP ePrint, Apple AirPrint™, HP Auto-On/Auto-Off technology, HP Color Access Control, HP EasyColor, Front-facing USB printing, store print jobs, HP EasyColor, print preview, automatic two-sided printing, prin
Scan	exterisionary solutions, whereas
Туре	Flatbed, ADF
Technology	Charge Coupled Device (CCD) & Contact Image Sensor (CIS)
Speed	Single-sided (A4): Up to 90 ipm (black and colour); Two-sided (A4): Up to 180 ipm (black and colour)
Bit depth Resolution	24-bit <b>Hardware:</b> Up to 600 ppi; <b>Optical:</b> Up to 600 dpi; <b>Enhanced:</b> Up to 600 ppi
Max scanning size	<b>Flatbed:</b> 297 x 432 mm; <b>ADF:</b> 297 x 432 mm; Up to 297 x 864 mm when "long scan size" selected
Grayscale levels	256
Input modes	Copy; E-mail; Fax; Save to Network Folder; Save to USB; Save to Device Memory; Save to SharePoint; Open Extensibility Platform
File format	(OXP) applications  Scan File Type supported by Software: Bitmap (.bmp), JPEG (.jpg), PDF (.pdf), PNG (.png), Rich Text (.rtf), Searchable PDF (.pdf), Text (.txt),
	TIFF (.tif)
Digital sending standard features	Scan to E-mail; Save-to-Network Folder; Save-to-USB drive; Send to FTP; Send to LAN Fax; Send to Internet Fax; Local Address Book; SMTP over SSL; Blank Page Removal; Edge Erase; Auto Colour Sense; Auto Crop To Content; Compact PDF
Сору	a ara. aaa, a age nemata, aage araas, nace estou sense, nace crop to content, compact to
Speed <sup>3</sup>	Black: Up to 80 cpm (General office mode, A4); Up to 60 cpm (Professional mode, A4); Colours Up to 80 cpm (General office mode, A4); Up to 60 cpm (Professional mode, A4)
First copy out <sup>3</sup>	Colour: Up to 80 cpm (General office mode, A4); Up to 60 cpm (Professional mode, A4)  Black (letter): As fast as 7.9 seconds; Colour (letter): As fast as 7.9 seconds
Resolution	Black (text and Graphics): Up to 600 x 600 dpi; Colour (text and graphics): Up to 600 x 600 dpi
Max copies	Up to 9,999 copies
Copier reduce/enlarge	25 to 400%
Copier settings	Two-sided copying, scalability, image adjustments (darkness, contrast, background cleanup, sharpness), N-up, N or Z-ordering, contenorientation, collation, booklet, ID Scan, job build, edge-to-edge, job storage
Copier smart software features	Auto scale; Reduce/enlarge from scanner glass (25 to 400 percent); Collate; Auto colour detection; Two-sided copying; Image
	adjustments (darkness, background cleanup, sharpness); Job build
Fax (Optional) Resolution	Black (best): Up to 300 x 300 dpi (400 x 400 dpi for received faxes only); Colour (fine): Up to 300 x 300 dpi (400 x 400 dpi for received
Resolution	faxes only)
Transmission speed <sup>4</sup>	Up to 33.6 kbps; 3 sec per page
Fax features	Faxing: Optional; Faxing options (ADP): Simultaneous Two-Sided; Auto-Redialling: Yes; Fax delayed sending: No; Distinctive ring detection supported: No; Fax forwarding supported: Yes; Fax polling supported: Yes; Fox (spoll to receive only); Auto fax reduction supported: Yes; Pax telephone mode supported: No; Junk barrier supported: Yes; PC interface supported: Yes; Fax broadcasting, ma locations: 210; Telephone handset supported: No
Display Duty cycle (monthly, A4) <sup>5</sup>	20.3 cm (8.0 in) touchscreen, XVA Colour Graphic Display (CGD)  Up to 250,000 pages
Recommended monthly	2,500 to 50,000 pages
page volume <sup>6</sup>	
Media	
Custom sizes Recommended Weights	Tray 1: 99.1 × 127 to 304.8 × 457.2 mm; Tray 2-5: 210.1 × 148.1 to 297.2 × 431.8 mm; HCl Trays 3 & 4: A4 & Letter Only 60 to 220 g/m², 300 g/m² Photo Paper Only
Types	Paper (Plain, Inkjet, Inkjet Brochure/Glossy), Photo Paper, Envelopes, Labels, Cards
Paper handling	Input (standard): 100-sheet multipurpose tray, 550-sheet input tray; Input (optional): 1x550/tray (A3/A4), 1x550/stand (A3/A4),
Processor speed	3x550/stand (A3/A4), HCI (2x2000 sheet A4); <b>Output (standard):</b> 500-sheet output bin 1.2 GHz
Operating system compatibility	Android, Linux Boss (5.0), Linux Debian (7.0, 7.1, 7.2, 7.3, 7.4, 7.5, 7.6, 7.7, 7.8, 7.9, 8.0, 8.1, 8.2, 8.3, 8.4, 8.5, 8.6), Linux Fedora (22, 23, 24), Linux Mint (17, 17.1, 17.2, 17.3, 18), Linux Red Hat Enterprise (6.0, 7.0), Linux SUSE (13.2, 42.1), Linux Ubuntu (12.04, 14.04, 15.10, 16.04, 16.10), OS macOS 10.12 Sierra, OS X 10.10 Vosemite, OS X 10.11 El Capitan, UNIX, Windows 10 all 32-& 64-bit editions (excluding RT OS for Tablets), Windows 7 all 32-& 64-bit editions (excluding RT OS for Tablets) Windows Vista all 32bit editions (Mondows XP Group et al., Windows XP SP3 32-bit editions (VP Home, XP Pro, etc.)
Minimum andrew and	
minimum system requirements	PC: Windows® 10, 8.1, 8, 7: 1 GHz 32-bit or 64-bit processor, 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection
Minimum system requirements	USB port, Microsoft® Internet Explorer. Windows Vista®: 800 MHz processor (32-bit only), 2 GB available hard disk space, CD-ROM/DVD
Minimum system requirements	USB port, Microsoft® Internet Explorer. Windows Vista®: 800 MHz processor (32-bit only), 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8. Windows® XP SP3 or higher (32-bit only): any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port,
minimum system requirements	USB port, Microsoft® Internet Explorer. Windows Vista®: 800 MHz processor (32-bit only), 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8. Windows® XP SP3 or higher (32-bit only): any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8; Mac: Apple® OS X v10.12 Sierra, OS X v10.11 El Capitan, OS X v10.10 Yosemite, minimum 1.3 GB
	USB port, Microsoft® Internet Explorer. Windows Vista®: 800 MHz processor (32-bit only), 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8. Windows® XP SP3 or higher (32-bit only): any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port,
	USB port, Microsoft® Internet Explorer. Windows Vista®: 800 MHz processor (32-bit only), 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8. Windows® XP SP3 or higher (32-bit only): any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8; Mac: Apple® OS X v10.12 Sierra, OS X v10.11 El Capitan, OS X v10.10 Yosemite, minimum 1.3 GB
Connectivity	USB port, Microsoft® Internet Explorer. Windows Vista®: 800 MHz processor (32-bit only), 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8. Windows® XP SP3 or higher (32-bit only): any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8: Mac: Apple® OS X v10.12 Sierra, OS X v10.11 El Capitan, OS X v10.10 Yosemite, minimum 1.3 GB available HD space; Internet required; USB port
Connectivity Connectivity (Standard) Wireless capability Mobile printing capability	USB port, Microsoft® Internet Explorer. Windows Vista® 800 MHz processor (32-bit only), 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8. Windows® XP SP3 or higher (32-bit only): any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8; Mac: Apple® OS X v10.12 Sierra, OS X v10.11 El Capitan, OS X v10.10 Yosemite, minimum 1.3 GB available HD space; Internet required: USB port 2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Hardware Integration Pocket Optional, enabled with purchase of HP Jetdirect 3000w NFC/Wireless Accessory  HP ePrint, Apple AirPrint™, Google Cloud Print
Connectivity Connectivity (Standard) Wireless capability	USB port, Microsoft® Internet Explorer. Windows Vista®: 800 MHz processor (32-bit only), 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8. Windows® XP SP3 or higher (32-bit only), any Intel® Pentlum® II, Celerom® or 233 MHz compatible processor, 850 MB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8; Mac: Apple® OS X v10.12 Sierra, OS X v10.11 El Capitan, OS X v10.10 Yosemite, minimum 1.3 GB available HD space; Internet required; USB port  2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Hardware Integration Pocket Optional, enabled with purchase of HP Jetdirect 3000w NFC/Wireless Accessory
Connectivity Connectivity (Standard) Wireless capability Mobile printing capability	USB port, Microsoft® Internet Explorer. Windows Vista®: 800 MHz processor (32-bit only), 2 GB available hard disk space, CD-ROM/OVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8. Windows® XP SP3 or higher (32-bit only): any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8; Mac Apple® OS X v10.12 Sierra, OS X v10.11 El Capitan, OS X v10.10 Yosemite, minimum 1.3 GB available HD space; Internet required; USB port  2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Hardware Integration Pocket  Optional, enabled with purchase of HP Jetdirect 3000w NFC/Wireless Accessory  HP ePrint, Apple AirPrint®, Google Cloud Print  Via HP Jetdirect Ethernet embedded print server (standard) supports: 10Base-T, 100Base-Tx, 1000Base-T; 802.3az (EEE) support on Fast Ethernet and Gigabit Ethernet; IPsec (standard)  IPv4/IPv6: Apple Bioriour Compatible (Mac OS v10.24 or higher), SNMPv1/v2c/v3, HTTP, HTTP, FTP, FTP, FTP, Port 9100, LPD, WS Discovery, IPP,
Connectivity  Connectivity (Standard)  Wireless capability  Mobile printing capability  Network capabilities  Supported network protocols	USB port, Microsoft® Internet Explorer. Windows Vista®: 800 MHz processor (32-bit only), 2 GB available hard disk space, CD-ROM/OVD drive or Internet Connection, USB port, Microsoft® Internet Explorer 8. Windows® XP SP3 or higher (32-bit only): any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8; Mac: Apple® OS X v10.12 Sierra, OS X v10.11 El Capitan, OS X v10.10 Yosemite, minimum 1.3 GB available HD space; Internet required; USB port  2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Hardware Integration Pocket Optional, enabled with purchase of HP Jetdirect 3000w NFC/Wireless Accessory  HP ePrint, Apple AirPrint™, Google Cloud Print Via HP Jetdirect Ethernet embedded print server (standard) supports: 10Base-T, 100Base-Tx, 1000Base-T; 802.3az (EEE) support on Fast Ethernet and Gigabit Ethernet; IPSec (standard) IPV4/IPV6: Apple Borojour Compatible (Mac Os Vio.24 or higher), SNMPV1/V2CV3, HTTP HTTPS, FTP TFP Port 9100, LPD, WS Discovery, IPP, Secure-IPP, IPSec/Friewalt; IPV6: DHCPV6, MLDV1, ICMPv6; IPv4: Auto-IP, SLP, Telnet, IGMPv2, BOOTP/DHCP, WINS, IP Direct Mode, WS Print
Connectivity Connectivity (Standard) Wireless capability Mobile printing capability Network capabilities Supported network protocols Dimensions (W x D x H)	USB port, Microsoft® Internet Explorer, Windows Vista®-800 MHz processor (32-bit only), 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8. Windows® XP SP3 or higher (32-bit only): any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8; Macc Apple® CS X v10.12 Sierra, OS X v10.11 El Capitan, OS X v10.10 Yosemite, minimum 1.3 GB available HD space; Internet required; USB port  2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Hardware Integration Pocket  Optional, enabled with purchase of HP Jetdirect 3000w NFC/Wireless Accessory  HP ePrint, Apple AirPrint™, Google Cloud Print  Via HP Jetdirect Ethernet embedded print server (standard) supports: 10Base–T, 100Base–Tx, 1000Base–T; 802.3az (EEE) support on Fast Ethernet and Gigabit Ethernet; (Psec (standard)  IPv4/IPv6: Apple Bonjour Compatible (Mac CS v10.24 or higher), SNMPv1/AzCv/2, HTTP, HTTP, FTP TFTP port 9100, LPD, WS Discovery, IPP, Secure-IPP, IPsec/Firewalt; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4: Auto-IP, SLP, Telnet, IGMPv2, 800TP/DHCP, WINS, IP Direct Mode, WS Print  Operating: 813 x 616 x 880 mm (32 x 24.25 x 26.75 in); Maximum: 896 x 718 x 880 mm (35.25 x 28.25 x 26.75 in)
Connectivity  Connectivity (Standard)  Wireless capability  Mobile printing capability  Network capabilities  Supported network protocols  Dimensions (W x D x H)  Weight	USB port, Microsoft® Internet Explorer. Windows Vista®: 800 MHz processor (32-bit only), 2 GB available hard disk space, CD-ROM/OVD drive or Internet Connection, USB port, Microsoft® Internet Explorer 8. Windows® XP SP3 or higher (32-bit only): any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8; Mac: Apple® OS X v10.12 Sierra, OS X v10.11 El Capitan, OS X v10.10 Yosemite, minimum 1.3 GB available HD space; Internet required; USB port  2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Hardware Integration Pocket Optional, enabled with purchase of HP Jetdirect 3000w NFC/Wireless Accessory  HP ePrint, Apple AirPrint™, Google Cloud Print Via HP Jetdirect Ethernet embedded print server (standard) supports: 10Base-T, 100Base-Tx, 1000Base-T; 802.3az (EEE) support on Fast Ethernet and Gigabit Ethernet; IPSec (standard) IPV4/IPV6: Apple Borojour Compatible (Mac Os Vio.24 or higher), SNMPV1/V2CV3, HTTP HTTPS, FTP TFP Port 9100, LPD, WS Discovery, IPP, Secure-IPP, IPSec/Friewalt; IPV6: DHCPV6, MLDV1, ICMPv6; IPv4: Auto-IP, SLP, Telnet, IGMPv2, BOOTP/DHCP, WINS, IP Direct Mode, WS Print
Connectivity Connectivity (Standard) Wireless capability Mobile printing capability Network capabilities Supported network protocols Dimensions (W x D x H) Weight Environmental Operating environment	USB port, Microsoft® Internet Explorer, Windows Vista® 800 MHz processor (32-bit only), 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8. Windows® XP SP3 or higher (32-bit only): any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8; Mac: Apple® CS X v10.12 Sierra, OS X v10.11 EL Capitan, OS X v10.10 Yosemite, minimum 1.3 GB available HD space; Internet required: USB port available HD space; Internet required: USB port Dytional, enabled with purchase of HP Jetdirect 3000w NFC/Wireless Accessory  HP ePrint, Apple AirPrint™, Google Cloud Print Via HP Jetdirect Ethernet embedded print server (standard) supports: 10Base-T, 100Base-Tx, 1000Base-T; 802.3az (EEE) support on Fast Ethernet and Gigabit Ethernet; IPsec (standard)  IPv4/IPv6: Apple Borijour Compatible (Mac: OS v10.24 or higher), SMINP\1/V2cV3, HTTP; HTTP, FTP TFTP Port 9100, LPD, WS Discovery, IPP, Secure-IPP, IPsec/Firewall; IPv6: DHCPv6, MLDV1, ICMPv6; IPv4: Auto-IP, SLP, Telnet, IGMPv2, B00TP/DHCP, WINS, IP Direct Mode, WS Print  Operating: 813 x 616 x 680 mm (32 x 24.25 x 26.75 in); Maximum: 896 x 718 x 680 mm (35.25 x 28.25 x 26.75 in)  Operating: 813 x 616 x 680 ms (32 x 24.25 x 26.75 in); Maximum: 896 x 718 x 680 mm (35.25 x 28.25 x 26.75 in)  Operating: 813 x 616 x 680 ms (32 x 24.25 x 26.75 in); Maximum: 896 x 718 x 680 ms (35.25 x 28.25 x 26.75 in)  Operating: 813 x 616 x 680 ms (32 x 24.25 x 26.75 in); Maximum: 896 x 718 x 680 ms (35.25 x 28.25 x 26.75 in)  Operating: 810 x 610
Wireless capability Mobile printing capability Network capabilities Supported network protocols Dimensions (W x D x H) Weight Environmental	USB port, Microsoft® Internet Explorer, Windows Vista® 800 MHz processor (32-bit only), 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8. Windows® XP SP3 or higher (32-bit only): any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8; Macc Apple® CS X v10.12 Sierra, OS X v10.11 EL Capitan, OS X v10.10 Yosemite, minimum 1.3 GB available HD space; Internet required; USB port available HD space; Internet 10/100/1000T network; 1 Hardware Integration Pocket Optional, enabled with purchase of HP Jetdirect 3000w NFC/Wireless Accessory  HP ePrint, Apple AirPrint™, Google Cloud Print Via HP Jetdirect Ethernet embedded print server (standard) supports: 10Base-T, 100Base-Tx, 1000Base-Tx, 802.3az (EEE) support on Fast Ethernet and Gigabit Ethernet; IPsec (standard)  IPv4/Pv5: Apple Borijour Compatible (Mac CS v10.24 or higher), SMMP1/Av2(v2, HTTP, HTTP, FTP TFTP port 9100, LPD, WS Discovey, IPP, Secure-IPP, IPsec/Firewall; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4: Auto-IP, SLP, Telnet, IGMPv2, BOOTP/DHCP, WINS, IP Direct Mode, WS Print  Operating; 813 x 616 x 680 mm (32 x 24.25 x 26.75 in); Maximum: 896 x 718 x 680 mm (35.25 x 28.25 x 26.75 in)  Operating humidity range: 10 to 80% RH; Recommended operating humidity range: 30 to 70% RH; Operating temperature range: 15 to 30°C (59 to 86°F): Recommended operating temperature range: 17 to 25°C (63 to 77°F); Non-operating humidity range: 10 to 80% RH; Recommended operating temperature range: 17 to 25°C (63 to 77°F); Non-operating humidity range: 10 to 80% RH; Storage before initial setup (Non-operating temperatur
Connectivity Connectivity (Standard) Wireless capability Mobile printing capability Network capabilities Supported network protocols Dimensions (W x D x H) Weight Environmental Operating environment Acoustics Power specifications	USB port, Microsoft® Internet Explorer, Windows Vista® 800 MHz processor (32-bit only), 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8. Windows® XP SP3 or higher (32-bit only): any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8; Mac Apple® CS X v10.12 Sierra, OS X v10.11 El Capitan, OS X v10.10 Yosemite, minimum 1.3 GB available HD space; Internet required; USB port, Microsoft® Internet Explorer 8; Mac Apple® CS X v10.12 Sierra, OS X v10.11 El Capitan, OS X v10.10 Yosemite, minimum 1.3 GB available HD space; Internet required; USB port  2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Hardware Integration Pocket  Optional, enabled with purchase of HP Jetdirect 3000w NFC/Wireless Accessory  HP ePrint, Apple AirPrint™, Google Cloud Print  Via HP Jetdirect Ethernet embedded print server (standard) supports: 10Base—T, 100Base—Tx, 1000Base—T; 802.3az (EEE) support on Fast Ethernet and Gigabit Ethernet; (Psec (standard)  IPv4/IPv6: Apple Bonjour Compatible (Mac CS v10.24 or higher), SNMPV1/V2c/v3, HTTR; HTTP, FTR TFTP, Port 9100, LPD, WS Discovery, IPP, Secure-IPP, IPsec/Frewalt; IPv6: DHCPv6, MLDV1, I/MPv6; IPv4: Auto-IPS LPF Telnet, IGMPv2, B00TP/DHCR; WINS, IP Direct Mode, WS Print  Operating: 813 x 616 x 680 mm (32 x 24.25 x 26.75 in); Maximum: 896 x 718 x 680 mm (35.25 x 28.25 x 26.75 in)  Operating humidity range: 10 to 80% RH; Recommended operating humidity range: 30 to 70% RH; Operating temperature range: 15 to 30°C (59 to 86°F); Recommended operating temperature range: 17 to 25°C (63 to 77°F); Non-operating humidity range: 10 to 80% RH; Storage before initial setup (Non-Purged): -40 to 60°C (-40 to 140°F); Storage after initial setup (Purged): 0 to 60°C (32 to 140°F)  Acoustic power emissions: 54 dB(A) (printing at 61 ppm); Acoustic pressure emissions Bystander (ready
Connectivity Connectivity (Standard) Wireless capability Mobile printing capability Network capabilities Supported network protocols Dimensions (W x D x H) Weight Environmental Operating environment Acoustics Power specifications Software included	USB port, Microsoft® Internet Explorer, Windows Vista® 800 MHz processor (32-bit only), 2 GB available hard disk space, CD-ROM/OVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8. Windows® XP SP3 or higher (32-bit only): any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8; Macc Apple® CS X v10.12 Sierra, OS X v10.11 EL Capitan, OS X v10.10 Yosemite, minimum 1.3 GB available HD space; Internet required; USB port available HD space; Internet Inter
Connectivity Connectivity (Standard) Wireless capability Mobile printing capability Network capabilities Supported network protocols Dimensions (W x D x H) Weight Environmental Operating environment  Acoustics Power specifications Software included	USB port, Microsoft® Internet Explorer, Windows Vista® 800 MHz processor (32-bit only), 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8. Windows® XP SP3 or higher (32-bit only): any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8; Mac Apple® OS X v10.12 Sierra, OS X v10.11 El Capitan, OS X v10.10 Yosemite, minimum 1.3 GB available HD space; Internet required: USB port  Alicrosoft® Internet Explorer 8; Mac Apple® OS X v10.12 Sierra, OS X v10.11 El Capitan, OS X v10.10 Yosemite, minimum 1.3 GB available HD space; Internet required: USB port  2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Hardware Integration Pocket  Optional, enabled with purchase of HP Jetdirect 3000w NFC/Wireless Accessory  HP ePrint, Apple AirPrint™, Google Cloud Print  Via HP Jetdirect Ethernet embedded print server (standard) supports: 10Base-T, 100Base-Tx, 1000Base-T; 802.3az (EEE) support on Fast Ethernet and Gigabit Ethernet; IPsec (standard)  IPv4/IPv6: Apple Bonjour Compatible (Mac OS v10.24 or higher), SNMPv1/v2c/v3, HTTR; HTTP, FTR FTR Port 9100, LPD, WS Discovery, IPP, Secure-IPP, Peec/Friewall; IPv6-IPv6-Mpc1/, ICMPv6-E; IPv6-IAv10-IP SLP Telnet, IGMPv2, B00TP/DHCR WINS, IP Direct Mode, WS Print  Operating: 813 x 616 x 680 mm (32 x 24.25 x 26.75 in); Maximum: 896 x 718 x 680 mm (35.25 x 28.25 x 26.75 in)  Operating humidity range: 10 to 80% RH; Recommended operating humidity range: 30 to 70% RH; Operating temperature range: 15 to 30° C (59 to 86° F); Recommended operating temperature range: 17 to 25° C (63 to 77° F); Non-operating humidity range: 10 to 80% RH; Storage before initial setup (Non-Purged): -40 to 60° C (-40 to 140° F); Storage after initial setup (Purged): 0 to 60° C (32 to 140° F)  Acoustic power emissions: 54 dB(A) (printing af 61 ppm); Acoustic pressure emissions Bystander (re
Connectivity Connectivity Connectivity (Standard) Wireless capability Mobile printing capability Network capabilities Supported network protocols Dimensions (W x D x H) Weight Environmental Operating environment  Acoustics Power specifications  Software included Warranty What's in the box	USB port, Microsoft® Internet Explorer, Windows Vista® 800 MHz processor (32-bit only), 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8, Windows® XP SP3 or higher (32-bit only): any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8; Mac Apple® OS X v10.12 Sierra, OS X v10.11 El Capitan, OS X v10.10 Yosemite, minimum 1.3 GB available HD space; Internet required: USB port  All-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Hardware Integration Pocket  Optional, enabled with purchase of HP Jetdrect 3000w NFC/Wireless Accessory  HP ePrint, Apple AirPrint™, Google Cloud Print  Via HP Jetdirect Ethernet embedded print server (standard) supports: 10Base-T, 100Base-Tx, 1000Base-T; 802.3az (EEE) support on Fast Ethernet and Gigabit Ethernet; IPSec (standard)  IPv4/IPv6. Apple Bonjour Compatible (Mac OS v10.24 or higher), ShMPv1/v2c/v3, HTTP, HTTP, FTP, FTP, FTP, FTP, FTP, Port 9100, LPD, WS Discovery, IPP, Secure-IPP, IPSec/Frewalt; IPv6. DHCPv6, MLDV1, IMCPv6; IPv6. Auto-IP, SLP, Felnet, IGMPv2, B00TP/DHCP, WINS., IP Direct Mode, WS Print  Operating: 813 x 616 x 680 mm (32 x 24.25 x 26.75 in); Maximum: 896 x 718 x 680 mm (35.25 x 28.25 x 26.75 in)  Operating humidity range: 10 to 80% RH; Recommended operating humidity range: 30 to 70% RH; Operating temperature range: 15 to 30° C (59 to 86° P); Recommended operating temperature range: 17 to 25° C (63 to 77° P); Non-operating humidity range: 10 to 80% RH; Storage before initial setup (Non-Purged): -40 to 60° C (-40 to 140° P); Storage after initial setup (Purged): 0 to 60° C (32 to 140° F)  Acoustic power emissions: 54 dB(A) (printing at 61 ppm); Acoustic pressure emissions Bystander (ready): Inaudible; Acoustic power emissions: 54 dB(A) (printing at 61 ppm); Acoustic pressure emissions Bystander (ready): Inaudible; Acoustic pressure emis
Connectivity Connectivity (Standard) Wireless capability Mobile printing capability Network capabilities Supported network protocols Dimensions (W x D x H) Weight Environmental Operating environment  Acoustics Power specifications  Software included Warranty What's in the box	USB port, Microsoft® Internet Explorer, Windows Vista® 800 MHz processor (32-bit only), 2 GB available hard disk space, CD-ROM/OVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8. Windows® XP SP3 or higher (32-bit only): any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8; Macc Apple® OS X v10.12 Sierra, OS X v10.11 EL Capitan, OS X v10.10 Yosemite, minimum 1.3 GB available HD space; Internet Explorer 8; Macc Apple® OS X v10.12 Sierra, OS X v10.11 EL Capitan, OS X v10.10 Yosemite, minimum 1.3 GB available HD space; Internet required; USB port VIII SPACE V

# Ordering information

Number	Description		
Z5G77A	HP PageWide Managed Color MFP E77660dn		
Accessories (Optional)			
Number	Description		
P1V16A	HP PageWide Managed 550-sheet Paper Tray		
P1V17A	HP PageWide Managed 550-sheet Paper Tray and Stan		
P1V18A	HP PageWide Managed 3x550-sheet Paper Tray and Stan		
P1V19A	HP PageWide Managed 4000-sheet HCI Paper Tray and Stan		
A7W99A	HP PageWide 550-sheet Paper Tray		
W1B50A	HP PageWide 550-sheet Paper Tray and Stand		
W1B51A	HP PageWide 3x550-sheet Paper Tray and Stand		
W1B52A	HP PageWide 4000-sheet HCI Paper Tray and Stand		
B5L29A	HP High-Performance Secure Hard Disk		
B5L28A	HP Internal USB Ports		
B5L31A	HP Foreign Interface Harness		
E5K48A	HP 1 GB x32 144-pin (800 MHz) DDR3 SODIMM		
J8031A	HP Jetdirect 2900nw Print Server		
J8030A	HP Jetdirect 3000w NFC/Wireless Accessory		
CC487A	HP LaserJet MFP Analog Fax Accessory 500		

#### Replacement Cartridges and LLC's<sup>9</sup>

Number	Description
M0K31XC	HP 993XC Black Contract PageWide Cartridge (22,000)
M0K08XC	HP 993XC Cyan Contract PageWide Cartridge (16,000)
M0K12XC	HP 993XC Magenta Contract PageWide Cartridge (16,000)
M0K27XC	HP 993XC Yellow Contract PageWide Cartridge (16,000)
W1B44A	HP PageWide Service Fluid Container (~150,000 pages)
W1B43A	HP PageWide Printhead Wiper Kit (~150,000 pages)
W1B45A	HP PageWide Roller Kit (~150,000 pages)

#### Recommended Papers<sup>10</sup>

Number	Description			
Z7S68A	HP PageWide Bro GL A3 100 sheets FSC Paper			
775671	LID DagoWido Pro CL A4 200 choots ESC Dapor			

Please visit  $\underline{\text{hp.com/apac/paper}}$  for more details.

### HP Care Packs

Number	Description
U9RL1E	HP 1-year Next Business Day w/DMR PageWide
	Color 776xx Managed SVC
U9RL2E	HP 3-year Next Business Day w/DMR PageWide
	Color 776xx Managed SVC
U9RL4E	HP 5-year Next Business Day w/DMR PageWide
	Color 776xx Managed SVC
U9RL5E	HP 3-year 4h9x5w/DMR PageWide Color 776xx
	Managed SVC
U9RL7E	HP 5-year 4h9x5w/DMR PageWide Color 776xx
	Managed SVC
U9JT2E	HP Installation Service w Network Workgroup Printer
	stment with HP Care Pack. Let HP certified engineers

hp.com/go/cpc

#### HP Inc offices

Australia	(613) 8833 5000	hp.com.au
China	(010) 6564 3888	hp.com.cn
Hong Kong	(852) 3559 7777	hp.com.hk
India	(80) 2612 9000	hp.com/in
Indonesia	(62-21) 5799 1088	hp.com/id
Korea	(02) 2199 0114	hp.co.kr
Malaysia	(603) 2332 3333	hp.com.my
New Zealand	(09) 918 9555	hp.co.nz
Philippines	(632) 888 5900	hp.com/ph
Singapore	(65) 6275 3888	hp.com.sg
Taiwan	(02) 8722 9000	hp.com.tw
Thailand	(662) 353 9500	hp.com/th
Vietnam	(848) 3823 4151	hp.com/vn

For the following countries, please fax your queries to: (65) 6275 6707 Bangladesh • Bhutan • Brunei • Cambodia • Maldives • Nepal • Pakistan • Srilanka For more information, please visit us at hp.com/apac/homeandoffice



Windows 10 Windows 8 Mac







<sup>1</sup>ISO speeds measured using ISO/IEC 24734. Excludes first page or first set of ISO test pages. For details see hp.com/go/printerclaims <sup>2</sup> Exact speed varies depending on the system configuration, software application, driver and document complexity. <sup>3</sup> First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity. <sup>4</sup>Based on standard ITU-T test image #1 at standard resolution and MMR encoding, the HP fax device can transmit at 3 sec/page for V.3 4 and 6 sec/page for V.17 <sup>5</sup> Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP Pagewide devices, and enables appropriate deployment of printers and MFPs to This value provides a comparison of product robustness in relation to other HP Pagewide devices, and enables appropriate deployment of printers and MFPs to astisfy the demands of connected individuals or groups. HP recommends that the number of printed pages per month be within the stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty period. "Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and vold the product warranty. Power consumption values typically based on measurement of 115V device. "Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and vold the product warranty, Energy Star value typically based on measurement of 115V device. "Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and vold the product warranty. Energy Star value typically based on measurement of 115V device. "Average colour composite (C/MY) and black declared yields based on ISO/IEC 24711 and continuous printing, Actual yields vary considerably based on images printed and other factors. For details see hp.com/go/learnaboutsupplies

© 2017 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. To the extent allowed by law, HP shall not be liable for technical or editorial errors or omissions contained herein.

ENERGY STAR and the ENERGY STAR logo are registered U.S. marks. Microsoft and Windows are registered trademarks of Microsoft Corporation. AirPrint, iPad, iPhone, and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries. Linux is a U.S. registered trademark of Linus Torvalds. UNIX is a registered trademark of The Open Group. NetWare® is a trademark of Novell, Inc.

