



# Waste Profile Datasheet

## HP 3D600 & 3D700 Detailing & Fusing Agents

### The information below is applicable for the below listed SKUs:

F9K08SERIES, V1Q60SERIES, V1Q61SERIES, V1Q63SERIES, V1Q64SERIES

#### Purpose of this document

HP Inc. ("HP") is providing the information in this document voluntarily as a service to its customers so that customers can determine appropriate disposal methods for the products at the end of life. Safety Data Sheets ("SDSs") such as the Hazard Communication Standard of the U.S. Occupational Safety and Health Administration ("OSHA") and similar requirements in other countries can be found at [www.hp.com/go/ecodata](http://www.hp.com/go/ecodata).

#### Flashpoint (USEPA Method 1020)

>110C

#### Corrosivity to steel (USEPA Method 1110)

Fusing Agent = 0.06 mm/year  
Detailing Agent <0.1 mm/year

#### pH (USEPA Method 9040)

9.18

#### Metals Content (ICP-MS)

Antimony	<0.1 mg/L
Arsenic	0.1 mg/L
Barium	<0.1 mg/L
Beryllium	<0.1 mg/L
Cadmium	<0.1 mg/L
Chromium	<0.1 mg/L
Copper	<0.1 mg/L
Lead	<0.1 mg/L
Mercury	<0.1 mg/L
Nickel	0.1 mg/L
Selenium	<0.1 mg/L
Silver	<0.1 mg/L
Thallium	<0.1 mg/L
Vanadium	<0.1 mg/L
Zinc	<0.1 mg/L

#### Toxicity (DOHS (Title 22) Hazardous Waste Bioassay using Fathead Minnow)

- The agents do not meet the criteria for classification according to Regulation (EC) 1272/2008 as amended.
- LC50 for fish is >750 mg/L for all agents.