

HP Fiber NIC Port Flex IO



Maximize PC life as your business needs change with the HP Fiber NIC Port Flex IO that offers superb transfer rates, reliability, and security versus standard Ethernet connections.

Specifications

HP Fiber NIC Port Flex IO

Part number	3TK73AA
Dimensions	1.57 x 2.87 x 0.75 in (4 x 7.29 x 1.92 cm)
Weight	.05 lb (23 gr)
Compatible operating systems	Windows 10, Windows 8, Linux
System requirements, minimum	CPU: Intel® i3 or higher or higher; RAM: 4 GB or higher; HDD: 128 GB or more of available space; Interface: 70 pin board to board connector (PCIE)
Operating temperature	0° to 50°C, operating
Storage temperature	20° to 80°C, non-operating
Humidity (non-condensing)	10-90% operating 5-95% non-operating
Altitude	10,000 ft, operating 50,000 ft, non-operating
Network boot code	27M2 PXE located in NVM
Network boot link speed	100 Mbps
LED mode	Green link, no speed indication
Network boot menu	Disabled (to be managed in BIOS)
Wake on LAN	Supported
Ethernet features	VLAN support required in driver to support capture of VLAN Tag information Application to support VLAN for mobile products when available
Compatibility	HP EliteDesk 800 G4 DM (35W), HP EliteDesk 800 G4 DM (65W) Only one FLEX IO module can be used at a time
What is in the box?	HP Fiber NIC Port Flex IO card
Country of origin	China

Sign up for updates
hp.com/go/getupdated



Share with colleagues



Rate this document

© Copyright 2018 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

