


HP Type-C USB 3.1 Gen2 Port with PD Flex IO



Maximize the life of your PC as your business needs change with the flexible connectivity of the HP Type-C USB 3.1 Gen2 Port with PD FlexIO, which supports ultra-fast transfer speeds compared to USB 3.1 Gen 1 and transmits data and power through one cable.

Specifications

HP Type-C USB 3.1 Gen2 Port with PD Flex IO

Part number	3TK79AA
Dimensions	1.55 x 1.5 x 0.77 in (3.94 x 3.82 x 1.95 cm)
Weight	0.02 lb (11 g)
Compatible operating systems	Windows 10, Windows 8
System requirements, minimum	CPU: Intel® i3 or higher or higher; RAM: 4 GB or higher; HDD: 128 GB or more of available space; Interface: 60 pin board to board connector (USB2.0 & USB3.1 Gen 2)
Compatibility	HP EliteDesk 800 G4 DM (35W). Only one FLEX IO module can be used at a time
What is in the box?	HP Type-C USB 3.1 Gen2 Port with PD Flex IO card
Country of origin	China

Sign up for updates
hp.com/go/getupdated



Share with colleagues



Rate this document

© Copyright 2018 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.
USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum.

