



Product Service

CERTIFICATE**No. Z1A 14 06 52878 098****Model(s):** HSTNN-I13C, HP EliteBook 720 G1,
HP EliteBook 820 G1**Parameters:**

Rated input voltage:	19.5 Vdc
Rated input current:	2.31 A or 3.33 A
Protection class:	III
Max. ambient temperature:	35 °C
Degree of protection against ingress of liquids:	Ordinary
Declared Sound Power level:	3.1 B(A)

Remarks: 1. See attachment for LCD(s) covered by this certificate.

2. The equipment is evaluated for operating in altitude up to 3,048 m (10,000 ft) above the sea level.

Factory(ies): 75263, 65256

Page 2 of 3



Taiwan

Attachment to the Certificate No. Z1A 14 06 52878 098

The following LCD's panel description of the models are as below:

- | | |
|---------------|-----------------|
| 1. AUO | Type: B125XTN02 |
| 2. LG Display | Type: LP125WH2 |
| 3. Hefei Boe | Type: HB125WX1 |

Suitable for Max. illuminance: $L_{REF,EXT} = 200 \text{ cd/m}^2$ and $L_{REF,SML} = 2000 \text{ cd/m}^2$

Suitable for Max. illuminance: 750 Lux

Pixel fault classification: I

Design viewing distance: 500 mm


Design viewing direction: (0°, 90°)

Viewing direction range: Φ range is 0° to 360°

θ range is 35.2°

Content and perception: Artificial information

Date: 2014-11-27



Testing Laboratory

Bill Lin