


Overview

HP ProBook 645 G1 Notebook PC



Front/Left


- | | |
|---|--|
| 1. WLAN antennas (2)* | 14. Hard drive light |
| 2. WWAN antennas (2)* | 15. AC adapter/Battery light |
| 3. Internal microphone array (2)** | 16. Power light |
| 4. Webcam light (select models only) | 17. Wireless light |
| 5. Webcam (select models only) | 18. Smart Card Reader |
| 6. Internal display switch | 19. Optical Drive (select models only) |
| 7. Wireless button | 20. Media Card Reader |
| 8. Volume mute button | 21. USB 3.0 port (1) |
| 9. Pointing stick (select models only) | 22. USB 3.0 charging port (1) |
| 10. Fingerprint reader | 23. RJ-45 (network) jack/lights |
| 11. Touchpad buttons | 24. Power connector |
| 12. Touchpad zone | 25. Power button |
| 13. Pointing stick buttons (select models only) | |

* The antennas are not visible from the outside of the computer. For optimal transmission, keep the areas immediately around the antennas free from obstructions.

** Models without optional webcam have single integrated microphone on left side of display panel.



Overview




1. Audio-out (headphone) jack/Audio-in (microphone) jack
2. USB 3.0 ports (2)
3. DisplayPort 1.2

Right

4. External VGA monitor port
5. Vents (2)
6. Security cable slot

Overview




1. Service cover
2. Battery release latch
3. SIM card slot
4. Docking connector

Bottom

5. Service cover release lock
6. Service door release latch
7. Battery bay
8. Vents

Overview

HP ProBook 655 G1 Notebook PC



Front/Left


- | | |
|---|---|
| 1. WLAN antennas (2)* | 14. Hard drive light |
| 2. WWAN antennas (2)* | 15. AC adapter/Battery light |
| 3. Internal dual-microphone array (2)** | 16. Power light |
| 4. Webcam light (select models only) | 17. Wireless light |
| 5. Webcam(select models only) | 18. Smart Card Reader |
| 6. Internal display switch | 19. Upgrade bay (optical drive shown)Optical Drive (select models only) |
| 7. Wireless button | 20. Media Card Reader |
| 8. Volume mute button | 21. USB 3.0 port (1) |
| 9. Pointing stick (select models only) | 22. USB 3.0 charging port (1) |
| 10. Fingerprint reader (select models only) | 23. RJ-45 (network) jack/lights |
| 11. Touchpad buttons | 24. Power connector |
| 12. Touchpad zone | 25. Power button |
| 13. Pointing stick buttons (select models only) | |

* The antennas are not visible from the outside of the computer. For optimal transmission, keep the areas immediately around the antennas free from obstructions.

** Models without optional webcam have single integrated microphone on left side of display panel.



Overview




1. Audio-out (headphone) jack/Audio-in (microphone) jack
2. USB 3.0 ports (2)
3. DisplayPort 1.2

Right

4. External VGA monitor port
5. Vents (2)
6. Security cable slot

Overview



- 1. Service cover
- 2. Battery release latch
- 3. SIM card slot
- 4. Docking connector

Bottom

- 5. Service cover release lock
- 6. Service door release latch
- 7. Battery bay
- 8. Vents



Overview

AT A GLANCE

- Windows 10 versions, Windows 8 versions, Windows 7 versions, SUSE Linux, or FreeDOS 2.0
- New thinner and lighter design – PC-ABS (Polycarbonate–Acrylnitrile/Butadiene/Styrene) durable material is nearly 20% thinner than previous generation; soft-touch, more durable 4-step paint process; larger buttons (power), revamped keyboard (arrow keys); latch/hook removal for clean palmrest design; top mounted speakers for optimized audio experience
- Full-sized spill-resistant keyboard; full separate numeric keypad (HP ProBook 655 only)
- Larger Touchpad with gestures support, on/off button with LED indicator
- New User Experience Software: HP ePrint, HP Wireless Hotspot (Win 8 only), HP PageLift, HP Mobile Connect (EMEA only)
- Enhanced security features including HP Client Security and HP Fingerprint Reader
- Accelerated Processing Unit and graphics from AMD
- LED-backlit display
 - HP ProBook 645: 14.0-inch diagonal HD, HD+, FHD
 - HP ProBook 655: 15.6-inch diagonal HD or FHD
- Optional HD webcam with dual-microphone array for video conferencing
- DisplayPort 1.2 now native with integrated graphics
- Four USB 3.0 ports for fast data transfer from devices (1 charging)
- HD Audio with DTS Sound+ optimized for high fidelity audio
- Wireless and speaker mute button to conveniently manage the connectivity and speaker.
- Flexible wireless connectivity options:
 - HP Connection Manager allows full control over wireless connections, including 3G and 4G mobile broadband, Wi-Fi, Ethernet and Bluetooth® (Win 7 only)
 - HP Mobile Connect (EMEA Only) (Win 8 Only)
 - Integrated 4G HP Mobile Broadband Modules
 - Integrated 802.11 b/g/n wireless LAN module
 - Integrated 802.11 a/b/g/n or b/g/n with Bluetooth 4.0 High Speed combo card (Linux support Bluetooth 2.1 only)
 - HP Wireless Hotspot (Win 8 Only)
- Choice of 7200 rpm user-removable hard drive (up to 500 GB) with HP 3D DriveGuard, 5400 rpm user-removable hard drive (up to 1 TB), 500 GB 7200 rpm Self Encrypting Drive, 500 GB 5400 rpm FIPS Self Encrypting Drive, 256 GB SED Solid State Drive, or 128/180 GB Solid State Drive

NOTE: See important legal disclosures for all listed specs in their respective features sections.



Features

PRODUCT NAME

HP ProBook 645 G1 Notebook PC

HP ProBook 655 G1 Notebook PC

OPERATING SYSTEM

Preinstalled

Windows 10 Pro 64*
Windows 10 Home 64*
Windows 8.1 Pro 64*
Windows 8.1 64*
Windows 8 Pro 64*
Windows 8 64*
Windows 7 Professional 64 (available through downgrade rights form Windows 8.1 Pro)**
Windows 7 Professional 32 (available through downgrade rights form Windows 8.1 Pro)**
Windows 7 Professional 64 (available through downgrade rights form Windows 8 Pro)**
Windows 7 Professional 32 (available through downgrade rights form Windows 8 Pro)**
Windows 7 Professional 64***
Windows 7 Professional 32***
SUSE Linux Enterprise Desktop 11
FreeDOS 2.0

Web-only Support

Windows 10 Pro 64*
Windows 10 Home 64*
Windows 8.1 Pro 64*
Windows 8.1 64*
Windows 8 Pro 64*
Windows 8 64*
Windows 7 Professional 64 (available through downgrade rights from Windows 10 Pro)***
Windows 7 Professional 32 (available through downgrade rights from Windows 10 Pro)***
Windows 7 Professional 64 (available through downgrade rights form Windows 8.1 Pro)**
Windows 7 Professional 32 (available through downgrade rights form Windows 8.1 Pro)**
Windows 7 Professional 64 (available through downgrade rights form Windows 8 Pro)**
Windows 7 Professional 32 (available through downgrade rights form Windows 8 Pro)**
Windows 7 Professional 64*
Windows 7 Professional 32*
Windows 10 Enterprise 64*
Windows 8.1 Enterprise 64*
Windows 8 Enterprise 64*
Windows 7 Enterprise 64*
Windows 7 Enterprise 32*
Windows 7 Home Basic 64*
Windows 7 Home Basic 32*
Windows 7 Home Premium 64*
Windows 7 Home Premium 32*
Windows 7 Ultimate 64*
Windows 7 Ultimate 32*

* Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See <http://http://www.microsoft.com>.

** This system is preinstalled with Windows 7 Professional software and also comes with a license and media for Windows 8 Pro



Features

software. You may only use one version of the Windows software at a time. Switching between versions will require you to uninstall one version and install the other version. You must back up all data (files, photos, etc.) before uninstalling and installing operating systems to avoid loss of your data.

*** This system is preinstalled with Windows 7 Professional software and also comes with a license and media for Windows 10 Pro software. You may only use one version of the Windows software at a time. Switching between versions will require you to uninstall one version and install the other version. You must back up all data (files, photos, etc.) before uninstalling and installing operating systems to avoid loss of your data

ACCELERATED PROCESSING UNIT

AMD Elite Quad-Core A10-5750M APU (2.5 GHz/3.5 GHz, 4 MB cache) with AMD Radeon™ HD 8650G Graphics
AMD Elite Quad-Core A8-5550M APU (2.1 GHz/3.1 GHz, 4 MB cache) with AMD Radeon™ HD 8550G Graphics
AMD Elite A6-5350M APU (2.9 GHz/3.5GHz, 1 MB cache, 2 cores) with AMD Radeon™ HD 8450G Graphics
AMD Elite A4-5150M APU (2.7 GHz/3.3GHz, 1 MB cache, 2 cores)with AMD Radeon™ HD 8350G Graphics
AMD Elite Quad-Core A10-4600M APU (2.3 GHz/3.2 GHz, 4 MB cache) with AMD Radeon™ HD 7660G Graphics
AMD Elite Quad-Core A8-4500M APU (1.9 GHz/2.8GHz, 4 MB cache) with AMD Radeon™ HD 7640G Graphics
AMD Elite A6-4400M APU (2.7 GHz/3.2GHz, 1 MB cache, 2 cores) with AMD Radeon™ HD 7520G Graphics
AMD Elite A4-4300M APU(2.5 GHz/3.0GHz, 1 MB cache, 2 cores) with AMD Radeon™ HD 7420G Graphics

NOTE: AMD Radeon™ Dual Graphics requires an AMD “A” series APU plus an AMD Radeon™ discrete graphics configuration. AMD Dynamic Switchable Graphics technology requires either an AMD “A” series APU or an Intel processor, plus an AMD Radeon™ discrete graphics configuration and is available on Windows 8 Pro, Windows 8, Windows® 7 Professional OS.

NOTE: With AMD Dynamic Switchable Graphics technology, full enablement of all discrete graphics video and display features may not be supported on all systems (e.g. OpenGL applications will run on the integrated GPU or the APU as the case may be).

NOTE: Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

FUSION CONTROLLER HUB (FCH)

AMD A76M FCH

GRAPHICS

Integrated graphics:

AMD Elite Quad-Core A10-5750M Accelerated Processor with AMD Radeon™ HD 8650G Graphics
AMD Elite Quad-Core A8-550M Accelerated Processor with AMD Radeon™ HD 8550G Graphics
AMD Elite A6-5350M Accelerated Processor with AMD Radeon™ HD 8450G Graphics
AMD Elite A4-5150M Accelerated Processor with AMD Radeon™ HD 8350G Graphics
AMD Elite Quad-Core A10-4600M Accelerated Processor with AMD Radeon™ HD 7660G Graphics
AMD Elite Quad-Core A8-4500M Accelerated Processor with AMD Radeon™ HD 7640G Graphics
AMD Elite A6-4400M Accelerated Processor with AMD Radeon™ HD 7520G Graphics
AMD Elite A4-4300M Accelerated Processor with AMD Radeon™ HD 7420G Graphics

NOTE: Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

DISPLAY

HP ProBook 645



Features

Internal

- 14" diagonal LED-backlit HD anti-glare (1366 x 768)
- 14" diagonal LED-backlit HD+ anti-glare (1600 x 900)
- 14" diagonal LED-backlit FHD anti-glare slim (1920 x 1080))

External

Up to 32-bit per pixel color depth

VGA

Port supports resolutions up to 1920 x 1200 external resolution @75 Hz

DisplayPort 1.2

Supports resolutions up to 2560 x 1600, 30-bit color depth at 60 Hz, and full HD (1920 x 1080) monitors, 24-bit color depth at 120 Hz

DVI-D (single link)

Video signal available through DVI port in optional HP Docking Station (sold separately) supports resolutions up to 1600 x 1200 at both full and reduced blanking, and 1920 x 1200 at reduced blanking

Number of Displays Supported

# Displays with HP Advanced Docking Station	UMA	Discrete
ProBook 645 with A10	4	n/a

NOTE: HD content required to view HD images.

NOTE: Resolutions are dependent upon monitor capability, and resolution and color depth settings.

HP ProBook 655

Internal

- 15.6" diagonal LED-backlit HD anti-glare (1366 x 768)
- 15.6" diagonal LED-backlit FHD anti-glare slim (1920 x 1080)

External

Up to 32-bit per pixel color depth

VGA

Port supports resolutions up to 1920 x 1200 external resolution @75 Hz

DisplayPort 1.2

Supports resolutions up to 2560 x 1600, 30-bit color depth at 60 Hz, and full HD (1920 x 1080) monitors, 24-bit color depth at 120 Hz

DVI-D (single link)

Video signal available through DVI port in optional HP Docking Station (sold separately) supports resolutions up to 1600 x 1200 at both full and reduced blanking, and 1920 x 1200 at reduced blanking

Number of Displays Supported

# Displays with HP Advanced Docking Station	UMA	Discrete
ProBook 655 with A10	4	n/a

NOTE: HD content required to view HD images.

NOTE: Resolutions are dependent upon monitor capability, and resolution and color depth settings.



Features

STORAGE AND DRIVES

Primary Storage Bay

Hard Drives*

320/500/1 TB 5400 rpm SMART SATA II HDD;
320/500/750 GB 7200 rpm SMART SATA II HDD
500 GB 7200 rpm SED (Self Encrypting Drive)
500 GB 5400 rpm FIPS** SED (Self Encrypting Drive)

Solid State Drive*

128/180 GB 2.5" Solid State Drive
256 GB SED Solid State Drive

HP 3D DriveGuard (Windows only)

The hard drive is mounted directly to the notebook frame, reducing the transmission of shock to the hard drive

*For hard drives and solid state drives, GB = 1 billion bytes. Actual formatted capacity is less. Up to 16 GB (for Windows 7) and up to 30 GB (for Windows 8 and 10) of system disk is reserved for the system recovery software.

** FIPS-certified, hardware-based AES-256 encryption image

NOTE: For Solid State Drives (SSD), GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 5GB for Windows 8 is reserved for system recovery software.

OPTICAL DRIVES

Fixed 9.5 mm Serial ATA Upgrade Bay

Blu-ray ROM DVD+/-RW SuperMulti DL Drive
DVD+/-RW SuperMulti DL Drive
DVD-ROM Drive

Weight saver

MEMORY

Standard

DDR3L-1600 (Transfer rates up to 1600 MT/s)
Two SODIMM slots supporting dual-channel memory
2 GB, 4 GB, and 8 GB SODIMMs*

Maximum

Upgradeable to 16384 MB with optional 8192 MB SODIMMs in slots 1 and 2

Dual-channel

Maximized dual-channel performance requires SODIMMs of the same size and speed in both memory slots.

* Maximum memory capacities assume Windows 64-bit operating systems or Linux. With Windows 32-bit operating systems, memory above 3 GB may not all be available due to system resource requirements.

NOTE: Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.

NETWORKING/COMMUNICATIONS

Wireless

Support for a broad range of secure, integrated wireless LAN and wireless WAN options featuring support for the latest industry standards. Broadband Wireless (WWAN) requires a Windows operating system and is available in select countries



Features

as a standard, factory configurable feature only. Integrated Bluetooth is also available (factory configurable only) and can be combined with any of the supported wireless LAN and wireless WAN options.

Broadband Wireless (WWAN)

HP hs3110 HSPA+ Mobile Broadband Module*

HP lt4111 LTE/EV-DO/HSPA+ Mobile Broadband Module (US) *,**

HP lt4112 LTE/HSPA+ Mobile Broadband Module (EMEA, APJ) *,**

Wireless LAN (WLAN)*

Atheros 802.11 b/g/n (1x1) ***

Atheros 802.11 b/g/n (1x1) with Bluetooth® v4.0 combo ***

Broadcom 802.11 a/b/g/n (2x2) with Bluetooth® v4.0 combo ***

* WWAN is an optional feature sold separately or as an add on feature. WWAN connection requires wireless data service contract, network support, and is not available in all areas. Contact service provider to determine the coverage area and availability. Connection speeds will vary due to location, environment, network conditions, and other factors.

** 4G LTE not available on all products, in all regions and only available on products featuring Intel processors.

***Wireless access point and Internet service is required and is not included. Availability of public wireless access points limited.

NOTE: Supports Bluetooth® v2.1 on Linux operating systems

Communications

Realtek 10/100/1000* Ethernet Controller

* The term "10/100/1000" or "Gigabit" Ethernet indicates compatibility with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/s. For high-speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

AUDIO/MULTIMEDIA

Audio

HD Audio with DTS Sound+

(2) Integrated stereo speakers

Integrated digital microphone (dual-microphone array when equipped with optional webcam)

Function keys for microphone mute, volume up, volume down

Stereo headphone/line out

Stereo microphone in

Webcam

Optional* 720p HD** webcam

- HD format (widescreen)
- Supports videoconferencing (non-HD) and still image capture
- High quality fixed focus lens
- Video capture at various resolutions up to 1280x720 resolution (720p) and up to 30fps
- M-JPEG compression supports higher frame rates for video capture and videoconferencing
- Improved low light sensitivity
- Improved dynamic range
- Skype-ready

* Sold separately as an optional feature.

** HD content required to view HD images.

KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS



Features

Keyboard

The HP spill-resistant keyboard is designed using a thin layer of Mylar film under the keyboard. The 101/102-key compatible keyboard features a full-pitch key layout with desktop keyboard features, such as editing keys, both left and right control and alt keys, and function keys. US and International key layouts are available. Includes a separate numeric keypad (HP ProBook 655 only).

Pointing Devices

Touchpad with gestures support, on/off button with LED indicator, two-way scroll, two pick buttons, optional point stick

Buttons and Function Keys

Separate launch buttons provide easy access to wireless on/off and speaker mute. Function keys provide control of features including: standby mode, display brightness, external display, microphone mute, volume down, and volume up.

SOFTWARE AND SECURITY

Preinstalled Software with Windows Operating System

BIOS

HP DriveLock | HP Automatic Drive Lock

HP BIOS Protection*

HP Disk Sanitizer**

HP SpareKey***

Update via Network

Master Record Security

Power On Authentication

Pre-Boot Security

Secure Erase****

Hybrid Boot

Measured Boot

Secure Boot

Absolute Persistence Module*****

* HP Tools partition with an HP BIOS required for automatic recovery.

** For the use cases outlined in the DOD 5220.22-M Supplement. Does not support Solid State Drives (SSDs). Initial setup required. Web history deleted only in Internet Explorer and Firefox browsers and must be user enabled.

*** Requires initial user set up.

**** For the methods outlined in the National Institute of Standards and Technology Special Publication 800-88.

***** The Absolute Persistence agent is shipped turned off, and will be activated when customers activate a purchased subscription. Subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. The Absolute Recovery Guarantee is a limited warranty. Certain conditions apply. For full details visit: <http://www.absolute.com/company/legal/agreements/computrace-agreement>. Data Delete is an optional service provided by Absolute Software. If utilized, the Recovery Guarantee is null and void. In order to use the Data Delete service, customers must first sign a Pre-Authorization Agreement and either obtain a PIN or purchase one or more RSA SecurID tokens from Absolute Software.

MultiMedia

CyberLink PowerDVD

CyberLink Power2Go (Optical drives)

CyberLink YouCam BE (Windows 7 only)

Communication

HP Connection Manager (Windows 7 only)

HP GPS and Location* (Windows 7 only)

HP Mobile Connect** (Windows 8 only)

HP Wireless Hotspot*** (Windows 8 only)

Intel WiDi Software****

HP Roaming Alert (Windows 8 only)



Features

Intel My WiFi and Wireless Drivers

HP Value Add Software

HP 3D DriveGuard
HP ePrint Driver***** (HP Exclusive)
HP PageLift (HP Exclusive)*****
HP Recovery Manager (Windows 7 only)
HP Support Assistant
HP Recovery Disc Creator (Windows 7 only)
UEFI System Diagnostics W8

3rd Party

Adobe Flash Player Skype*****
Buy Office
Free 50GB Box Cloud Storage & Collaboration Account*****

*GPS access requires an unobstructed path to multiple satellites. Performance may be affected if/when used inside of buildings, bridges or heavily congested metropolitan areas. Requires separately purchased GPS navigation software available from multiple GPS applications.

**Internet access required.

*** The wireless hotspot application requires an active internet connection and separately purchased data plan. While HP wireless hotspot is active, on-device applications will continue to work and will use the same data plan as the wireless hotspot. Wireless hotspot data usage may incur additional charges. Check with your service provider for plan details. Requires Windows 8.1 or HP Connection Manager for Windows 7.

**** Integrated Intel Wi-Di feature is available on select configurations only and requires separately purchased projector, tv or computer monitor with an integrated or external Wi-Di receiver. External Wi-Di receivers connect to the projector, tv or computer monitor via a standard HDMI cable, also sold separately.

*****Requires an Internet connection to HP web-enabled printer and HP ePrint account registration (for a list of eligible printers, supported documents and image types and other HP ePrint details, see www.hp.com/go/eprintcenter). Requires optional broadband module. Broadband use requires separately purchased service contract. Check with service provider for coverage and availability in your area. Separately purchased data plans or usage fees may apply. Print times and connection speeds may vary.

***** HP PageLift requires Windows 7 or higher edition.

***** Skype is not offered in China.

***** Offer available on new 2013 HP commercial PC and requires Box registration. Offer subject to change without notice.

Security

Standard

HP Client Security*
HP Client Security
HP Credential Manager
HP Password Manager
HP Drive Encryption (FIPS 140-2)**
HP Device Access Manager with Just In Time Authentication
TPM 1.2 Embedded Security Chip (Common Criteria EAL4+ Certified)
HP File Sanitizer***
HP Spare Key
Integrated Smart Card Reader (FIPS 201)
Security lock slot
Security screw for bottom access door
Microsoft Security Essentials (Windows 7)****
Microsoft Defender (Windows 8)



Features

HP Fingerprint Sensor

* Not all features are remotely manageable.

*** Requires Windows. Data is protected prior to Drive Encryption login. Turning the PC off or into hibernate logs out of Drive Encryption and prevents data access. Drive encryption planned to be available in October 2013.

*** For the use cases outlined in the DOD 5220.22-M Supplement. Does not support Solid State Drives (SSDs). Initial setup required. Web history deleted only in Internet Explorer and Firefox browsers and must be user enabled.

**** Opt in and internet connection required for updates.

For more information on HP security solutions refer to: <http://www.hp.com/go/security>.

POWER

Power Supply

External 65W HP Smart AC Adapter

Power cord included is 1.8 m (+/- 0.1 m) or 1.0 m (+/- 0.1 m).

Total length including external AC adapter is TBD feet (TBD meter).

HP Fast Charge*

Primary Battery

HP 9-cell Lithium-Ion Battery (100 WHr)

HP 6-cell Lithium-Ion Battery (55 WHr)

HP 6-cell Long Life Lithium-Ion Battery (55 WHr)

HP 3-cell Lithium-Ion Battery (33 WHr)

Battery Life*

	Dual-Core	Quad-Core
HP ProBook 645 G1		
6-cell (55 WHr) with hard drive	Up to 9 hours	Up to 9 hours 15 minutes
6-cell (55 WHr) with 2.5" solid state drive	Up to 9 hours 30 minutes	Up to 10 hours 15 minutes
9-cell (100 WHr) with hard drive	Up to 16 hours	Up to 16 hours 15 minutes
9-cell (100 WHr) with 2.5" solid state drive	Up to 17 hours 15 minutes	Up to 18 hours
6-cell Long Life (55 WHr) with hard drive	N/A	Up to 9 hours
6-cell Long Life (55 WHr) with 2.5" solid state drive	N/A	Up to 9 hours 45 minutes
HP ProBook 655 G1		
6-cell (55 WHr) with hard drive	Up to 8 hours 15 minutes	Up to 8 hours 45 minutes
6-cell (55 WHr) with 2.5" solid state drive	Up to 9 hours 15 minutes	Up to 9 hours 15 minutes
9-cell (100 WHr) with hard drive	Up to 14 hours 45 minutes	Up to 14 hours 45 minutes
9-cell (100 WHr) with 2.5" solid state drive	Up to 15 hours 45 minutes	Up to 16 hours 15 minutes
6-cell Long Life (55 WHr) with hard drive	N/A	N/A
6-cell Long Life (55 WHr) with 2.5" solid state drive	N/A	N/A



Features

System Standby Time**

Up to TBD days

* Windows 7 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See www.bapco.com for additional details.

** Standby life will vary depending on various factors including battery, Memory, CPU, EC and LAN chip. The maximum capacity of the battery will naturally decrease with time and usage.

NOTE: Fast Charge recharges your battery up to 90% within 120 minutes when the system is off (6-cell only).

Power Conservation

AMD PowerPlay technology (discrete models)

Hibernation

Standby

ACPI compliance

WEIGHTS & DIMENSIONS

HP ProBook 645 Notebook PC

Weight

Lightest possible configuration across battery and panel options (HD Panel, No-ODD, 3-cell (31Whr) Battery, M.2 128GB SSD) at 4.4lb / 2kg. Lightest Weight Configurations (across panel, battery and ODD options, if applicable)

	3-cell (31Whr)	6-Cell (55Whr)	6-Cell Long Life (55Whr)	9-Cell (100Whr)
No-ODD	4.4lb/2kg	4.59lb/2.083kg	4.65lb/2.109kg	4.80lb/2.18kg
ODD	4.69lb/2.13kg	4.87lb/2.21kg	4.94lb/2.24kg	5.09lb/2.31kg

Dimensions (w x d x h)

13.39 x 9.33 x 0.99 (front)/1.14 (rear) in

34.0 x 23.7 x 2.53 (front)/2.90 (rear) cm

HP ProBook 655 Notebook PC

Weight

Lightest possible configuration across battery and panel options (HD Panel, No-ODD, 3-cell (31Whr) Battery, M.2 128GB SSD) at 5.1lb / 2.32kg. Lightest Weight Configurations (across panel, battery and ODD options, if applicable)

	3-cell (31Whr)	6-Cell (55Whr)	6-Cell Long Life (55Whr)	9-Cell (100Whr)
No-ODD	5.1lb/2.32kg	5.30lb/2.40kg	5.35lb/2.43kg	5.51lb/2.5kg
ODD	5.39lb/2.50kg	5.58lb/2.53kg	5.64lb/2.56kg	5.80lb/2.63kg

Dimensions (w x d x h)

14.88 x 10.12 x 0.99 (front) -1.14 in (rear)

37.80 x 25.70 x 2.53 (front) -2.90 cm (rear)

PORTS/SLOTS

Ports



Features

- USB 3.0 – Three
- USB 3.0 charging port – One
- DisplayPort 1.2 – One
- VGA – One
- Stereo microphone input – One
- Headphone/line out – One
- RJ-45 (Ethernet) – One
- Docking connector – One
- Serial port – One*
- Power connector – One
- * ProBook 655 only

Expansion Slots

- Media Card Reader
- supports SD, SDHC, SDXC

SERVICE AND SUPPORT

HP Services offers limited 3-year and 1-year warranty options depending on country; 1-year limited warranty on primary battery. On-site service and warranty upgrades are also available. Optional* HP Care Pack Services** are extended service contracts which go beyond your standard warranties. For more details visit: <http://www.hp.com/go/lookuptool>.

*Sold separately or as an optional feature.

** Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. Consult the HP Customer Support Center for details. <http://h20000.www2.hp.com/bizsupport/TechSupport/ProductRoot.jsp>

NOTE: Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit <http://www.hp.com/go/cpc>



Technical Specifications

SYSTEM UNIT

Stand-Alone Power Requirements (AC Power)	Nominal Operating Voltage	TBD
	Average Operating Power	TBD W
	Max Operating Power	< 65 W
Temperature	Operating	32° to 95° F (0° to 35° C) (not writing optical) 41° to 95° F (5° to 35° C) (writing optical)
	Non-operating	-4° to 140° F (-20° to 60° C)
Relative Humidity	Operating	10% to 90%, non-condensing
	Non-operating	5% to 95%, 101.6° F (38.7° C) maximum wet bulb temperature
Shock	Operating	40 G, 2 ms, half-sine
	Non-operating	200 G, 2 ms, half-sine
Random Vibration	Operating	0.75 grms
	Non-operating	1.50 grms
Altitude (unpressurized)	Operating	-50 to 10,000 ft (-15.24 to 3,048 m)
	Non-operating	-50 to 40,000 ft (-15.24 to 12,192 m)
Planned Industry Standard Certifications	UL	Yes
	CSA	Yes
	FCC Compliance	Yes
	ENERGY STAR®	Select models*
	EPEAT	Registered TBD in United States**
	ICES	Yes
	Australia / NZ A-Tick Compliance	Yes
	CCC	Yes
	Japan VCCI Compliance	Yes
	KC	Yes
	BSMI	Yes
	CE Marking Compliance	Yes
	BNCI or BELUS	Yes
	CIT	Yes
	GOST	Yes
	Saudi Arabian Compliance (ICCP)	Yes
	SABS	Yes
	UKRSERTCOMPUTER	Yes

* Configurations of the HP ProBook 645 and HP ProBook 655 that are ENERGY STAR qualified are identified as HP ProBook 645 ENERGY STAR and HP ProBook 655 ENERGY STAR on HP websites and on <http://www.energystar.gov>.

** EPEAT registration varies by country. See <http://www.epeat.net> for registration status by country. EPEAT status listed above applies to U.S.

For accessibility information on HP products, please visit: <http://www.hp.com/accessibility>.

DISPLAYS

14.0" diagonal LED-backlit HD anti-glare SVA eDP 1.2 flat (1366x768)	Outline Dimensions (W x H x D)	12.6 x 8.09 x 0.14 in (32.09 x 20.56 x 0.36 cm)
	Active Area	12.18 x 6.85 in (30.94 x 17.395 cm)
	Weight	0.71 lb (320g) (max)
	Diagonal Size	14.0 in (35.6cm)



Technical Specifications

	Surface Treatment	Anti-glare		
	Contrast Ratio	300:1 (min)		
	Refresh Rate	60 Hz		
	Brightness	200 nit (typical)		
	Pixel Resolution	Format	1366 x 768 (HD)	
		Configuration	RGB Stripe	
	Interface	eDP 1.2 (1 lane)		
	LCD Mode	TN		
	PPI	125 ppi		
	Viewing Angle	SVA 40/40/15/30 (Left/Right/Down/Up)		
14.0" diagonal LED-backlit HD+ anti-glare SVA eDP 1.2 flat (1600 x 900)	Outline Dimensions (W x H x D)	12.6 x 8.09 x 0.14 in (32.09 x 20.56 x 0.36 cm)		
	Active Area	12.19 x 6.86 in (30.96 x 17.415 cm)		
	Weight	0.72 lb (325 g) (max)		
	Diagonal Size	14.0 in (35.6cm)		
	Surface Treatment	Anti-glare		
	Contrast Ratio	300:1 (min)		
	Refresh Rate	60 Hz		
	Brightness	250 nit (typical)		
	Pixel Resolution	Format	1600 x 900 (HD+)	
		Configuration	RGB Stripe	
		Interface	eDP 1.2 (1 lane)	
		LCD Mode	TN	
		PPI	131 ppi	
	Viewing Angle	SVA 40/40/15/30 (Left/Right/Down/Up)		
14.0" diagonal LED-backlit FHD anti-glare UWA eDP 1.3 slim PSR (1920x1080)	Outline Dimensions (W x H x D)	12.6 x 8.09 x 0.12 in (32.09 x 20.56 x 0.3 cm)		
	Active Area	12.18 x 6.85 in (30.93 x 17.4 cm)		
	Weight	0.75 lb (340 g) (max)		
	Diagonal Size	14.0 in (35.6cm)		
	Surface Treatment	Anti-glare		
	Contrast Ratio	600:1 (min)		
	Refresh Rate	60 Hz		
	Brightness	300 nit (typical)		
	Pixel Resolution	Format	1920 x 1080 (FHD)	
		Configuration	RGB Stripe	
		Interface	eDP 1.3+PSR (2 lane)	
		LCD Mode	IPS/FFS/VA	



Technical Specifications

	PPI	157 ppi		
	Viewing Angle	UWVA 85/85/85/85 (Left/Right/Down/Up)		
15.6" diagonal LED-backlit HD anti-glare SVA eDP 1.2 flat (1366x768)	Outline Dimensions (W x H x D)	14.17 x 8.83 x 0.15 in (36.0 x 22.43 x 0.38 cm)		
	Active Area	13.55 x 7.62 in (34.42 x 19.35 cm)		
	Weight	< 1.1 lb (500 g) (max)		
	Diagonal Size	15.6 in (39.62 cm)		
	Surface Treatment	Anti-glare		
	Contrast Ratio	300:1 (min)		
	Refresh Rate	60 Hz		
	Brightness	200 nit (typical)		
	Pixel Resolution	Format	1366 x 768 (HD)	
		Configuration	RGB Stripe	
	Interface	eDP 1.2 (1 lane)		
	LCD Mode	TN		
	PPI	101 ppi		
	Viewing Angle	SVA 40/40/15/30 (Left/Right/Down/Up)		
15.6" diagonal LED-backlit FHD anti-glare SVA eDP 1.2 slim (1920x1080)	Outline Dimensions (W x H x D)	TBD		
	Active Area	TBD		
	Weight	TBD		
	Diagonal Size	TBD		
	Surface Treatment	TBD		
	Contrast Ratio	TBD		
	Refresh Rate	TBD		
	Brightness	TBD		
	Pixel Resolution	Format	1920 x 1080 (FHD)	
		Configuration	RGB Stripe	
	Interface	eDP 1.2 (2 lane)		
	LCD Mode	TN		
	PPI	TBD		
	Viewing Angle	UWVA 85/85/85/85 (Left/Right/Down/Up)		

STORAGE AND DRIVES

Internal Storage

320 GB* 5400 rpm SATA Hard Drive	Drive Weight	0.25 lbs (115 g)
	Capacity	320 GB
	Height	0.37 in (9.5 mm)



Technical Specifications

	Width	2.75 in (70 mm)
	Interface	ATA-8, SATA 2.6, 3.0 Gb/s, NCQ
	Transfer Rate	Synchronous (maximum) 300 MB/s (Drive Capability)
	Seek Time (typical reads, including settling)	Single Track 1.5 ms Average 11 ms Maximum 22 ms
	Rotational Speed	7200 rpm
	Logical Blocks	625,142,448
	Operating Temperature	32° to 140° F (0° to 60° C) [case temp]
	Features	ATA Security
500 GB* 5400 rpm SATA Hard Drive	Drive Weight	0.22 lb (101 g)
	Capacity	500 GB
	Height	0.37 in (9.5 mm)
	Width	2.75 in (70 mm)
	Interface	ATA-8, SATA 2.6, 3.0 Gb/s, NCQ
	Transfer Rate	Synchronous (maximum) 300 MB/s (Drive Capability)
	Seek Time (typical reads, including settling)	Single Track 3 ms Average 13 ms Maximum 24 ms
	Rotational Speed	5400 rpm
	Logical Blocks	976,773,168
	Operating Temperature	32° to 140° F (0° to 60° C) [case temp]
	Features	ATA Security
1 TB* 5400 rpm SATA Hard Drive	Drive Weight	0.254 lb (115 g)
	Capacity	1 TB
	Height	0.37 in (9.5 mm)
	Width	2.75 in (70 mm)
	Interface	ATA-8, SATA 2.6, 3.0 Gb/s, NCQ
	Transfer Rate	Synchronous 300 MB/s (Drive Capability) (maximum)
	Seek Time (typical reads, including settling)	Single Track 3 ms Average 13 ms Maximum 24 ms
	Rotational Speed	5400 rpm
	Logical Blocks	1,953,525,168
	Operating Temperature	32° to 140° F (0° to 60° C) [case temp]
	Features	ATA Security
320 GB* 7200 rpm SATA Hard Drive	Drive Weight	0.25 lbs (115 g)
	Capacity	320 GB
	Height	0.37 in (9.5 mm)
	Width	2.75 in (70 mm)
	Interface	ATA-8, SATA 2.6, 3.0 Gb/s, NCQ



Technical Specifications

Transfer Rate	Synchronous (maximum)	300 MB/s (Drive Capability)
Seek Time (typical reads, including settling)	Single Track	1.5 ms
	Average	11 ms
	Maximum	22 ms
Cache		16 MB
Rotational Speed		7200 rpm
Logical Blocks		625,142,448
Operating Temperature		32° to 140° F (0° to 60° C) [case temp]
Features		ATA Security

500 GB* 7200 rpm SATA Hard Drive

Drive Weight		0.25 lbs (115g)
Capacity		500 GB
Height		0.37 in (9.5 mm)
Width		2.75 in (70 mm)
Interface		ATA-8, SATA 2.6, 3.0 Gb/s, NCQ
Transfer Rate	Synchronous (maximum)	300 MB/s (Drive Capability)
Seek Time (typical reads, including settling)	Single Track	1.5 ms
	Average	11 ms
	Maximum	22 ms
Rotational Speed		7200 rpm
Logical Blocks		976,773,168
Operating Temperature		32° to 140° F (0° to 60° C) [case temp]
Features		ATA Security

750 GB* 7200 rpm SATA Hard Drive

Drive Weight		0.25 lbs (115g)
Capacity		750 GB
Height		0.37 in (9.5 mm)
Width		2.75 in (70 mm)
Interface		ATA-8, SATA 2.6, 3.0 Gb/s, NCQ
Transfer Rate	Synchronous (maximum)	300 MB/s (Drive Capability)
Seek Time (typical reads, including settling)	Single Track	1.5 ms
	Average	11 ms
	Maximum	22 ms
Rotational Speed		7200 rpm
Logical Blocks		1,465,149,168
Operating Temperature		32° to 140° F (0° to 60° C) [case temp]
Features		ATA Security

500 GB* 7200 rpm SMART SATA II Self Encrypting Drive

Drive Weight		0.25 lbs (115g)
Capacity		500 GB
Height		0.37 in (9.5 mm)
Width		2.50 in (63.5 mm)



Technical Specifications

	Interface	ATA-8, SATA 2.6, 3.0 Gb/s	
	Transfer Rate	Synchronous (maximum)	300 MB/s (Drive Capability)
	Seek Time (typical reads, including settling)	Single Track	1 ms
		Average	12 ms
		Maximum	20 ms
	Cache	16 MB	
	Rotational Speed	7200 rpm	
	Logical Blocks	976,773,168	
	Operating Temperature	32° to 140° F (0° to 60° C) [case temp]	
	Features	ATA Security	
500 GB* 5400 rpm SATA FIPS** Hard Drive	Drive Weight	0.25 lbs (95g)	
	Capacity	500 GB	
	Height	0.28 in (7 mm)	
	Width	2.75 in (70 mm)	
	Interface	ATA-8, SATA 2.6, 3.0 Gb/s, NCQ	
	Transfer Rate	Synchronous (maximum)	300 MB/s (Drive Capability)
	Seek Time (typical reads, including settling)	Single Track	1.5 ms
		Average	11 ms
		Maximum	22 ms
	Cache	16 MB	
	Rotational Speed	5400 rpm	
	Logical Blocks	976,773,168	
	Operating Temperature	32° to 140° F (0° to 60° C) [case temp]	
	Features	ATA Security	
* FIPS-certified, hardware-based AES-256 encryption image			
SATA 6 Gb/s 128 GB*, 2.5-inch Solid State Drive	Drive Weight	73 Grams	
	Capacity	128 GB	
	Height	0.276 in (7 mm)	
	Width	2.76 in (70 mm)	
	Interface	SATA 3 (6 Gb/s)	
	Performance	Maximum Sequential Read	Maximum Sequential Write
		415 MB/s	175 MB/s
	Logical Blocks	250,069,680	
	Operating Temperature	32° to 158°F (0° to 70°C) [case temp]	
	Features	ATA Security; ATA-8; SATA 3.0; DIPM; TRIM	
SATA 6 Gb/s 180 GB*, 2.5-inch SATA Solid State Drive	Drive Weight	78 Grams	
	Capacity	180 GB	
	Height	0.276 in (7 mm)	
	Width	2.76 in (70 mm)	
	Interface	SATA Gen 3 (6 Gb/s)	



Technical Specifications

	Performance	Maximum Sequential Read	Maximum Sequential Write
		Up to 550 MB/s (Compressible performance)	Up to 520 MB/s (Compressible performance)
	Logical Blocks	351,651,888	
	Operating Temperature	32° to 158°F (0° to 70°C) [case temp]	
	Features	ATA Security; ATA-8, SATA 3.0; DIPM; TRIM	
SATA 6 Gb/s 256 GB*, 2.5-inch SATA SED Solid State Drive	Drive Weight	73 Grams	
	Capacity	256 GB	
	Height	0.276 in (7 mm)	
	Width	2.76 in (70 mm)	
	Interface	SATA 3 (6 Gb/s)	
	Performance	Maximum Sequential Read	Maximum Sequential Write
		Up to 460 MB/s	Up to 260 MB/s
	Logical Blocks	500,118,192	
	Operating Temperature	32° to 158°F (0° to 70°C) [case temp]	
	Features	ATA Security; ATA-8 compliant; SATA 3.0; DIPM; TRIM	

* For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 16 GB (for Windows 7) and 36 GB (for Windows 8) of system disk is reserved for the system recovery software.

** * FIPS-certified, hardware-based AES-256 encryption image.

Optical Drives

Blu-ray ROM DVD+/-RW SuperMulti DL Drive	Access Times	Random	<190 ms CD-ROM (typical) <180ms DVD-ROM (typical) <230 ms BD-ROM (typical)
	Max Data Transfer Rate	24X CD-ROM 8X DVD-ROM 24X CD-R 16X CD-RW 8X DVD+R 8X DVD+RW 8X DVD-R 6X DVD-RW 4X - DVD+R Dual Layer 4X - DVD-R Dual Layer 5X DVD-RAM 6X BD-ROM	
	Transfer Mode	UDMA Mode 5	
	Interface	Gen 1 SATA	



Technical Specifications

Supported Media (read)	CD-DA, , CD-TEXT, CD-ROM, CD-ROM XA, MIXED MODE CD, CD-I, CD-I Bridge (Photo-CD, Video CD), Multisession CD (Photo-CD, CD-EXTRA, Portfolio, CD-R, CD-RW), CD-R, CD-RW, DVD-ROM (DVD-5, DVD-9, DVD-10, DVD-18), DVD-R, DVD-RW, DVD+R, DVD+RW. DVD-RAM, BD-ROM, BD-R, BD-RE
Supported Media (write)	CD-R, CD-RW, DVD+R, DVD+R DL, DVD+RW, DVD-R, DVD-R DL, DVD-RW, DVD-RAM
Max Media Capacity (read)	50.0 GB
Max Media Capacity (write)	8.5 GB
Transport	Tray Loading

DVD+/-RW SuperMulti DL Drive	Access Times	Random	<140ms CD (typical) < 160 ms DVD (typical)
-------------------------------------	---------------------	--------	---

Max Data Transfer Rate	24X CD-ROM
	8X DVD
	24X CD-R
	24X CD-RW
	8X DVD+R
	8X DVD+RW
	8X DVD-R
	6X DVD-RW
	6X - DVD+R Dual Layer
	6X - DVD-R Dual Layer
5X DVD-RAM	

Transfer Mode UDMA Mode 5

Interface Gen 1 SATA

Supported Media (read) CD-DA, CD-TEXT, CD-ROM, CD-ROM XA, MIXED MODE CD, CD-I, CD-I Bridge (Photo-CD, Video CD), Multisession CD (Photo-CD, CD-EXTRA, Portfolio, CD-R, CD-RW), CD-R, CD-RW, DVD-ROM (DVD-5, DVD-9, DVD-10, DVD-18), DVD-R, DVD-RW, DVD+R, DVD+RW, DVD-RAM

Supported Media (write) CD-R, CD-RW, DVD+R, DVD+RW, DVD-R, DVD-RW, DVD-RAM, DVD+R DL, DVD-R DL

Max Media Capacity (read) 8.5 GB

Max Media Capacity (write) 8.5 GB

Transport Tray Loading

DVD-ROM Drive	Access Times	Random	< 140 ms CD (typical) < 160 ms DVD (typical)
----------------------	---------------------	--------	---



Technical Specifications

Max Data Transfer Rate	24X CD-ROM 8X-DVD
Transfer Mode	UDMA Mode 5
Interface	Gen 1 SATA
Supported Media (read)	CD-DA, CD-TEXT, CD-ROM, CD-ROM XA, MIXED MODE CD, CD-I, CD-I Bridge (Photo-CD, Video CD), Multisession CD (Photo-CD, CD-EXTRA, Portfolio, CD-R, CD-RW), CD-R, CD-RW, DVD-ROM (DVD-5, DVD-9, DVD-10, DVD-18), DVD-R, DVD-RW, DVD+R, DVD+RW, DVD-RAM
Supported Media (write)	None
Max Media Capacity (read)	8.5GB
Transport	Tray Loading

SECURITY

HP Fingerprint Reader	Mobile Voltage Operation 3.0V-3.6V
	Operating Temperature 14° – 167°F (-10° – 75°C)
	Current Consumption 36 mA peak
	Image
	Low Latency Wait for Finger 950 uA
	Capture Rate 6000 lines/sec
	ESD Resistance IEC 61000-4-2 4B (±15KV)
	Detection Matrix 200*1 (plus another secondary line) 508 dpi 12*3 mm sensor area

NETWORKING/COMMUNICATIONS

Integrated Realtek 10/100/1000 NIC	Ethernet Features	10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14) 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30) 1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 8023 clauses 40) Auto-Negotiation (Automatic Speed Selection) Full Duplex Operation at all Speeds, Half Duplex operation at 10 and 100 Mbit/s IEEE 802.1p QoS (Quality of Service) Support IEEE 802.1q VLAN support IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable) IEEE 802.3az EEE (Energy Efficient Ethernet) Jumbo Frame 9K Auto MDI/MDIX Crossover cable detection
	Power Management	ACPI compliant - multiple power modes Situation-sensitive features reduce power consumption Advanced link down power saving for reducing link down power consumption



Technical Specifications

Performance Features	TCP/IP/UDP Checksum Offload (configurable) Protocol Offload (ARP & NS) Large send offload and Giant send offload Receiving Side Scaling
Manageability	Wake-on-LAN from standby and hibernation (Magic Packet and Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only) PXE 2.1 Remote Boot Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30)) Comprehensive diagnostic and configuration software suite Virtual Cable Doctor for Ethernet cable status
Interface NIC Device Driver Name	PCI Express 1.1 x1 to fully support ASPM L0s/L1 and CLKREQ Realtek PCIe GBE Ethernet Family Controller
HP hs3110 HSPA+ Mobile Broadband Module*	<p>Technology/Operating Bands</p> <p>CDMA/1xRTT/EvDO: 800MHz (Cell), 1900MHz (PCS) GSM/GPRS/EDGE: 850MHz (Cell), 900MHz (EGSM), 1800MHz (DCS), 1900MHz (PCS) UMTS/WCDMA with receive diversity: 2100MHz (UTRA FDD Band I), 1900MHz (UTRA FDD Band II), 900MHz (UTRA FDD Band VIII), 850 MHz (UTRA FDD Band V) LTE: 700 MHz (Verizon, Band XIII)</p> <p>Mobile Operator Verizon (US only)</p> <p>Wireless Protocol Standards GSM/GPRS/EDGE: Class B, Multi-slot class 10 operation, coding schemes CS1 - CS4 and MSC1 - MSC9. CDMA: 1xEVDO Release 0 and Release A, IS-95A, IS-95B, IS-856, IS-2000 UMTS/WCDMA: Release 99 and Release 7 LTE: Power Class III as per 3GPP TS 36.101</p> <p>Wireless Parametric Standards Complies with 3GPP specifications Release 8 for LTE</p> <p>Maximum Data Rates EvDO (Revision A) - 3.1 Mbps (Download), 1.8 Mbps (Upload) WCDMA (DC-HSPA+) - 42Mbps (Download) LTE (Category 3) - 100 Mbps (Download), 50Mbps (Upload)</p> <p>GPS GPS Bands Standalone, Assisted, XTRA 1575.42 MHz (± 1.023 MHz)</p> <p>Maximum Output Power GSM/GPRS/EDGE: 32dBm (+/-1) WCDMA: 24dBm (+0.7/-2.3) LTE: +23 dBm (+2.7 dBm/-1.7 dBm) 1xRTT/EvDO: +24 dBm (+0.5 dBm/-1.5 dBm)</p> <p>Maximum Power Consumption 2700mA (peak)</p> <p>Power Consumption, Sleep Mode 10 mA</p> <p>Power Management USB selective suspend Integrated notebook wireless button</p> <p>Antenna Type Dual high efficiency 6 band antennae with spatial diversity, mounted in the display enclosure</p> <p>Form Factor PCI-Express MiniCard, USB 2.0 interface</p>



Technical Specifications

Weight	< 10 g
Dimensions (Length x Width x Thickness)	2.01 x 1.18 x 0.18 in (51 x 30 x 5 mm)
Voltage, Operating	3.3v +/- 9%
Temperature, Operating (from TIA/EIA/IS-98-D)	-4° to 149° F (-20° to 65° C)
Temperature, Non-operating, 96 hours (from MIL-STD 202 Method 108)	-40° to 185° F (-40° to 85° C)
Humidity, Non-operating	85% relative humidity for 48 hours @ 185° F (85° C) (non-condensing)
LED Activity	LED Off - Radio Off; Solid LED On - Radio On

* Mobile Broadband is an optional feature sold separately or as an add on feature. Connection requires wireless data service contract, network support, and is not available in all areas. Contact service provider to determine the coverage area and availability. Connection speeds will vary due to location, environment, network conditions, and other factors.

HP It4111 LTE/EV-DO/HSPA+ 4G WWAN*

Technology/Operating bands	LTE FDD all bands with diversity: 1900 MHz (Band II) ¹ , 1700/2100MHz (Band IV (AWS), 850 MHz (Band V), 700MHz (Band XIII), 700MHz (Band XVII), 1900MHz G Block (Band XXV) WCDMA/HSDPA/HSUPA/HSPA+: all bands with diversity: 2100 MHz (Band I), 1900 MHz (Band II) , AWS 1700/2100MHz (Band IV), 850 MHz (Band V), 800 MHz (Band VIII) GSM/GPRS/EDGE: 1900 MHz, 1800 MHz , 850 MHz , 900 MHz CDMA: Cellular 800MHz (BC0), PCS 1900MHz (BC1)
Wireless protocol standards	3GPP Release 8 LTE Specification WCDMA R99, 3GPP Release 5, 6 and 7 UMTS Specification EVDO Release 0 and Release A
Wireless parametric standards	Complies with 3GPP specifications Release 8 for LTE
Maximum data rates	LTE (Category 3): 100 Mbps (Download), 50Mbps (Upload) DC-HSPA+: 42 Mbps (Download), 5.76 Mbps (Upload) HSPA+: 21.6 Mbps (Download), 5.76 Mbps (Upload) EDGE: 236.8 kbps (Download), 236.8 kbps (Upload) GPRS: 85.6 kbps(Download), 85.6 kbps (Upload)
GPS	Standalone GPS, A-GPS, GPS XTRA
GPS bands	1575.42 MHz (± 1.023 MHz), GLONASS 1596-1607MHz
Maximum output power	LTE: +23 dBm (+/- 1 dBm) WCDMA: +23 dBm (+/- 1 dBm) GSM850/900, GMSK: +32dBm (+/- 1dBm) GSM850/900, 8PSK: +27dBm (+/- 1dBm) DCS1800 / PCS 1900, GMSK: +29dBm (+/- 1dBm) DCS1800 / PCS 1900, 8PSK: +26dBm (+/- 1dBm) CDMA: +24dBm (+/- 1dBm)
Maximum power consumption	LTE: 1,200 mA (peak); <900 mA (average) WCDMA: 1,100 mA (peak); <800 mA (average) EGPRS: 2,500 mA (peak); <700 mA (average)



Technical Specifications

Power consumption, sleep mode	2 mA
Power management	USB selective suspend, Integrated notebook wireless button
Antenna type	Dual high efficiency multi-band antennae with spatial diversity
Form Factor	M.2, 3042-S3 Key B
Weight	6 g
Dimensions (Length x Width x Thickness)	42 mm x 30 mm x 2.3 mm
Voltage, Operating	3.135 V to 4.4 V (3.3 V +1.1V/-0.165V)
Temperature, operating (from TIA/EIA/IS-98-D)	-13° to 140° F (-25° to 60° C)
Temperature, non-operating, 96 hours (from MIL-STD 202 Method 108)	-40° to 185° F (-40° to 85° C)
Humidity, non-operating	95% relative humidity for 48 hours @ 185° F (85° C) (non-condensing)
LED activity	LED Off – Radio Off; Solid LED On – Radio On

¹ 1900 MHz (Band II) and 850 MHz (Band V) not supported at launch but support planned in a future firmware update.

* 4G LTE not available on all products, in all regions and only available on products featuring Intel processors. WWAN use requires separately purchased service contract. Check with service provider for coverage and availability in your area. Connection speeds will vary due to location, environment, network conditions, and other factors.

HP It4112 LTE/HSPA+ Gobi 4G Module*

Technology/Operating bands	LTE FDD all bands with diversity: 2100 MHz (Band I), 1900 MHz (Band II), 1800 MHz (Band III), 850 MHz (Band V), 2600 MHz (Band VII), 900 MHz (Band VIII), 800 MHz (Band XX, DD800) WCDMA/HSDPA/HSUPA/HSPA+ all bands with diversity: 2100 MHz (Band I), 1900 MHz (Band II), 800 MHz (Band V), 900 MHz (Band VIII) GSM/GPRS/EDGE: 1900 MHz (Band II), 1800 MHz (Band III), 850 MHz (Band V), 900 MHz (Band VIII)
Wireless protocol standards	3GPP Release 8 LTE Specification WCDMA R99, 3GPP Release 5, 6 and 7 UMTS Specification
Wireless parametric standards	Complies with 3GPP specifications Release 8 for LTE
Maximum data rates	LTE (Category 3): 100 Mbps (Download), 50Mbps (Upload) DC-HSPA+: 42 Mbps (Download), 5.76 Mbps (Upload) HSPA+: 21.6 Mbps (Download), 5.76 Mbps (Upload) EDGE: 236.8 kbps (Download), 236.8 kbps (Upload) GPRS: 85.6 kbps(Download), 85.6 kbps (Upload)
GPS	Standalone
GPS bands	1575.42 MHz (± 1.023 MHz), GLONASS 1596-1607MHz
Maximum output power	LTE: +23 dBm (+/- 2 dBm) WCDMA: +23.5 dBm (+/- 1 dBm) GPRS Band II, III: +29.5 dBm (+/- 1 dBm) GPRS Band V, VIII: +32.5 dBm (+/- 1 dBm)



Technical Specifications

Maximum power consumption	EGPRS Band II, III: +26.5 dBm (+/-1.5 dBm) EGPRS Band V, VIII: +27.5 dBm (+/-1.5 dBm) LTE: 1,200 mA (peak); <900 mA (average) WCDMA: 1,100 mA (peak); <800 mA (average) EGPRS: 2,800 mA (peak); <700 mA (average)
Power consumption, sleep mode	3 mA
Power management	USB selective suspend, Integrated notebook wireless button
Antenna type	Dual high efficiency multi-band antennae with spatial diversity
Form Factor	M.2, USB 2.0 interface
Weight	6 g
Dimensions (Length x Width x Thickness)	42 mm x 30 mm x 2.3 mm
Voltage, Operating	3.135 V to 4.4 V (3.3 V +1.1V/-0.165V)
Temperature, operating (from TIA/EIA/IS-98-D)	14° to 131° F (-10° to 55° C)
Temperature, non-operating, 96 hours (from MIL-STD 202 Method 108)	-40° to 185° F (-40° to 85° C)
Humidity, non-operating	95% relative humidity for 48 hours @ 185° F (85° C) (non-condensing)
LED activity	LED Off - Radio Off; Solid LED On - Radio On

* 4G LTE not available on all products, in all regions and only available on products featuring Intel processors. WWAN use requires separately purchased service contract. Check with service provider for coverage and availability in your area. Connection speeds will vary due to location, environment, network conditions, and other factors.

Atheros 802.11 b/g/n (1x1)*

Wireless LAN Standards	IEEE 802.11b IEEE 802.11g IEEE 802.11n
Interoperability	Wi-Fi certified
Frequency Band	2.4 GHz
Data Rates	802.11b: 1, 2, 5.5, 11 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: many possible data rates, ranging from 6 Mbps to 300 Mbps, depending on the combination of Bandwidth, Modulation Coding Scheme, and Guard Interval used, as defined in IEEE 802.11n specification
Modulation	Direct Sequence Spread Spectrum DBPSK, DQPSK, CCK, OFDM, BPSK, QPSK, 16-QAM, 64-QAM
Security¹	Supports 64- and 128-bit WEP, WPA, WPA2, hardware-accelerated AES, 802.1x authentication types EAP-TLS, EAP-TTLS, PEAP-GTC, PEAP-MSCHAPv2, LEAP, EAP-FAST.
Sub-channels	Multinational support with frequency bands and channels compliant to local regulations.
Media Access Protocol	CSMA/CA (Collision Avoidance) with ACK



Technical Specifications

Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)	
Roaming	IEEE 802.11 compliant roaming between access points	
Output²	13.5 dBm, nominal	
Power Consumption	Transmit: 2.0 W (max) Receive: 1.6 W (max) Associated to Access Point, Idle: 250 mW nominal Wireless Button Off: 100 mW nominal Radio disabled: 75 mW nominal	
Power Management	ACPI compliant power management 802.11 compliant power saving mode	
Receiver Sensitivity³	72.2 Mbps: -70 dbm, 54 Mbps: -74 dBm, 11 Mbps: -88 dBm , 1 Mbps: -95 dBm	
Antenna Connections	High efficiency antenna with spatial diversity, mounted in the display enclosure	
Form Factor	PCI-Express Half-MiniCard 1.2	
Weight	0.013 lb (6 g)	
Dimensions	0.19 x 1.06 x 1.18 in (4.75 x 26.8 x 30 mm)	
Operating Voltage	3.3v +/- 9%	
Temperature	Operating	14° to 158° F (-10° to 70° C)
	Non-operating	-40° to 176° F (-40° to 80° C)
Humidity	Operating	10% to 90% (non-condensing)
	Non-operating	5% to 95% (non-condensing)
Altitude	Operating	0 to 10,000 ft (3,048 m)
	Non-operating	0 to 50,000 ft (15,240 m)
LED Activity	LED Off - Radio OFF; Solid LED On - Radio ON	
	1. Check latest software/driver release for updates on supported security features.	
	2. Maximum output power may vary by country according to local regulations.	
	3. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).	
	* Wireless access point and internet service required. Availability of public wireless access points limited.	

Atheros 802.11 b/g/n (1x1) with Bluetooth® v4.0 combo* TBD

* Wireless access point and internet service required. Availability of public wireless access points limited.

Broadcom 802.11 a/b/g/n (2x2) with Bluetooth® v4.0 combo*	Wireless LAN Standards	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n
--	-------------------------------	--



Technical Specifications

Interoperability	Wi-Fi certified
Frequency Band	802.11b/g/n <ul style="list-style-type: none"> • 2.402 – 2.482 GHz 802.11a/n <ul style="list-style-type: none"> • 4.9 – 4.95 GHz (Japan) • 5.15 – 5.25 GHz • 5.25 – 5.35 GHz • 5.47 – 5.725 GHz • 5.825 – 5.850 GHz • 2.402 – 2.482 GHz
Data Rates	802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11b: 1, 2, 5.5, 11 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: card will support rates for NSS=1 and NSS=2 for RX and TX for 20 and 40 MHz channels. Short and long guard interval shall be supported.
Modulation	Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM
Security¹	<ul style="list-style-type: none"> • IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only • AES-CCMP: 128 bit in hardware • 802.1x authentication • WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. • WPA2 certification • IEEE 802.11i • Cisco Certified Extensions, all versions through V5 • WAPI
Network Architecture	Ad-hoc (Peer to Peer)
Models	Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power²	<ul style="list-style-type: none"> • 2.4G: +13.5dBm minimum • 5G: +12dBm minimum • Maximum output power must be able to achieve modular regulatory certification with notebooks that have antennas >20cm from the user and peak gain of +3dBi at 2.4GHz and +4dBi at 5GHz
Power Consumption	Transmit: 2.0 W (max) Receive: 1.6 W (max) Idle mode (PSP): 250 mW (WLAN Associated) Idle mode: 100 mW (WLAN unassociated) Radio disabled: 75 mW
Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
Receiver Sensitivity³	802.11b:-95 dBm (1 Mbps), -93 dBm (2 Mbps), -91 dBm (5.5 Mbps), -88 dBm (11 Mbps)



Technical Specifications

	802.11a/g:-90 dBm (6 Mbps), -89 dBm (9 Mbps), -87 dBm (12 Mbps), -85 dBm (18 Mbps), -82 dBm (24 Mbps), -79 dBm (36 Mbps), -76 dBm (48 Mbps), -74 dBm (54 Mbps)
Antenna type	802.11n:-69 dBm (72.2 Mbps), -66 dBm (300 Mbps) High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
Form Factor	PCI-Express Half-MiniCard
Dimensions	0.19 x 1.06 x 1.18 in (4.75 x 26.8 x 30 mm)
Weight	TBD
Operating Voltage	3.3v +/- 9%
Temperature	Operating 14° to 158° F (-10° to 70° C) Non-operating -40° to 176° F (-40° to 80° C)
Humidity	Operating 10% to 90% (non-condensing) Non-operating 5% to 95% (non-condensing)
Altitude	Operating 0 to 10,000 ft (3,048 m) Non-operating 0 to 50,000 ft (15,240 m)
LED Activity	LED Off – Radio OFF; Solid LED On – Radio ON
	<ol style="list-style-type: none"> 1. Check latest software/driver release for updates on supported security features. 2. Maximum output power may vary by country according to local regulations. 3. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).
Bluetooth Specification	V4.0 High Speed, V2.1+EDR, backwards compatible with V1.1, 1.2 and 2.0
Number of Available Channels	79 (1 MHz) available channels
Data Rates and Throughput	3 Mbps data rate; throughput up to 2.17 Mbps Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric or 1306.9 kbps symmetric
Transmit Power	-6 dBm to 4 dBm (Bluetooth Class II)
Receiver Sensitivity	Better than -80 dBm at 0.1 % raw bit error rate
Power Consumption	Peak (Tx) 330 mW Peak (Rx) 230 mW Sleep <17 mW
Antenna Range	Internally integrated within module Up to 33 ft (10 m)
Electrical Interface	USB 2.0 compliant Microsoft Windows Plug and Play compliant
Bluetooth Software Supported	Broadcom Bluetooth for Windows Microsoft Windows Bluetooth Software
Link Topology	Point to Point, Multipoint Pico Nets up to 7 slaves
Security	Full support of Bluetooth Security Provisions
Power Management	Microsoft Windows ACPI, and USB Bus Support Self configurable to optimize power conservation in all operating modes, including Standby, Hold, Park, and Sniff



Technical Specifications

Certifications	All necessary regulatory approvals for supported countries, including: FCC (47 CFR) Part 15C, Section 15.247 & 15.249 ETS 300 328, ETS 300 826 Low Voltage Directive IEC950 UL, CSA, and CE Mark
Bluetooth Profiles Supported	Generic Access Profile (GAP) Service Discovery Application Profile (SDAP) Serial Port Profile (SPP) Dial_Up Networking Profile (DUN) Generic Object Exchange Profile (GOEP) Object Push Profile (OPP) File Transfer Profile (FTP) Synchronization Profile (SYNC) Hard Copy Cable Replacement (HCRP) Personal Area Networking Profile (PAN) Human Interface Device Profile (HID) Generic Audio/Video Distribution Profile (GAVDP) Advanced Audio/Video Distribution Profile (A2DP) FAX Profile (FAX) Basic Imaging Profile (BIP) Headset Profile (HSP) Hands Free Profile (HFP) Basic Printing Profile (BPP) VDP (Video Distribution Profile) AVRCP (Audio Video Remote Control Profile)
	* Wireless access point and internet service required. Availability of public wireless access points limited.

AUDIO/MULTIMEDIA - DTS SOUND+

Hardware	Implementation	IDT 92HD91
	Function Key Volume Controls	Volume up, volume down, and mute
	Full Duplex	Yes
	Microphone In	Stereo
	Headphone/Line Out	Stereo
	Integrated Microphone	Yes, dual digital microphone array when equipped with optional webcam
Audio Output Quality	Frequency Response	20 Hz – 20 kHz
	Signal to Noise Ratio	>85 dB
	Total Harmonic Distortion	0.01%
	Noise Floor	-110 dB
	Play/Record Sampling Rate(s)	8 kHz – 48kHz
	DAC	16, 20 or 24-bit



Technical Specifications

	ADC	16 or 20-bit	
Integrated Stereo Speakers	Power Rating	2 Watts	
	Impedance	4 Ohms	
POWER			
HP 65W Smart AC Adapter	Dimensions	4.17 x 1.85 x 1.1 in (10.6 x 4.7 x 2.8 cm)	
	Weight	0.62 lb (280 g)	
	Input	Input	100 to 240 VAC
		Input Efficiency	87% min at 115/230 VAC
		Input frequency range	47 to 63 Hz
	Output	Input AC current	1.7 A at 90 VAC, 0.85 A at 180 VAC
		Output power	65W
		DC output	18.5V
		Hold-up time	5 msec at 115 VAC input
		Output current limit	<11A, Over voltage protection- 29V max automatic shutdown
	Connector	3 pin/grounded, mates with interchangeable cords	
	Environmental Design	Operating temperature	32° to 104° F (0° to 40° C)
		Non-operating (storage) temperature	-4° to 149° F (-20° to 65° C)
		Altitude	0 to 10,000 ft (0 to 3,048 m)
		Humidity	20% to 80%
Storage Humidity		10% to 90%	
EMI and Safety Certifications	CE Mark - full compliance with LVD and EMC directives; Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE; MTBF - over 200,000 hours at 25°C ambient condition.		
HP 9-cell (100 WHr) Lithium-Ion Primary battery	Dimensions (H x W x L)	0.8 x 2.4 x 8.1in (2 x 6.6 x 20.5cm)	
	Weight (max)	1.1lb, (.488kg)	
	Cells/Type	Lithium-Ion	
	Energy	Voltage	11.25V
		Amp-hour capacity	8.85Ah
		Watt-hour capacity	100Wh
	Temperature	Operating (Charging)	32° to 113° F (0° to 45° C)
		Operating (Discharging)	14° to 122° F (-10° to 50° C)
		Non-operating	-4° to 122° F (-20° to 50° C)
	Battery Re-Charge Time	System in OFF or Standby Mode	3.5 to 5 hours
System ON		4 to 7 hours	
Fuel Gauge LED	No		



Technical Specifications

HP 6-cell (55 WHr) Lithium-Ion Primary battery	Warranty	1 year
	Compatible with optional Travel Battery	Yes
	Dimensions (H x W x L)	0.8 x 1.8 x 8.0in (2.0 x 4.7 x 20.5cm)
	Weight (max)	.70lb, (.313kg)
	Cells/Type	Lithium-Ion
	Energy	Voltage 10.8V
		Amp-hour capacity 5.1Ah
		Watt-hour capacity 55Wh
	Temperature	Operating (Charging) 32° to 113° F (0° to 45° C)
		Operating (Discharging) 14° to 122° F (-10° to 50° C)
		Non-operating -4° to 122° F (-20° to 50° C)
	Battery Re-Charge Time	System in OFF or Standby Mode 2.5 hours
		System ON 3 to 5 hours
Fuel Gauge LED	No	
HP 6-cell (55 WHr) Long Life Primary Battery	Warranty	1 year
	Compatible with optional Travel Battery	Yes
	Dimensions (H x W x L)	0.8 x 1.8 x 8.0in (2.0 x 4.7 x 20.5cm)
	Weight (max)	.72lb, (.323kg)
	Cells/Type	Lithium-Ion
	Energy	Voltage 10.8V
		Amp-hour capacity 5.1Ah
		Watt-hour capacity 55Wh
	Temperature	Operating (Charging) 32° to 113° F (0° to 45° C)
		Operating (Discharging) 14° to 122° F (-10° to 50° C)
		Non-operating -4° to 122° F (-20° to 50° C)
	Battery Re-Charge Time	System in OFF or Standby Mode 2.5 hours
		System ON 3 to 5 hours
Fuel Gauge LED	No	
Warranty	3 years*	
Compatible with optional Travel Battery	Yes	
* 3-year platform warranty is required for a 3-year Long Life Battery warranty.		
HP 3-cell (33 WHr) Lithium-Ion Primary battery	Dimensions (H x W x L)	TBD in (TBD cm)
	Weight (max)	TBD lb, TBD kg)
	Cells/Type	Lithium-Ion
	Energy	Voltage 11.1V
		Amp-hour capacity 2.95Ah



Technical Specifications

	Watt-hour capacity	33Wh
Temperature	Operating (Charging)	32° to 113° F (0° to 45° C)
	Operating (Discharging)	14° to 140° F (-10° to 60° C)
	Non-operating	-4° to 140° F (-20° to 60° C)
Battery Re-Charge Time	System in OFF or Standby Mode	TBD hours
	System ON	TBD hours
Fuel Gauge LED	No	
Warranty	1 year	

ENVIRONMENTAL

Environmental Data

Eco-Label Certifications & Declarations

This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:

- IT ECO declaration
- US ENERGY STAR®
- EPEAT Gold registered in the United States. See <http://www.epeat.net> for registration status in your country.

HP ProBook 645 G1 Notebook PC

System Configuration

The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a "Typically Configured Notebook".

Energy Consumption (in accordance with US ENERGY STAR® test method)

	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation (Short idle)	12.79 W	12.72 W	11.05 W
Normal Operation (Long idle)	8.42 W	8.43 W	8.36 W
Sleep	0.98 W	1.11 W	0.96 W
Off	0.49 W	0.59 W	0.47 W

NOTE:

Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.

Heat Dissipation*

	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation (Short idle)	44 BTU/hr	44 BTU/hr	38 BTU/hr
Normal Operation (Long idle)	29 BTU/hr	29 BTU/hr	29 BTU/hr
Sleep	3 BTU/hr	4 BTU/hr	3 BTU/hr
Off	2 BTU/hr	2 BTU/hr	2 BTU/hr

* Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.



Technical Specifications

Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)

	Sound Power (LWAd, bels)	Sound Pressure (LpAm, decibels)
Typically Configured - Idle	3.3	27
Fixed Disk - Random writes	3.4	27

Batteries

This battery(s) in this product comply with EU Directive 2006/66/EC

Batteries used in the product do not contain:

- Mercury greater than 1ppm by weight
- Cadmium greater than 20ppm by weight

Battery size: CR2032 (coin cell)

Battery type: Lithium

Additional Information

- This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.
- This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive - 2002/96/EC.
- This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).
- This product is in compliance with the IEEE 1680 (EPEAT) standard at the Gold level, see <http://www.epeat.net>
- Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.
- This product contains 0.0 % post-consumer recycled plastic (by wt.)
- This product is 95.4% recycle-able when properly disposed of at end of life.

Packaging Materials

- External:
 - PAPER/Corrugated 482.6 g
- Internal:
 - PLASTIC/EPE (Expanded Polyethylene) 28 g
 - PLASTIC/Polyethylene low density 30.4 g
- The PAPER/Corrugated contains at least 70% recycled content.
- The PLASTIC/EPE (Expanded Polyethylene) materials contains at least 50 % recycled content.
- The PLASTIC/Polyethylene low density) materials contains at least 50 % recycled content.

HP ProBook 655 G1 Notebook PC

System Configuration

The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a "Typically Configured Notebook".

Energy Consumption (in accordance with US ENERGY STAR® test method)

	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation (Short idle)	11.3 W	12.24 W	12.37 W
Normal Operation (Long idle)	8.64 W	9.04 W	8.6 W
Sleep	0.93 W	1.04 W	0.92 W



Technical Specifications

Off 0.51 W 0.66 W 0.51 W

NOTE:

Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.

Heat Dissipation*	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation (Short idle)	39 BTU/hr	42 BTU/hr	42 BTU/hr
Normal Operation (Long idle)	30 BTU/hr	31 BTU/hr	30 BTU/hr
Sleep	3 BTU/hr	4 BTU/hr	3 BTU/hr
Off	2 BTU/hr	2 BTU/hr	2 BTU/hr

* Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

**Declared Noise Emissions
(in accordance with
ISO 7779 and ISO 9296)**

	Sound Power (LWAd, bels)	Sound Pressure (LpAm, decibels)
Typically Configured - Idle	3.37	27
Fixed Disk - Random writes	3.42	27

Batteries

This battery(s) in this product comply with EU Directive 2006/66/EC

Batteries used in the product do not contain:

- Mercury greater than 1ppm by weight
- Cadmium greater than 20ppm by weight

Battery size: CR2032 (coin cell)

Battery type: Lithium

Additional Information

- This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.
- This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive - 2002/96/EC.
- This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).
- This product is in compliance with the IEEE 1680 (EPEAT) standard at the Gold level, see <http://www.epeat.net>
- Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.
- This product contains 0.0% post-consumer recycled plastic (by wt.)
- This product is 97.5 % recycle-able when properly disposed of at end of life.

Packaging Materials

- External:
 - PAPER/Corrugated 513.5 g
- Internal:
 - PLASTIC/EPE (Expanded Polyethylene) 33.4 g
 - PLASTIC/Polyethylene low density 26 g



Technical Specifications

- The PAPER/Corrugated contains at least 70% recycled content.
- The PLASTIC/EPE (Expanded Polyethylene) materials contain at least 50 % recycled content.
- The PLASTIC/Polyethylene low density) materials contain at least 50 % recycled content.

ALL MODELS

MATERIAL USAGE

This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at: <http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf>):

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants - may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Formaldehyde
- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Nickel - finishes must not be used on the external surface designed to be frequently handled or carried by the user.
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) - except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)

PACKAGING USAGE

HP follows these guidelines to decrease the environmental impact of product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

END-OF-LIFE MANAGEMENT AND RECYCLING

Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <http://www.hp.com/go/reuse-recycle> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.



Technical Specifications

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <http://www.hp.com/go/recyclers>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

HEWLETT-PACKARD CORPORATE ENVIRONMENTAL INFORMATION

For more information about HP's commitment to the environment:

Global Citizenship Report

<http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html>

Eco-label certifications

<http://www8.hp.com/us/en/hp-information/environment/ecolabels.html>

ISO 14001 certificates:

http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/PC_GBU_Product_Design_ISO_14K_Certificate.pdf

and

<http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf>

COUNTRY OF ORIGIN

TBD



Options and Accessories (sold separately and availability may vary by country)

Type	Description	Part #
Cases	HP Professional Series Carrying Case (up to 15.6")	H4J90AA
	HP Professional Slim Top Load Case (up to 17.3")	H4J91AA
	HP Business Backpack (up to 17.3")	H5M90AA
	HP Business 4 Wheel Roller Case	H5M93AA
Docking	HP Adjustable Dual Monitor Stand	AW664AA#xxx
	HP Adjustable Display Stand	AW663AA#xxx
	HP Display and Notebook Stand	AW662AA#xxx
	HP LCD Monitor Stand	QM196AA
	HP 90W Docking Station	A7E32AA#xxx
	HP 120W Advd Docking Station	A7E36AA#xxx
Input/Output	HP Ultra Mobile Wireless Mouse	H6F25AA
	HP Stylish Wireless KB/Mouse	H4B79AA
	HP Stylish USB KB/Mouse	H4B80AA
Adapters	HP 65W Slim Adapter	AX727AA#XXX
	90W Smart AC Adapter	ED495AA#xxx
	90W Slim Adapter	BT796AA#xxx
	HP 65W Smart AC Adapter	H6Y89AA
	HP 90W Smart AC Adapter	H6Y90AA
	HP 65W Slim AC Adapter	H6Y82AA
	HP 90W Slim AC Adapter	H6Y83AA
Batteries	HP CA06XL Notebook Battery 6-cell 55 WHr	E7U21AA
	HP CA09 Notebook Battery 9-cell 100 WHr	E7U22AA
Security	HP Docking Station Cable Lock	AU656AA#XXX
	HP UltraSlim Keyed Cable Lock	H4D73AA
Storage - External Storage	HP Mobile USB DVDRW	A2U57AA
Health and Education	HP 20-Notebook Managed Charging Cart	QL489AA#xxx
	HP 30-Notebook Managed Charging Cart	QL490AA

Copyright © 2015 Hewlett-Packard Development Company, L.P.

All rights reserved. Intel, Core, and Celeron are registered trademarks or trademarks of Intel Corporation in the U.S. and/or other countries. Bluetooth is a trademark owned by its proprietor and used by Hewlett-Packard Company under license. Microsoft and Windows are U.S. registered trademarks of Microsoft Corporation. Adobe is a trademark of Adobe Systems Incorporated. ENERGY STAR is a registered mark owned by the U.S. government.

The information contained herein is subject to change without notice and is provided "as is" without warranty of any kind. The warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.



Summary of Changes

Date of change:	Version History:		Description of change:
June 26, 2014	Version 1 to 2	Changed	Batteries
July 7, 2014	From v12 to v13	Changed	Weight specs
July 11, 2014	From v13 to v14	Removed	Lync Optimized
July 22, 2014	From v14 to v15	Changed	Added 230VAC to input efficiency, deleted Trust circles.
August 7, 2014	From v15 to v16	Added	Windows 8.1 Pro 64 OS
August 8, 2014	From v16 to v17	Added	Web-only Support OS list
August 28, 2014	From v17 to v18	Added	180 GB SSD Details
October 6, 2014	From v18 to v19	Changed	APU details.
October 28, 2014	From v10	Removed	Windows 7 versions
June 3, 2015	From v19 to v20	Added	HP CA06XL Notebook Battery 6-cell 55 WHr HP CA09 Notebook Battery 9-cell 100 WHr to Options page.
June 29, 2015	From v20 to v21	Added	Windows 10 to overview on page 7, OS list on page 8, footnotes on pages 8, 10
April 26, 2016	From v21 to v22	Changed	Fast charge spec to 120 min

