



Product Service

# CERTIFICATE

No. Z1A 16 04 93407 043

**Holder of Certificate:** **HP Inc.**  
 1501 Page Mill Road  
 Palo Alto CA 94304  
 USA

**Certification Mark:**



**Product:** **Computer**  
**( All-in-One PC )**

**Tested according to:** EN 60950-1:2006/A2:2013  
 EK1-ITB 2000:2016  
 AfPS GS 2014:01 PAK 3.1

The product meets the safety and health requirements of the German Product Safety Act section 20 to 22 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. See also notes overleaf.

**Test report no.:** 612101630201

**Valid until:** 2021-04-07

**Date,** 2016-04-13

*Bill Lin*  
 ( Bill Lin )



Page 1 of 3



Product Service

## CERTIFICATE

No. Z1A 16 04 93407 043

**Model(s):** TPC-P033,  
HP ProOne 400 G1 AiO Business PC (19.5" NT)

**Parameters:**

|   |           |
|---|-----------|
| Rated input voltage:                                | 19.5 Vdc  |
| Rated input current:                                | 6.15 A    |
| Protection class:                                   | III       |
| Max. ambient temperature:                           | 35 °C     |
| Degree of protection<br>against ingress of liquids: | Ordinary  |
| Declared Sound Power level:                         | 4.04 B(A) |

Remark: See attachment for LCD(s) covered  
by this certificate.

**Factory(ies):** 43857

Page 2 of 3

*Bill L.*



Taiwan

**Attachment to the Certificate      No. Z1A 16 04 93407 043**

**The following LCD's panel description of the model is as below:**

- 1. LG Display                      Type: LM195WD1
- 2. AUO                                Type: M195RTN01.0

Suitable for Max. illuminance:  $L_{REF,EXT}= 200 \text{ cd/m}^2$  and  $L_{REF,SML}= 2000 \text{ cd/m}^2$   
Suitable for Max. illuminance: 1000 Lux

Pixel fault classification: I

Design viewing distance: 500 mm

Design viewing direction: (0°, 90°)

Viewing direction range:  $\Phi$  range is 0° to 360°  
 $\theta$  range is 52.6°

Content and perception: Artificial information

**Date: 2016-04-13**



**Testing Laboratory**

*Bill Lin*

**Bill Lin**