

### Overview

## HP ElitePad Accessories

### Jackets

HP ElitePad Security Jacket Cover	E6N31AA
HP ElitePad Security Jacket with Smart Card Reader	E5S90AA
HP ElitePad Security Jacket HP ElitePad Security Jacket with Smart Card Reader and Fingerprint Reader	E5S91AA
HP ElitePad Expansion Jacket Cover	H7A97AA
HP ElitePad Expansion Jacket	H4J85AA
HP ElitePad Expansion Jacket with Battery	D2A23AA
HP ElitePad Productivity Jacket	D6S54AA

### Power

HP ElitePad Expansion Jacket Battery	H4F20AA
HP ElitePad 10W AC Adapter	H4K08AA
HP 40W Smart AC Adapter	H5W93AA
HP Multi-Tablet Charging Module (separate specs)	H4W98AA
HP ElitePad Power/Ethernet Adapter	F9D31AA

### Docking Station

HP ElitePad Dockable Case	F1M97AA
HP ElitePad Docking Station	COM84AA

### Adapters

HP ElitePad USB 3.0 Adapter	E8F98AA
HP ElitePad 12W USB Auto Adapter (w/cable)	F5V87AA
HP ElitePad USB Adapter	H3N46AA
HP ElitePad Smart AC Adapter	H3N47AA
HP ElitePad HDMI & VGA Adapter	H3N45AA
HP ElitePad Serial Adapter	H3N50AA
HP ElitePad Ethernet Adapter	H3N49AA
HP ElitePad SD Card Reader	H3N48AA

### Input/Output

HP Slim Bluetooth Keyboard	H4Q44AA
HP Executive Tablet Pen G2	F3G73AA

### Cases

ElitePad Leather Slip Case	E5L02AA
HP ElitePad Case	H4R88AA
HP ElitePad Rugged Case	H4R89AA
HP ElitePad Rugged Case G2	F5A38AA
HP Pro 10 EE G1 Sleeve	LOW36AA
HP ElitePad 1000 G2 Healthcare/Rugged Tablet Shoulder Strap	L8L92AA
HP ElitePad Bluetooth Keyboard Case	K4U68AA

### Cleaning

HP Tablet Cleaning Kit	K6F99AA
------------------------	---------

### Technical Specifications

#### Jackets

##### HP ElitePad Security Jacket Cover

<b>Dimensions</b> (H x W x D)	10.34 x 7.83 x 0.80 in (262.7 x 177.8 x 2.1 mm)
<b>Materials</b>	
Exterior cover material	Microfiber short hair
Exterior cover surface	Smooth
Exterior cover color	Grey
Interior color	Grey
Cover strip material	Graphite Polycarbonate
Compatibility	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet

##### HP ElitePad Security Jacket with Smart Card Reader

<b>Dimensions</b> (H x W x D)	10.57 x 7.75 x 0.65 in (268.4x 196.9 x 16.5 mm)	
<b>Weight</b>	0.70 lb (317 g) Jacket only	
<b>USB ports</b>	(1) USB 3.0	
<b>Audio connectors</b>	Combo stereo/headphone jack	
<b>Other connectors</b>	(1) HDMI	
<b>Stand-alone power requirements</b>	<b>Normal Operating Voltage</b>	6.5 V
	<b>Average Operating Power</b>	8.5 W
	<b>Max Operating Power</b>	< 40 W
<b>Temperature</b>	<b>Operating</b>	32° to 95° F (0° to 35° C)
	<b>Non-operating</b>	4° to 140° F (-20° to 60° C)
<b>Relative humidity</b>	<b>Operating</b>	10% to 90%, relative humidity
	<b>Non-operating</b>	5% to 90% relative humidity, 101.6° F (38.7° C) maximum wet bulb temperature
<b>Altitude</b>	<b>Operating</b>	-50 to 10,000 ft (-15.24 to 3,048 m)
	<b>Non-operating</b>	-50 to 40,000 ft (-15.24 to 12,192 m)
<b>Shock</b>	<b>Operating</b>	40 G, 2 ms, half-sine
	<b>Non-operating</b>	200 G, 2 ms, half-sine
<b>Random vibration</b>	<b>Operating</b>	10-500 Hz, 0.5 grms
	<b>Non-operating</b>	10-500 Hz, 1.0 grms
<b>Option kit contents</b>	HP ElitePad Security Jacket with Smart Card Reader, documentation	
	<b>NOTE:</b> Weight is measure using a PV unit and aluminum CAC cover, cover/kick stand is not included.	
<b>Compatibility</b>	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet	

##### HP ElitePad Security Jacket HP ElitePad Security Jacket with Smart Card Reader and Fingerprint Reader

<b>Dimensions</b> (H x W x D)	10.57 x 7.75 x 0.65 in (268.4x 196.9 x 16.5 mm)
<b>Weight</b>	0.70 lb (317 g) Jacket only
<b>USB ports</b>	(1) USB 3.0
<b>Audio connectors</b>	Combo stereo/headphone jack

### Technical Specifications

<b>Other connectors</b>	(1) HDMI
<b>Stand-alone power requirements</b>	<b>Normal Operating Voltage</b> 6.5 V
	<b>Average Operating Power</b> 8.5 W
	<b>Max Operating Power</b> < 40 W
<b>Temperature</b>	<b>Operating</b> 32° to 95° F (0° to 35° C)
	<b>Non-operating</b> 4° to 140° F (-20° to 60° C)
<b>Relative humidity</b>	<b>Operating</b> 10% to 90%, relative humidity
	<b>Non-operating</b> 5% to 90% relative humidity, 101.6° F (38.7° C) maximum wet bulb temperature
<b>Altitude</b>	<b>Operating</b> -50 to 10,000 ft (-15.24 to 3,048 m)
	<b>Non-operating</b> -50 to 40,000 ft (-15.24 to 12,192 m)
<b>Shock</b>	<b>Operating</b> 40 G, 2 ms, half-sine
	<b>Non-operating</b> 200 G, 2 ms, half-sine
<b>Random vibration</b>	<b>Operating</b> 10-500 Hz, 0.5 grms
	<b>Non-operating</b> 10-500 Hz, 1.0 grms
<b>Option kit contents</b>	HP ElitePad Security Jacket with Smart Card Reader, documentation

**NOTE:** Weight is measure using a PV unit and aluminum CAC cover, cover/stand is not included.

**Compatibility** HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet

### HP ElitePad Expansion Jacket Cover

<b>Dimensions (H x W x D)</b>	10.77 x 8.30 x 0.89 in (273.65x 210.75x 22.60mm)
<b>Shell material</b>	Black rubber PU
<b>Protective shell material</b>	Black TPU
<b>Lining material</b>	Black Microflex lining
<b>Hardware</b>	Black plastic
<b>Option kit contents</b>	HP ElitePad Protective Jacket Cover and documentation
<b>Compatibility</b>	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet

### HP ElitePad Expansion Jacket

<b>Dimensions (H x W x D)</b>	10.60 x 8.05 x 0.69 in (269.2x 204.6 x 17.5 mm)
<b>Weight</b>	0.56 lb (254 g) (jacket only)
<b>USB ports</b>	(2) USB 2.0 ports
<b>Audio connectors</b>	Combo stereo/headphone jack
<b>Other connectors</b>	(1) HDMI, (1) HCSD
<b>Stand-alone power requirements</b>	<b>Normal Operating Voltage</b> 6.5 V
	<b>Average Operating Power</b> 8.5 W
	<b>Max Operating Power</b> < 40 W
<b>Temperature</b>	<b>Operating</b> 32° to 95° F (0° to 35° C)
	<b>Non-operating</b> 4° to 140° F (-20° to 60° C)
<b>Relative humidity</b>	<b>Operating</b> 10% to 90%, relative humidity
	<b>Non-operating</b> 5% to 90% relative humidity, 101.6° F (38.7° C) maximum wet bulb temperature
<b>Altitude</b>	<b>Operating</b> -50 to 10,000 ft (-15.24 to 3,048 m)

### Technical Specifications

<b>Shock</b>	<b>Non-operating</b>	-50 to 40,000 ft (-15.24 to 12,192 m)
	<b>Operating</b>	40 G, 2 ms, half-sine
<b>Random vibration</b>	<b>Non-operating</b>	200 G, 2 ms, half-sine
	<b>Operating</b>	10-500 Hz, 0.5 grms
<b>Option kit contents</b>	<b>Non-operating</b>	10-500 Hz, 1.0 grms
	<b>Operating</b>	10-500 Hz, 0.5 grms
<b>Option kit contents</b>	HP ElitePad Expansion Jacket, documentation	
<b>Compatibility</b>	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet	

### HP ElitePad Expansion Jacket With Battery

<b>Dimensions</b>	<b>Battery and Jacket (H x W x D)</b> 10.60 x 8.05 x 0.69 in (269.2x 204.6 x 17.5 mm)		
	<b>Battery only (H x W x D)</b> 4.3 x 118.5 x 200 mm		
<b>Weight</b>	<b>Jacket and Battery only</b> 0.86 lbs (450 g)		
	<b>Jacket only</b> 0.57 lbs (260 g)		
	<b>Battery only</b> 0.42 lbs (190 g)		
<b>Specs</b>	<b>HP ElitePad Main Battery</b>	<b>HP ElitePad Jacket Battery</b>	
<b>Battery Cells/Type</b>	Lithium-ion Polymer	Lithium-ion Polymer	
<b>Energy</b>	<b>Voltage</b>	7.4V	7.4V
	<b>Amp-hour capacity</b>	3.38Ah	2.96Ah
	<b>Watt-hour capacity</b>	25Wh	21Wh
<b>Temperature Battery</b>	<b>Operating (Charging)</b>	32° to 113° F (0° to 45° C)	32° to 113° F (0° to 45° C)
	<b>Operating (Discharging)</b>	14° to 140° F (-10° to 60° C)	14° to 140° F (-10° to 60° C)
	<b>Non-operating</b>	-4° to 140° F (-20° to 60° C)	-4° to 140° F (-20° to 60° C)
<b>Temperature Jacket Only</b>	32° to 95° F (0° to 35° C) 4° to 140° F (-20° to 60° C)		
<b>Battery Re-Charge Time</b>	<b>System in OFF or Standby Mode</b>	2.5~3.5 hours	1.5 to 3 hours
	<b>System ON</b>	2.5 to 5 hours	1.5 to 4 hours
<b>Relative humidity (Jacket)</b>	10% to 90%, relative humidity 5% to 90% relative humidity, 101.6° F (38.7° C) maximum wet bulb temperature		
<b>Altitude (Jacket)</b>	-50 to 10,000 ft (-15.24 to 3,048 m)		
	-50 to 40,000 ft (-15.24 to 12,192 m)		
<b>Shock (Jacket)</b>	40 G, 2 ms, half-sine		
	200 G, 2 ms, half-sine		
<b>Random vibration (Jacket)</b>	10-500 Hz, 0.5 grms		
	10-500 Hz, 1.0 grms		
<b>Fuel Gauge LED on Battery</b>	NO		
<b>Warranty</b>	1 year		
<b>Ports on Jacket</b>	(2) USB 2.0 ports, combo stereo/headphone, (1) HDMI, (1) HCSD		
<b>Stand-alone power requirements for Jacket</b>	6.5 V		
	8.5 W		
	< 40 W		
<b>Option kit contents</b>	HP ElitePad Expansion Jacket, battery, documentation		
<b>Power conservation</b>	Standby, hibernation		
<b>Compatibility</b>	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet		

### Technical Specifications

#### HP ElitePad Productivity Jacket

<b>Dimensions</b> (H x W x D)	10.60 x 8.50 x 0.91 in (269.2x 215.9 x 23 mm)
<b>Weight</b>	<1.87 lb (< 850 g)
<b>Stand-alone power requirements</b>	<b>Average Operating Power</b> 1.0 W <b>Max Operating Power</b> < 10 W
<b>Ports</b>	(2) USB 2.0 ports Power connector
<b>Other connectors</b>	(1) SD card slot
<b>Audio connectors</b>	Combo stereo/ headphone and microphone jack
<b>Additional features</b>	Integrated wired keyboard Digital pen holder 3 adjusting viewing positions
<b>Option kit contents</b>	HP ElitePad Productivity Jacket, documentation
<b>Compatibility</b>	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet

### Power

#### HP ElitePad Expansion Jacket Battery

<b>Dimensions</b> (H x W x L)	0.17 x 4.67 x 7.88 in (4.3 x 118.6 x 200 mm)	
<b>Weight</b>	0.41 lb (186 g)	
<b>Cell Type</b>	Lithium-ion Polymer	
<b>Energy</b>	<b>Voltage</b>	7.4V
	<b>Amp-hour capacity</b>	2.96Ah
	<b>Watt-hour capacity</b>	21Wh
<b>Temperature</b>	<b>Operating</b> (charging)	32° to 113° F (0° to 45° C)
	<b>Operating</b> (discharging)	14° to 140° F (-10° to 60° C)
	<b>Non-operating</b>	-4° to 140° F (-20° to 60° C)
<b>Battery Recharge Time</b>	<b>System in OFF or Standby Mode</b>	1.5 to 3 hours
	<b>System ON</b>	1.5 to 4 hours
<b>Fuel Gauge LED</b>	No	
<b>Warranty</b>	1 year	
<b>Optional Travel Battery Available</b>	No	
<b>Compatibility</b>	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet	

#### HP ElitePad 10W AC Adapter

<b>Dimensions</b> (H x W x D)	2.56 x 2.16 x 1.14 in (65 x 55 x 29 mm)	
<b>Weight</b>	4.06 oz (115 g)	
<b>Input</b>	90 to 265 VAC	
<b>Input Efficiency</b>	76.6% min at 115 VAC	
<b>Input frequency range</b>	47 to 63 Hz	
<b>Input AC current</b>	1.0 A at 90 VAC	
<b>Output</b>	<b>Output power</b>	10W

### Technical Specifications

	<b>DC output</b>	9.00V
	<b>Hold-up time</b>	5 msec at 115 VAC input
	<b>Output current limit</b>	<3.5A, Over voltage protection- 20V max automatic shutdown
<b>Connector</b>	Tyco 70pin connector	
<b>Environmental Design</b>	<b>Operating temperature</b>	41° to 95° F (5° to 35° C)
	<b>Non-operating (storage) temperature</b>	-4° to 185° F (-20° to 85° C)
	<b>Altitude</b>	0 to 10,000 ft (0 to 3,048 m)
	<b>Non-Operating altitude</b>	0 to 50,000 ft (0 to 15,240 m)
	<b>Humidity</b>	Up to 95%
	<b>Storage Humidity</b>	Up to 95%
<b>EMI and Safety Certifications</b>	Worldwide safety and EMC approvals including CE, UL, cUL, GS, Australian Electric Permit, RCM, NOM, CCC, KC, CU, S mark, BSMI, ISC, PSE, PSB, NRcan, Ukrain and SII	
<b>Option kit contents</b>	HP ElitePad 10W AC Adapter, adapter duckhead(s), documentation	
<b>Compatibility</b>	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet	

### HP 40W Smart AC Adapter

<b>Dimensions (H x W x D)</b>	3.67 x 1.57 x 1.18 in (93 x 40 x 30 mm)
<b>Weight</b>	8.64 oz (245 g)
<b>Input</b>	90 to 265 VAC
<b>Input Efficiency</b>	84% min at 115 VAC
<b>Input frequency range</b>	47 to 63 Hz
<b>Input AC current</b>	1.0 A at 90 VAC
<b>Output</b>	
<b>Output power</b>	40W
<b>DC output</b>	9.50V
<b>Hold-up time</b>	5 msec at 115 VAC input
<b>Output current limit</b>	5A
<b>Connector</b>	HP Smart Barrel
<b>Environmental Design</b>	
<b>Operating temperature</b>	41° to 95° F (5° to 35° C)
<b>Non-operating (storage) temperature</b>	-4° to 185° F (-20° to 85° C)
<b>Altitude</b>	0 to 10,000 ft (0 to 3,048 m)
<b>Non-Operating altitude</b>	0 to 50,000 ft (0 to 15,240 m)
<b>Humidity</b>	Up to 95%
<b>Storage Humidity</b>	Up to 95%
<b>EMI and Safety Certifications</b>	Worldwide safety and EMC approvals including CE, UL, cUL, GS, Australian Electric Permit, RCM, NOM, CCC, KC, CU, S mark, BSMI, ISC, PSE, PSB, NRcan, Ukrain and SII
<b>Option kit contents</b>	HP 40W Smart AC Adapter, power cord, documentation
<b>Compatibility</b>	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet

### Technical Specifications

#### HP ElitePad Power/Ethernet Adapter

**Dimensions** (H x W x L) 0.602 x 2.165 x 215.56 in (15.3 x 55 x 547.54 mm)

**Weight** 1.69 lb (48 g)

**RMN No.** HSTNN-GD11

**Host Interface** HP ElitePad 70 pin connector

**Device interface** RJ45 Ethernet  
70-pin female connector

**Connectors** Device output: RJ45 Ethernet , 70-pin female connector  
Host input: 70pin male Connector

**Supported** 10/100 Mbps / ElitePad power adapter

**Operating Temperature** 0-40°C (32-104°F)

**Storage Temperature** -10~70°C (14~158°F)

**System Requirements** Microsoft Windows 7 with Service Pack 1 (32-bit or 64-bit), Windows Vista® with Service Pack 1 (32-bit or 64-bit), Microsoft Windows XP Home or Professional with Service Pack 3, Windows 8.

**Environmental EMC** FCC Part 15 Class B, IC ICES-003, CE (EN55022, EN61000, EN55024), BSMI, UL, C-tick, VCCI, KC

**RoHS** RoHS Compliant

**Compatibility** HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet

**Box contents** HP Power/RJ45 Adapter Cable, AU / WW Warranty Card, Quick Installation Guide

---

### Docking

#### HP ElitePad Dockable Case

**Dimensions** (H x W x D) 10.43 x 7.09 x 0.39 in (264 x 180 x 9.91 mm)

**Weight** .44 lb (200 g)

**Materials** Plastic cradle  
Microfiber cover  
Magnets inside flap  
Stand function

**Option kit contents** HP ElitePad Dockable Case and documentation

**Compatibility** HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet

---

#### HP ElitePad Docking Station

**Dimensions** (H x W x D) 4.83 x 5.34 x 2.24 in (122.8 x 135.7 x 57 mm)

**Weight** 1.48 lb (670 g)

**USB ports** (3) USB 2.0 ports, (1) Power-USB 2.0 port

**Audio connectors** Combo stereo/headphone jack

**Other connectors** (1) HDMI, (1) VGA, (1) RJ-45, (1) Smart AC adapter, (1) charge LED

**Stand-alone power requirements** **Normal Operating Voltage** 19.5 V

**Average Operating Power** 8.5 W

**Max Operating Power** < 40 W

### Technical Specifications

<b>Temperature</b>	<b>Operating</b>	32° to 95° F (0° to 35° C)
	<b>Non-operating</b>	4° to 140° F (-20° to 60° C)
<b>Relative humidity</b>	<b>Operating</b>	10% to 90%, relative humidity
	<b>Non-operating</b>	5% to 90% relative humidity, 101.6° F (38.7° C) maximum wet bulb temperature
<b>Altitude</b>	<b>Operating</b>	-50 to 10,000 ft (-15.24 to 3,048 m)
	<b>Non-operating</b>	-50 to 40,000 ft (-15.24 to 12,192 m)
<b>Shock</b>	<b>Operating</b>	N/A
	<b>Non-operating</b>	200 G, 2 ms, half-sine
<b>Random vibration</b>	<b>Operating</b>	N/A
	<b>Non-operating</b>	10-500 Hz, 1.0 grms
<b>Option kit contents</b>	HP ElitePad Docking Station, 40W Smart AC adapter, power cord, documentation	
<b>Compatibility</b>	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet	

### Adapters

#### HP ElitePad USB 3.0 Adapter

<b>Host Interface</b>	70 pin		
<b>Device interface</b>	USB 3.0		
<b>Connectors</b>	<b>Signal output:</b>	USB female Connector	
	<b>Host input:</b>	70PIN male Connector	
<b>Supported</b>	Bus Power 5V output		
<b>Operating Temperature</b>	0-40°C (32-104°F)		
<b>Storage Temperature</b>	-10~70°C (14~158°F)		
<b>System Requirements</b>	<b>Software</b>	Microsoft Windows 7 with Service Pack 1 (32-bit or 64-bit), Windows Vista® with Service Pack 1 (32-bit or 64-bit), Microsoft® Windows XP Home or Professional with Service Pack 3, Windows 8, Windows 10.	
	<b>Mechanical</b>	<b>Dimensions (H x W x L)</b>	<b>Unpackaged:</b> 3.94 x 1.162 x 5.98 in (10 x 29.5 x 151.86 mm)
		<b>Weight</b>	<b>Unpackaged:</b> 0.60 oz (17 g)
<b>Environmental</b>	<b>Operating</b>	<b>Temperature</b>	(0° to 55° C)
		<b>Humidity:</b>	10% to 90%, relative humidity
		<b>Altitude: Operating</b>	100, 00 feet and Non-Operating 30,000 feet used in vehicles.
	<b>Box contents</b>	HP ElitePad USB 3.0 Adapter, AU / WW Warranty Card, Quick Installation Guide	
<b>Compatibility</b>	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet		

#### HP ElitePad 12W USB Auto Adapter (w/cable)

<b>Host Interface</b>	HP ElitePad docking connector	
<b>Device interface</b>	USB3.0	
<b>Connectors</b>	<b>Signal output:</b>	USB female connector
	<b>Host input:</b>	70-pin male connector
<b>Supported</b>		
<b>Operating Temperature</b>	0-40°C (32-104°F)	
<b>Storage Temperature</b>	-10~70°C (14~158°F)	



### Technical Specifications

<b>System Requirements</b>	<b>Software</b>	Microsoft® Windows® 7 with Service Pack 1 (32-bit or 64-bit), Windows Vista® with Service Pack 1 (32-bit or 64-bit), Microsoft® Windows® XP Home or Professional with Service Pack 3, Windows 8, Windows 10.
<b>Mechanical</b>	<b>Dimensions (H x W x L)</b>	<b>Unpackaged:</b> 3.94 x 1.162 x 5.98 in (10 x 29.5 x 151.86 mm)
	<b>Weight</b>	<b>Unpackaged:</b> 0.60 oz (17 g)
<b>Environmental</b>	<b>EMC</b>	FCC Part 15 Class B, IC ICES-003, CE (EN55022, EN61000, EN55024), BSMI, UL, C-tick, VCCI, KC
	<b>RoHS</b>	RoHS Compliant
<b>Box contents</b>	HP USB Dongle Cable, AU / WW Warranty Card, Quick Installation Guide	
<b>Compatibility</b>	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet	

### HP ElitePad USB Adapter

<b>Host Interface</b>	HP ElitePad docking connector	
<b>Device interface</b>	USB	
<b>Connectors</b>	<b>Signal output:</b> USB female connector <b>Host input:</b> 70-pin male connector	
<b>Supported</b>	Bus Power 5V output	
<b>Operating Temperature</b>	0~40° C (32~104° F)	
<b>Storage Temperature</b>	-10~70° C (14~158° F)	
<b>System Requirements</b>	<b>Software</b>	Windows 8 32-bit
<b>Mechanical</b>	<b>Dimensions (H x W x L)</b>	<b>Unpackaged:</b> 0.43 x 0.85 x 5.08 in (11x 21.5 x 129.11 mm)
	<b>Weight</b>	<b>Unpackaged:</b> 0.49 oz (13.8 g)
<b>Environmental</b>	<b>EMC</b>	FCC Part 15 Class B, IC ICES-003, CE (EN55022, EN61000, EN55024), BSMI, UL, C-tick, VCCI, KC
	<b>RoHS</b>	RoHS Compliant
<b>Box contents</b>	HP ElitePad USB Adapter, documentation	
<b>Compatibility</b>	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet	

### HP ElitePad Smart AC Adapter

<b>Host Interface</b>	HP ElitePad docking connector	
<b>Device interface</b>	DC jack	
<b>DC Jack size</b>	7.5 mm	
<b>Connectors</b>	<b>Device output:</b> DC jack female connector <b>Host input:</b> 70-pin male connector	
<b>Supported</b>	Bus Power 5V output	
<b>Operating Temperature</b>	0~40° C (32~104° F)	
<b>Storage Temperature</b>	-10~70° C (14~158° F)	
<b>System Requirements</b>	<b>Software</b>	Windows 8 32-bit, Windows 10
<b>Mechanical</b>	<b>Dimensions (H x W x L)</b>	<b>Unpackaged:</b> 0.87 x 1.38 x 6.13 in (22 x 35.13 x 155.72 mm)
	<b>Weight</b>	<b>Unpackaged:</b> 0.92 oz (26.2 g)
<b>Environmental</b>	<b>EMC</b>	FCC Part 15 Class B, IC ICES-003, CE (EN55022, EN61000, EN55024), BSMI, UL, C-tick, VCCI, KC
	<b>RoHS</b>	RoHS Compliant
<b>Box contents</b>	HP ElitePad Smart AC Adapter, documentation	

### Technical Specifications

**Compatibility** HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet

#### HP ElitePad HDMI & VGA Adapter

<b>Host Interface</b>	HP ElitePad docking connector	
<b>Device interface</b>	HDMI, VGA	
<b>Connectors</b>	<b>Video output:</b> HDMI female/VGA female connector <b>Host input:</b> 70-pin male connector	
<b>Supported resolutions</b>	600 x 800, 768 x 1280, 1024 x 1280, 1680 x 1050, 1920 x 1080	
<b>Operating Temperature</b>	0-40° C (32-104° F)	
<b>Storage Temperature</b>	-10~70° C (14~158° F)	
<b>System Requirements</b>	<b>Software</b>	Windows 8 32-bit, Windows 10.
<b>Mechanical</b>	<b>Dimensions (H x W x L)</b>	<b>Unpackaged:</b> 0.551 x 2.56 x 6.02 in (14 x 65 x 152.91 mm)
	<b>Weight</b>	<b>Unpackaged:</b> 1.78 oz (50.4 g)
<b>Environmental</b>	<b>EMC</b>	FCC Part 15 Class B, IC ICES-003, CE (EN55022, EN61000, EN55024), BSMI, UL, C-tick, VCCI, KC
	<b>RoHS</b>	RoHS Compliant
<b>Box contents</b>	HP ElitePad HDMI & VGA Adapter, documentation	
<b>Compatibility</b>	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet	

#### HP ElitePad Serial Adapter

<b>Host Interface</b>	HP ElitePad docking connector	
<b>Device interface</b>	Serial Port	
<b>Connectors</b>	<b>Device output:</b> RS232 connector <b>Host input:</b> 70-pin male connector	
<b>Supported</b>	Serial port	
<b>Operating Temperature</b>	0-40° C (32-104° F)	
<b>Storage Temperature</b>	-10~70° C (14~158° F)	
<b>System Requirements</b>	<b>Software</b>	Windows 8 32-bit, Windows 10.
<b>Mechanical</b>	<b>Dimensions (H x W x L)</b>	<b>Unpackaged:</b> 0.59 x 1.53 x 5.86 in (15 x 38.77 x 148.9 mm)
	<b>Weight</b>	<b>Unpackaged:</b> 0.97 oz (27.4 g)
<b>Environmental</b>	<b>EMC</b>	FCC Part 15 Class B, IC ICES-003, CE (EN55022, EN61000, EN55024), BSMI, UL, C-tick, VCCI, KC
	<b>RoHS</b>	RoHS Compliant
<b>Box contents</b>	HP ElitePad Serial Adapter, documentation	
<b>Compatibility</b>	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet	

#### HP ElitePad Ethernet Adapter

<b>Host Interface</b>	HP ElitePad docking connector	
<b>Device interface</b>	RJ45 Ethernet	
<b>Connectors</b>	<b>Device output:</b> RJ45 connector <b>Host input:</b> 70-pin male connector	
<b>Supported</b>	10/100 M	
<b>Operating Temperature</b>	0-40° C (32-104° F)	
<b>Storage Temperature</b>	-10~70° C (14~158° F)	

### Technical Specifications

<b>System Requirements</b>	<b>Software</b>	Windows 8 32-bit, Windows 10.
<b>Mechanical</b>	<b>Dimensions</b> (H x W x L)	<b>Unpackaged:</b> 0.62 x 0.96 x 6.65 in (15.75 x 24.39 x 169 mm)
	<b>Weight</b>	<b>Unpackaged:</b> 0.89 oz (25.2 g)
<b>Environmental</b>	<b>EMC</b>	FCC Part 15 Class B, IC ICES-003, CE (EN55022, EN61000, EN55024), BSMI, UL, C-tick, VCCI, KC
	<b>RoHS</b>	RoHS Compliant
<b>Box contents</b>	HP ElitePad Ethernet Adapter, documentation	
<b>Compatibility</b>	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet	

### HP ElitePad SD Card Reader

<b>Host Interface</b>	HP ElitePad docking connector	
<b>Device interface</b>	SD connector	
<b>Connectors</b>	<b>Device output:</b> SD connector	<b>Host input:</b> 70-pin male connector
<b>Supported</b>	SD card	
<b>Operating Temperature</b>	0~40° C (32~104° F)	
<b>Storage Temperature</b>	-10~70° C (14~158° F)	
<b>System Requirements</b>	<b>Software</b>	Windows 8 32-bit, Windows 10.
<b>Mechanical</b>	<b>Dimensions</b> (H x W x L)	<b>Unpackaged:</b> 0.35 x 1.34 x 1.81 in (9 x 34 x 46 mm)
	<b>Weight</b>	<b>Unpackaged:</b> 0.45 oz (12.8 g)
<b>Environmental</b>	<b>EMC</b>	FCC Part 15 Class B, IC ICES-003, CE (EN55022, EN61000, EN55024), BSMI, UL, C-tick, VCCI, KC
	<b>RoHS</b>	RoHS Compliant
<b>Box contents</b>	HP ElitePad SD Adapter, documentation	
<b>Compatibility</b>	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet	

### Input/Output

#### HP Slim Bluetooth Keyboard

<b>Dimensions</b> (H x L x W)	0.6 x 10.3 x 4.6 in (17.1 x 264 x 116.8mm)
<b>Weight</b>	9.5 oz (270 g)
<b>Operating distance</b>	32.8 ft (10.0 m) with no obstructions
<b>System requirements</b>	Windows Vista, Windows 7, Windows 8; Bluetooth®-enabled PC
<b>Kit contents</b>	HP Slim Bluetooth Keyboard, two AAA batteries, documentation
<b>Compatibility</b>	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet

#### HP Executive Tablet Pen G2

<b>Dimensions</b> (H x L x W)	5.65 x 0.47 in (143.5 x 11.8 mm)
<b>Weight</b>	1.06 oz (30 g)
<b>Color</b>	Black
<b>Power</b>	One AAA battery
<b>System requirements</b>	Windows 8, Windows 8.1
<b>Kit contents</b>	HP Executive Tablet Pen G2, AAA battery and documentation

### Technical Specifications

<b>Functionality</b>	Right-click, draw, type, and navigate better than ever with a capacitive tip that offers pin-point accuracy to help improve productivity. Pen supports hover feature and pressure sensitivity levels up to 256 Windows 8 Certified Soft tip for quiet performance and more precise writing capabilities
<b>Compatibility</b>	HP ElitePad 1000 G2 Tablet

### Cases

#### HP ElitePad Leather Slip Case

<b>Dimensions</b>	10.75 x 9 x 0.75 in (273.05 x 228.60 x 19.05 mm)
<b>Weight</b>	0.50 lb (226g)
<b>Kit contents</b>	HP ElitePad Leather Slip Case
<b>Compatibility</b>	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet

#### HP ElitePad Case

<b>Dimensions</b>	14.71 x 10.5 x 0.50 in (373.73 x 268.16 x 13.00 mm)
<b>Weight</b>	0.50 lb (226 g)
<b>Kit contents</b>	HP ElitePad Case
<b>Compatibility</b>	HP ElitePad 900 G1 Tablet , HP ElitePad 1000 G2 Tablet

#### HP ElitePad Rugged Case

<b>Dimensions</b>	10.86 x 7.59 x 0.90 in (275.85 x 192.71 x 22.95 mm)
<b>Weight</b>	1.32 lb (600 g)
<b>Kit contents</b>	HP ElitePad Rugged Case, stand, hand strap, shoulder strap, documentation
<b>Compatibility</b>	HP ElitePad 900 G1 Tablet

#### HP ElitePad Rugged Case G2

<b>Dimensions</b>	10.86 x 7.59 x 0.90 in (275.85 x 192.71 x 22.95 mm)
<b>Weight</b>	1.32 lb (600 g)
<b>Kit contents</b>	HP ElitePad Rugged Case, stand, hand strap, shoulder strap, documentation

#### HP Pro 10 EE G1 Sleeve

<b>Dimensions (H x W x D)</b>	9.0 x 11.8 x 1.8 in (229 x 302 x 46 mm)
<b>Weight</b>	13.8 oz (391.2 g)
<b>Materials</b>	<b>Exterior material</b> Polyester <b>Interior material</b> Microsuede
<b>Compatibility</b>	HP ElitePad 1000 G1

#### HP ElitePad 1000 G2 Healthcare/Rugged Tablet Shoulder Strap

<b>Dimensions</b>	<b>Strap Length:</b> Adjustable from 35 to 74 cm (13.5 to 29.1 in) from middle of pad
-------------------	---

### Technical Specifications

	<b>Strap Width:</b>	2 cm (0.78 in)
	<b>Shoulder Pad Width:</b>	4.3 cm (1.69 in) - thickest point in the middle
<b>Weight</b>		0.1 kg (0.22 lb)
<b>Strap materials</b>		PC Plastic Neoprene (strap) Nylon (webbing)
<b>Kit contents</b>		Tablet Shoulder Strap
<b>Compatibility</b>		HP ElitePad 1000 G2 Rugged Tablet, HP ElitePad 1000 G2 Healthcare Tablet

### HP ElitePad Bluetooth Keyboard Case

<b>Dimensions (H x W x D)</b>	288.4 x 184.85 x 8.8 mm	
<b>Weight</b>	400 g	
<b>Interface</b>	Bluetooth® 3.0	
<b>Keys Layout</b>	83 keys (US layout), 84 keys (UK layout), 85 keys (JP layout)	
<b>Hot Keys</b>	12 hot keys	
<b>Battery</b>	Type	Li-Polymer 700mA
<b>Power Consumption</b>	DC	3.7V +/- 5%
<b>Operation</b>	23 mA (Max, with backlight)	
<b>Standby</b>	0.8 mA (Max)	
<b>Sleep</b>	150 uA (Max)	
<b>Recharging time</b>	Less than 4 hours, charging current : 280mA.	
<b>Operating Distance</b>	Up to 10m (32ft)	
<b>Operating Humidity</b>	10%-90%	
<b>Operating Temperature</b>	-15°C - 60°C	
<b>Ports</b>	Micro USB	
<b>Cable</b>	Micro USB charging cable (106.68 cm)	
<b>Additional features</b>	Integrated Bluetooth® keyboard	
<b>Outer material</b>	Graphite PU	
<b>Inner material</b>	Black Microfiber and Plastic	
<b>Option kit contents</b>	HP ElitePad Bluetooth® Keyboard Case, Micro USB charging cable, documentation	
<b>Compatibility</b>	HP ElitePad 900, HP ElitePad 1000	

Bluetooth is a trademark owned by its proprietor and used by Hewlett Packard Company under license.

### Cleaning

#### HP Tablet Cleaning Kit

<b>Dimensions</b>	6.30 x 2.17 x 2.17 in (160 x 55 x 55 mm)
<b>Weight</b>	.49 lb (225 g)

### Technical Specifications

<b>Materials</b>	Plastic Spray bottle Microfiber cleaning cloth PVC Carrying pouch
<b>Option kit contents</b>	Cleaning gel in spray bottle Double-sided cleaning cloth Carrying pouch Documentation
<b>Compatibility</b>	HP Tablets and Notebooks

---

### Compatibility

Each HP ElitePad Expansion Suite accessory included in this QuickSpecs is compatible with the HP ElitePad 900 G1 and ElitePad 1000 G2 Tablet.

---

### Service and support

Each accessory carries a one-year limited warranty. Technical support is available seven days a week, 24 hours a day, by phone, as well as online support forums. Certain restrictions and exclusions apply.

---

Copyright © 2014 Hewlett-Packard Development Company, L.P. All rights reserved.

Bluetooth is a trademark owned by its proprietor and used by Hewlett Packard Company under license.

The information contained herein is subject to change without notice and is provided "as is" without warranty of any kind. The warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. All other trademarks are the property of their respective owners.

### Summary of changes

<b>Date of change:</b>	<b>Version History:</b>		<b>Description of change:</b>
September 23, 2014	From v21 to v23	Change	Change the typo on “other connections” should be SD, not HD
		Added	Add the change log
October 2, 2014	From v23 to v24	Added	New section “HP Tablet Cleaning Kit”
November 13, 2014	From v24 to v25	Added	Added a new section under cases “HP Pro 10 EE G1 Sleeve” and separate cleaning kit in a separate Cleaning section
January 30, 2015	From v25 to v26	Change	Arrange a name mistake on the overview, change it to “HP ElitePad Expansion Jacket Cover”
February 3, 2015	From v26 to v27	Added	Added the section “HP ElitePad 1000 G2 Healthcare/Rugged Tablet Shoulder Strap”
June 19, 2015	From v27 to v28	Added	Added a new Spec, “HP ElitePad 1000 Rugged Tablet G2 Antimicrobial Hand Strap”
			Added a new spec for “HP ElitePad Bluetooth Keyboard Case”
July 16, 2015	From v28 to v29	Added	Added OS Windows 10
September 17, 2015	From v29 to 30	Deleted	Deleted “HP ElitePad 1000 Rugged Tablet G2 Antimicrobial Hand Strap”
	Version 1 to 2		