




Product Service

CERTIFICATE

No. Z1A 14 10 52878 112

Holder of Certificate: Hewlett-Packard Company3000 Hanover Street
Palo Alto, California 94304
USA**Certification Mark:****Product:** Notebook Computer**Tested according to:**EN 60950-1/A12:2011
EK1-ITB 2000:2014
ZEK 01.4-08

The product meets the safety and health requirements of the German Product Safety Act section 20 to 22 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. See also notes overleaf.

Test report no.: 612101474701**Valid until:** 2016-07-01**Date,** 2014-10-20
(Bill Lin)

Page 1 of 3



Product Service

CERTIFICATE

No. Z1A 14 10 52878 112

Model(s): HSTNN-I26C-4, HP EliteBook 840 G2,
HP EliteBook 740 G2, HP ZBook 14 G2**Parameters:**

Rated input voltage:	19.5 Vdc
Rated input current:	2.31 A or 3.33 A
Protection class:	III
Max. ambient temperature:	35 °C
Degree of protection against ingress of liquids:	Ordinary
Declared Sound Power level:	3.0 B(A)

Remarks:

1. See attachment for LCD(s) covered by this certificate.
2. The equipment is evaluated for operating in altitude up to 3,048 m (10,000 ft) above the sea level.

Factory(ies): 65256, 75263

Page 2 of 3

Bill Li-



The following LCD's panel description of the models are as below:

- | | |
|-----------------------------------|------------------|
| 1. AUO | Type: B140HAN01 |
| 2. LG Display | Type: LP140WF1 |
| 3. AUO | Type: B140XTN03 |
| 4. Chimei Innolux (Innolux Corp.) | Type: N140BGE |
| 5. LG Display | Type: LP140WH8 |
| 6. Samsung | Type: LTN140AT29 |
| 7. AUO | Type: B140RTN02 |
| 8. Chimei Innolux (Innolux Corp.) | Type: N140FGE |
| 9. Samsung | Type: LTN140KT13 |
| 10. Beijing BOE Display | Type: HB140WX1 |
| 11. LG Display | Type: LP140WF3 |

Suitable for environments: $L_{REF,EXT} = 200 \text{ cd/m}^2$ and $L_{REF,SML} = 2000 \text{ cd/m}^2$

Suitable for Max. illuminance: 750 Lux

Pixel fault classification: I

Design viewing distance: 500 mm


Design viewing direction: (0°, 90°)

Viewing direction range: Φ range is 0° to 360°

θ range is 39.1°

Content and perception: Artificial information

Date: 2014-11-27



Testing Laboratory

Bill Lin