



Product Service

# CERTIFICATE

No. Z1A 14 10 52878 111

**Holder of Certificate:** Hewlett-Packard Company3000 Hanover Street  
Palo Alto, California 94304  
USA**Certification Mark:****Product:****Notebook Computer****Tested according to:**EN 60950-1/A12:2011  
EK1-ITB 2000:2014  
ZEK 01.4-08

The product meets the safety and health requirements of the German Product Safety Act section 20 to 22 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. See also notes overleaf.

**Test report no.:** 612101474601**Valid until:** 2016-07-01**Date,** 2014-10-16  
( Bill Lin )

Page 1 of 3



Product Service

**CERTIFICATE****No. Z1A 14 10 52878 111****Model(s):** HSTNN-I29C, HP EliteBook 720 G2, HP EliteBook 820 G2**Parameters:**

Rated input voltage:	19,5 Vdc
Rated input current:	2.31 A or 3.33 A
Protection class:	III
Max. ambient temperature:	35 °C
Degree of protection	
against ingress of liquids:	Ordinary
Declared Sound Power level:	3.1 B(A)

**Remarks:**

1. See attachment for LCD(s) covered by this certificate.
2. The equipment is evaluated for operating in altitude up to 3,048 m (10,000 ft) above the sea level.

**Factory(ies):** 65256, 75263

Page 2 of 3

*Bill L.*



Taiwan

**Attachment to the Certificate      No. Z1A 14 10 52878 111**

**The following LCD's panel description of the models are as below:**

- |               |                  |
|---------------|------------------|
| 1. LG Display | Type: LP125WF2   |
| 2. Samsung    | Type: LTN125HL02 |
| 3. AUO        | Type: B125XTN02  |
| 4. Hefei Boe  | Type: HB125WX1   |
| 5. LG Display | Type: LP125WH2   |

Suitable for Max. illuminance:  $L_{REF,EXT} = 200 \text{ cd/m}^2$  and  $L_{REF,SML} = 2000 \text{ cd/m}^2$

Suitable for Max. illuminance: 750 lx

Pixel fault classification: I

Design viewing distance: 500 mm


Design viewing direction: (0°, 90°)

Viewing direction range:  $\Phi$  range is 0° to 360°

$\theta$  range is 35.2°

Content and perception: Artificial information

**Date: 2014-11-27**



**Testing Laboratory**

**Bill Lin**