

Models

HP USB 3.0 to Gigabit RJ45 Adapter	N7P47AA
HP USB-C™ to USB 3.0	N2Z63AA
HP USB-C™ to 3 mm and 4.5 mm Power Adapter	N2Z65AA
HP USB-C™ to RJ54/USB 3.0/USB-C	N2Z64AA
HP USB-C™ to RJ45	V7W66AA
HP USB-C™ to USB-A Hub	Z6A00AA
HP USB-A to USB-C Dongle <i>New!</i>	3RV49AA

Overview

HP USB 3.0 to Gigabit RJ45 Adapter

Convert your notebook's high-speed USB 3.0 connection to a fast 10/100/1000 Ethernet connection with the USB 3.0 to Giga LAN Adapter.

HP USB-C™ to USB 3.0

Convert your notebook or tablet's USB-C™ port to USB 3.0 with the HP USB-C™ to USB 3.0 Adapter.

HP USB-C™ to 3 mm and 4.5 mm Power Adapter

Travel light with the HP USB-C™ to 3 mm and 4.5 mm Adapter, which lets you use one power adapter to charge your tablet and notebook.

HP USB-C™ to RJ54/USB 3.0/USB-C

Easily enable reliable connectivity through wired USB 3.0, Ethernet, and USB-C™ power-in connections with the HP USB-C™ to RJ45/USB3/USB-C™ Adapter.

HP USB-C™ to RJ45

Easily connect to your network through your notebook or tablet's USB-C™ power-in port with the HP USB-C™ to RJ45 Adapter.

HP USB-C to USB-A Hub

Optimize your workspace with easy connectivity to your frequently-used accessories in the office and on the road. Convert your notebook or tablet's USB-C™ port to a portable, lightweight USB hub and enable simultaneous connections to up to three USB accessories with the HP USB-C to USB-A Hub.

HP USB-A to USB-C Dongle

Give your HP notebook or mobile device access to the complete desktop experience of your HP USB-C Universal Dock with the HP USB-A to USB-C Dongle.

Technical Specifications

HP USB 3.0 to Gigabit RJ45 Adapter

Part number	N7P47AA
Dimensions (L x W x H)	6.1 X 2.0 x 1.4 cm 2.4 x 0.78 x 0.55 in
Weight	19 g .67 ounce
Networking	
Connectivity Technology	Wired
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Data Transfer Rate	1000
Expansion / Connectivity	
Interfaces	1 x network - Ethernet 10Base-T/100Base-TX/1000Base-T - RJ-45
Connections	1 x Super-Speed USB - 9 pin USB Type A
LED's	Yes
Compatible Operating Systems	Windows 7 (32-bit and 64-bit) Windows 8 (32-bit and 64-bit) Chrome

HP USB-C™ to USB 3.0

Part number	N2Z63AA
Dimensions	14.08 X 2.33 X 1.10 cm 5.55 x 0.92 x 0.43 in
Weight	175 g 6.17 ounces
Connectors:	HP USB Type-C to USB 3.0 Adapter
LED's:	NA
Environmental Design	
Operating Temperature	0°C to 40°C
Non-operating (storage)	-20°C to 60°C
Humidity	20%-80%RH
Storage Humidity	20%-90%RH
EMI and Safety Certifications	CE/FCC&IC/BSMI/VCCI/C-tick(RCM)/UL&cUL
Compatibility	TBD

HP USB-C™ to 3 mm and 4.5 mm Power Adapter

Part number N2Z65AA

Dimensions (L x W x H) 16.06 x 4.75 x 1.90 cm
6.32 x 1.87 x .75

Weight 50 g
1.76 ounces

Connectors	I/O Port	Description	Quantity
	Input	3 mm DC jack	1
	Input	4.5 mm DC Jack	1
	Output	Type C PD cable connector	1

LEDS None

Environmental Design

Non-operating mode

Transportation & Storage -40 to +70 °C for 72 hours
Test Time of 4 hours
Temperature Gradient: 20°C/ hour Min.
Humidity 50%
Max Wet Bulb Temperature 29°C

Operating mode

Operating Temperature +0 to +40 °C
Test Time of 4 hours
Temperature Gradient: 20°/ hour
Humidity 50%
Max Wet Bulb Temperature 29°C

EMI and Safety Certifications USB IF

Compatibility TBD

HP AC adapter compatibility Please connect a HP AC Adapter up to 65W.

HP USB-C™ to RJ54/USB 3.0/USB-C

Part number	N2Z64AA
Dimensions	18.07 x 7.10 x 1.87 cm 7.12 x 2.80 x 0.74 in
Weight	245 g 8.64 ounces
Networking	
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Data Transfer Rate	10/100/1000Mbps
Connectivity	
Connectors	HP USB-C to RJ45/USB 3/USB-C
LED's	NA
Environmental Design	
Operating Temperature	0°C to 40°C
Non-operating (storage)	-20°C to 60°C
Humidity	20%-80%RH
Storage Humidity	20%-90%RH
EMI and Safety Certifications	CE/FCC&IC/BSMI/VCCI/C-tick(RCM)/UL&cUL/KCC/EAC/UK/SABS&NRCS/CB
Compatibility	TBD

HP USB-C™ to RJ45

Part number	V7W66AA
Dimensions (L x W x H)	18.0 X 2.1 x 1.7 cm 7.1 x 0.8 x 0.7 in
Weight	71.4 gm 2.5 ounce
Networking	
Connectivity Technology	Wired
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Data Transfer Rate	10/100/1000Mbps
Connectivity	
Interfaces	1 x network - Ethernet 10Base-T/100Base-TX/1000Base-T - RJ-45
Connections	1 x 22 pin USB Type C
LED's	Yes
Environmental Design	
Operating Temperature	0°C to 70°C
Non-operating (storage)	-55°C to +125°C
Humidity	Level 3
Storage Humidity	<=90% Rh in Al bag
EMI and Safety Certifications	EMC, CB, VCCI, CE, REACH, FCC, RCM, KCC, EAC, Ukraine

Compatible Operating Systems	Windows 7/8/8.1/10 Chrome OS MACBOOK OSX
-------------------------------------	--

HP USB-C™ to USB-A Hub



Part number	Z6A00AA
Dimensions	6.68 x 4.14 x 1.05 cm 2.63 x 1.63 x 0.42 in
Weight	36.5 g 1.28 ounces
Connectors:	HP USB-C™ to USB-A Hub
LED's:	NO
Environmental Design	
Operating Temperature	0°C to 35°C
Non-operating (storage)	-10°C to 35°C
Humidity	5%-85%RH
Storage Humidity	85%RH
EMI and Safety Certifications	CE/CB/FCC&IC/BSMI/VCCI/RCM/KCC/EAC/UL&Cul/Ukraine
Compatibility	HP Elite x2 1012 G1-G2, HP Pro x2 612 G2 HP EliteBook x360 1030 G2 HP EliteBook Folio 1040 G3 HP EliteBook Folio G1 HP EliteBook 1030 G1 HP EliteBook 820, 840, 850 G3-G4 HP EliteBook 725, 745, 755 G3-G4 HP ProBook 640, 650, 645, 655 G2-G3 HP ProBook 430, 440, 450, 470, 455 G4 HP Spectre Pro 13 G1 HP Chromebook 13 G1

HP USB-A to USB-C Dongle

Part number	3RV49AA
Dimensions (Not including cable and USB-C plug)	36.6 x 23.3 x 11 mm
Dimensions (Including cable and USB-C plug)	138 x 23.3 x 11 mm
Weight	17g
Upstream port	USB Type-A (USB 3.0) plug to host platform
Downstream port	USB 3.0 Type-C receptacle x1 Standard USB-C CC Logic IC integrated Standard USB-C MUX IC integrated for USB-C Reversible Function
Temperature (operation)	32~104 °F (0~40°C)
Temperature (Non-operation)	-4~140 °F (-20~+60°C)
Relative humidity (operation)	5%~90% RH, non-condensing
Relative humidity (Non-operation)	5%~95% RH, non-condensing
Altitude (operation)	10000ft (3048m)
Altitude (Non-operation)	30000ft (9144m)
Shock (operation)	40G, 2ms, half-sine
Shock (Non-operation)	240G, 2ms, half-sine
Random vibration (operation)	~0.21Grms, 5~500 Hz
Random vibration (Non-operation)	~2.09Grms, 5-500 Hz, Non-Operating
EMI and Safety Certifications	TBA
Compatibility	HP USB-C Universal Dock
Service and Support	



One-year limited warranty. Additional support is available 24 hours a day, seven days a week by phone as well as online support forums.

NOTE: Certain restrictions and exclusions apply. Consult the HP Customer Support Center for details.

Date of change:	Version History:		Description of change:
January 19, 2016	Version 1 to 2	Added	HP USB-C™ to RJ45
February 1, 2015	Version 2 to 3	Added	Environmental Design Specs for HP USB-C™ to RJ45
May 18, 2016	Version 3 to 4	Changed	Name and specs for HP USB-C™ to 3 mm and 4.5 mm Power Adapter
January 30, 2017	Version 4 to 5	Added	HP USB-C™ to USB-A Hub specs added
March 22, 2018	Version 5 to 6	Added	HP USB-A to USB-C Dongle specs
April 3, 2018	Version 6 to 7	Removed	“Multigenerational” removed from HP USB-A to USB-C Dongle overview

© Copyright 2018 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are US registered trademarks of Microsoft Corporation. USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum.