

### Overview

## HP Elite x2 1012 G1 Accessories

### Docking Stations

HP Advanced Wireless Docking Station <sup>1</sup>	F7M97AA
HP Elite 65W Thunderbolt 3 Dock	P5Q54AA
HP Elite USB-C Docking Station	T3V74AA

### Adapters

HP USB Type-C™ to USB 3.0 Adapter	N2Z63AA
HP USB Type-C™ to VGA Adapter	N9K76AA
HP USB Type-C™ to DisplayPort Adapter	N9K78AA
HP USB Type-C™ to HDMI Adapter	N9K77AA
HP 45W USB-C™ Power Adapter	V5Y26AA
HP 45W USB-C™ Auto Adapter	Z3Q87AA

### Input/Output

HP Elite x2 1012 Travel Keyboard	T4Z25AA
HP Elite x2 1012 Advanced Keyboard	P5Q65AATBD
HP Active Pen with App Launch	T4Z24AA

### Cases

HP Elite Top Load Colombian Leather Case	T9H72AA
HP Elite Top Load Herringbone Nylon Case	T9H73AA
HP x2 1012 Protective Case	T3P15AA

### Power

HP USB-C™ to USB 3.0 and 4.5mm Power Adapter	N2Z65AA
--	---------

### Security

HP Tablet Master Cable Lock	T8X45AA
HP Elite x2 Privacy Screen	W7C36AA

### Miscellaneous

HP Ultralim Tablet Sling up to 12"	F7Z97AA
HP Ultra Mobile Wireless Mouse	H6F25AA
HP Tablet Cleaning Kit	K6F99AA

### Technical Specifications

#### Overview

---

#### Docking Stations

##### HP Advanced Wireless Docking Station<sup>1</sup>

Expand your workspace with the HP Advanced Wireless Docking Station<sup>1</sup>, which enables seamless connectivity through WiGig technology.<sup>1</sup>

##### HP Elite 65W Thunderbolt 3 Dock<sup>2</sup>

Get expansive device, display, and network connectivity plus simultaneous charging of your system through one simple cable from the dock.

##### HP Elite USB-C™ Docking Station

Charge your device, view content on dual displays, access a range of accessories, and connect to a desktop PC experience with a single cable connection to the HP Elite USB-C™ Docking Station.

#### Adapters

##### HP USB Type-C™ to USB 3.0 Adapter

Convert your notebook or tablet's USB-C™ port to USB 3.0 with the HP USB-C™ to USB 3.0 Adapter.

##### HP USB Type-C™ to VGA Adapter

Drive your notebook or tablet's video content to an external display, TV, or projector with the HP USB-C™ to VGA Adapter.

##### HP USB Type-C™ to DisplayPort Adapter

Put your notebook or tablet's high-definition video content up on the big screen with the HP USB-C™ to DP Adapter, which enables connection to an external display, TV or projector.

##### HP USB Type-C™ to HDMI Adapter

Project your notebook or tablet's high-definition video and audio content to an external display, TV, or projector with the HP USB-C™ to HDMI Adapter.

##### HP 45W USB-C™ Power Adapter

Power and charge your notebook or tablet from its USB-C™ port with the HP 45W USB-C™ AC Adapter.

##### HP 45W USB-C™ Auto Adapter

Power and charge your notebook, tablet or phone when work takes you on the road with the HP 45W USB-CTM Auto Adapter, which connects to your car's cigarette lighter outlet.

---

#### Input/Output

##### HP Elite x2 1012 Travel Keyboard

Be productive on the go with the executive-class, full-sized the HP Elite x2 1012 G1 Travel Keyboard.<sup>3</sup>

##### HP Elite x2 1012 Advanced Keyboard

Enhance the productivity of your HP Elite x2 1012 Tablet by connecting it to the full-featured, sturdy HP Elite x2 1012 Advanced Keyboard.<sup>3</sup>

##### HP Active Pen with App Launch

Write naturally, launch an app with the touch of a button, and maximize your mobile productivity with the HP Active Pen with App Launch.

---

### Technical Specifications

#### Cases

##### HP Elite Top Load Colombian Leather Case

Set a new style standard when you're on the move with the HP Elite Top Load Colombian Leather Case, a beautifully lush full-grain leather bag that helps protect your devices and data and has ultimate expandability for your everyday essentials without the extra bulk.

##### HP Elite Top Load Herringbone Nylon Case

Take mobility to the max and carry your mobile device and everyday essentials in style with the eye-catching HP Elite Top Load Herringbone Nylon Case, which helps protect your devices and data and delivers ultimate expandability without the extra bulk.

##### HP x2 1012 Protective Case

Give your HP Elite x2 1012 an extra layer of protection wherever the day takes you with the stylish, business-class HP Elite x2 1012 Protective Case.

---

#### Power

##### HP USB-C™ to USB 3.0 and 4.5mm Power Adapter

Travel light with the HP USB-C™ to 3 and 4.5 mm Adapter, which lets you use one power adapter to charge your tablet and notebook.

---

#### Security

##### HP Tablet Master Cable Lock

Help protect your mobile device from walking away with the HP Tablet Master Cable Lock.

##### HP Elite x2 Privacy Screen

Help protect your HP Elite x2's onscreen data from prying eyes with the HP Elite x2 Privacy Screen<sup>5</sup>, which also supports your interactive touchscreen features.

---

#### Miscellaneous

##### HP UltraSlim Tablet Sling up to 12"

Present a polished, professional appearance in and out of the office with the HP UltraSlim Tablet Sling, a stylish, durable, and compact black case with gray plaid accents designed to help protect your tablet.

##### HP Ultra Mobile Wireless Mouse

Low-profile, long-life, and designed for comfort. Here's the long-life wireless mouse that's so compact you can toss it in your carrying case without bulking out its profile, so power-smart it keeps up with your work day, and so comfortable you'll look for reasons to use it.

##### HP Tablet Cleaning Kit

Quickly and easily wipe away smudges, streaks, and fingerprints and help maintain optimal screen clarity with the HP Tablet Cleaning Kit.<sup>4</sup>

### Technical Specifications

## Docking Stations

### HP Advanced Wireless Docking Station<sup>1</sup>

<b>Unpackaged Dimensions</b> (W x D x H)	3.35 x 3.35 x 3.43 in (8.5 x 8.5 x 8.7 cm)
<b>Weight</b>	0.92 lb (0.42 kg)
<b>Stand-alone power requirements</b>	
Normal Operating Voltage	18.5 V
Average Operating Power	18.5 W
Max Operating Power	< 45 W
<b>Temperature</b>	
Operating	32° to 95° F (0° to 35° C) (not writing optical)
Non-operating	4° to 140° F (-20° to 60° C)
<b>Relative humidity</b>	
Operating	10% to 90%, non-condensing
Non-operating	5% to 95%, 101.6° F (38.7° C) maximum wet bulb temperature
<b>Altitude</b> (unpressurized)	
Operating	-50 to 10,000 ft (-15.24 to 3,048 m)
Non-operating	-50 to 40,000 ft (-15.24 to 12,192 m)
<b>Shock</b>	
Operating	40 G, 2 ms, half-sine
Non-operating	240 G, 2 ms, half-sine
<b>Random vibration</b>	
Operating	0.251-1.043 g
Non-operating	3.50 g
<b>Option kit contents</b>	HP Wireless Dock, AC power adapter, documentation

### HP Elite 65W Thunderbolt 3 Dock

<b>Dimensions</b> (H x W x D)	9.06 x 2.24 x .69 in 230 x 57 x 17.5 mm(w/ feet)
<b>Weight</b>	.5 lbs (220-227g)
<b>Stand-alone power requirements</b>	
<b>Normal Operating Voltage</b>	19.7V
<b>Average Operating Power</b>	0.368W
<b>Max Operating Power</b>	65W
<b>Temperature</b>	
Operating	50 – 60 Hz 32° to 95° F (0° to 35° C)
Non-operating	4° to 140° F (-20° to 60° C)
<b>Relative humidity</b>	
Operating	10% to 90%, non-condensing
Non-operating	5% to 95%, 101.6° F (38.7° C) maximum wet bulb temperature
<b>Altitude</b>	

### Technical Specifications

Operating	-50 to 10,000 ft (-15.24 to 3,048 m)
Non-operating	-50 to 40,000 ft (-15.24 to 12,192 m)
<b>Shock</b>	
Operating	125 G, 2 ms, half-sine
Non-operating	200 G, 2 ms, half-sine
<b>Random vibration</b>	
Operating	0.75 g
Non-operating	1.50 g
<b>Option kit contents</b>	HP Elite 65W TB3 Dock, Thunderbolt/AC power cable, 65W AC Adapter and documentation

### HP Elite USB-C Docking Station

<b>Dimensions</b> (H x W x D)	6x2.76x0.77 in 152.4x70x19.6 mm
<b>Weight</b>	0.66 +/-0.4lbs (300+/-20g)
<b>Stand-alone power requirements</b>	
<b>Normal Operating Voltage</b>	19.5V
<b>Average Operating Power</b>	55 W
<b>Max Operating Power</b>	62 W
<b>Temperature</b>	
Operating	32-104 F (0-40 C)
Non-operating	-40 to 158 F (-40 to +70C)
<b>Relative humidity</b>	
Operating	5%- 95% RH , non-condensing
Non-operating	90% RH, 84.2F (29° C) maximum wet bulb temperature
<b>Altitude</b>	
Operating	10000 ft (3048 m)
Non-operating	30000 ft (9144 m)
<b>Shock</b>	
Operating	40 G, 2 ms, half-sine
Non-operating	240 G, 2 ms, half-sine
<b>Random vibration</b>	
Operating	0.21 grms, 5 to 500 Hz, 1 hour per axis (X,Y,Z)
Non-operating	2.09 grms, 5 to 500 Hz, 1 hour per axis (X,Y, Z)
<b>Option kit contents</b>	HP Elite USB-C Docking Station, AC power cable, 65W A/C adapter, Documentation.

### Technical Specifications

#### Adapters

##### HP USB Type-C™ to USB 3.0 Adapter

<b>System Requirements</b>	WINXP/WIN7/WIN8
<b>Cable length</b>	14.09 cm (5.54 in)
<b>Weight (approx.)</b>	1.18 kg (2.59 pd)
<b>Conversion technology</b>	Type-C™ to USB3.0
<b>Connector type</b>	Type-C™/Type-A
<b>Industry standard certifications</b>	BC1.2 charge, Bus Power 5V/1.5A output CE/FCC&IC/BSMI/VCCI/C-tick(RCM)/UL&cUL
<b>Color</b>	Black
<b>Option kit contents</b>	HP Type-C™ to USB 3.0 Adapter, documentation

##### HP USB Type-C™ to HDMI Adapter

<b>Host Interface</b>	USB Type-C™
<b>Device interface</b>	HDMI 1.4a compliant
<b>Connectors</b>	Video output: HDMI female Connector Host input: USB Type-C™ male Connector
<b>Supported Resolutions</b>	4K x 2K @ 30Hz
<b>Operating Temperature</b>	0°C ~ 40°C
<b>Storage Temperature</b>	0°C ~ 85°C
<b>System Requirements</b>	Microsoft Windows 7 with Service Pack 1 (32-bit or 64-bit), Windows 8, Windows 10
<b>Dimensions (H x W x L)</b>	Unpackaged: 0.43 x 0.98 x 5.90 in (11 x 25 x 150 mm)
<b>Weight</b>	Unpackaged: 0.89 oz (25.4 g)
<b>Environmental</b>	ROHS, REACH, WEEE
<b>Option kit contents</b>	HP USB Type-C™ to HDMI Adapter, documentation
<b>Compatibility</b>	HP Pro Tablet 608 G1

##### HP USB Type-C™ to VGA Adapter

<b>Host Interface</b>	USB Type-C™
<b>Device interface</b>	VGA
<b>Connectors</b>	Video output: VGA female Connector Host input: USB Type-C™ male Connector
<b>Supported Resolutions</b>	2560 x 1600@60Hz (HBR2)
<b>Operating Temperature</b>	0°C ~ 40°C
<b>Storage Temperature</b>	0°C ~ 85°C
<b>System Requirements</b>	Microsoft Windows 7 with Service Pack 1 (32-bit or 64-bit), Windows 8, Windows 10
<b>Dimensions (H x W x L)</b>	Unpackaged: 0.51 x 1 x 5.90 in (13 x 25.5 x 150 mm)

### Technical Specifications

<b>Weight</b>	Unpackaged: 0.84 oz (23.9 g)
<b>Environmental</b>	ROHS, REACH, WEEE
<b>Option kit contents</b>	HP USB Type-C™ to VGA Adapter, documentation
<b>Compatibility</b>	HP Pro Tablet 608 G1

### HP USB Type-C™ to DisplayPort Adapter

<b>Host Interface</b>	USB Type-C™
<b>Device interface</b>	DisplayPort
<b>Connectors</b>	Video output: DisplayPort female Connector Host input: USB Type-C™ male Connector
<b>Supported Resolutions</b>	4K x 2K @ 30Hz
<b>Operating Temperature</b>	0°C ~ 40°C
<b>Storage Temperature</b>	0°C ~ 85°C
<b>System Requirements</b>	Microsoft Windows 7 with Service Pack 1 (32-bit or 64-bit), Windows 8, Windows 10
<b>Dimensions (H x W x L)</b>	Unpackaged: 0.6 x .93 x 7.09 in (15.2 x 23.6 x 180 mm)
<b>Weight</b>	Unpackaged: 1.14 oz (32.3 g)
<b>Environmental</b>	ROHS, REACH, WEEE
<b>Option kit contents</b>	HP USB Type-C™ to DisplayPort Adapter, documentation
<b>Compatibility</b>	HP Pro Tablet 608 G1

### HP 45W USB-C™ Power Adapter

<b>Dimensions</b>	66x 66 x 28.5 mm 2.6x2.6x1.1in
<b>Input Efficiency</b>	78.71% min at 115V/230V(option) @5V/2A 87.41% min at 115V/230V(option) @12V/3A 87.73% min at 115V/230V(option) @15V/3A
<b>Input frequency range</b>	47 to 63 Hz
<b>Input AC current</b>	1.4 A at 90 VAC and maximum load
<b>Output power</b>	45W max
<b>DC output</b>	5V/12V/15V
<b>Hold-up time</b>	5msec at 115 VAC input
<b>Output current limit</b>	< 5A Over voltage protection: 5V less than 7.25V 12V less than 16.85V 15V less than 20.5V
<b>Connector</b>	3 pin/grounded, mates with type-C connector
<b>Environmental Design</b>	
<b>Operating temperature</b>	0° to 35° C
<b>Non-operating (storage) temperature</b>	-20° to 85° C
<b>Altitude</b>	0 to 5,000 m

### Technical Specifications

<b>Humidity</b>	0% to 95%
<b>Storage Humidity</b>	0% to 95%
<b>Safety Certifications</b>	CE Mark - EMC directives; Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE; Reliability - failure rate of less than 0.1% annually within the first three years of operation.

### HP 45W USB-C™ Auto Adapter

<b>Host interface</b>	HP Notebook, Tablet or Phone USB-C port via adapter captive USB-C cable
<b>Power source interface</b>	Car cigarette lighter socket(12~24V/ at least 75W)
<b>Output power</b>	Maximum 45W
<b>DC output</b>	15V/3A, 12V/3A, 10V/3A, 9V/3A, 5V/3A at USB-C, 5V/0.9A at USB-A
<b>Maximum current</b>	3A (Static loading)
<b>Additional Connector Interface</b>	USB-A 3.0 port (USB 3.0 data and power output)
<b>Operating Temperature</b>	0° to 35°C @ <45W power output; 35° to 55°C @ <20W power output,
<b>Storage Temperature</b>	-20° to 85°C, 5% ~ 95% RH, non-condensing
<b>Altitude</b>	0 to 10,000 ft (0 to 3,048 m)
<b>Non-operating altitude</b>	0 to 50,000 ft (0 to 15,240 m)
<b>System Requirements</b>	Windows 10
<b>Weight</b>	Unpackaged: 3.82 oz (108.4 g)
<b>Environmental</b>	EMC RoHS
<b>Box contents</b>	HP 45W USB-C Auto Adapter, Double adhesive accessory, WW Warranty Card, QSP, Product Notice
<b>Compatibility</b>	HP Elite x3, HP Elite x3 Lap Dock, HP x2 1012 G1, HP x2 1012 G2, HP x2 612 G2 and HP x2 210 G2



### Technical Specifications

#### Input/Output

##### HP Elite x2 1012 Travel Keyboard

<b>Dimensions (H x W x D)</b>	11.83 x 8.65 x .24 in (300 x 219.3 x 6.1 mm)
<b>Weight</b>	.85 lb (385 g)
<b>Operating Humidity</b>	10%-90%
<b>Operating Temperature</b>	-15°C - 55°C
<b>Outer material</b>	Dark Gray Microfiber
<b>Inner material</b>	Dark Gray Microfiber and Plastic
<b>Option kit contents</b>	Keyboard and documentation
<b>Compatibility</b>	HP Elite x2 1012 G1

##### HP Elite x2 1012 Advanced Keyboard

<b>Dimensions (H x W x D)</b>	11.83 x 8.65 x .34 in (300 x 219.3 x 8.65 mm)
<b>Weight</b>	.99 lb (450 g)
<b>Operating Humidity</b>	10%-90%
<b>Operating Temperature</b>	-15°C - 55°C
<b>Outer material</b>	Dark Gray Microfiber
<b>Inner material</b>	Dark Gray Microfiber and Plastic
<b>Option kit contents</b>	Keyboard and documentation
<b>Compatibility</b>	HP Elite x2 1012 G1

##### HP Active Pen with App Launch

<b>Dimensions (L x W)</b>	5.79 x .37 in (147.29 x 9.5 mm)
<b>Weight</b>	0.61 oz (17.5 g)
<b>Tip Diameter</b>	1 mm
<b>Power</b>	One AAAA battery + 2 Li Ion coin cell batteries
<b>Buttons</b>	Yes, 3
<b>Pressure Sensitivity</b>	Yes (2048 levels)
<b>Tilt Operation</b>	Yes
<b>Palm Rejection</b>	Yes
<b>Hover Reading Height</b>	8mm+
<b>Operating Temperature</b>	5° to 40° C (41° F – 104° F)
<b>Operating Humidity</b>	30 - 80 %
<b>Storage Temperature</b>	-10 to 55°C (14° F – 131° F)
<b>Storage Humidity</b>	30 - 80 %
<b>Pen technology</b>	Wacom
<b>System Requirements</b>	Windows 8.1, Windows 10
<b>Color</b>	Silver/Grey
<b>Option kit contents</b>	HP Active Pen with App Launch, AAAA battery, lanyard, 3 replacement tips, replacement tip tool, 2 replacement pen loops, documentation
<b>Compatibility</b>	HP Elite x2 1012 G1

### Technical Specifications

#### Cases

---

##### HP Elite Top Load Colombian Leather Case

<b>Dimensions</b> (W x H x D)	15.5 x 10.5 x 3.0 in (394 x 267 x 76 mm)
<b>Weight</b>	2.5 lbs (1.13 kg) w/shoulder strap
<b>Materials</b>	Columbian Leather & Nickel hardware w/ Gunmetal finish
<b>Compatibility</b>	Padded compartment inside compatible for up to 14" mobile platforms
<b>Security</b>	RFID-blocking pocket
<b>Country of origin</b>	China
<b>Option kit contents</b>	HP Elite Top Load Leather Case, documentation

##### HP Elite Top Load Herringbone Nylon Case

<b>Dimensions</b> (W x H x D)	15.5 x 10.5 x 3.0 in (394 x 267 x 76 mm)
<b>Weight</b>	1.7 lbs (0.77 kg) w/shoulder strap
<b>Materials</b>	Herringbone Nylon and Vegan Leather
<b>Compatibility</b>	Padded compartment inside compatible for up to 14" mobile platforms
<b>Security</b>	RFID-blocking pocket
<b>Country of origin</b>	China
<b>Option kit contents</b>	HP Top Load Nylon Case, documentation

##### HP x2 1012 Protective Case

<b>Dimensions</b> (W x H x D)	12 x 8.6 x .57 in (306 x 219.6 x 14.6 mm)	
<b>Shoulder strap dimensions</b>	Length	Adjustable 41.7 – 67.7 in (106 – 172 cm)
	Width	2.2 in (5.6 cm)
	Thickness	.23 in (6 mm)
<b>Weight</b>	Protective Case	10 oz (298 g)
	Shoulder Strap w/buckle	2.1 oz (60 g)
	Hand Strap	.6 oz (17.5 g)
<b>Case materials</b>	Polycarbonate (PC) Polyurethane (PU)	
<b>Compatibility</b>	HP Elite x2 1012 G1 Tablet HP Elite x2 1012 G1 Tablet with Travel Keyboard	
<b>Country of origin</b>		
<b>Option kit contents</b>	Protective Case, Shoulder Strap, Hand Strap, documentation	

### Technical Specifications

#### Power

##### HP USB-C™ to USB 3.0 and 4.5mm Power Adapter

<b>Dimensions</b> (L x W x H)	7.12 x 2.80 x 0.74 in (18.07 x 7.10 x 1.87 cm)		
<b>Weight</b>	8.64 ounces (245 g)		
<b>Connectors</b>	<b>I/O Port</b>	<b>Description</b>	<b>Quantity</b>
	<b>Input</b>	3mm DC jack	1
	<b>Input</b>	4.5mm DC Jack	1
	<b>Output</b>	Type C PD cable connector	1
<b>LEDs</b>	None		
<b>Environmental Design</b>	<b>Non-operating mode</b>		
	<b>Transportation &amp; Storage</b>	-40 to +70 °C for 72 hours Test Time of 4 hours Temperature Gradient: 20°C/ hour Min. Humidity 50%	
	<b>Operating mode</b>	+0 to +40 °C Test Time of 4 hours Temperature Gradient: 20°/ hour Humidity 50%	
<b>EMI and Safety Certifications</b>	USB IF		
<b>Option kit contents</b>	Adapter and documentation		

#### Security

##### HP Tablet Master Cable Lock

<b>Cable Length</b>	6 ft (183cm)
<b>Cable Break Point</b>	>= 1,000 lbs
<b>Swivel Head</b>	3 dimensions (360 degree for lock head and cable. 90 degree for cable angle)
<b>Lock Slot</b>	Wedge
<b>Key Cylinder</b>	Tubular
<b>Material</b>	Zinc Alloy for lock body, stainless steel for tip, galvanized steel cable with PVC coating
<b>Locking Operation</b>	Insert Key
<b>Packaging</b>	Brown envelope
<b>Option kit contents</b>	Lock, cable and documentation

### Technical Specifications

#### HP Elite x2 Privacy Screen

<b>Dimensions</b>	295.2 x 208.65 mm
<b>Net Weight</b>	22 g
<b>Weight with Complete Package</b>	148 g
<b>Mechanical</b>	
Functional film thickness	290 um
Release film	38 um
<b>Property</b>	
Viewing angle	60 degrees
Light transmittance	68%
Thickness	.29 mm
<b>Environmental testing</b>	
Heat resistance	65° C, 240 hrs
Cold resistance	-30° C, 240 hrs
Humidity resistance	40° C x 90% relative humidity, 240 hrs
Thermal shock	(-20° C x 1 hr — 60° C x 1 hr) x 5 times

---

### Technical Specifications

#### Miscellaneous

---

#### HP Ultralim Tablet Sling up to 12"

<b>Dimensions (H x W x D)</b>	12.8 x 8.9 x .98 in (32.5 x 22.6 x 2.5 cm)
<b>Weight</b>	.71 lbs (.32 kg)
<b>Option kit contents</b>	Sling and documentation

#### HP Ultra Mobile Wireless Mouse

<b>Dots per inch (DPI)</b>	1200
<b>Connectivity</b>	2.4 GHz, Link 5
<b>Dimensions (H x L x W)</b>	0.98 x 4.00 x 2.54 in (2.50 x 10.17 x 6.46 cm)
<b>Weight</b>	3.25 oz (92 g)
	Windows XP, Vista, Windows 7, Windows 8, Windows 10, Mac OSX, and Android
<b>Option kit contents</b>	HP Ultra Mobile Wireless Mouse, two AA batteries and documentation

#### HP Tablet Cleaning Kit

<b>Dimensions</b>	6.30 x 2.17 x 2.17 in (160 x 55 x 55 mm)
<b>Weight</b>	.49 lb (225 g)
<b>Materials</b>	Plastic Spray bottle Microfiber cleaning cloth PVC Carrying pouch
<b>Option kit contents</b>	Cleaning gel in spray bottle Double-sided cleaning cloth Carrying pouch Documentation
<b>Compatibility</b>	HP Tablets and Notebooks

---

#### Service and support

Each accessory carries a one-year limited warranty. Technical support is available seven days a week, 24 hours a day, by phone, as well as online support forums. Certain restrictions and exclusions apply.

© Copyright 2018 HP Development Company, L.P.

Bluetooth is a trademark owned by its proprietor and used by Hewlett Packard Company under license.

USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum.

The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

### *Technical Specifications*

#### **Footnotes**

1. The WiGig-compatible notebook or tablet must be positioned within 1.2 m (4 ft) and without obstruction in the line of sight of the wireless dock. HP Advanced Wireless Docking1 is compatible with the HP Elite x2 1012 G1 with an optional installed Intel® Tri Band Wireless AC with WiGig Combo card available at the time of purchase.
2. Your tablet must support Thunderbolt 3 to enable the docking station. Docking station, and monitor must all support USB-C, USB 3.0 and DisplayPort 1.2 to benefit from the advanced speeds or features that these technologies provide. If one of the devices does not support these technologies, you will still have USB 2.0 and DisplayPort 1.1 functionality.
3. The keyboard is only compatible with HP Elite x2 1012 G1, sold separately. Not intended for use on antimicrobial treated screens.
4. Not intended for use on antimicrobial treated screens.
5. Important: Drawing or writing on your HP Elite x2 with the pen while the HP Elite x2 Privacy Screen is installed may cause excessive pen tip wear. Pen use for writing or drawing while using the privacy screen is not recommended.

### Change Log

<b>Date of change:</b>	<b>Version History:</b>	<b>Action</b>	<b>Description of change:</b>
December 1, 2015	From v1 to v2	Deleted	HP USB-C to RJ54/USB 3.0/USB-C
January 20, 2015	From v2 to v3	Added	HP 45W USB-C™ Power Adapter
February 11, 2016	From v3 to v4	Added	Footnotes
March 2, 2016	From v4 to v5	Added	HDMI 1.4a compliant to HP USB-C to HDMI Adapter
March 10, 2016	From v5 to v6	Added	HP Elite x2 Privacy Screen
March 18, 2016	From v6 to v7	Added	Privacy Screen Statement and footnote
April 21, 2016	From v7 to v8	Added	Privacy Screen dimensions and weight
October 25, 2016	From v8 to v9	Added	HP 45W USB-C™ Auto Adapter specs
December 13, 2016	From v9 to v10	Updated	HP Active Pen with App Launch section updated
March 9, 2018	From v10 to v11	Added	Compatibility for HP USB-C Auto Adapter updated