




Product Service

CERTIFICATE

No. Z1A 16 01 93407 038

Holder of Certificate: **HP Inc.**
 1501 Page Mill Road
 Palo Alto CA 94304
 USA

Certification Mark:



Product: **Notebook Computer**

Tested according to: EN 60950-1:2006/A2:2013
 EK1-ITB 2000:2016
 AfPS GS 2014:01 PAK


The product meets the safety and health requirements of the German Product Safety Act section 20 to 22 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. See also notes overleaf.

Test report no.: 612101600301

Valid until: 2021-01-05

Date, 2016-01-07

Watson Yang
 (Watson Yang)



Page 1 of 3



Product Service

CERTIFICATE
No. Z1A 16 01 93407 038

Model(s): **HSTNN-I67C-4, HP ProBook 645 G2**

Parameters:

Rated input voltage:	19.5 Vdc
Rated input current:	2.31 A or 3.33 A
Protection class:	III
Max. ambient temperature:	35 °C
Degree of protection against ingress of liquids:	Ordinary
Declared Sound Power level:	3.5 B(A)

Remarks:
1) See attachment for LCD(s) covered by this certificate.
2) The equipment is evaluated for operating in altitude up to 3,048 m (10,000 ft) above the sea level.

Factory(ies): 75263

Page 2 of 3 *Wath yf*



The following LCD's panel description of the models are as below:

- | | |
|-------------------------|-------------------|
| 1. AUO | Type: B140XTN03.3 |
| 2. Beijing BOE Display | Type: HB140WX1 |
| 3. Chimei Innolux Corp. | Type: N140HGE-EA1 |
| 4. Chimei Innolux Corp. | Type: N140BGE-E33 |
| 5. SAMSUNG | Type: LTN140AT35 |
| 6. LG Display | Type: LP140WH8 |

Suitable for environments: $L_{REF,EXT} = 200 \text{ cd/m}^2$ or $L_{REF,SML} = 2000 \text{ cd/m}^2$
Suitable for Max. illuminance: 750 Lux

Pixel fault classification: I

Design viewing distance: 500 mm

Design viewing direction: $(0^\circ, 90^\circ)$

Viewing direction range: Φ range is 0° to 360°

θ range is 39.1°

Content and perception: Artificial information

Date: 2016-01-07



Testing Laboratory

A handwritten signature in black ink, appearing to read 'Watson Yang'.

Watson Yang