

Technical Specifications

HP PS/2 Business Slim Keyboard and Mouse and MousePad

Model

HP PS/2 Business Slim Keyboard and Mouse and MousePad

T4E66AA

Introduction

Boost your productivity, make a stylish IT choice, and get legacy compatibility with your environment with the compact yet full-featured HP PS/2 Business Slim Keyboard/Mouse/Mousepad, designed to complement the 2015 class of HP Business PCs.

Key Benefits

- Keyboard
 - Pair your PC with a sleek, restyled, reduced-size keyboard that packs a familiar notebook-style layout and function keys into a smaller¹, space-saving design. The comfortably intuitive, low-profile, quiet keys make data entry easy.
 - Interact seamlessly with a full-sized keyboard layout that's optimized for use with multiple operating systems.²
 - Easily connect the keyboard to the PS/2 port on your PC.
- Mouse
 - Get precision movement with a tracking system that works through light for less moving parts and greater durability than ball-based mice.
 - The optical sensor within the HP PS/2 Mouse employs a resolution of approximately 800dpi.
 - Left-handed or right-handed users can enjoy a contoured shape that suits either preference, with a wheel that also functions as a third button.
 - A ball-free design reduces sticking and the need for constant cleaning
 - Left-handed or right-handed users can enjoy a contoured shape that suits either preference, with a wheel that also functions as a third button.
 - A ball-free design reduces sticking and the need for constant cleaning.
 - Get the reassurance of a one-year limited warranty.

1. Compared to predecessor, standalone commercial HP keyboards.

2. See product QuickSpecs for compatible operating systems.

Compatibility

The HP PS/2 Business Slim Keyboard and Mouse and MousePad is compatible with HP 280 G2 MT, HP 285 (Pro) G2 MT, HP ProDesk 400 G3 SFF, HP ProDesk 400 G3 MT, HP ProDesk 490 G3 MT, HP ProDesk 400 G2 DM (Mini), HP ProOne 400 G2 AIO Touch, HP ProOne 400 G2 AIO Non-Touch, HP ProDesk 600 G2 MTW, HP ProDesk 600 G2 SFF, HP ProDesk 600 G2 Desktop Mini, HP ProOne 600 G2 AIO 21.5" Touch, HP ProOne 600 G2 AIO 21.5" Non-Touch, HP EliteDesk 705 G2 MT, HP EliteDesk 705 G2 SFF, HP EliteOne 705 G2 AIO 23" Touch, HP EliteOne 705 G2 AIO 23" Non-Touch, HP EliteDesk 705 G2 Desktop Mini, HP EliteDesk 800 G2 TWR, HP EliteDesk 800 G2 SFF, HP EliteDesk 800 G2 35W Desktop Mini, HP EliteDesk 800 G2 65W Desktop Mini, HP Collaboration PC G2, HP EliteOne 800 G2 AIO 23" Touch, HP EliteOne 800 G2 AIO 23" Non-Touch.

NOTE: *Not all models are available in all regions.*

Service and Support

Your Option Limited Warranty is a one (1) year (HP Option Limited Warranty Period) parts replacement warranty on any HP-branded or Compaq-branded options (HP Options). If your HP Option is installed in an HP Hardware Product, HP may provide warranty service either for the HP Option Limited Warranty Period or the remaining Limited Warranty Period of the HP Hardware Product in

Technical Specifications

which the HP Option is being installed, whichever period is the longer but not to exceed three (3) years from the date you purchased the HP Option.

HP PS/2 Business Slim Keyboard

	Keys	104, 105, 106, 107, 109 layout (depending upon country)
Physical Characteristics	Dimensions (L x W x H)	171.97 x 68.35 x 8.27 in (436.8± 1.5 x 173.6± 1.0 x 21.0± 1.0 cm)
	Weight	1.32 lb (600± 80 g) + 4.4 – 5.25VDC
	Operating voltage	
Electrical	Power consumption	50-mA maximum (with 5 VDC power supplied and three LEDs ON)
	System interface	PS/2 6-pin mini din connector
	ESD	Contact Discharge: 2, 4, 6, 8KV Air Discharge: 2, 4, 8, 10, 12.5KV
	EMI - RFI	Conforms to FCC rules for a Class B computing device
	Microsoft PC 99 - 2001	Functionally compliant
	Keycaps	Low-profile design
	Switch actuation	60±12.5g nominal peak force with tactile feedback
	Switch life	10 million keystrokes (Life tester)
	Switch type	Contamination-resistant switch membrane
	Key-leveling mechanisms	For all double-wide and greater-length keys
	Cable length	6 ft (1.8 m)
	Microsoft PC 99 - 2001	Mechanically compliant
	Acoustics	43-dBA maximum sound pressure level
	Operating temperature	50° to 122° F (10° to 50° C)
Non-operating temperature	-22° to 140° F (-30° to 60° C)	
Operating humidity	10% to 90% (non-condensing at ambient)	
Non-operating humidity	20% to 80% (non-condensing at ambient)	
Environmental	Operating shock	N/A
	Non-operating shock	65 inch 2.9 ms, six surface; 30g 266 inch/second; 50g 266 inch/second six surface
	Operating vibration	2-g peak acceleration
	Non-operating vibration	Starting at 5 Hz, vary the frequency of vibration from 5 to 500 Hz and back to 5 Hz at a Logarithmic sweep rate of 1 octave per minute.
	Drop (out of box)	26 in (66 cm) on carpet, six-drop sequence
Drop (in box)	29.93 in (76 cm) on concrete, 16-drop sequence	
Approvals	UL, FCC, CE Mark, TUV, TUV GS, VCCI, BSMI, C-Tick, KC	
	Ergonomic compliance	ANSI HFS 100, ISO 9241-4, and TUVGS
Dimensions (H x L x W)		1.46 x 2.48 x 4.53 in (3.70 x 6.29 x 11.50 cm)

Technical Specifications

Weight	3.53 oz (100g; +10g/- 5 g)	
Environmental	Operating temperature	-32° to 104°F (0° to 40° C)
	Non-operating temperature	-4° to 140°F (-20° to 60° C)
	Operating humidity	10% to 90% (non-condensing at ambient)
	Non-operating humidity	10% to 90% non-condensing
	Operating shock	40 g, 6 surfaces
	Non-operating shock	80 g, 6 surfaces
	Operating vibration	2 g peak acceleration
	Non-operating vibration	4 g peak acceleration
	Drop (out of box)	80 cm height onto asphalt tile over concrete or equivalent, 5-drop in 5 direction except the cable face
	Electrical	Operating voltage
Power consumption		100mA
System consumption		PS/2 mini-din connector
ESD		CE level 4, 15 kV air discharge
EMI-RFI		Conforms to FCC rules for a Class B computing device
Microsoft® PC99 – 2001		Functionally compliant
Mechanical	Resolution	800 DPI
	Tracking speed	10 in/s (25.4 cm/s) maximum
	Acceleration	±15%
	Switch actuation (left and right buttons operating force)	65□20 gf
	Switch life	3,000,000 operations (using Hasco modified tester)
	Switch type	Low force micro-switches
	Tracking mechanism life	80km
	Cable length	6 ft (1.8 m)
	Microsoft PC99 – 2001	Mechanically compliant
	Scroll wheel	Width
Diameter		22.5 ± 0.2 mm
Maximum rotation force		50 gf-cm
Switch type		Light force micro-switch
Switch life		1 million operations
Rotation cycle		Max 200,000 revolutions
Regulatory approvals	Compliant	UL/cUL, FCC, CE Mark, TUV/GS, VCCI, KCC, BSMI, C-Tick
Kit contents	PS/2 Business Slim Keyboard, PS/2 Mouse, MousePad, Installation Guide, Warranty Card, Safety and Comfort Guide	

© Copyright 2017 HP Development Company, L.P.

The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Microsoft and Windows are US registered trademarks of Microsoft Corporation.

Technical Specifications

Date of change:	Version History:		Description of change:
October 25, 2017	V1 to V2	Update	Typo fixed on dimensions for HP PS/2 Buisness Slim Keyboard section.