


### Technical Specifications

#### HP Z23i 23-inch IPS Display



- |                          |   |                     |  |
|--------------------------|---|---------------------|--|
| <b>1. Menu</b>           | Opens, selects or exits the OSD menu.   | <b>4. OK/Auto</b>   | If the OSD menu is on, press to select the highlighted menu item. If the OSD menu is inactive, press to activate the auto adjustment feature to optimize the screen image. |
| <b>2. Minus "-"</b>      | If the OSD menu is on, press to navigate backward through the OSD menu and decrease adjustment levels.  | <b>5. Power</b>     | Turns the monitor on or off  |
| <b>3. Plus "+"/Input</b> | If the OSD menu is on, press to navigate forward through the OSD menu and increase adjustment levels.<br>If the OSD menu is inactive, press to activate the source button that chooses the video signal input (VGA, DVI, or DisplayPort). | <b>6. Power LED</b> | LED:<br>fully powered = white;<br>sleep mode = amber;<br>sleep timer mode = flashing amber.  |

### Technical Specifications

**Model:** D7Q13A4, D7Q13A8, D7Q13AS, D7Q13AT

<b>Panel</b>	<b>Type</b>	23-inch IPS Gen 2, LED Backlit	
	<b>Viewable Image Area (diagonal)</b>	<b>58,42cm</b> (23 in.) widescreen; diagonally measured	
	<b>Panel Active Area (W x H)</b>	<b>50,91 x 28,64 cm</b> (20.04 x 11.27 in.)	
	<b>Panel Type</b>	Gen 2 IPS (Gen 2 technology, also called AH-IPS, enables lower power consumption).	
	<b>Resolution</b>	1920 x 1080 @ 60 Hz	
	<b>Aspect Ratio</b>	16:9	
	<b>Viewing Angle (typical)</b>	Up to 178° horizontal/178° vertical (10:1 minimum contrast ratio)	
	<b>Brightness (typical)*</b>	250 cd/m <sup>2</sup>	
	<b>Contrast Ratio (typical)*</b>	1,000:1	
	<b>Dynamic Contrast Ratio (typical)*</b>	5,000,000:1	
	<b>Response Time (typical)*</b>	8 ms gray to gray	
	<b>Pixel Pitch</b>	0.265 mm	
	<b>Backlight Lamp Life (to half brightness)</b>	30,000 hours minimum	
	<b>Color Support**</b>	16.7 million colors	
	<b>Color Gamut</b>		
		Size vs. NTSC (CIE 1931)	72%
	Size vs NTSC (CIE 1976)	86%	
	Coverage of sRGB (CIE 1976)	95%	
	*All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.		
	** With the use of FRC technology.		
<b>User Controls</b>	<b>Buttons or Switches</b>	Menu, Minus ("-"), Plus ("+") /Input, OK/Auto, Power	
	<b>Languages</b>	10 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese and S-Chinese)	
	<b>On Screen Display (OSD) User Controls</b>	Brightness, Contrast, Color, Image Control, OSD control, Management, Language, Information, Factory Reset, Input Control	
<b>Signal Interface/ Performance</b>	<b>Horizontal Frequency</b>	24-94 kHz	
	<b>Vertical Frequency</b>	50.76 Hz	
	<b>Native Resolution</b>	1920 x 1080 @ 60 Hz	
	<b>Preset VESA Graphic Modes (non-interlaced)</b>		640 x 480 @ 60Hz
			720 x 400 @ 70 Hz
			800 x 600 @ 60 Hz
			1024 x 768 @ 60 Hz
			1280 x 720 @ 60 Hz
	1280 x 1024 @ 60 Hz		
	1440 x 900 @ 60 Hz		
	1600 x 900 @ 60 Hz		
	1680 x 1050 @ 60 Hz		

### Technical Specifications

		1920 x 1080 @ 60 Hz	
<b>Video/Other Inputs</b>	<b>Maximum Pixel Clock Speed</b>	170 MHz	
	<b>User Programmable Modes</b>	Yes, 10	
	<b>Anti-Glare</b>	Yes	
	<b>Default Color Temperature</b>	6500 K	
	<b>Plug and Play</b>	Yes	
	<b>Self Powered USB 2.0 Hub</b>	One upstream, two downstream ports (cable included)	
	<b>Input Connectors</b>	1 VGA, 1 DisplayPort 1.2 (1.1 compatible), 1 DVI-D; HDCP support on DisplayPort and DVI	
	<b>Sync Input</b>	Separate synch	
	<b>Video Cables Included</b>	(1) DVI-D <b>1,8 m</b> (5.9 ft), (1) DisplayPort <b>2 m</b> (6.56 ft)	
<b>Power</b>	<b>Power Supply</b>	Internal	
	<b>Input Power</b>	100- 240 VAC, 50 to 60 Hz	
	<b>ENERGY STAR® Power<sup>1</sup></b>	22 W	
	<b>Default Power<sup>2</sup></b>	28 W	
	<b>Maximum Power<sup>3</sup></b>	36 W	
	<b>Sleep/Off Mode Power</b>	> 0.5 W	
	<b>Power Cable Length</b>	<b>1,9 m</b> (6.2 ft)	
<b>Mechanical</b>	<b>Dimensions (W x D x H)</b>	<b>Unpacked w/stand</b> (highest setting)	<b>54,4 x 24,29 x 46,99 cm</b> (21.4 x 9.5 x 18.5 in)
		<b>Unpacked w/o stand</b> (head only)	<b>54,4 x 5,1 x 32,9 cm</b> (21.4 x 2 x 12.9 in)
		<b>Packaged</b>	<b>62 x 18,3 x 51,8 cm</b> (24.4 x 7.2 x 20.4 in)
	<b>Weight</b>	<b>Head Only</b>	<b>4,19 Kg</b> (9.23 lbs)
		<b>Unpacked</b>	<b>6,4 Kg</b> (14.1 lbs)
		<b>Packaged</b>	<b>8,4 Kg</b> (18.52 lbs)
<b>Ergonomic Features</b>	<b>4-Way Comfort Adjust</b>	Easily adjust the display in height, tilt, swivel and pivot for maximum comfort.	
	<b>Cable Management</b>	Enhanced cable management for easy concealment of power, video and USB cables. Effortless routing of cables through the base of the column integrated cable management clip	
	<b>Detachable Stand</b>	No	
	<b>Tilt Range</b>	-5° to + 30° vertical	
	<b>Swivel Range</b>	360°	
	<b>Height Adjustable</b>	Yes, 150 mm	
	<b>Pivot Rotation</b>	Yes	
<b>Environmental</b>	<b>Temperature - Operating</b>	<b>5° to 35° C</b> (41° to 95° F)	
	<b>Temperature - Non-operating</b>	<b>-20° to 60° C</b> (-4° to 140° F)	
	<b>Humidity - Operating</b>	20% to 80% non-condensing	
	<b>Humidity - Non-operating</b>	5% to 95%, 38.7° C max wet-bulb	
	<b>Altitude - Operating</b>	<b>0 to 5,000 m</b> (16,404 ft)	
	<b>Altitude - Non-operating</b>	<b>0 to 12,192 m</b> (0 to 40,000 ft)	
	<b>White LED Backlights</b>	Yes	
	<b>CCFL Panel</b>	No	

### Technical Specifications

<b>Arsenic-Free Display Glass</b>	Yes
<b>Low Halogen<sup>4</sup></b>	Yes
<b>Mercury-Free Display Backlighting</b>	Yes

### Environmental Data Eco-Label Certifications & declarations

This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:

- IT ECO declaration
- US ENERGY STAR®
- TCO 6.0 and TCO Certified Edge
- EPEAT® Gold where HP registers commercial display products. See <http://www.epeat.net> for registration status in your country US Federal Energy Management Program (FEMP)

### Energy Consumption (in accordance with US ENERGY STAR® test method)

	<b>115VAC, 60Hz</b>	<b>230VAC, 50Hz</b>	<b>100VAC, 60Hz</b>
Normal Operation	20.9 W	21.4 W	21.1 W
Sleep	0.2 W	0.27 W	0.21 W
Off	0.12 W	0.17 W	0.12 W

### Heat Dissipation\*

	<b>115VAC, 60Hz</b>	<b>230VAC, 50Hz</b>	<b>100VAC, 60Hz</b>
Normal Operation	71 BTU/hr	73 BTU/hr	72 BTU/hr
Sleep	1 BTU/hr	1 BTU/hr	1 BTU/hr
Off	0.4 BTU/hr	0.5 BTU/hr	0.4 BTU/hr

\* Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

### Additional Information

- This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2002/95/EC.
- This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive - 2002/96/EC.
- This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).
- This product is in compliance with the IEEE 1680 (EPEAT) standard at the gold level, see: <http://www.epeat.net>
- Plastics parts weighing over 25 grams used in the product are marked per ISO 11469 and ISO1043.
- This product contains 28.6 % post-consumer recycled plastic (by wt.)
- This product is 98.5 % recycle-able when properly disposed of at end of life.

### Packaging Materials

<b>External:</b>	PAPER/Corrugated	750 g
<b>Internal:</b>	PLASTIC/EPS (Expanded Polystyrene)	449 g

### Technical Specifications

PLASTIC/EPE-Expanded Polyethylene 26 g  
PLASTIC/Other plastics 3 g  
unknown

#### RoHS Compliance

Hewlett-Packard is committed to compliance with all applicable environmental laws and regulations, including the European Union Restriction of Hazardous Substances (RoHS) Directive. HP's goal is to exceed compliance obligations by meeting the requirements of the RoHS Directive on a worldwide basis. By July 1, 2006, RoHS substances will be virtually eliminated (virtually = to levels below legal limits) for all HP electronic products subject to the RoHS Directive, except where it is widely recognized that there is no technically feasible alternative (as indicated by an exemption under the EU RoHS Directive).

#### Material Usage

This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at:

<http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf>):

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants - may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Formaldehyde
- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Nickel - finishes must not be used on the external surface designed to be frequently handled or carried by the user.
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBEBs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) - except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)

#### Packaging

HP follows these guidelines to decrease the environmental impact of product packaging:

### Technical Specifications

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

#### End-of-life Management and Recycling

Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <http://www.hp.com/go/reuse-recycle> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <http://www.hp.com/go/recyclers>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

#### Hewlett-Packard Corporate Environmental Information

For more information about HP's commitment to the environment:

Global Citizenship Report

<http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html>

Eco-label certifications

<http://www.hp.com/hpinfo/globalcitizenship/environment/productdesign/ecolabels.html>

ISO 14001 certificates:

<http://www.hp.com/hpinfo/globalcitizenship/environment/operations/envmanagement.html>

#### Options

For more information refer to the product's QuickSpecs.

#### HP LCD Monitor Quick Release— Part number EM870AA<sup>5</sup>

An easy-to-use, VESA-compliant, LCD monitor mounting solution that allows you to quickly and securely attach an LCD monitor to a variety of stands, brackets, arms or wall mounts. For more information, refer to this product's QuickSpecs document.

#### HP USB Graphics Adapter—Part number NL571AA

Enables connection of up to six simultaneous displays to help you boost productivity and multi-task across several open applications. Use one Adapter to bridge between a notebook or desktop PC and second monitor or use multiple Adapters to connect several displays to each other.

### Technical Specifications

<b>HP LCD Speaker Bar—Part number NQ576AA</b>	Powered directly by the monitor or the PC, the Speaker Bar seamlessly attaches to the monitor's lower bezel to bring full audio support to select HP LCD monitors. Features include dual speakers with full sound range and external jack for headphones. Sold separately. For more information, refer to the product's QuickSpecs.
<b>HP Business PC Security Lock Kit—Part number PV606AA</b>	Attaches to the rear of the PC with a six-foot steel cable that can be used to secure a PC or peripherals such as mice, keyboards, monitors or USB security devices to protect them against unauthorized removal by physically connecting the system to an anchor point.
<b>HP Integrated Work Center Stand - USDT and Thin Clients)—Part number LH526AA</b>	Allows mounting of a 17 - 24 inch diagonal HP LCD monitor and an HP Compaq dc8000 series Ultra-slim Desktop PC as well as select HP Thin Clients on a single stand for the convenience of an "all-in-one" form factor. For more information, refer to this product's QuickSpecs document.
<b>HP Integrated Work Center 2 - Small Form Factor (SFF) —Part number QP897AA</b>	Designed specifically for use with the HP Compaq Small Form Factor (SFF) Desktop PC and a 17 to 24-inch (43.18 to 60.96 cm) diagonal monitor, the HP Integrated Work Center 2 (IWC) - Small Form Factor (SFF) provides a portable, compact workspace to help maximize space-constrained work environments. (17 to 24-inch diagonal monitors need to meet supported weight limits of 7.5 to 12.1 lbs. (3.38 to 5.5 kg). For more information, refer to the product's QuickSpecs.
<b>HP Single Monitor Arm—Part number BT861AA</b>	The flexible design of the HP Single Monitor Arm provides a seemingly endless range of display adjustments with an amazing 13 inches of lift, 50 degrees of tilt, and 360 degrees of pan and rotation – all at your fingertips -- helping you stay comfortable and productive throughout the day.
<b>HP Adjustable Dual Display Stand—Part Number AW664AA</b>	Premium space-saving dual screen solution provides access to more monitor real estate and makes it possible to manage multiple applications simultaneously. Weight adjustable for dual monitors from 17-24". Rotate displays into portrait/landscape positions.
<b>HP DisplayPort Cable Kit —Part number VN567AA</b>	Connects a DisplayPort connector on an HP Business Desktop computer to a DisplayPort connector on a monitor
<b>HP Display and Notebook Stand—Part number AW662AA</b>	Use two displays at once to increase productivity - your notebook display, plus one external display up to 24 inches in size. The adaptable design of the HP Adjustable Display Stand can accommodate a range of notebook sizes with the innovative adjustable shelf.
<b>HP Adjustable Display Stand—Part number AW663AA</b>	Turn your HP Business Notebook into a desktop solution supporting up to a 24 inch display. A dual-hinged, smooth-motion display stand allows for greater depth, height and tilt adjustment for maximum comfort.
<b>What's in the box?</b>	<b>Monitor and Accessories</b> HP Z23i 23-inch IPS Display, AC power cord, DVI cable, USB cable, DisplayPort cable <b>Documentation</b> CD (includes user guide, warranty, drivers)

### Technical Specifications

	<b>Featured Software</b>	HP Display Assistant is a software utility that enables theft deterrence and allows monitor adjustment, color calibration, and security/asset management using the Display Data Channel Command Interface (DDC/CI) protocol of the connected PC or workstation.
<b>Other</b>	<b>User Guide Languages</b>	English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish.
	<b>Warranty Languages</b>	English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish.
	<b>Color</b>	Black
	<b>VESA External Mounting Security Lock-Ready</b>	Yes (one set of standard 4-hole pattern, 100 mm). Yes
	<b>Country of Origin</b>	China
<b>Certification and Compliance</b>	CB, CE, TUV, GS, GOST, CUL, CEL Grade 1, FCC, E-Star 5.0, CSA, NOM, S-Mark, VCCI, MIC, PSB, ISC, CCC, BSMI, C-Tick, ICES, Microsoft WHQL Certification (Windows 8 and Windows 7), ENERGY STAR® Qualified, EPEAT® Gold <sup>6</sup> , TCO 6.0 Edge Certified.	
<b>Compatibility Service and Warranty</b>	Compatible with platforms using the VESA standard video modes. Recommended for use with HP products. Protected by HP, including a 3 year standard limited warranty. Optional HP Care Pack Services are extended service contracts that extend your protection beyond the standard warranties. <sup>7</sup>	

© Copyright 2016 Hewlett-Packard Development Company, L.P.

ENERGY STAR is a registered mark owned by the U.S. government. All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

1. ENERGY STAR® power is measured with factory defaults, brightness at ENERGY STAR® level of 200 cd/m<sup>2</sup> and with no USB loads.
2. Default Power is measured with factory defaults, including factory default brightness and USB ports loaded at 25% of maximum.
3. Maximum Power is measured with monitor at maximum brightness and with USB ports loaded at 100% of maximum.
4. External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.
5. The HP Quick Release has been designed to support a maximum of up to 24 lbs (10.9 kg) for all devices mounted. Because mounting surfaces vary widely and the final mounting method and configuration may vary, mounting fasteners are not supplied (other than the VESA-compliant screws). HP recommends that you consult with a qualified engineering, architectural or construction professional to determine the appropriate type and quantity of mounting fasteners required for your application and to ensure that your mounting solution is properly installed to support applied loads.
6. EPEAT® Gold where HP registers commercial display products. See [www.epeat.net](http://www.epeat.net) for registration status in your country.
7. Service levels and response times for HP Care Pack Services may vary depending on your geographic location. Service starts from date of hardware purchase. Restrictions and limitations apply. See <http://www.hp.com/go/cpc> for details.



### Technical Specifications

#### Summary of Changes

<b>Date of change:</b>	<b>Version History:</b>		<b>Description of change:</b>
04/11/2016	From v1 to v2	New	Uploaded