


### Technical Specifications

#### HP LV2011 20-inch LED Backlit LCD Monitor



- |                 |  |                   |   |
|-----------------|--|-------------------|---|
| <b>1. Menu</b>  | Opens, selects or exits the OSD menu.  | <b>4. OK/auto</b> | If the OSD menu is on, press to select the highlighted menu item.<br>If the OSD menu is inactive, press to activate the auto adjustment feature to optimize the screen image. |
| <b>2. Minus</b> | If the OSD menu is on, press to navigate backward through the OSD menu and decrease adjustment levels. | <b>5. Power</b>   | Turns the monitor on or off.<br>Blue = Fully powered.<br>Amber = Sleep mode.<br>Flashing Amber = Sleep Timer mode.  |
| <b>3. Plus</b>  | If the OSD menu is on, press to navigate forward through the OSD menu and increase adjustment levels.  |                   |   |

**Model:** A3R82AA, A3R82A8, A3R82AP



### Technical Specifications

<b>Panel</b>	<b>Type</b> <b>Viewable Image Area (diagonal)</b> <b>Active Area (W x H)</b> <b>Aspect Ratio</b> <b>Viewing Angle (typical)*</b> <b>Brightness (typical)*</b> <b>Contrast Ratio (typical)*</b> <b>Dynamic Contrast Ratio (typical)*</b> <b>Response Time (typical)*</b> <b>Pixel Pitch</b> <b>Backlight Lamp Life (to half brightness)*</b> <b>Color Gamut (typical)*</b> <b>Color Support**</b>	TN (Twisted Nematic) LED Backlit LCD <b>50,8 cm</b> (20.0 in.) widescreen; diagonally measured  <b>442,8 mm x 249,1 mm</b> , (17.43 x 9.81 in.)  16:9 Up to 90° horizontal/50° vertical (10:1 minimum contrast ratio) 200 nits (cd/m <sup>2</sup> ) 600:1 3,000,000:1 5 ms (on/off) 0.2768 mm 30,000 hours  72% Can display up to 16 million colors
*All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower. ** With the use of FRC technology.		
<b>On Screen Display (OSD) Controls</b>	<b>Buttons or Switches</b>  <b>User Controls</b>	OSD menu select, OSD down, OSD UP, OK/Auto , Power English, French, Brazilian Portuguese, Spanish, S. Chinese, T. Chinese, Basaha Indonesia, Japanese, Korean  Brightness, contrast, color (6500k, 9300k, 5000k, custom), Image control, OSD control, Management, Language, Information, Factory Reset, Source Control (on select model), Exit
<b>Signal Interface/ Performance</b>	<b>Horizontal Frequency</b> <b>Vertical Frequency</b> <b>Native Resolution</b> <b>Preset VESA Graphic Modes (non-interlaced)</b>  <b>Text Mode</b> <b>Maximum Pixel Clock Speed</b> <b>User Programmable Modes</b> <b>Anti-Glare</b> <b>Default Color Temperature</b>	24 to 83 kHz 50 to 76 Hz 1600 x 900 @ 60 Hz 1600 x 900 @ 60 Hz 1440 x 900 @ 60Hz 1280 x 1024 @ 60Hz 1280 x 720 @ 60Hz 1024 x 768 @ 60Hz 800 x 600 @ 60Hz 720 x 400 @ 70Hz 640 x 480 @ 60Hz 720 x 400 @ 70 Hz 170 MHz No Yes 6500 K
<b>Video/Other Inputs</b>	<b>Plug and Play</b> <b>Input Connectors</b> <b>Input Impedance</b> <b>Sync Input</b> <b>Video Cable</b> <b>Video Cable Length</b> <b>Audio</b>	Yes (1) VGA (analog) 75 Ohms TTL separate synch (1) VGA <b>1,8 m</b> (5.9 ft.) No
<b>Power</b>	<b>Input Power</b> <b>Typical Power Consumption</b> <b>Maximum</b> <b>Power Saving</b> <b>Power Cable Length</b>	90 – 265 VAC, 45 or 63 Hz 20 W 22 W < 0.5 W <b>1,9 m</b> (6.2 ft.)



### Technical Specifications

<b>Mechanical</b>	<b>Dimensions (W x D x H)</b>	<b>Unpacked w/stand</b>	<b>47,73 x 17 x 35,66 cm,</b> (18.79 x 6.69 x 14.04 in.)		
		<b>Unpacked w/o stand</b> (head only)	<b>47,73 x 4,78 x 29,9 cm,</b> (18.79 x 1.88 x 11.77 in.)		
		<b>Packaged</b>	<b>52,9 x 37,3 x 10,8 cm,</b> (20.82 x 14.68 x 4.25 in.)		
		<b>Base area (footprint)</b>	<b>18,01 x 17,02 cm,</b> (7.09 x 6.70 in.)		
		<b>Weight</b>	<b>Head Only</b>	<b>2,8 kg (6.17lb.)</b>	
			<b>Unpacked</b>	<b>3,5 kg (7.72 lb.)</b>	
			<b>Packaged</b>	<b>4,7 kg (10.36 lb.)</b>	
		<b>Tilt Range</b>	-5° to +19°		
		<b>Swivel Range</b>	No		
		<b>Height Adjustable</b>	No		
	<b>Pivot Rotation</b>	No			
	<b>Base</b>	Detachable, ships attached			
<b>Environmental</b>	<b>Temperature - Operating</b>	<b>5° to 35° C (41° to 95° F)</b>			
	<b>Temperature - Non-operating</b>	<b>-20° to 60° C (-4° to 140° F)</b>			
	<b>Humidity - Operating</b>	20% to 80% non-condensing			
	<b>Humidity - Non-operating</b>	5% to 95%, 38.7° C max wet-bulb			
	<b>Altitude - Operating</b>	<b>0 to 5,000 m (16,404 ft)</b>			
	<b>Altitude - Non-operating</b>	<b>0 to 12,192 m (0 to 40,000 ft)</b>			
	<b>White LED Backlights</b>	Yes			
	<b>CCFL Panel</b>	No			
	<b>Arsenic-Free Display Glass</b>	Yes			
	<b>Low Halogen<sup>2</sup></b>	No			
	<b>Mercury-Free Display</b>	Yes			
<b>Environmental Data</b>	<b>Eco-Label Certifications &amp; declarations</b>	This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:			
		<ul style="list-style-type: none"> <li>IT ECO declaration</li> </ul>			
	<b>Energy Consumption</b> (in accordance with US ENERGY STAR® test method)	<b>115VAC, 60Hz</b>	<b>230VAC, 50Hz</b>	<b>100VAC, 60Hz</b>	
	Normal Operation	25.64 W	25.64 W	25.87 W	
	Sleep	0.21 W	0.22 W	0.25 W	
	Off	0.15 W	0.15 W	0.17 W	
	<b>Heat Dissipation*</b>	<b>115VAC, 60Hz</b>	<b>230VAC, 50Hz</b>	<b>100VAC, 60Hz</b>	
	Normal Operation	87.6 BTU/hr	87.6 BTU/hr	88.4 BTU/hr	
	Sleep	0.7 BTU/hr	0.7 BTU/hr	0.8 BTU/hr	
	Off	0.5 BTU/hr	0.5 BTU/hr	0.5 BTU/hr	
	*NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.				
<b>Additional Information</b>	<ul style="list-style-type: none"> <li>This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2002/95/EC.</li> <li>This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.</li> <li>This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).</li> <li>Plastics parts weighing over 25 grams used in the product are marked per ISO 11469 and ISO1043.</li> <li>This product contains 13.2% post-consumer recycled plastic (by wt.)</li> </ul>				



### Technical Specifications

#### Packaging Materials

- This product is 96.4% recycle-able when properly disposed of at end of life.

**External:** PAPER/Cardboard & misc 420 g  
**Internal:** PLASTIC/Polyethylene low density 12 g

#### RoHS Compliance

Hewlett-Packard is committed to compliance with all applicable environmental laws and regulations, including the European Union Restriction of Hazardous Substances (RoHS) Directive. HP's goal is to exceed compliance obligations by meeting the requirements of the RoHS Directive on a worldwide basis. By July 1, 2006, RoHS substances will be virtually eliminated (virtually = to levels below legal limits) for all HP electronic products subject to the RoHS Directive, except where it is widely recognized that there is no technically feasible alternative (as indicated by an exemption under the EU RoHS Directive).

#### Material Usage

This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at

[http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen\\_specifications.html](http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html)):

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants – may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Formaldehyde
- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)

#### Packaging

HP follows these guidelines to decrease the environmental impact of product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.



### Technical Specifications

- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

#### End-of-life Management and Recycling

Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <http://www.hp.com/go/reuse-recycle> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <http://www.hp.com/go/recyclers>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

#### Hewlett-Packard Corporate Environmental Information

For more information about HP's commitment to the environment:

Global Citizenship Report

<http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html>

Eco-label certifications

<http://www.hp.com/hpinfo/globalcitizenship/environment/productdesign/ecolabels.html>

ISO 14001 certificates:

<http://www.hp.com/hpinfo/globalcitizenship/environment/operations/envmanagement.html>

#### Options (sold separately)

##### HP Single Monitor Arm Part number BT861AA

The flexible design of the HP Single Monitor Arm provides a seemingly endless range of display adjustments with an amazing 13 inches of lift, 50 degrees of tilt, and 360 degrees of pan and rotation – all at your fingertips -- helping you stay comfortable and productive throughout the day.

##### HP USB Graphics Adapter— Part number NL571AA

Enables connection of up to six simultaneous displays to help you boost productivity and multi-task across several open applications. Use one Adapter to bridge between a notebook or desktop PC and second monitor or use multiple Adapters to connect several displays to each other.

##### HP Business PC Security Lock Kit—Part number PV606AA

Attaches to the rear of the PC with a six-foot steel cable that can be used to secure a PC or peripherals such as mice, keyboards, monitors or USB security devices to protect them against unauthorized removal by physically connecting the system to an anchor point.

#### Other

##### Accessories Included Software

VGA cable and AC Power cable

HP Display Assistant is a software utility that enables theft deterrence and allows monitor adjustment, color calibration, and security/asset management using the Display Data Channel Command Interface (DDC/CI) protocol of the connected PC or workstation.

##### User Guide Languages

English, French, Brazilian Portuguese, Spanish, S. Chinese, T. Chinese, Basaha Indonesia, Japanese, Korean



### Technical Specifications

<b>Warranty Languages</b>	English, French, Brazilian Portuguese, Spanish, S. Chinese, T. Chinese, Basaha Indonesia, Japanese, Korean
<b>Color</b>	Black
<b>VESA External Mounting</b>	Yes (one set of standard 4-hole pattern, 75 mm).
<b>Security Lock-Ready</b>	Yes
<b>Certification and Compliance</b>	CB, CE, TUV-GS, ISO9241-307, UL/CAS, FCC, EPA, GOST, NOM, TUV-S, VCCI, KC/KCC, PSB, ISC, CCC, BSMI, C-TICK, CCC, CECP, S EPA, CEL Grade 2, E-standby
<b>Compatibility Service and Warranty</b>	Compatible with platforms using the VESA standard video modes. Recommended for use with HP products. Protected by HP, including a 3 year standard limited warranty. Optional Care Pack Services are extended service contracts which go beyond your standard warranties. <sup>1</sup>

Copyright © 2017 HP Development Company, L.P

ENERGY STAR® is a US registered mark of the United States Environmental Protection Agency.

<sup>1</sup>HP Care Pack Services extend service contracts beyond the standard warranties. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts from date of hardware purchase. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at <http://www.hp.com/go/lookuptool>. Additional HP Care Pack Services information by product is available at <http://www.hp.com/hps/carepack>.

<sup>2</sup>External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.

All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.



### Summary of Changes

Date of change	Version History		Description of change
February 16, 2017	V2		