


Overview

HP N270c 27-inch Curved Monitor




1. Power indicator



- | | |
|--|---|
| <ol style="list-style-type: none"> 1. Menu/OK button 2. Plus ("+")/Up/Next Input Port button 3. Minus ("-")/Down/Viewing Modes button 4. Exit/Back/Information button 5. Power button 6. Power connector | <ol style="list-style-type: none"> 7. DisplayPort™ 1.2 input 8. HDMI 1.4 input 9. VGA Port 10. Audio-out (headphone) jack 11. Security lock slot |
|--|---|

Overview



1. Menu/OK button
2. Plus ("+")/Up/Next Input Port button
3. Minus ("-")/Down/Viewing Modes button
4. Exit/Back/Information button
5. Power button

Technical Specifications

Models: YGJ31AA, Y6J31A8

| | | |
|--------------|--|---|
| Panel | Type | 27-inch VA Curved |
| | Viewable Image Area (diagonal) | 68,58 cm (27 in) widescreen; diagonally measured |
| | Panel Active Area (W × H) | 59,78 x 33,63 cm (23.54 × 13.24 in) at a 1800r* curvature *radius of the arc of the panel curvature in mm |
| | Resolution | 1920 x 1080 @ 60 Hz |
| | Aspect Ratio | 16:9 |
| | Viewing Angle* | Up to 178° horizontal/178° vertical typical |
| | Brightness* | 300 cd/m ² |
| | Contrast Ratio* (Typical) | 3000:1 Static; 10,000,000:1 Dynamic (DCR) |
| | Response Times* | 5 ms Gray to Gray with Overdrive** |
| | Pixel Pitch* | 0.3114 mm |
| | Pixels Per Inch (PPI)* | 82 DPI |
| | Backlight Lamp Life* (to half brightness) | 30,000 hours minimum |
| | Color Production* | Can display up to 16.7 million colors with the use of FRC technology |
| | Color Gamut* (Typical) | sRGB 99% or above |

* Performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

**Product default is 21 ms response time and can be adjusted to as low as 5ms in the display menu. See user guide for more information. All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

| | | |
|--------------------------------------|--|---|
| User Controls | Buttons or Switches | Menu, Plus ("+")/Next Active Input, Minus ("-")/Viewing Modes, Back/Information, Power |
| | Languages | 10 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese and S-Chinese) |
| | On Screen Display (OSD) User Controls | Brightness, Contrast, Color Control, Input Control, Image Control, Power control, Menu Control, Management, Language, Information, EXIT |
| Signal Interface/ Performance | Horizontal Frequency | 30–86 kHz |
| | Vertical Frequency | 50-76 Hz |
| | Native Resolution | 1920 x 1080 @ 60 Hz |
| | Preset Graphic Modes (non-interlaced) | 640 x 480 @ 60Hz 720 x 400 @ 60 Hz 800 x 600 @ 60 Hz 1024 x 768 @ 60 Hz 1280 x 720 @ 60 Hz 1280 x 800 @ 60 Hz 1280 x 1024 @ 60 Hz 1440 x 900 @ 60 Hz |

Technical Specifications

| | | | |
|---------------------------|------------------------------------|--|--|
| | | 1600 x 900 @ 60 Hz | |
| | | 1680 x 1050 @ 60 Hz | |
| | | 1920 x 1080 @ 60 Hz | |
| | Maximum Pixel Clock Speed | 180 MHz | |
| | Anti-Glare | No | |
| | Low Haze | Yes | |
| Video/Other Inputs | Plug and Play | Yes | |
| | Input Connectors | (1) VGA | |
| | | (1) HDMI 1.4 | |
| | | (1) DisplayPort™ 1.2 | |
| | | HDCP support on HDMI and DisplayPort™ inputs | |
| | Video Cables Included | (1) VGA 1,8 m (5.9 ft) | |
| Power | Power Supply | External | |
| | Input Power | 100 - 240 VAC 50/60 Hz | |
| | Maximum Power | 41.5 W | |
| | Typical Power | 33.5 W | |
| | Sleep Power | 0.5 W | |
| | Power Cable Length | 1,8 m (5.9 ft) | |
| Mechanical | Dimensions (W × D × H) | Unpacked w/stand (lowest setting) | 61,33 x 16,89 x 43,85 cm (24.15 x 6.65 x 17.26 in) |
| | | Unpacked w/o stand (head only) | 61,33 x 6,99 x 36,37 cm (24.15 x 2.75 x 14.32 in) |
| | | Packaged | 73,2 x 22,5 x 52,6 cm (28.82 x 8.86 x 20.71 in) |
| | Weight | Head Only | 4.2 kg (9.24 lb) |
| | | Unpacked | 5,5 kg (12.1 lb) |
| | | Packaged | 8,9 kg (19.6 lb) |
| Ergonomic Features | Detachable Stand | Yes, ships detached | |
| | Tilt Range | -5° to + 12.5° vertical | |
| Environmental | Temperature - Operating | 5° to 35° C (41° to 95° F) | |
| | Temperature - Non-operating | -20° to 60° C (-4° to 140° F) | |
| | Humidity - Operating | 20% to 80% non-condensing | |
| | Humidity - Non-operating | 5% to 95%, 38.7° C max wet-bulb | |
| | Altitude - Operating | 0 to 5,000 m (0 to 16,404 ft) | |
| | Altitude - Non-operating | 0 to 12,192 m (0 to 40,000 ft) | |
| | White LED Backlights | Yes | |
| | CCFL Panel | No | |

Technical Specifications

| | | |
|--|--|--|
| | Arsenic-Free Display Glass | Yes |
| | Low Halogen¹ | Yes (except cables) |
| | Mercury-Free Display Backlighting | Yes |
| Options (each sold separately) | HP Single Monitor Arm — Part number BT861AA | The flexible design of the HP Single Monitor Arm provides a seemingly endless range of display adjustments with an amazing 13 inches of lift, 75 degrees of tilt, and 360 degrees of pan and rotation – all at your fingertips -- helping you stay comfortable and productive throughout the day. |
| | HP Business PC Security Lock V2 Kit — Part number N3R93AA | Help prevent chassis tampering and secure your PC and display in workspaces and public areas. Simply route the cable through the PC's lock slot and your display, anchor to a desk, table, or other fixed surface, and lock with your individual key. A master key configuration is also available upon request. |
| What's in the box? | Monitor and Accessories | HP N270c 27-in Curved Monitor, AC power cord (1,8 m) 5.9 ft, External Power Supply, VGA cable (1.8m) 5.9 ft, VESA wall/arm mount adapter |
| | Documentation | CD (includes user guide, warranty, drivers) |
| | Software | HP Display Assistant |
| Other | User Guide Languages | English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish. |
| | Warranty Languages | English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish. |
| | Color | Black (Bezel) and Silver (Stand) |
| | VESA Mounting | External Mount Bracket (included), 4-hole pattern, 100 mm x 100 mm |
| | Security Lock-Ready | Yes |
| | Country of Origin | China |
| Certification and Compliance | | CEL Grade 2, Microsoft WHQL Certification (Windows 10, Windows 8.1 and Windows 7), CE, CB, MSIP, ICES, CCC, EPA, ISC, VCCI, FCC, Taiwan: BSMI, ISO9241-307, Mexico CoC, cTUVus, EAC, RCM, Ukraine, Morocco, WEEE, KCC. |
| Compatibility | | Compatible with platforms using the VESA standard video modes. Recommended for use with HP products. |
| Service and Warranty | | Protected by HP, including a 3-year standard limited warranty. Optional HP Care Pack Services are extended service contracts that extend your protection beyond the standard warranties. ² |

Copyright © 2017 HP Development Company, L.P.

The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

ENERGY STAR is a registered trademark owned by the U.S. Environmental Protection Agency. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries.

Technical Specifications

1. External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.
2. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit: <http://www.hp.com/go/cpc>.

Change Log

| Date of change: | Version History: | | Description of change: |
|-----------------|------------------|--|------------------------|
| | From v1 to v2 | | |