

### Technical Specifications

## HP USB Keyboard and Mouse Healthcare Edition

### Models

HP USB Keyboard and Mouse Healthcare Edition

1VDB1AA

### Compatibility

The HP USB Keyboard and Mouse Healthcare Edition is compatible with HP ProDesk 400 G4 SFF, HP ProDesk 400 G4 MT, HP ProDesk 400 G3 DM (Mini), HP ProOne 400 G3 AIO Touch, HP ProOne 400 G3 AIO Non-Touch, HP ProDesk 600 G3 MT, HP ProDesk 600 G3 SFF, HP ProDesk 600 G3 Desktop Mini, HP ProOne 600 G3 AIO 21.5" Non-Touch, HP EliteDesk 800 G3 TWR, HP EliteDesk 800 G3 SFF, HP EliteDesk 800 G3 35W Desktop Mini, and HP EliteDesk 800 G3 65W Desktop Mini. HP EliteOne 800 G3 AIO 23.8" NT, HP EliteOne 800 G3 AIO 23.8" Touch, HP EliteOne 800 G3 AIO 23.8" Touch 4K.

**NOTE:** Not all models are available in all regions.

### Service and Support

Your Option Limited Warranty is a one (1) year (HP Option Limited Warranty Period) parts replacement warranty on any HP-branded or Compaq-branded options (HP Options). If your HP Option is installed in an HP Hardware Product, HP may provide warranty service either for the HP Option Limited Warranty Period or the remaining Limited Warranty Period of the HP Hardware Product in which the HP Option is being installed, whichever period is the longer but not to exceed three (3) years from the date you purchased the HP Option.

<b>Keyboard</b>		
<b>Physical Characteristics</b>	Keys	99 (US) 100(UK)
	Dimensions (H x W x D)	13.5x4.4x1.1 in (342.5x112.5x28.0 mm)
	Weight	0.6 lbs without cable (270 g)
<b>Electrical</b>	ESD	+/- 4KV
	Operating voltage	+ 4.75 to 5.25VDC
	Power consumption	50-mA maximum
	System interface	USB Type A plug connector
	EMI - RFI	Conforms to FCC rules for a Class B computing device
	Microsoft PC 99 - 2001	Functionally compliant
<b>Mechanical</b>	Keycaps	Low-profile design
	Switch actuation	55±10g nominal peak force with tactile feedback
	Switch life	10 million keystrokes (Life tester)
	Switch type	Membrane switch
	Key-leveling mechanisms	For all double-wide and greater-length keys
	Cable length	6 ft (1.8 m)
	Microsoft PC 99 - 2001	Mechanically compliant
<b>Environmental</b>	Acoustics	<40-dBA maximum sound pressure level
	Operating temperature	32° to 122° F (0° to 50° C)
	Non-operating temperature	23° to 131° F (-5° to 55° C)
<b>Approvals</b>	FCC, CE Mark, C-Tick, ICES-003, EN 55022, EN55024, EN55032, (NRTL will be available by the end of March)	

### Technical Specifications

<b>Mouse</b>		
<b>Physical characteristics</b>	Buttons	3 buttons + a scroll wheel
	Dimensions (L x W x H)	4.7×2.5×1.5 in (118.9×64.5×37.3 mm)
	Weight	0.2 lbs (100 g)
<b>Electrical</b>	ESD	+/- 4KV
	Operating voltage	+ 4.75 to 5.25VDC
	Power consumption	50-mA maximum
	System interface	USB Type A plug connector
	EMI - RFI	Conforms to FCC rules for a Class B computing device
	Microsoft® PC 99 - 2001	Functionally compliant
	Switch actuation	100±50g nominal peak force with tactile feedback
	Switch life	3 million
	Switch type	Mechanical switch
	Cable length	6 ft (1.8 m)
	Microsoft PC 99 - 2001	Mechanically compliant
	<b>Environmental</b>	Acoustics
Operating temperature		32° to 104° F (0° to 40° C)
Non-operating temperature		-40° to 140° F (-40° to 60° C)
Non-operating vibration		Frequency : 55 HZ, amplitude: 0.10Grm, 30 min.
Drop (in box)		Height : 76.2 cm, b. ground : 30mm iron plate, c. test one corner, 3 edges, 6 surfaces(one time for each)
<b>Approvals</b>	FCC, CE Mark, C-Tick, ICES-003, EN 55022, EN55024, EN55032, (NRTL will be available by the end of March)	
<b>Country of Origin</b> (keyboard and mouse)	China	
<b>Kit contents</b> (keyboard and mouse)	Keyboard, Keyboard Drape, Mouse, Installation Guide	

© Copyright 2018 HP Development Company, L.P. All rights reserved.

The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

### *Technical Specifications*

<b>Date of change:</b>	<b>Version History:</b>	<b>Description of change:</b>
June 16, 2017	From V1 to V2	First version uploaded in Concentra
March 7, 2018	From V1 to V2	ESD +/- 4KV added