

Overview

HP ElitePOS Serial USB Thermal Printer



Model

HP ElitePOS Serial USB Thermal (Black)

1RL96AA

HP ElitePOS Serial USB Thermal (White)

3GS19AA

Introduction

Redefine your perception of retail printing with the HP ElitePOS Serial USB Thermal Printer, an eye-catching, compact, cubist printer designed to dazzle alongside your HP ElitePOS at the point of sale.

Key Features and Benefits

- Print quickly with 114 mm per second print speed and 8 MB of integrated memory. Add your logo, special offers or coupons to receipts with 203 DPI and fonts that include Unicode, Arabic, and Asian.
- Connect to your retail system with an optional USB, PUSB or Serial cable kit (sold separately), and drive up to two optional cash drawers through connections on the printer.
- Place the ultra-compact printer where you need it with the assurance that the internal steel frame can withstand the everyday wear and tear of retail environments.

Overview

Compatibility

The HP ElitePOS Serial USB Printer is compatible with the HP ElitePOS G1 Retail Point of Sale Systems.

NOTE: Not all Point of Sale system models are available in all regions. Not all HP Cash Drawer models are available in all regions. This printer does not comply with fiscalization requirements that may be required in certain countries.

Service and Support

Three (3) year limited warranty with advance exchange when purchased from HP. Additional HP Care Pack Services options are available to extend warranty coverage.

Technical Specifications

General

Supported Character Sets Resident Code Pages:

437 (US)
720(Arabic)
737 (Greek)
775(Lithuanian)
850(Multilingual)
852 (Slavic)
857(Turkish)
858 (with Eurosymbol)
860(Portuguese)
862(Hebrew)
863 (French Canadian)
864(Arabic)
865(Nordic)
866(Cyrillic)
874(Thai)
932(Kanji)
936(Simplified Chinese)
949(Korean - Hangul)
950(Traditional Chinese)
KZ_1048 (Kazakh)
1250(Latin)
1251(Cyrillic)
1252 (Windows Latin I)
1254
(Turkish)
1255
(Hebrew)
1256(Arabic)
1257(Baltic)
Katakana
28591 (ISO8859-1, Latin 1)
28592 (ISO8859-2, Latin 2)
28594 (ISO8859-4, Latin 4)
28596(ISO8859-6, Latin/Arabic)
28599(ISO8859-5, Latin 5/Turkish)
28605 (ISO8859-15, Latin 9)
Unicode UTF-8 encoding for listed code pages

Bar Codes

1D: UPC-A, UPC-E, EAN8, EAN13, Code 39, Code 93, Interleaved 2 of 5
Codabar, Code 128, Code 128, EAN 128, GS1 Databar
2D: Datamatrix, QR code, PDF 417

Print Method

Direct Thermal

Printing Speed

114 mm/sec (33.75 LPS)

Resolution

203 DPI

Flash Memory

8 MB

RAM

8 MB

Knife

Full and Partial cuts supported

Technical Specifications

| | | |
|------------------------------|---|---|
| | Receipt-Columns | 44/56 |
| | Paper Type | Direct Thermal Monochrome POS Grade(s) |
| | Paper Roll Size (W x D) | 3.1 in. X 3.26 in. (80 mm X 83 mm) |
| | Paper Thickness Range | 2.3 – 3.2 mil |
| | Cash Drawers | 1 connector can drive 2 cash drawers with separately purchased splitter cable (default configuration is connection to 1 cash drawer) |
| Mechanical | Dimensions (WxDxH) | 4.4 in. X 5.2 in. X 4.06 in. (111.8 mm X 131.6 mm X 103 mm) |
| | Weight | 1.75lbs. (.793 kg) (printer only) |
| | Color | Ebony Black or Ceramic White |
| Interface/Connection | Interface | RS232 (9-Pin Female to 9-Pin Female NULL modem cable) or standard USB 2.0 cable. 24V Cash Drawers support with RJ 12 interface |
| Power | External Power Supply | 48 w |
| | Operating Voltage | 24 V |
| | Full Load Current | 2 A w/active power management system |
| | Idle Current | 25mA |
| | Idle Power | 0.6 W |
| Temperature Range | Operating | 41°F to 95°F (5°C to 35°C) at 5% to 90% humidity 95°F to 122°F (35°C to 50°C) at 5% to 40% humidity |
| | Non-operating | Transit range: -40°F to 140°F (-40°C to 60°C) 5% to 95% humidity Storage range: 14°F to 122°F (35°C to 50°C) at 5% to 90% humidity |
| Drivers | Windows, OPOS, JPOS | |
| Operating Systems | Windows | <ul style="list-style-type: none"> • Windows 10 IoT Enterprise for Retail (64-bit) • Windows 10 Pro (64-bit) |
| | Linux | <ul style="list-style-type: none"> • Red Hat/CentOS 6 and 7 (32-bit and 64 bit) • Suse Linux® Enterprise POS 11 and 12 (32-bit and 64-bit) • Ubuntu 14.04 LTS (32-bit and 64-bit) |
| Reliability | MCBF Print Mechanism: 29-million lines MCBF Knife Cuts: 1-million Print Head Life: 100 km | |
| Agency Certifications | Flammability: | UL 94V-0 |
| | Safety: | UL 60950-1 2nd edition 2014-10-14; UL 62382-1 CAN/CSA C22.2 No. 60950-1-07, 2nd Edition, 2014-10 EN 60950-1:2006 + A1:2010+ A2:2013 IEC/EN 62382-1 2ND Edition CB Report: IEC 60950-1:2005 + A1:2009 +A2:2013 GB4943.1-2011-China IS 13252-1 (2010)/A1:2013/A2:2015 |

Technical Specifications

Radiated Emissions: FCC 47CFR, Part 15, Class B

ICES-003: 2012, Issue 6, Class B

EN 55032:2015 Class B

CISPR22 Class B

VCCI: V-3/2015.04 Class B

AS/NZS 3548

Immunity: EN55024: 2010

EN61000-4-2 Level 4 (8kV direct, 15kV air discharge)

EN61000-4-3: Level 3 (10V/m)

EN61000-4-6 Level 3 (10V rms)

EN61000-4-4: Level 3 (2kV mains, 1kV data lines)

RoHS, WEEE

Option kit contents

HP ElitePOS Serial USB Thermal Printer, Starter paper roll

NOTE: This printer does not comply with fiscalization requirements that may be required in certain countries.

Cable kits sold separately:

1RM02AA – HP ElitePOS USB + Pwr Adapter

1RM03AA – HP ElitePOS Serial + Pwr Adapter

BM477AA – HP PUSB Y Cable

1RM05AA – HP ElitePOS PUSB Pw only

NOTE: For cable routing configuration information refer to HP ElitePOS system quick specs.

| Date of change: | Version History: | | Description of change: |
|------------------|------------------|-------|---|
| October 19, 2017 | From v1 to v2 | Added | Cable kits and note to refer to system quick specs for cable routing note |
| January 14, 2018 | From v2 to v3 | Added | New part number and model colors |

© Copyright 2018-2017 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Linux® is the registered trademark of Linus Torvalds in the U.S. and other countries.