



Product Service

# CERTIFICATE

No. Z1A 17 06 93407 067

**Holder of Certificate:** **HP Inc.**  
 1501 Page Mill Road  
 Palo Alto CA 94304  
 USA

**Certification Mark:**



**Product:** **Computer**  
**( All-in-One PC )**

**Tested according to:** EN 60950-1:2006/A2:2013  
 EK1-ITB 2000:2017  
 AfPS GS 2014:01 PAK 3.1


The product meets the safety and health requirements of the German Product Safety Act section 20 to 22 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. See also notes overleaf.

**Test report no.:** 612101740501

**Valid until:** 2020-12-20

**Date,** 2017-06-07

*Watson Yang*  
 ( Watson Yang )





Product Service

**CERTIFICATE****No. Z1A 17 06 93407 067****Model(s):** TPC-T009-21

**Parameters:**

Rated input voltage:	100-240 Vac
Rated frequency:	50-60 Hz
Rated input current:	2 A
Protection class:	I
Max. ambient temperature:	45 °C
Degree of protection against ingress of liquids:	Ordinary
Declared Sound Power level:	4.5 B(A)

Remark: The equipment is evaluated for operating in altitude up to 5,000 m above the sea level.

**Factory(ies):** 43857



The following LCD's panel description of the models are as below:

1. LG Display Type: LM215WF3
2. AUO Type: M215HAN01.2
3. BOE Type: MV215FHM-N60

Suitable for Max. illuminance:  $L_{REF,EXT} = 200 \text{ cd/m}^2$  and  $L_{REF,SML} = 2000 \text{ cd/m}^2$

Suitable for Max. illuminance: 1000 lx

Pixel fault classification: I

Design viewing distance: 500 mm

Design viewing direction: (0°, 90°)

Viewing direction range:  $\Phi$  range is 0° to 360°

$\theta$  range is 57.3°

Content and perception: Artificial information

Date, 2017-06-07

Page 3 of 3

Wath yef