



Product Service

# CERTIFICATE

No. Z1A 17 06 93407 068

**Holder of Certificate:** **HP Inc.**  
1501 Page Mill Road  
Palo Alto CA 94304  
USA

**Certification Mark:**

**Product:** **Computer**  
**( All-in-One PC )**

**Tested according to:** EN 60950-1:2006/A2:2013  
EK1-ITB 2000:2017  
AfPS GS 2014:01 PAK 3.1

The product meets the safety and health requirements of the German Product Safety Act section 20 to 22 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. See also notes overleaf.

**Test report no.:** 612101740601

**Valid until:** 2020-12-20

**Date,** 2017-06-07

*Watson Yang*  
( Watson Yang )



Page 1 of 3



Product Service

**CERTIFICATE****No. Z1A 17 06 93407 068****Model(s): TPC-T010-20**

**Parameters:**

Rated input voltage:	19.5 Vdc
Rated input current:	4.62 A
Protection class:	III
Max. ambient temperature:	35 °C
Degree of protection against ingress of liquids:	Ordinary
Declared Sound Power level:	4.6 B(A)

Remark: The equipment is evaluated for operating in altitude up to 5,000 m above the sea level.

**Factory(ies): 43857**



The following LCD's panel description of the models are as below:

1. Innolux Type: M200FGE
2. Samsung Type: LTM200KT12

Suitable for Max. illuminance:

1.  $L_{REF, EXT} = 200 \text{ cd/m}^2$  and  $L_{REF, SML} = 2000 \text{ cd/m}^2$  (without touch glass function)
2.  $L_{REF, EXT} = 200 \text{ cd/m}^2$  or  $L_{REF, SML} = 2000 \text{ cd/m}^2$  (with touch glass function)

Suitable for Max. illuminance: 750 lx

Pixel fault classification: I

Design viewing distance: 500 mm

Design viewing direction: (0°, 90°)

Viewing direction range:  $\Phi$  range is 0° to 360°

$\theta$  range is 53.9°

Content and perception: Artificial information

Wath yf