

Overview

HP USB Hardened Mouse

Models

HP USB Hardened Mouse

P1N77AA

Introduction

Boost your productivity even in the grittiest settings with the HP USB Hardened Mouse, which is designed to help prevent sulfur corrosion and sealed to help prevent dust ingress.

Key Benefits

- Simply plug into any available USB port on your PC.
 - Enjoy natural left or right hand operation and smooth navigation and scrolling.
 - Get a one-year limited warranty.
-

Compatibility

The HP USB Hardened Mouse is compatible with HP ProOne 400 G2 AiO Touch, HP ProOne 400 G2 AiO Non-Touch, P ProDesk 600 G2 MT, HP ProDesk 600 G2 SFF, HP ProDesk 600 G2 Desktop Min, HP ProOne 600 G2 AiO 21.5-inch Touch, HP ProOne 600 G2 AiO 21.5-inch Non-Touch, HP EliteDesk 800 G2 TWR, HP EliteDesk 800 G2 SFF, HP EliteDesk 800 G2 35W Desktop Mini, HP EliteDesk 800 G2 65W Desktop Mini, HP Collaboration PC G2, HP EliteOne 800 G2 AIO 23" Touch, HP EliteOne 800 G2 AIO 23" Non-Touch; HP Z2 Mini Workstation, HP Z240 Tower and SFF Workstation, HP Z440 Workstation, HP Z640 Workstation, HP Z840 Workstation, HP Z4 G4 Workstation, HP Z6 G4 Workstation, HP Z8 G4 Workstation

Service and Support

Your Option Limited Warranty is a one (1) year (HP Option Limited Warranty Period) parts replacement warranty on any HP-branded or Compaq-branded options (HP Options). If your HP Option is installed in an HP Hardware Product, HP may provide warranty service either for the HP Option Limited Warranty Period or the remaining Limited Warranty Period of the HP Hardware Product in which the HP Option is being installed, whichever period is the longer but not to exceed three (3) years from the date you purchased the HP Option.

Technical Specifications

Mouse Type	Wired optical mouse		
Interface	USB 2.0		
Dimensions (H x L x W)	114.97 x 62.92 x 37.3 mm (+/-0.3 mm) (11.49 x 6.29 x 1.46 in)		
Weight	92 g (+/-10 g) (3.2 oz)		
Cable length	1.8 M		
Tracking	X-Y Positioning	X-Y Wheel Resolution	1000 DPI
		Tracking Speed	Up to 30 in/sec in either X or Y direction
	Z Axis Wheel	Z Wheel Revolution	24 counts per revolution
		Tracking Speed	0 ~ 120 rpm
Environmental	Operating temperature	0° - 40°C	
	Non-operating temperature	-40° - 65°C	
	Operating humidity	90%	
	Agency Approvals	CE FCC RCM VCCI EMC EAC BSMI UL ICES-003 Class B KCC TUV/GS	
Electrical	Input Voltage & Current	4.4 ~ 5.25 VDC / 100 mA	
	Power Consumption	Under nominal 5 VDC power supplied, max current consumption is 100mA with tracking speed up to 30 in/sec	
Color	Black		
System requirements	Windows 10, Windows 8.1 32/64bit, Windows 7 32/64bit		

© Copyright 2017 HP Development Company, L.P. All rights reserved.

The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries.

Change Log

Date of change:	Version History:	Description of change:
September 18	V1 to V2	New version