


### Overview

### HP EliteBook 840 G5 Notebook PC




#### Left

- |  |                                    |
|--|------------------------------------|
| 1. HD Camera (Select models only)      | 9. Ethernet port                   |
| 2. IR Camera (Select models only)      | 10. HDMI port (Cable not included) |
| 3. Webcam LED (Select models only)     | 11. USB 3.1 Gen 1 port             |
| 4. Internal microphones                | 12. Audio combo jack               |
| 5. IR Camera LEDs (Select models only) | 13. SIM card slot <sup>1</sup>     |
| 6. Power connector                     | 14. Fingerprint reader             |
| 7. USB Type-C™ with Thunderbolt™       | 15. Clickpad                       |
| 8. Docking connector                   | 16. Pointstick                     |

1. All units have a SIM card slot and icon but units that do not support WWAN are shipped with a non-removable SIM slot plug

### Overview



1. Indicator LEDs:  
Power light  
Wireless light  
Storage usage light
2. Smartcard Reader (Select models)
3. USB 3.1 Gen 1 charging port

#### Right

4. Security Lock slot (Lock sold separately)
5. Power button

### Overview

#### AT A GLANCE

- Eye-catching ultraslim design, premium precision-crafted machined aluminum (CNC), seamless formed aluminum chassis for clean, crisp, premium look and feel
- Choice of 8th Generation Intel® Core™ i5, i7 Processors and 7th generation Intel® Core™ i5 Processors
- Designed to support all HP docking options including HP's traditional Ultraslim mechanical dock and all-new Thunderbolt™ dock<sup>2</sup> (Available in May 2018)
- Featuring HP Collaboration Keyboard with Clickpad to manage most commonly used conferencing functions with a single keystroke
- Innovative world-facing third mic improves inbound ambient noise cancellation
- Optional ultrabright displays with ambient light sensor
- Enterprise grade security with HP SureStart Gen4, HP Privacy Camera<sup>3</sup>, HP Sure View<sup>2</sup>, HP Sure Run, HP Sure Recover, SmartCard Reader<sup>2</sup> and Fingerprint reader<sup>2</sup>
- Choice of displays:
  - 35.6cm (14.0") diagonal FHD IPS anti-glare LED-backlit non-touch, 220 cd/m<sup>2</sup>, 67% sRGB
  - 35.6cm (14.0") diagonal FHD IPS anti-glare LED-backlit non-touch, 400 cd/m<sup>2</sup>, 100% sRGB
  - 35.6cm (14.0") diagonal UHD IPS anti-glare LED-backlit non-touch, 400 cd/m<sup>2</sup>, 100% sRGB
  - 35.6cm (14.0") diagonal FHD IPS anti-glare LED-backlit non-touch, 700 cd/m<sup>2</sup>, 100% sRGB with HP Sure View
  - 35.6cm (14.0") diagonal FHD IPS LED-backlit Corning® Gorilla® Glass 3 touch, 220 cd/m<sup>2</sup>, 67% sRGB
  - 35.6cm (14.0") diagonal FHD IPS LED-backlit Corning® Gorilla® Glass 3 touch, 700 cd/m<sup>2</sup>, 100% sRGB with HP Sure View
  - 35.6cm (14.0") diagonal FHD IPS LED-backlit Anti-glare on-cell touch, 700 cd/m<sup>2</sup>, 100% sRGB with HP Sure View
- Optional AMD Radeon™ RX540 discrete graphics with 2 GB GDDR5 video memory
- Flexible wireless connectivity options
- Preinstalled with Windows 10 versions or FreeDOS 2.0
- Choice of solid state drives up to 1 TB and DDR4 memory up to 32 GB
- Supports fast charging (50% in 30 minutes) with no impact on battery recharge cycles<sup>4</sup>
- Optional HD camera or Infra Red camera with multi-array microphone
- Battery life:
  - UMA graphics: Up to 14 hours ( Intel® 7th generation CPU and 3-cell 50 WHr battery)
  - Discrete graphics: Up to 13 hours and 45 mins ( Intel® 7th generation CPU and 3-cell 50 WHr battery)
- Passed MIL-SPEC 810G testing<sup>5</sup>

2. Sold separately or as an optional feature.

3. Only available with non-touch configurations.

4. Recharges your battery up to 50% within 30 minutes when the system is off or in standby mode. Power adapter with a minimum capacity of 65 watts is required. After charging has reached 50% capacity, charging will return to normal. Charging time may vary +/-10% due to System tolerance.

5. MIL STD 810G testing is not intended to demonstrate fitness for Department of Defense contracts requirements or for military use. Test results are not a guarantee of future performance under these test conditions. Damage under the MIL STD test conditions or any accidental damage requires an optional HP Accidental Damage Protection Care Pack.

**NOTE: See important legal disclosures for all listed specs in their respective features sections.**

### Features

#### PRODUCT NAME

HP EliteBook 840 G5 Notebook PC

#### OPERATING SYSTEM

<b>Preinstalled</b>	Windows 10 Pro 64 <sup>1</sup> Windows 10 Home 64 <sup>1</sup> FreeDOS 2.0
---------------------	--

1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com/>

#### PROCESSORS

Intel® Core™ i5-7200U with Intel® HD Graphics 620 (2.5 GHz base frequency, up to 3.1 GHz with Intel® Turbo Boost Technology, 3 MB cache, 2 cores)<sup>2,3,4</sup>

Intel® Core™ i5-7300U vPro™ processor with Intel® HD Graphics 620 (2.6 GHz base frequency, up to 3.5 GHz with Intel® Turbo Boost Technology, 3 MB cache, 2 cores)<sup>2,3,4</sup>

Intel® Core™ i5-8250U with Intel® UHD Graphics 620 (1.6 GHz base frequency, up to 3.4 GHz with Intel® Turbo Boost Technology, 6 MB cache, 4 cores)<sup>2,3,4</sup>

Intel® Core™ i5-8350U vPro™ processor with Intel® UHD Graphics 620 (1.7 GHz base frequency, up to 3.6 GHz with Intel® Turbo Boost Technology, 6 MB cache, 4 cores)<sup>2,3,4</sup>

Intel® Core™ i7-7600U vPro™ processor with Intel® HD Graphics 620 (2.8 GHz, up to 3.9 GHz with Intel Turbo Boost Technology, 4 MB cache, 2 cores)<sup>2,3,4</sup>

Intel® Core™ i7-7500U with Intel® HD Graphics 620 (2.7 GHz, up to 3.5 GHz with Intel Turbo Boost Technology, 4 MB cache, 2 cores)<sup>2,3,4</sup>

Intel® Core™ i7-8550U with Intel® UHD graphics 620 (1.8 GHz base frequency, up to 4 GHz with Intel® Turbo Boost Technology, 8 MB cache, 4 cores)<sup>2,3,4</sup>

Intel® Core™ i7-8650U vPro™ processor with Intel® UHD graphics 620 (1.9 GHz base frequency, up to 4.2 GHz with Intel® Turbo Boost Technology, 8 MB cache, 4 cores)<sup>2,3,4</sup>

##### Processor Family

7th Generation Intel® Core™ i5 processor (i5-7300U, i5-7200U models)

7th Generation Intel® Core™ i7 processor (i7-7600U, i7-7500U models)

8th Generation Intel® Core™ i5 processor (i5-8350U, i5-8250U models)

8th Generation Intel® Core™ i7 processor (i7-8650U, i7-8550U models)

2. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance.

3. Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

4. In accordance with Microsoft's support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel® and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on <http://www.support.hp.com>.

### Features

#### **CHIPSET**

Integrated with processor

---

### Features

#### GRAPHICS

##### Integrated

Intel® HD Graphics 620<sup>5</sup>  
Intel® UHD Graphics 620<sup>5</sup>

##### Discrete

AMD Radeon™ RX 540 (2 GB GDDR5 video memory)<sup>6,7</sup>  
Support HD decode, DX12, HDMI 1.4b<sup>5,8</sup>

5. HD content required to view HD images.

6. Sold separately or as an optional feature.

7. AMD Dynamic Switchable Graphics technology requires an Intel processor, plus an AMD Radeon™ discrete graphics configuration and is not available on FreeDOS and Linux OS. With AMD Dynamic Switchable Graphics technology, full enablement of all discrete graphics video and display features may not be supported on all systems (e.g. OpenGL applications will run on the integrated GPU or the APU as the case may be).

8. HDMI cable sold separately.

#### DISPLAY

##### Non-Touch

35.6 cm (14") diagonal FHD IPS anti-glare LED-backlit, 220 cd/m<sup>2</sup>, 67% sRGB (1920 x 1080)<sup>9,10,11</sup>

35.6 cm (14") diagonal FHD IPS anti-glare LED-backlit, 220 cd/m<sup>2</sup>, 67% sRGB with HD camera (1920 x 1080)<sup>9,10,11</sup>

35.6 cm (14") diagonal FHD IPS anti-glare LED-backlit, 220 cd/m<sup>2</sup>, 67% sRGB with HD IR webcam (1920 x 1080)<sup>9,10,11</sup>

35.6 cm (14") diagonal FHD IPS anti-glare LED-backlit, 220 cd/m<sup>2</sup>, 67% sRGB for WWAN (1920 x 1080)<sup>9,10,11</sup>

35.6 cm (14") diagonal FHD IPS anti-glare LED-backlit, 220 cd/m<sup>2</sup>, 67% sRGB with HD camera for WWAN (1920 x 1080)<sup>9,10,11</sup>

35.6 cm (14") diagonal FHD IPS anti-glare LED-backlit, 220 cd/m<sup>2</sup>, 67% sRGB with HD IR webcam for WWAN (1920 x 1080)<sup>9,10,11</sup>

35.6 cm (14") diagonal FHD IPS anti-glare LED-backlit, 400 cd/m<sup>2</sup>, 100% sRGB with Ambient Light Sensor and HD IR webcam (1920 x 1080)<sup>9,10,11</sup>

35.6 cm (14") diagonal FHD IPS anti-glare LED-backlit, 400 cd/m<sup>2</sup>, 100% sRGB with Ambient Light Sensor and HD IR webcam for WWAN (1920 x 1080)<sup>9,10,11</sup>

35.6 cm (14") diagonal 4K IPS anti-glare LED-backlit, 400 cd/m<sup>2</sup>, 100% sRGB with Ambient Light Sensor and HD IR webcam for WWAN (3840 x 2160)<sup>9,10,11</sup>

HP Sure View Integrated Privacy Screen 35.6 cm (14") diagonal FHD IPS anti-glare LED-backlit, 700 cd/m<sup>2</sup>, 100% sRGB with HD IR webcam for WWAN (1920 x 1080)<sup>9,10,11,12</sup>

##### Touch

35.6 cm (14") diagonal FHD IPS LED-backlit touch screen with Corning® Gorilla® Glass 3, 220 cd/m<sup>2</sup>, 67% sRGB with HD IR webcam (1920 x 1080)<sup>9,10,11</sup>

35.6 cm (14") diagonal FHD IPS LED-backlit touch screen with Corning® Gorilla® Glass 3, 220 cd/m<sup>2</sup>, 67% sRGB with HD IR webcam for WWAN (1920 x 1080)<sup>9,10,11</sup>

HP Sure View Integrated Privacy Screen 35.6 cm (14") diagonal FHD IPS LED-backlit touch screen with Corning® Gorilla® Glass 3, 700 cd/m<sup>2</sup>, 100% sRGB with HD IR webcam for WWAN (1920 x 1080)<sup>9,10,11,12</sup>

HP Sure View Integrated Privacy Screen 35.6 cm (14") diagonal FHD IPS LED-backlit Anti-glare on-cell touch, 700 cd/m<sup>2</sup>, 100% sRGB with HD IR webcam for WWAN (1920 x 1080)<sup>9,10,11,12</sup>

##### HDMI 1.4b

Supports resolution up to 4k @ 24 Hz

### Features

#### Displays support

Docking station model	Total number of supported displays (incl. the notebook display)	Max.resolutions supported	Dock Connectors	Technical limitations
HP UltraSlim Docking Station	3	Dual 2.5K @ 60Hz	2xDP, 1xVGA	Dual 2.5k only with both displays into DP
HP Thunderbolt Dock G2 (Available 2Q 2018)	3	Dual 4K @ 60Hz	2xDP, 1xVGA, 1xTB, 1xUSB-C alt-mode	Dual 4k only with one display in to DP and + TB port or USB-C alt mode + TB port
HP Elite USB-C Dock G4 (Available 2Q 2018)	3	Dual 2K @ 60Hz Single 4K @ 60Hz (3840 x 1440)	1xHDMI, 2xDP	
HP USB-C Universal Dock	3	Dual 4K @ 60Hz Single 5K @ 60Hz	2xDP	
HP USB-C Travel Dock	2	Single 2K @ 60Hz	1xHDMI, 1xVGA	Single external display Only HDMI or VGA at the time
HP USB-C Mini Dock	2	Single 4K @ 30Hz	1xHDMI, 1xVGA	Single external display Only HDMI or VGA at the time

9. HD content required to view HD images.

10. Sold separately or as an optional feature.

11. Resolutions are dependent upon monitor capability, and resolution and color depth settings.

12. HP Sure View is optional and must be configured at purchase.

### STORAGE AND DRIVES

#### Primary M.2 Storage

128 GB SATA-3 SS TLC<sup>13</sup>

256 GB PCIe NVMe Value SS TLC<sup>13</sup>

256 GB PCIe Gen3x4 NVMe SS TLC<sup>13</sup>

256 GB SATA-3 SS TLC Opal 2<sup>13</sup>

360 GB PCIe Gen3x4 NVMe SS TLC (Intel®)<sup>13</sup>

512 GB PCIe Gen3x4 NVMe SS TLC<sup>13</sup>

512 GB PCIe Gen3x4 NVMe SS TLC Opal 2<sup>13</sup>

512 GB SATA-3 SS TLC FIPS-140-2<sup>13</sup>

1 TB PCIe Gen3x4 NVMe SS TLC<sup>13</sup>

13. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10) is reserved for system recovery software.

### Features

#### MEMORY

##### Maximum Memory

32 GB DDR4-2400 SDRAM<sup>14</sup>

##### Memory

32 GB DDR4-2400 SDRAM (2 X 16 GB)<sup>14</sup>

16 GB DDR4-2400 SDRAM (1 X 16 GB)<sup>14</sup>

16 GB DDR4-2400 SDRAM (2 X 8 GB)<sup>14</sup>

8 GB DDR4-2400 SDRAM (1 x 8 GB)<sup>14</sup>

8 GB DDR4-2400 SDRAM (2 x 4 GB)<sup>14</sup>

4 GB DDR4-2400 SDRAM (1 x 4 GB)<sup>14</sup>

##### Memory Slots

2 SODIMM

Both slots are upgradeable

System runs at 2133 for Intel® 7th generation processors

System runs at 2400 for Intel® 8th generation processors

Supports Dual Channel Memory.

14. Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.

#### NETWORKING/COMMUNICATIONS

##### WLAN<sup>15</sup>

Intel® Dual Band Wireless-AC 8265 802.11a/b/g/n/ac (2x2) Wi-Fi® and Bluetooth® 4.2 Combo, vPro™<sup>16</sup>

Intel® Dual Band Wireless-AC 8265 802.11a/b/g/n/ac (2x2) Wi-Fi® and Bluetooth® 4.2 Combo, non-vPro™<sup>16</sup>

Realtek RTL8822BE 802.11ac (2x2) Wi-Fi® and Bluetooth® 4.2 Combo, non-vPro™<sup>16</sup>

##### WWAN<sup>15</sup>

HP lt4132 LTE/HSPA+ 4G Mobile Broadband<sup>17</sup>

Intel® XMM™ 7360 LTE-Advanced<sup>17</sup>

##### NFC<sup>15</sup>

NXP NPC300 Near Field Communication Module

##### Miracast

Native Miracast Support<sup>18</sup>

##### Ethernet

Intel® I219-LM 10/100/1000 GbE, vPro™<sup>19</sup>

Intel® I219-V 10/100/1000 GbE, non-vPro™<sup>19</sup>

15. Sold separately or as an optional feature.

16. Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited. The specifications for the 802.11ac WLAN are draft specifications and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the notebook to communicate with other 802.11ac WLAN devices.

17. WWAN module requires separately purchased service contract. Check with service provider for coverage and availability in your area. Connection speeds will vary due to location, environment, network conditions, and other factors. 4G LTE not available on all products, in all regions.

18. Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming



### Features

19. The term "10/100/1000" or "Gigabit" Ethernet indicates compatibility with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/s. For high-speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

---

### AUDIO/MULTIMEDIA

#### Audio

Audio by Bang & Olufsen  
Integrated 3 Multi Array Microphone  
2 Integrated Stereo Speakers (74Db)

#### Webcam

HD camera<sup>20,21</sup>  
HD IR camera<sup>20,21</sup>

20. HD content required to view HD images.  
21. Sold separately or as an optional feature.

---

### KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

#### Keyboard

HP Premium Collaboration Keyboard, spill resistant with drain  
Backlit keyboard available as an option

#### Pointing Device

Clickpad with multi-touch gestures enabled, taps enabled as default  
Microsoft Precision Touchpad Default Gestures Support

#### Function Keys

F1 - Display Switching  
F2 - Blank or Privacy  
F3 - Brightness Down  
F4 - Brightness Up  
F5 - Audio Mute  
F6 - Volume Down  
F7 - Volume Up  
F8 - Mic Mute  
F9 - Blank or Backlit Toggle  
F10 - numlk  
F11 - Wireless  
F12 - Calendar  
Share/Present  
Call Answer  
Call End

#### Hidden Functions

Fn+R = Break  
Fn+S = Sys Rq  
Fn+C = Scroll Lock  
Fn+E = Insert  
Fn+W = Pause

---

### Features

#### SOFTWARE AND SECURITY

##### Preinstalled Software

###### BIOS

HP BIOSphere Gen4<sup>23</sup>  
HP Drive Lock & Automatic Drive Lock<sup>41</sup>  
BIOS Update via Network  
Master Boot Record Security  
Power On Authentication  
Secure Erase<sup>24</sup>  
Absolute Persistence Module<sup>25</sup>  
Pre-boot Authentication  
HP Wireless Wakeup

###### Software

HP Native Miracast Support<sup>22</sup>  
HP LAN-Wireless Protection  
HP Connection Optimizer  
HP ePrint + JetAdvantage<sup>26</sup>  
HP Hotkey Support - CMIT  
HP Recovery Manager  
HP Jumpstart  
HP Support Assistant<sup>27</sup>  
HP Noise Cancellation Software  
Buy Office

###### Manageability Features

HP Driver Packs<sup>23</sup>  
HP System Software Manager (SSM)  
HP BIOS Config Utility (BCU)  
HP Client Catalog  
HP Manageability Integration Kit Gen2<sup>24</sup>  
Ivanti Management Suite<sup>30</sup>

###### Client Security Software

HP Client Security Suite Gen4<sup>31</sup> including:  
HP Security Manager<sup>32</sup> (including Credential Manager, HP Password Manager, HP Spare Key)  
Power On Authentication  
HP Fingerprint Sensor<sup>35</sup>  
HP Device Access Manager  
HP Power On Authentication  
Microsoft Defender<sup>33</sup>

### Features

#### Security Management

HP BIOSphere Gen4<sup>23</sup>

HP Drive Lock & Automatic Drive Lock<sup>40</sup>

BIOS Update via Network

Secure Erase<sup>24</sup>

Pre-boot Authentication

TPM 2.0 Embedded Security Chip shipped with Windows 10 (Common Criteria EAL4+ Certified)

SATA 0,1 port disablement (viaBIOS)

RAID configurations<sup>36</sup>

Serial, USB enable/disable (viaBIOS)

Power-on password (viaBIOS)

Setup password (viaBIOS)

Support for chassis padlocks and cable lock devices

HP Sure Click<sup>37</sup>

HP Sure Start Gen4<sup>34</sup>

HP Sure Run<sup>38</sup>

HP Sure Recover<sup>39</sup>

#### TPM

Model: Infineon SLB9670

Version: 7.62.3126.0

Revision: TPM 2.0

FIPS 140-2 Compliant: Yes (select models only)

#### Smartcard Reader

Model number: Alcor AU9560

FIPS 201 Compliant: Yes

#### IPv6 Certification:

Yes

**MD5 Hash:** Please follow the instructions below to access MD5 Hash.

Log-on to <http://hp.com/support>, enter your product name, select software and drivers, select OS, select driver. After selecting the driver, click on "Associated files" and then click on "Download". When opening the file, under "Purpose" you should see the appropriate "SOFTPAQ MD5:" Field

**Is the BIOS on this notebook ISO/IEC 19678:2015 (formerly NIST 800-147) compliant?:**

Yes

UEFI version: 2.5

22. Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming

23. HP BIOSphere Gen4 features may vary depending on the PC platform and configurations requires 8th Gen Intel® processors.

24. Secure Erase for the methods outlined in the National Institute of Standards and Technology Special Publication 800-88. Supported on Elite platforms with BIOS version F.03 or higher.

25. Absolute agent is shipped turned off, and will be activated when customers activate a purchased subscription. Subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability

### Features

- outside the U.S. The Absolute Recovery Guarantee is a limited warranty. Certain conditions apply. For full details visit: <http://www.absolute.com/company/legal/agreements/computrace-agreement>. Data Delete is an optional service provided by Absolute Software. If utilized, the Recovery Guarantee is null and void. In order to use the Data Delete service, customers must first sign a Pre-Authorization Agreement and either obtain a PIN or purchase one or more RSA SecurID tokens from Absolute Software.
26. HP ePrint Driver requires an Internet connection to HP web-enabled printer and HP ePrint account registration (for a list of eligible printers, supported documents and image types and other HP ePrint details, see <http://www.hp.com/go/eprintcenter>). Print times and connection speeds may vary.
  27. HP Support Assistant requires Windows and Internet access.
  28. HP Driver Packs not preinstalled, however available for download at <http://www.hp.com/go/clientmanagement>.
  29. HP Manageability Integration Kit can be downloaded from <http://www8.hp.com/us/en/ads/clientmanagement/overview.html>
  30. Ivanti Management Suite subscription required.
  31. HP Client Security Suite Gen4 requires Windows and Intel® or AMD 8th generation processors.
  32. HP Password Manager requires Internet Explorer or Chrome or FireFox. Some websites and applications may not be supported. User may need to enable or allow the add-on / extension in the internet browser.
  33. Microsoft Defender Opt in and internet connection required for updates.
  34. HP Sure Start Gen4 is available on HP EliteBook products equipped with Intel® 8th generation processors
  35. HP Fingerprint Sensor sold separately or as an optional feature.
  36. RAID configuration is optional and does require a second hard drive.
  37. HP Sure Click is available on most HP PCs and supports Microsoft® Internet Explorer and Chromium™. Supported attachments include Microsoft Office (Word, Excel, PowerPoint) and PDF files in read only mode, when Microsoft Office or Adobe Acrobat are installed.
  38. HP Sure Run is available on HP Elite products equipped with Intel® or AMD® 8th generation processors
  39. HP Sure Recover is available on HP Elite PCs with 8th generation Intel® or AMD processors and requires an open, wired network connection. You must back up important files, data, photos, videos, etc. before using HP Sure Recover to avoid loss of data
  40. HP Drive Lock is not supported on NVMe drives
-

### Features

#### POWER

##### Power Supply

HP Smart 45 W External AC power adapter<sup>41</sup>  
HP Smart 45 W External AC power adapter, 2-prong (Japan only)<sup>41</sup>  
HP Smart 65 W External AC power adapter<sup>41</sup>  
HP Smart 65 W EM External AC power adapter<sup>41</sup>  
45 W USB Type-C™ adapter<sup>41</sup>  
65 W USB Type-C™ adapter<sup>41</sup>

##### Primary Battery

HP Long Life 3-cell, 50 Wh Li-ion<sup>42</sup>

##### Power Cord

2-wire plug - 1.0m (Japan only)<sup>41</sup>  
3-wire plug - 1.0m<sup>42</sup>  
3-wire plug - 1.8m<sup>42</sup>  
Duckhead power cord - 1.0m<sup>41</sup>  
Duckhead power cord - 1.8m<sup>41</sup>

##### Battery Life

UMA graphics: Up to 14 hours (Intel® 7th generation CPU and 3-cell 50 WHr battery)<sup>43</sup>  
Discrete graphics: Up to 13 hours and 45 mins (Intel® 7th generation CPU and 3-cell 50 WHr battery)<sup>43</sup>

41. Availability may vary by country.

42. Battery is internal and not replaceable by customer. Serviceable by warranty.

43. Windows 10 MM14 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See <http://www.bapco.com> for additional details.

---

#### WEIGHTS & DIMENSIONS

##### Weight

Starting at 3.27 lb (non-touch); Starting at 3.56 lb (touch)<sup>44</sup>  
Starting at 1.48 kg (non-touch); Starting at 1.61 kg (touch)<sup>44</sup>

##### Dimensions (w x d x h)

###### Non-touch

12.84 x 9.22 x 0.7 in  
32.6 x 23.4 x 1.79 cm

###### Touch

12.84 x 9.22 x 0.71 in  
32.6 x 23.4 x 1.81 cm

44. Weight will vary by configuration.

### Features

#### PORTS/SLOTS

##### Ports

- 1 Thunderbolt™ (USB Type-C™ connector)
- 2 USB 3.1 Gen 1 (1 charging)
- 1 HDMI 1.4b<sup>45</sup>
- 1 RJ-45
- 1 docking connector
- 1 headphone/microphone combo
- 1 AC power
- 1 SIM card slot<sup>46</sup>
- 1 Smartcard reader<sup>46</sup>

45. HDMI cable sold separately.

46. Sold separately or as an optional feature.

---

#### SERVICE AND SUPPORT

3 year and 1 year limited warranties and 90-day software limited warranty options depending on country. Batteries have a default one year limited warranty except for Long Life batteries which will have same 1 year or 3 year limited warranty as the platform. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at <http://www.hp.com/go/cpc>.<sup>47</sup>

47. HP Care Packs are sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit <http://www.hp.com/go/cpc>. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.

---

### Technical Specifications

#### SYSTEM UNIT

<b>Stand-Alone Power Requirements</b> (AC Power)	<b>Nominal Operating Voltage</b>	19V
	<b>Average Operating Power</b>	Win 10
	<b>Integrated Graphics</b>	6.78W
	<b>Discrete Graphics</b>	18W
	<b>Max Operating Power</b>	Discrete < 65W UMA < 45W
<b>Temperature</b>	<b>Operating</b>	32° to 95° F (0° to 35° C) (not writing optical) 41° to 95° F (5° to 35° C) (writing optical)
	<b>Non-operating</b>	-4° to 140° F (-20° to 60° C)
<b>Relative Humidity</b>	<b>Operating</b>	10% to 90%, non-condensing
	<b>Non-operating</b>	5% to 95%, 101.6° F (38.7° C) maximum wet bulb temperature
<b>Shock</b>	<b>Operating</b>	40 G, 2 ms, half-sine
	<b>Non-operating</b>	200 G, 2 ms, half-sine
<b>Random Vibration</b>	<b>Operating</b>	0.75 grms
	<b>Non-operating</b>	1.50 grms
<b>Altitude</b> (unpressurized)	<b>Operating</b>	-50 to 10,000 ft (-15.24 to 3,048 m)
	<b>Non-operating</b>	-50 to 40,000 ft (-15.24 to 12,192 m)
<b>Planned Industry Standard Certifications</b>	<b>UL</b>	Yes
	<b>CSA</b>	Yes
	<b>FCC Compliance</b>	Yes
	<b>ENERGY STAR®</b>	Select models <sup>48</sup>
	<b>EPEAT®</b>	Registered Gold in United States <sup>49</sup>
	<b>ICES</b>	Yes
	<b>Australia / NZ A-Tick Compliance</b>	Yes
	<b>CCC</b>	Yes
	<b>Japan VCCI Compliance</b>	Yes
	<b>KC</b>	Yes
	<b>BSMI</b>	Yes
	<b>CE Marking Compliance</b>	Yes
	<b>BNCI or BELUS</b>	Yes
	<b>CIT</b>	Yes
	<b>GOST</b>	Yes
	<b>Saudi Arabian Compliance (ICCP)</b>	Yes
<b>SABS</b>	Yes	
	<b>UKRSERTCOMPUTER</b>	

48. Configurations of the HP Elitebook 840 G5 that are ENERGY STAR® qualified are identified as HP Elitebook 840 G5 ENERGY STAR on HP websites and on <http://www.energystar.gov>.

49. EPEAT® registered where applicable. EPEAT registration varies by country. See <http://www.epeat.net> for registration status by country. Search keyword generator on HP's 3rd party option store for solar generator accessories at <http://www.hp.com/go/options>.

### Technical Specifications

#### DISPLAYS

**Panel LCD 14 inch FHD  
(1920x1080) Anti-Glare WLED  
UWVA 67% cg 220nits eDP slim  
NB Non-Touch**

<b>Outline Dimensions (W x H)</b>	316.112 x 197.98 max.
<b>Active Area</b>	309.312 x 173.988
<b>Weight</b>	<280g max.
<b>Diagonal Size</b>	14.0"
<b>Thickness</b>	3.0mm max.
<b>Interface</b>	eDP 1.2
<b>Surface Treatment</b>	Anti-glare
<b>Touch Enabled</b>	No
<b>Contrast Ratio</b>	600:1 (typical)
<b>Refresh Rate</b>	60Hz
<b>Brightness</b>	220 nits typical (Panel Only)
<b>Pixel Resolution</b>	1920 x 1080 (FHD)
<b>Format</b>	RGB
<b>Backlight</b>	LED
<b>Color Gamut Coverage</b>	67% sRGB
<b>Color Depth</b>	6 bits + Hi FRC
<b>Viewing Angle</b>	UWVA 85/85/85/85

**NOTE:** All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.



### Technical Specifications

**Panel LCD 14 inch FHD  
(1920x1080) WLED UWVA 67%  
cg 220nits eDP slim NB Touch**

<b>Outline Dimensions (W x H)</b>	316.112 x 197.98 max.
<b>Active Area</b>	309.312 x 173.988
<b>Weight</b>	<413g max.
<b>Diagonal Size</b>	14.0"
<b>Thickness</b>	3.2mm max.
<b>Interface</b>	eDP 1.2
<b>Surface Treatment</b>	BrightView Glass
<b>Touch Enabled</b>	Yes
<b>Contrast Ratio</b>	600:1 (typical)
<b>Refresh Rate</b>	60Hz
<b>Brightness</b>	220 nits typical (Panel Only)
<b>Pixel Resolution</b>	1920 x 1080 (FHD)
<b>Format</b>	RGB
<b>Backlight</b>	LED
<b>Color Gamut Coverage</b>	67% sRGB
<b>Color Depth</b>	6 bits + Hi FRC
<b>Viewing Angle</b>	UWVA 85/85/85/85

### Technical Specifications

<b>Panel LCD 14 inch FHD (1920x1080) Anti-Glare WLED UWVA 100% cg 400nits eDP 1.3 + PSR slim NB</b>	<b>Outline Dimensions (W x H)</b>	316.11 x 197.98 max.
	<b>Active Area</b>	309.31 x 173.99
	<b>Weight</b>	<285g max.
	<b>Diagonal Size</b>	14.0"
	<b>Thickness</b>	3.0mm max.
	<b>Interface</b>	eDP 1.3 + PSR (2 lane)
	<b>Surface Treatment</b>	Anti-glare
	<b>Touch Enabled</b>	No
	<b>Contrast Ratio</b>	600:1 (typical)
	<b>Refresh Rate</b>	60Hz
	<b>Brightness</b>	400 nits typical (Panel Only)
	<b>Pixel Resolution</b>	1920 x 1080 (FHD)
	<b>Format</b>	RGB
	<b>Backlight</b>	LED
	<b>Color Gamut Coverage</b>	100% sRGB
	<b>Color Depth</b>	6 bits + Hi FRC
	<b>Viewing Angle</b>	UWVA 85/85/85/85

### Technical Specifications

<b>(3840x2160) Anti-Glare WLED UWVA 100% cg 400nits eDP 1.3 + PSR ultraslim NB</b>	<b>Outline Dimensions (W x H)</b>	315.31 x 199.54 max.
	<b>Active Area</b>	309.31 x 173.99
	<b>Weight</b>	<240 max.
	<b>Diagonal Size</b>	14.0"
	<b>Thickness</b>	2.4mm max
	<b>Interface</b>	eDP 1.3 + PSR (4 lane)
	<b>Surface Treatment</b>	Anti-glare
	<b>Touch Enabled</b>	No
	<b>Contrast Ratio</b>	1200:1 (typ) - AG
	<b>Refresh Rate</b>	60Hz
	<b>Brightness</b>	400 nits typical (Panel Only)
	<b>Pixel Resolution</b>	3840 x 2160 (UHD)
	<b>Format</b>	RGB
	<b>Backlight</b>	LED
	<b>Color Gamut Coverage</b>	100% sRGB
	<b>Color Depth</b>	8 bits
	<b>Viewing Angle</b>	UWVA 85/85/85/85

---

### Technical Specifications

**Panel LCD 14 inch FHD (1920x1080) WLED UWVA 100% cg 700nits eDP 1.3+PSR ultraslim Privacy**

<b>Outline Dimensions (W x H)</b>	315.41x 196.14 max.
<b>Active Area</b>	309.312 x 173.988
<b>Weight</b>	<225g max.
<b>Diagonal Size</b>	14.0"
<b>Thickness</b>	3.0mm max.
<b>Interface</b>	eDP 1.4
<b>Surface Treatment</b>	Anti-glare
<b>Touch Enabled</b>	No
<b>Contrast Ratio</b>	Sharing mode, 600:1 (typ.) Privacy mode, 150:1 (typ.)
<b>Refresh Rate</b>	120Hz
<b>Brightness</b>	Sharing mode, 700 nits (typ.) Privacy mode, 350 nits (typ.)
<b>Pixel Resolution</b>	1920 x 1080 (FHD)
<b>Format</b>	RGB strip
<b>Backlight</b>	LED
<b>Color Gamut Coverage</b>	100% sRGB
<b>Color Depth</b>	8 bits
<b>Viewing Angle</b>	Sharing mode, CR >10, L/R/U/D, 85/85/85/85 (typ.) Privacy mode CR>2, L/R/U/D, 50/50/85/85 (typ.)

**Panel LCD 14 inch FHD (1920x1080) Anti-Glare On-Cell Touch WLED UWVA 72percent cg 700nits eDP 1.3+PSR ultraslim**

<b>Outline Dimensions (W x H)</b>	315.41x 196.14 max.
<b>Active Area</b>	309.312 x 173.988
<b>Weight</b>	<265g max.
<b>Diagonal Size</b>	14.0"
<b>Thickness</b>	2.7mm max.
<b>Interface</b>	eDP 1.3
<b>Surface Treatment</b>	Anti-glare On-cell
<b>Touch Enabled</b>	Yes
<b>Contrast Ratio</b>	Sharing mode, 600:1 (typ.) Privacy mode, 150:1 (typ.)
<b>Refresh Rate</b>	120Hz
<b>Brightness</b>	Sharing mode, 700 nits (typ.) Privacy mode, 350 nits (typ.)
<b>Pixel Resolution</b>	1920 x 1080 (FHD)
<b>Format</b>	RGB strip

### Technical Specifications

<b>Backlight</b>	LED
<b>Color Gamut Coverage</b>	Sharing mode, 100% sRGB Privacy mode, 83% sRGB
<b>Color Depth</b>	8 bits
<b>Viewing Angle</b>	Sharing mode, CR >10, L/R/U/D, 85/85/85/85 (typ.) Privacy mode CR>2, L/R/U/D, 50/50/85/85 (typ.)

### STORAGE<sup>1</sup>

<b>SSD 128 GB 2280 M2 SATA-3 TLC</b>	<b>Drive Weight</b>	0.02 lb (10 g)
	<b>Capacity</b>	128 GB
	<b>Height</b>	0.09 in (2.3 mm)
	<b>Width</b>	0.87 in (22 mm)
	<b>Interface</b>	ATA-8, SATA 3.0
	<b>Maximum Sequential Read</b>	Up To 520 MB/s
	<b>Maximum Sequential Write</b>	Up To 450 MB/s
	<b>Logical Blocks</b>	250,069,680
	<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
	<b>Features</b>	DIPM; TRIM; DEVSLP

<b>SSD 1 TB 2280 PCIe-3x4 NVMe TLC DS</b>	<b>Drive Weight</b>	0.02 lb (10 g)
	<b>Capacity</b>	1024 GB
	<b>Height</b>	0.09 in (2.3 mm)
	<b>Width</b>	0.87 in (22 mm)
	<b>Interface</b>	PCIe NVMe Gen3X4
	<b>Maximum Sequential Read</b>	Up To 2800 MB/s
	<b>Maximum Sequential Write</b>	Up To 1600 MB/s
	<b>Logical Blocks</b>	2,000,409,264
	<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
	<b>Features</b>	TRIM; L1.2

<b>SSD 256 GB 2280 M2 PCIe-3x4 SS NVMe TLC</b>	<b>Drive Weight</b>	0.02 lb (10 g)
	<b>Capacity</b>	256 GB
	<b>Height</b>	0.09 in (2.3 mm)
	<b>Width</b>	0.87 in (22 mm)
	<b>Interface</b>	PCIe NVMe Gen3X4
	<b>Maximum Sequential Read</b>	Up To 2600 MB/s

### Technical Specifications

<b>Maximum Sequential Write</b>	Up To 900 MB/s
<b>Logical Blocks</b>	500,118,192
<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
<b>Features</b>	TRIM; L1.2

#### SSD 256 GB 2280 M2 SATA-3 Self Encrypted OPAL2 TLC

<b>Drive Weight</b>	0.02 lb (10 g)
<b>Capacity</b>	256 GB
<b>Height</b>	0.09 in (2.3 mm)
<b>Width</b>	0.87 in (22 mm)
<b>Interface</b>	ATA-8, SATA 3.0
<b>Maximum Sequential Read</b>	Up To 530 MB/s
<b>Maximum Sequential Write</b>	Up To 515 MB/s
<b>Logical Blocks</b>	500,118,192
<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
<b>Features</b>	DIPM; TRIM; DEVSLP

#### 256 GB 2280 PCIe NVMe Value Solid State Drive

<b>Drive Weight</b>	0.02 lb (10 g)
<b>Capacity</b>	256 GB
<b>Height</b>	0.09 in (2.3 mm)
<b>Width</b>	0.87 in (22 mm)
<b>Interface</b>	PCIe NVMe Gen3X4
<b>Maximum Sequential Read</b>	Up To 1700 MB/s
<b>Maximum Sequential Write</b>	Up To 600 MB/s
<b>Logical Blocks</b>	500,118,192
<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
<b>Features</b>	TRIM; L1.2

#### SSD 360 GB 2280 PCIe-3x4 NVMe TLC

<b>Drive Weight</b>	0.02 lb (10 g)
<b>Capacity</b>	360 GB
<b>Height</b>	0.09 in (2.3 mm)
<b>Width</b>	0.87 in (22 mm)
<b>Interface</b>	PCIe NVMe Gen3X4
<b>Maximum Sequential Read</b>	Up To 1700 MB/s
<b>Maximum Sequential Write</b>	Up To 600 MB/s
<b>Logical Blocks</b>	703,282,608
<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
<b>Features</b>	TRIM; L1.2

### Technical Specifications

---

<b>SSD 512 GB 2280 M2 PCIe-3x4 SS NVMe TLC</b>	<b>Drive Weight</b>	0.02 lb (10 g)
	<b>Capacity</b>	512 GB
	<b>Height</b>	0.09 in (2.3 mm)
	<b>Width</b>	0.87 in (22 mm)
	<b>Interface</b>	PCIe NVMe Gen3X4
	<b>Maximum Sequential Read</b>	Up To 2600 MB/s
	<b>Maximum Sequential Write</b>	Up To 1400 MB/s
	<b>Logical Blocks</b>	1,000,215,216
	<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
	<b>Features</b>	TRIM; L1.2

---

<b>SSD 512GB 2280 M2 SATA-3 TLC FIPS</b>	<b>Drive Weight</b>	0.02 lb (10 g)
	<b>Capacity</b>	512GB
	<b>Height</b>	0.09 in (2.3 mm)
	<b>Width</b>	0.87 in (22 mm)
	<b>Interface</b>	ACS-3, SATA 3.2
	<b>Maximum Sequential Read</b>	Up To 530 MB/s
	<b>Maximum Sequential Write</b>	Up To 400 MB/s
	<b>Logical Blocks</b>	1,000,215,216
	<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
	<b>Features</b>	DIPM; TRIM; DEVSLP

---

<b>SSD 512 GB 2280 PCIe-3x4 NVMe Self Encrypted OPAL2 TLC</b>	<b>Drive Weight</b>	0.02 lb (10 g)
	<b>Capacity</b>	512GB
	<b>Height</b>	0.09 in (2.3 mm)
	<b>Width</b>	0.87 in (22 mm)
	<b>Interface</b>	PCIe NVMe Gen3X4
	<b>Maximum Sequential Read</b>	Up To 2900 MB/s
	<b>Maximum Sequential Write</b>	Up To 1400 MB/s
	<b>Logical Blocks</b>	1,000,215,215
	<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
	<b>Features</b>	DIPM; TRIM; DEVSLP

---

1. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10) is reserved for system recovery software.

---

### Technical Specifications

#### NETWORKING/COMMUNICATIONS

<b>Intel® 802.11a/b/g/n/ac (2x2) WiFi and Bluetooth® 4.2 Combo<sup>1</sup></b>	<b>Wireless LAN Standards</b>	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac
	<b>Interoperability</b>	Wi-Fi certified
	<b>Frequency Band</b>	802.11b/g/n <ul style="list-style-type: none"> <li>• 2.402 – 2.482 GHz</li> </ul> 802.11a/n <ul style="list-style-type: none"> <li>• 4.9 – 4.95 GHz (Japan)</li> <li>• 5.15 – 5.25 GHz</li> <li>• 5.25 – 5.35 GHz</li> <li>• 5.47 – 5.725 GHz</li> <li>• 5.825 – 5.850 GHz</li> </ul>
	<b>Data Rates</b>	<ul style="list-style-type: none"> <li>• 802.11b: 1, 2, 5.5, 11 Mbps</li> <li>• 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>• 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>• 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz)</li> <li>• 802.11ac : MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, and 80MHz)</li> </ul>
	<b>Modulation</b>	Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM
	<b>Security<sup>3</sup></b>	<ul style="list-style-type: none"> <li>• IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only</li> <li>• AES-CCMP: 128 bit in hardware •802.1x authentication •WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. •WPA2 certification •IEEE 802.11i •Cisco Certified Extensions, all versions through CCX4 and CCX Lite</li> <li>• WAPI</li> </ul>
	<b>Network Architecture Models</b>	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
	<b>Roaming</b>	IEEE 802.11 compliant roaming between access points
	<b>Output Power<sup>2</sup></b>	<ul style="list-style-type: none"> <li>• 802.11b : +14dBm minimum</li> <li>• 802.11g : +12dBm minimum</li> <li>• 802.11a : +12dBm minimum</li> <li>• 802.11n HT20(2.4GHz) : +12dBm minimum</li> <li>• 802.11n HT40(2.4GHz) : +12dBm minimum</li> <li>• 802.11n HT20(5GHz) : +10dBm minimum</li> <li>• 802.11n HT40(5GHz) : +10dBm minimum</li> <li>• 802.11ac VHT80(5GHz) : +10dBm minimum</li> </ul>
	<b>Power Consumption</b>	<ul style="list-style-type: none"> <li>• Transmit mode 2.0 W</li> <li>• Receive mode 1.6 W</li> <li>• Idle mode (PSP) 180 mW (WLAN Associated)</li> <li>• Idle mode 50 mW (WLAN unassociated)</li> <li>• Connected Standby 10mW</li> <li>• Radio disabled 8 mW</li> </ul>
	<b>Power Management</b>	ACPI compliant power management 802.11 compliant power saving mode



### Technical Specifications

<b>Receiver Sensitivity<sup>4</sup></b>	802.11b, 1Mbps : -93.5dBm maximum 802.11b, 11Mbps : -84dBm maximum 802.11a/g, 6Mbps : -86dBm maximum 802.11a/g, 54Mbps : -72dBm maximum 802.11n, MCS07 : -67dBm maximum 802.11n, MCS15 : -64dBm maximum 802.11ac, MCS0 : -84dBm maximum 802.11ac, MCS9 : -59dBm maximum
<b>Antenna type</b>	High efficiency antenna with spatial diversity, mounted in the display enclosure  Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
<b>Form Factor</b>	PCI-Express Half-MiniCard
<b>Dimensions</b>	Type 2230 : 2.3 x 22.0 x 30.0 mm
<b>Weight</b>	Type 2230 : 2.8g
<b>Operating Voltage</b>	3.3v +/- 9%
<b>Temperature</b>	<b>Operating</b> 14° to 158° F (-10° to 70° C) <b>Non-operating</b> -40° to 176° F (-40° to 80° C)
<b>Humidity</b>	<b>Operating</b> 10% to 90% (non-condensing) <b>Non-operating</b> 5% to 95% (non-condensing)
<b>Altitude</b>	<b>Operating</b> 0 to 10,000 ft (3,048 m) <b>Non-operating</b> 0 to 50,000 ft (15,240 m)
<b>LED Activity</b>	<b>LED Amber</b> – Radio OFF; <b>LED White</b> – Radio ON

### HP Integrated Module with Bluetooth 4.0/4.1/4.2 Wireless Technology

<b>Bluetooth Specification</b>	4.0/4.1/4.2 Compliant
<b>Frequency Band</b>	2402 to 2480 MHz
<b>Number of Available Channels</b>	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)
<b>Data Rates and Throughput</b>	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps BLE : 1 Mbps data rate; throughput up to 0.2 Mbps Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
<b>Transmit Power</b>	The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.
<b>Power Consumption</b>	Peak (Tx) 330 mW Peak (Rx) 230 mW Selective Suspend 17 mW
<b>Electrical Interface</b>	USB 2.0 compliant

### Technical Specifications

<b>Bluetooth Software Supported</b>	Microsoft Windows Bluetooth Software
<b>Power Management Certifications</b>	Microsoft Windows ACPI, and USB Bus Support FCC (47 CFR) Part 15C, Section 15.247 & 15.249
<b>Power Management Certifications</b>	ETS 300 328, ETS 300 826 Low Voltage Directive IEC950 UL, CSA, and CE Mark
<b>Bluetooth Profiles Supported</b>	BT4.1-ESR 5/6/7 Compliance LE Link Layer Ping LE Dual Mode LE Link Layer LE Low Duty Cycle Directed Advertising LE L2CAP Connection Oriented Channels Train Nudging & Interlaced Scan BT4.2 ESR08 Compliance LE Secure Connection- Basic/Full LE Privacy 1.2 –Link Layer Privacy LE Privacy 1.2 –Extended Scanner Filter Policies LE Data Packet Length Extension FAX Profile (FAX) Basic Imaging Profile (BIP)2 Headset Profile (HSP) Hands Free Profile (HFP) Advanced Audio Distribution Profile (A2DP)

1. Wireless access point and Internet service is required. Availability of public wireless access point is limited. The specifications for the 802.11ac WLAN are draft specifications and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the notebook to communicate with other 802.11ac WLAN devices
2. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
3. Check latest software/driver release for updates on supported security features.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

### Technical Specifications

<b>HP It4132 LTE/HSPA+ 4G Mobile Broadband<sup>5</sup></b>	<b>Technology/Operating bands</b>	LTE: 2100 (Band 1), 1900 (Band 2), 1800 (Band 3) MHz, 850 (Band 5), 2600 (Band 7), 900 (Band 8) MHz, 800 (Band 20), 700 (Band 28) MHz. HSPA+: 2100 (Band 1), 1900 (Band 2), 850 (Band 5), 900 (Band 8) MHz E-GPRS: 1900 (Band 2), 1800 (Band 3), 850 (Band 5), 900 (Band 8) MHz
	<b>Wireless protocol standards</b>	3GPP Release 10 LTE Specification CAT.4, 20MHz BW WCDMA R99, 3GPP Release 5, 6, 7 and 8 UMTS Specification E-GPRS: Class B, Multi-slot class 12, coding schemes CS1 - CS4 and MSC1 - MSC9
	<b>GPS</b>	Standalone, A-GPS (MS-B and LTO)
	<b>GPS bands</b>	1575.42 MHz ± 1.023 MHz, GLONASS 1596-1607MHz
	<b>Maximum data rates</b>	LTE: 150 Mbps (Download), 50 Mbps (Upload) DC-HSPA+: 42 Mbps (Download), 5.76 Mbps (Upload) HSPA+: 21Mbps (Download), 5.76 Mbps (Upload) EDGE: 236.8 kbps (Download), 236.8 kbps (Upload) GPRS: 85.6 kbps(Download), 85.6 kbps (Upload)
	<b>Maximum output power</b>	LTE: 23 dBm HSPA+: 23.5 dBm E-GPRS 1900/1800: 26 dBm E-GPRS 900/850: 27 dBm GPRS 1900/1800: 29.5 dBm GPRS 900/850: 32.5 dBm
	<b>Maximum power consumption</b>	LTE: 1,200 mA (peak); 900 mA (average) HSPA+: 1,100 mA (peak); 800 mA (average) E-GPRS: 2,600 mA (peak); 500 mA (average)
	<b>Form Factor</b>	M.2, 3042-S3 Key B
	<b>Weight</b>	6 g
	<b>Dimensions (Length x Width x Thickness)</b>	42 30 x 2.3 mm

5. Wireless access point and Internet service is required. Availability of public wireless access point is limited. The specifications for the 802.11ac WLAN are draft specifications and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the notebook to communicate with other 802.11ac WLAN devices

### Technical Specifications

<b>Intel® XMM™ 7360 LTE-Advanced<sup>6</sup></b>	<b>Technology/Operating bands</b>	FDD LTE: 2100 (Band 1), 1900 (Band 2), 1800 (Band 3), 1700/2100 (Band 4), 850 (Band 5), 2600 (Band 7), 900 (Band 8), 1400 (Band 11), 700 (Band 12 lower), 700 (Band 13 upper), 700 (Band 17 lower), 850 (Band 18 lower), 850 (Band 19 upper), 800 (Band 20), 1400 (Band 21), 850 (Band 26), 700 (Band 28), 700 (Band 29 RX only), 2300 (Band 30), 2100 (Band 66). TDD LTE: 2600 (Band 38), 1900 (Band 39), 2300 (Band 40), 2500 (Band 41). HSPA+: 2100 (Band 1), 1900 (Band 2), 1700/2100 (Band 4), 850 (Band 5), 900 (Band 8) MHz
	<b>Wireless protocol standards</b>	3GPP Release 11 LTE Specification CAT.9, DL 60MHz BW throughput up to 450Mbps; UL 20MHz throughput up to 50Mbps WCDMA R99, 3GPP Release 5, 6, 7 and 8 UMTS Specification
	<b>GPS</b>	Standalone, A-GPS (MS-A, MS-B and XTRA)
	<b>GPS bands</b>	1575.42 MHz ± 1.023 MHz, GLONASS 1596-1607MHz, Beidou 1561.098 MHz
	<b>Maximum data rates</b>	LTE: 450 Mbps (Download), 50 Mbps (Upload) DC-HSPA+: 42 Mbps (Download), 5.76 Mbps (Upload) HSPA+: 21Mbps (Download), 5.76 Mbps (Upload)
	<b>Maximum output power</b>	LTE: 23 dBm HSPA+: 23.5 dBm
	<b>Maximum power consumption</b>	LTE: 1,200 mA (peak); 900 mA (average) HSPA+: 1,100 mA (peak); 800 mA (average)
	<b>Form Factor</b>	M.2, 3042-S3 Key B
	<b>Weight</b>	5.8 g
	<b>Dimensions (Length x Width x Thickness)</b>	42 x 30 x 2.3 mm

6. Wireless access point and Internet service is required. Availability of public wireless access point is limited. The specifications for the 802.11ac WLAN are draft specifications and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the notebook to communicate with other 802.11ac WLAN devices

### Technical Specifications

<b>Realtek 802.11b/g/n (2x2) WiFi and Bluetooth® 4.2 Combo<sup>7</sup></b>	<b>Wireless LAN Standards</b>	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac
	<b>Interoperability</b>	Wi-Fi certified
	<b>Frequency Band</b>	802.11b/g/n [2] • 2.402 – 2.482 GHz
	<b>Data Rates</b>	802.11b: 1, 2, 5.5, 11 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: MCS 0 ~ MCS 07, (20MHz)
	<b>Modulation</b>	Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM,
	<b>Security<sup>9</sup></b>	<ul style="list-style-type: none"> <li>• IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only</li> <li>• AES-CCMP: 128 bit in hardware</li> <li>• 802.1x authentication</li> <li>• WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.</li> <li>• WPA2 certification</li> <li>• IEEE 802.11i</li> <li>• Cisco Certified Extensions, all versions through CCX4 and CCX Lite</li> <li>• WAPI</li> </ul>
	<b>Network Architecture Models</b>	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
	<b>Roaming</b>	IEEE 802.11 compliant roaming between access points
	<b>Output Power<sup>8</sup></b>	<ul style="list-style-type: none"> <li>• 802.11b : +14dBm minimum</li> <li>• 802.11g : +12dBm minimum</li> <li>• 802.11a : +12dBm minimum</li> <li>• 802.11n HT20(2.4GHz) : +12dBm minimum</li> <li>• 802.11n HT40(2.4GHz) : +12dBm minimum</li> <li>• 802.11n HT20(5GHz) : +10dBm minimum</li> <li>• 802.11n HT40(5GHz) : +10dBm minimum</li> <li>• 802.11ac VHT80(5GHz) : +10dBm minimum</li> </ul>
	<b>Power Consumption</b>	<ul style="list-style-type: none"> <li>• Transmit mode 2.0 W</li> <li>• Receive mode 1.6 W</li> <li>• Idle mode (PSP) 180 mW (WLAN Associated)</li> <li>• Idle mode 50 mW (WLAN unassociated)</li> <li>• Connected Standby 10mW</li> <li>• Radio disabled 8 mW</li> </ul>
	<b>Power Management</b>	ACPI compliant power management 802.11 compliant power saving mode
	<b>Receiver Sensitivity<sup>10</sup></b>	802.11b, 1Mbps : -93.5dBm maximum 802.11b, 11Mbps : -84dBm maximum 802.11a/g, 6Mbps : -86dBm maximum 802.11a/g, 54Mbps : -72dBm maximum 802.11n, MCS07 : -67dBm maximum 802.11n, MCS15 : -64dBm maximum 802.11ac, MCS0 : -84dBm maximum

### Technical Specifications

<b>Antenna type</b>	802.11ac, MCS9 : -59dBm maximum High efficiency antenna with spatial diversity, mounted in the display enclosure
<b>Form Factor</b>	Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
<b>Dimensions</b>	PCI-Express M.2 MiniCard Type 2230 : 2.3 x 22.0 x 30.0 mm Or Type 1630 : 2.3 x 16.0 x 30.0 mm
<b>Weight</b>	Type 2230 : 2.8g Or Type 1630 : 2g
<b>Operating Voltage</b>	3.3v +/- 9%
<b>Temperature</b>	Operating: 14° to 158° F (-10° to 70° C) Non-operating: -40° to 176° F (-40° to 80° C)
<b>Humidity</b>	<b>Operating:</b> 10% to 90% (non-condensing) <b>Non-operating:</b> 5% to 95% (non-condensing)
<b>Altitude</b>	<b>Operating:</b> 0 to 10,000 ft (3,048 m) <b>Non-operating:</b> 0 to 50,000 ft (15,240 m)
<b>LED Activity</b>	<b>LED Amber</b> – Radio OFF <b>LED White</b> – Radio ON

#### HP Integrated Module with Bluetooth 4.0/4.1/4.2 Wireless Technology

<b>Bluetooth Specification</b>	4.0/4.1/4.2 Compliant
<b>Frequency Band</b>	2402 to 2480 MHz
<b>Number of Available Channels</b>	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)
<b>Data Rates and Throughput</b>	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps BLE : 1 Mbps data rate; throughput up to 0.2 Mbps Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
<b>Transmit Power</b>	The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.

7. Wireless access point and Internet service is required. Availability of public wireless access point is limited. The specifications for the 802.11ac WLAN are draft specifications and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the notebook to communicate with other 802.11ac WLAN devices

8. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.

9. Check latest software/driver release for updates on supported security features.

10. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

### Technical Specifications

#### Near Field Communications Controller (optional)

<b>Dimensions (L x W x H)</b>	Module 25 mm by 10 mm by 2.0 mm
<b>Chipset</b>	NPC100
<b>System interface</b>	I2C
<b>NFC RF standards</b>	ISO/IEC 14443 A ISO/IEC 14443 B ISO/IEC 15693 ISO/IEC 18092 ECMA-340 NFCIP-1 Target and Initiator ECMA-320 NFCIP-2
<b>NFC Forum Support</b>	Tag Type 1, Type 2, Type3 and Type 4, NFCIP-1 and NFCIP-2
<b>Reader (PCD-VCD) Mode(1)</b>	ISO/IEC 14443 A ISO/IEC 14443 B ISO/IEC 15693 MIFARE 1K MIFARE 4K MIFARE DESFire FeliCa Jewel and Topaz cards
<b>Card Emulation (PICC-VICC) Mode(1)</b>	ISO/IEC 14443 A ISO/IEC 14443 B and B' MIFARE FeliCa
<b>Frequency</b>	13.56 MHz
<b>NFC Modes Supported</b>	Reader/Writer, Peer-to-Peer
<b>Raw RF Data Rates</b>	106, 212, 424, 848 kbps
<b>Operating temperature</b>	0°C to 70°C
<b>Storage temperature</b>	-20°C to 125°C
<b>Humidity</b>	10-90% operating 5-95% non-operating
<b>Supply Operating voltage</b>	2.97 to 5.5 Volts
<b>I/O Voltage</b>	1.8V or 3.3V

#### Power Consumption

(Booster enable, VBAT= 3.3V, VCC\_BOOST = 5V)

<b>Mode</b>	Power Consumption, Typical
<b>Polling</b>	7.3 mA
<b>Detected Test Tag Type 1</b>	Total 283.8 mA Net Module 236.8 mA
<b>Detected Test Tag Type 2</b>	Total 288.8 mA Net Module 241.8 mA
<b>Detected Test Tag Type 3</b>	Total 287.7 mA

### Technical Specifications

	Net Module 240.7 mA
<b>Detected Test Tag Type 4</b>	Total 282.3 mA Net Module 235.3 mA
<b>Antenna</b>	Antenna connector, 0.5mm pitch, 7 connector FPC. Antenna matching is external to module.

### POWER

<b>AC Adapter 65 Watt nPFC USB type C</b>	<b>Dimensions</b>	74x74x28.5mm	
	<b>Weight</b>	unit: 245g +/- 10g	
<b>Input</b>	<b>Input Efficiency</b>	81.5% min at 115 Vac/ 230Vac @ 5V/3A 86.7% min at 115 Vac/ 230Vac @ 9V/3A 88% min at 115 Vac/ 230Vac @ 10V/5A 88% min at 115 Vac/ 230Vac @ 12V/5A 89% min at 115 Vac/ 230Vac @ 15V/4.33A 89% min at 115 Vac/ 230Vac @ 20V/3.25A	
	<b>Input frequency range</b>	47 ~ 63 Hz	
	<b>Input AC current</b>	1.7 A at 90 VAC and maximum load	
	<b>Output</b>	<b>Output power</b>	65W
		<b>DC output</b>	5V/9V/10V/12V/15V/20V
		<b>Hold-up time</b>	5ms at 115 Vac input
	<b>Environmental Design</b>	<b>Output current limit</b>	<8.0A
		<b>Operating temperature</b>	32°F to 95°F (0° to 35°C)
		<b>Non-operating (storage) temperature</b>	-4°F to 185°F (-20° to 85°C)
		<b>Altitude</b>	0 to 16,400 ft (0 to 5000m)
<b>Humidity</b>		5% to 95%	
<b>EMI and Safety Certifications</b>	<b>Storage Humidity</b>	5% to 95%	
	CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. MTBF - over 100,000 hours at 25°C ambient condition.		



### Technical Specifications

<b>AC Adapter 45 Watt nPFC USB type C</b>	<b>Dimensions</b>	62.0x62.0x28.5mm	
	<b>Weight</b>	unit: 220g +/- 10g	
	<b>Input</b>	<b>Input Efficiency</b>	Average Efficiency of 25%, 50%, 75%, 100% load condition with 115Vac/230Vac Spec:5V : 81.5%9V : 86.7%10V : 87.5%12V : 87.8%15V : 87.8%20V : 87.8%
		<b>Input frequency range</b>	47 ~ 63Hz
		<b>Input AC current</b>	Max. 1.4 A at 90 Vac
	<b>Output</b>	<b>Output power</b>	5V/15W 9V/27W 10V/37.5W 12V/45W 15V/45W 20V/45W
		<b>DC output</b>	5V / 9V / 10V /12V / 15V / 20V
		<b>Hold-up time</b>	5ms at 115 Vac input
		<b>Output current limit</b>	<5.0A
	<b>Connector</b>		USB Type-C
	<b>Environmental Design</b>	<b>Operating temperature</b>	32oF to 95oF (0oto 35oC)
		<b>Non-operating (storage) temperature</b>	-4oF to 185oF (-20oto 85oC)
		<b>Altitude</b>	0 to 16,400 ft (0 to 5000m)
	<b>Humidity</b>	20% to 95%	
	<b>Storage Humidity</b>	10% to 95%	
<b>Safety Certifications</b>		CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. MTBF - over 200,000 hours at 25°C ambient condition.	
<b>HP 45W Smart AC adapter</b>	<b>Dimensions</b>	3.74 x 1.57 x 1.04 in (9.5 x 4.0 x 2.65 cm)	
	<b>Weight</b>	0.386 lb (175g) max	
	<b>Input</b>	<b>Input Efficiency</b>	87.74% at 115Vac and 88.4% at 230Vac
		<b>Input frequency range</b>	47 ~ 63Hz
		<b>Input AC current</b>	Max. 1.4 A at 90 Vac
	<b>Output</b>	<b>Output power</b>	45W
		<b>DC output</b>	19.5V
		<b>Hold-up time</b>	5 msec at 115 VAC input
		<b>Output current limit</b>	<8.0A
	<b>Connector</b>		4.5mm Barrel Type, 3 pin/grounded, mates with interchangeable cords
	<b>Environmental Design</b>	<b>Operating temperature</b>	32° to 95° F (0° to 35° C)
		<b>Non-operating (storage) temperature</b>	-4° to 185° F (-20° to 85° C)
		<b>Altitude</b>	0 to 16,400 ft (0 to 5000m)
	<b>Humidity</b>	20% to 95%	
	<b>Storage Humidity</b>	10% to 95%	
<b>Safety Certifications</b>		CE Mark - full compliance with LVD and EMC directives	

### Technical Specifications

Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE.  
MTBF - over 200,000 hours at 25°C ambient condition.

<b>HP 65W Smart AC adapter</b>	<b>Dimensions</b>	107.0x47.0x30.0mm	
	<b>Weight</b>	unit: 250g +/- 10g	
	<b>Input</b>	<b>Input Efficiency</b>	88.0 % at 115 Vac and 89.0 % at 230Vac
		<b>Input frequency range</b>	47 ~ 63 Hz
		<b>Input AC current</b>	Max. 1.7 A at 90 Vac
	<b>Output</b>	<b>Output power</b>	65W
		<b>DC output</b>	19.5V
		<b>Hold-up time</b>	5ms at 115 Vac input
		<b>Output current limit</b>	<11.0A
	<b>Connector</b>	4.5mm Barrel Type	
	<b>Environmental Design</b>	<b>Operating temperature</b>	32°F to 95°F (0°to 35°C)
		<b>Non-operating (storage) temperature</b>	-4°F to 185°F (-20° to 85°C)
		<b>Altitude</b>	0 to 16,400 ft (0 to 5000m)
		<b>Humidity</b>	20% to 95%
	<b>Storage Humidity</b>	10% to 95%	
<b>Safety Certifications</b>	CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. MTBF - over 200,000 hours at 25°C ambient condition.		
<b>HP 65W EM Smart AC adapter</b>	<b>Dimensions</b>	102x55x30mm	
	<b>Weight</b>	270g +/- 10g	
	<b>Input</b>	<b>Input Efficiency</b>	87% min at 115V/230V
		<b>Input frequency range</b>	47 to 63 Hz
		<b>Input AC current</b>	1.7 A at 90 VAC and maximum load
	<b>Output</b>	<b>DC output</b>	65W(19.5V/3.33A)
		<b>Hold-up time</b>	5 msec at 115 VAC input
		<b>Output current limit</b>	<11A, Over voltage protection- 29V max automatic shutdown
		<b>Connector</b>	4.5mm Barrel Type, 3 pin/grounded, mates with interchangeable cords
	<b>Environmental Design</b>	<b>Operating temperature</b>	0° to 35° C
		<b>Non-operating (storage) temperature</b>	-20° to 85° C
		<b>Altitude</b>	0 to 5,000 m
		<b>Humidity</b>	0% to 95%
		<b>Storage Humidity</b>	0% to 95%
<b>Safety Certifications</b>	CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. MTBF - over 200,000 hours at 25°C ambient condition.		

### Technical Specifications

<b>Battery SS 3 Cell 50 WHr Long Life -PL</b>	<b>Dimensions (H x W x L)</b>	L 278.7mm x W 76.3mm x H 7.1mm
	<b>Weight</b>	193 +/- 10g
	<b>Cells/Type</b>	3cell Lithium-Ion Polymer cell / P604883A1
	<b>Voltage</b>	11.55V/
	<b>Energy</b>	<b>Amp-hour capacity</b> 4.113Ah/ 4.330Ah
		<b>Watt-hour capacity</b> 50Wh
	<b>Temperature</b>	<b>Operating (Charging)</b> 0° to 50° C
		<b>Operating (Discharging)</b> -10° to 60° C
	<b>Fuel Gauge LED</b>	N/A
	<b>Warranty</b>	3 years
	<b>Optional Travel Battery Available</b>	No

### ENVIRONMENTAL

**Eco-Label Certifications & declarations** This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:

- IT ECO declaration
- US ENERGY STAR®
- EPEAT® Gold registered in the United States. See <http://www.epeat.net> for registration status in your country.

**System Configuration** The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a Typically Configured Notebook.

#### Energy Consumption (in accordance with US ENERGY STAR® test method)

	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation (Short idle)	8.24 W	8.11 W	7.97 W
Normal Operation (Long idle)	3.95 W	3.41 W	3.46 W
Sleep	0.85 W	0.88 W	0.85 W
Off	0.50 W	0.53 W	0.50 W

**NOTE:** Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.

### Technical Specifications

Heat Dissipation*	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation (Short idle)	28 BTU/hr	28 BTU/hr	27 BTU/hr
Normal Operation (Long idle)	14 BTU/hr	12 BTU/hr	12 BTU/hr
Sleep	3 BTU/hr	3 BTU/hr	3 BTU/hr
Off	2 BTU/hr	2 BTU/hr	2 BTU/hr

**NOTE:** Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

#### Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)

Sound Power (L<sub>WAd</sub>, bels)

Sound Pressure (L<sub>pAm</sub>, decibels)

Typically Configured – Idle  
Fixed Disk – Random writes

2.9

3.3

16

22

#### Longevity and Upgrading

This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the product may include:

- 3 USB ports
- 1 PC card slot (type I/II)
- 1 ExpressCard/54 slot
- 1 IEEE 1394 Port
- 2 SODIMM memory slots
- Optional expansion base docking station
- 1 multi-bay II storage port
- Interchangeable HDD

Spare parts are available throughout the warranty period and or for up to “5” years after the end of production.

#### Batteries

This battery(s) in this product comply with EU Directive 2006/66/EC

Batteries used in the product do not contain:  
Mercury greater the 1ppm by weight  
Cadmium greater than 20ppm by weight

Battery size: CR2032 (coin cell)  
Battery type: Lithium

### Technical Specifications

#### Additional Information

- This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.
- This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.
- This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).
- This product is in compliance with the IEEE 1680 (EPEAT) standard at the <gold> level, see [www.epeat.net](http://www.epeat.net)
- Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.
- This product contains 0% post-consumer recycled plastic (by wt.)
- This product is 95.1% recycle-able when properly disposed of at end of life.

#### Packaging Materials

<b>External:</b>	PAPER/Corrugated	357 g
<b>Internal:</b>	PLASTIC/Expanded Polyethylene - EPE	66 g
	PLASTIC/Polyethylene low density - LDPE	4 g
	PLASTIC/Polypropylene - PP	15 g

The plastic packaging material contains at least 50% recycled content.

The corrugated paper packaging materials contains at least 70% recycled content.

#### Material Usage

This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at <http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf>):

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants – may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Formaldehyde
- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)

### Technical Specifications

#### Packaging Usage

HP follows these guidelines to decrease the environmental impact of product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

#### End-of-life Management and Recycling

HP Inc. offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <http://www.hp.com/go/reuse-recycle> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <http://www.hp.com/go/recyclers>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

#### HP Inc.

For more information about HP's commitment to the environment:

#### Corporate Environmental Information

Global Citizenship Report

<http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html>

Eco-label certifications

<http://www8.hp.com/us/en/hp-information/environment/ecolabels.html>

ISO 14001 certificates:

<http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755842>

and

<http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf>

### COUNTRY OF ORIGIN

China

### Options and Accessories (sold separately and availability may vary by country)

Type	Description	Part #
<b>Cases</b>	HP Exec Midnight 15.6" Backpack	1KM16AA
	HP Slim Top Load	F3W15AA
<b>Docking</b>	HP Thunderbolt Dock 120W G2 (Available in May 2018)	2UK37AA
	HP USB-C Universal Dock	1MK33AA
	HP USB-C Mini Dock	1PM64AA
	HP UltraSlim Docking Station	D9Y32AA
	HP USB-C Dock G4	3FF69AA
	HP Elite 90W Thunderbolt 3 Dock	1DT93AA
<b>Input/Output</b>	HP Slim Wireless Keyboard and Mouse	T6L04AA
	HP Slim USB Keyboard and Mouse	T6T83AA
	HP Wireless (Link-5) Keyboard	T6U20AA
	HP Wireless Premium Mouse	1JR31AA
	HP USB Premium Mouse	1JR32AA
	HP Comfort Grip Wireless Mouse	H2L63AA
	HP Ultra Mobile Wireless Mouse	H6F25AA
	HP Slim Bluetooth Mouse	F3J92AA
	HP Elite Presenter Mouse	2CE30AA
	HP USB-C to USB-A Hub	Z6A00AA
	HP USB-C to DP	N9K78AA
	HP USB-C to VGA	N9K76AA
	HP HDMI to DVI	F5A28AA
	HP HDMI to VGA	H4F02AA
HP USB-C to HDMI 2.0	1WC36AA	
<b>Power</b>	HP 45W USB-C Power Adapter	1HE07AA
	HP 65W USB-C Power Adapter	1HE08AA
	HP Notebook Power Bank	N9F71AA
	HP USB-C Notebook Power Bank	1TZ86AA
	HP 65W Slim AC Adapter	H6Y82AA
	HP 90W Slim AC Adapter	H6Y83AA
HP 90W Slim Combo AC Adapter w/ USB	H6Y84AA	
<b>Storage</b>	HP USB External DVDRW Drive	F2B56AA
	HP 256GB M2 PCIe NVME SSD TLC (2280)	1FU87AA
	HP 512GB M2 PCIe NVME SSD TLC (2280)	1FU88AA
<b>Memory</b>	HP 4GB 2400MHz DDR4 Memory	Z4Y84AA
	HP 8GB 2400MHz DDR4 Memory	Z4Y85AA
	HP 16GB 2400MHz DDR4 Memory	Z4Y86AA

### Options and Accessories (sold separately and availability may vary by country)

<b>Security</b>	HP Docking Station Cable Lock	AU656AA
	HP Keyed Cable Lock	TOY14AA
	HP Keyed Cable Lock 10mm	T1A62AA
	HP Dual Head Keyed Cable Lock	T1A64AA
<b>UCC</b>	HP USB Collaboration Keyboard	Z9N38AA
	HP Wireless Collaboration Keyboard	Z9N39AA
	HP UC Wireless Mono Headset	W3K08AA
	HP UC Wireless Duo Headset	W3K09AA
	HP UC Speaker Phone	K7V16AA
<b>Displays</b>	HP EliteDisplay E273m 27-inch Monitor	1FH51AA
	HP EliteDisplay E273q 27-inch Monitor	1FH52AA
	HP EliteDisplay E243 23.8-inch Monitor	1FH47AA

---



### Summary of Changes

Date of change:	Version History:		Description of change:
February 12, 2018	V1 to V2	Update	Processor speed updated
February 28, 2018	V2 to V3	Update	256GB 2280 PCIe NVMe Value Solid State Drive features specs added
March 12, 2018	V3 to V4	Update	Processor list updated
April 30, 2018	V4 to V5	Update	Weight updated
May 7, 2018	V5 to V6	Update	Display support matrix moved to Display Support section
May 11, 2018	V6 to V7	Update	Displays and At a glance sections updated and environmental data added.
May 14, 2018	V7 to V8	Update	Docking at Options section updated
May 16, 2018	V8 to V9	Update	Mistake on panel display fixed and Touch enable field switched to no on Panel LCD 14 inch FHD (1920x1080) WLED UWVA 100% cg 700nits eDP 1.3+PSR ultraslim Privacy
June 15, 2018	V9 to V10	Update	Networking
July 12, 2018	V10 to V11	Update	Environmental tab
July 16, 2018	V11 to V12	Update	Hidden functions
July 23, 2018	V12 to V13	Update	Software section
August 8, 2018	V13 to V14	Updated	Storage
August 9, 2018	V14 to V15	Removed	Software HP Velocity
October 3, 2018	V15 to V16	Updated	Display section
November 14, 2018	V16 to V17	Updated	
February 13, 2019	V17 to V18	Removed	Phonewise Software

©Copyright 2019 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties are contained in the limited warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Bluetooth is a trademark of its proprietor used by HP Inc. under license. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. USB Type-C and USB-C are trademarks of USB Implementers Forum. AMD and Radeon are a trademark of Advanced Micro Devices, Inc. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.